

Bill of Materials: 3bitcounter_1_2

Assembly List

Label	MN (manufacturer number)	MPN (manufacturer part number)	Part Type	Properties
+5V			Screw terminal - 2 pins	hole size 1.1mm,0.508mm; package THT; pin spacing 0.137in (3.5mm); pins 2
5161AS			7 Segment Display	common cathode; size 13mm; type 7 Segment
74HC393			74HC393	chip label 74HC393; true; hole size 1.0mm,0.508mm; package DIP (Dual Inline) [THT] v2; pin spacing 300mil; pins 14
C1			Ceramic Capacitor	capacitance 100nF; voltage 35V; package 100 mil [THT, multilayer]
C2			Electrolytic Capacitor	capacitance 10µF; voltage 35V; package 100 mil [THT, electrolytic]
C3			Ceramic Capacitor	capacitance 100nF; voltage 35V; package 100 mil [THT, multilayer]
CD4511			CD4511	chip label CD4511; true; hole size 1.0mm,0.508mm; package DIP (Dual Inline) [THT] v2; pin spacing 300mil; pins 16
LED1			Red (633nm) LED	color Red (633nm); current 0.030A; leg yes; package 3 mm [THT]
LED2			Red (633nm) LED	color Red (633nm); current 0.030A; leg yes; package 3 mm [THT]
LED3			Red (633nm) LED	color Red (633nm); current 0.030A; leg yes; package 3 mm [THT]
NE555			555 Timer	package DIP8 [THT]
R1			100kΩ Resistor	resistance 100kΩ; tolerance ±5%; power 0.25W; bands 4; package THT; pin spacing 400 mil
R2			100kΩ Resistor	resistance 100kΩ; tolerance ±5%; power 0.25W; bands 4; package THT; pin spacing 400 mil
R3			330Ω Resistor	resistance 330Ω; tolerance ±5%; power 0.25W; bands 4; package THT; pin spacing 400 mil
R4			330Ω Resistor	resistance 330Ω; tolerance ±5%; power 0.25W; bands 4; package THT; pin spacing 400 mil
R5			330Ω Resistor	resistance 330Ω; tolerance ±5%; power 0.25W; bands 4; package THT; pin spacing 400 mil
R6			330Ω Resistor	resistance 330Ω; tolerance ±5%; power 0.25W; bands 4; package THT; pin spacing 400 mil
R7			330Ω Resistor	resistance 330Ω; tolerance ±5%; power 0.25W; bands 4; package THT; pin spacing 400 mil
R8			330Ω Resistor	resistance 330Ω; tolerance ±5%; power 0.25W; bands 4; package THT; pin spacing 400 mil
R9			330Ω Resistor	resistance 330Ω; tolerance ±5%; power 0.25W; bands 4; package THT; pin spacing 400 mil
R10			330Ω Resistor	resistance 330Ω; tolerance ±5%; power 0.25W; bands 4; package THT; pin spacing 400 mil
R11			330Ω Resistor	resistance 330Ω; tolerance ±5%; power 0.25W; bands 4; package THT; pin spacing 400 mil
R12			330Ω Resistor	resistance 330Ω; tolerance ±5%; power 0.25W; bands 4; package THT; pin spacing 400 mil

Shopping List

Amount	MN (manufacturer number)	MPN (manufacturer part number)	Part Type	Properties
1			Screw terminal - 2 pins	hole size 1.1mm,0.508mm; package THT; pin spacing 0.137in (3.5mm); pins 2
1			7 Segment Display	common cathode; size 13mm; type 7 Segment
1			74HC393	chip label 74HC393; true; hole size 1.0mm,0.508mm; package DIP (Dual Inline) [THT] v2; pin spacing 300mil; pins 14
2			Ceramic Capacitor	capacitance 100nF; voltage 35V; package 100 mil [THT, multilayer]
1			Electrolytic Capacitor	capacitance 10µF; voltage 35V; package 100 mil [THT, electrolytic]
1			CD4511	chip label CD4511; true; hole size 1.0mm,0.508mm; package DIP (Dual Inline) [THT] v2; pin spacing 300mil; pins 16
3			Red (633nm) LED	color Red (633nm); current 0.030A; leg yes; package 3 mm [THT]
1			555 Timer	package DIP8 [THT]
2			100kΩ Resistor	resistance 100kΩ; tolerance ±5%; power 0.25W; bands 4; package THT; pin spacing 400 mil
10			330Ω Resistor	resistance 330Ω; tolerance ±5%; power 0.25W; bands 4; package THT; pin spacing 400 mil