Instruction selection

Simple approach:

- Macro-expand each IR tuple/subtree into machine instructions
- Expanding tuples/subtrees independently ⇒ poor quality code
- Sometimes mapping is many-to-one
- "Maximal munch": works reasonably well with RISC

Other approaches:

- Model target machine *state* as IR is expanded (*interpretive code generation*)

Register and temporary management

Temporaries hold data values relevant to current computation:

- Usually registers
- May be in-memory *storage* temporaries in local stack frame

Register allocation: assign registers to temporaries

- Limited number of hard registers
  ⇒ some temporaries may need to be allocated to storage
  - assume a *pseudo-register* for each temporary
  - register allocator chooses temporaries to spill
  - allocator generates corresponding mapping
  - allocator inserts code to spill/restore pseudo-registers to/from storage as necessary

We will deal with register allocation *after* instruction selection

Tree patterns

- Express each machine instruction as fragment of IR tree: a *tree pattern*
- Instruction selection means *tiling* IR tree with minimal set of tree patterns

MIPS tree patterns

Notations:

r_i	register i
Rd	destination register
Rs	source register
Rb	base register
I	32-bit immediate
I_{16}	16-bit immediate
label	code label

Addressing modes:

- register: R
- indexed: I_{16}(Rb)
- immediate: I_{16}

MIPS tree patterns

—	r_i		TEMP
—	r_0		CONST 0
li	Rd	I	CONST
la	Rd	label	NAME
move	Rd	Rs	MOVE(•, •)
lw	Rd	I_{16}(Rb)	MEM($+$(•, CONST$_{16}$)), MEM($+$(CONST$_{16}$, •)), MEM(CONST$_{16}$), MEM(•)
sw	Rs	I_{16}(Rb)	MOVE(MEM($+$(•, CONST$_{16}$)), •), MOVE(MEM($+$(CONST$_{16}$, •)), •), MOVE(MEM(CONST$_{16}$), •), MOVE(MEM(•), •)

MIPS tree patterns

add	Rd	Rs$_1$	Rs$_2$	$+$(•, •)
	Rd	Rs$_1$	I_{16}	$+$(•, CONST$_{16}$), $+$(CONST$_{16}$, •)
mulo	Rd	Rs$_1$	Rs$_2$	$\times$(•, •)
	Rd	Rs	I_{16}	$\times$(•, CONST$_{16}$), $\times$(CONST$_{16}$, •)
and	Rd	Rs$_1$	Rs$_2$	AND(•, •)
	Rd	Rs$_1$	I_{16}	AND(•, CONST$_{16}$), AND(CONST$_{16}$, •)
or	Rd	Rs$_1$	Rs$_2$	OR(•, •)
	Rd	Rs$_1$	I_{16}	OR(•, CONST$_{16}$), OR(CONST$_{16}$, •)
xor	Rd	Rs$_1$	Rs$_2$	XOR(•, •)
	Rd	Rs$_1$	I_{16}	XOR(•, CONST$_{16}$), XOR(CONST$_{16}$, •)

MIPS tree patterns

sub	Rd	Rs$_1$	Rs$_2$	$-$(•, •)
	Rd	Rs	I_{16}	$-$(•, CONST$_{16}$)
div	Rd	Rs$_1$	Rs$_2$	$/$(•, •)
	Rd	Rs	I_{16}	$/$(•, CONST$_{16}$)
srl	Rd	Rs$_1$	Rs$_2$	RSHIFT(•, •)
	Rd	Rs	I_{16}	RSHIFT(•, CONST$_{16}$)
sll	Rd	Rs$_1$	Rs$_2$	LSHIFT(•, •)
	Rd	Rs	I_{16}	LSHIFT(•, CONST$_{16}$)
	Rd	Rs	I_{16}	$\times$(•, CONST$_{2^k}$)
sra	Rd	Rs$_1$	Rs$_2$	ARSHIFT(•, •)
	Rd	Rs	I_{16}	ARSHIFT(•, CONST$_{16}$)
	Rd	Rs	I_{16}	$/$(•, CONST$_{2^k}$)

MIPS tree patterns

label:				LABEL
b	label			JUMP(NAME, [•])
jr	Rs			JUMP(•, [•])
beq	Rs$_1$	Rs$_2$	label	CJUMP(EQ, •, •, label, •)
	Rs$_1$	I_{16}	label	CJUMP(EQ, •, CONST$_{16}$, label, •)
				CJUMP(EQ, CONST$_{16}$, •, label, •)
bne	Rs$_1$	Rs$_2$	label	CJUMP(NE, •, •, label, •)
	Rs$_1$	I_{16}	label	CJUMP(NE, •, CONST$_{16}$, label, •)
				CJUMP(NE, CONST$_{16}$, •, label, •)
jal	label			CALL(NAME, [•])

MIPS tree patterns

blt	Rs_1	Rs_2	label	CJUMP(LT, •, •, label, •)
	Rs_1	I_{16}	label	CJUMP(LT, •, CONST_{16}, label, •)
bgt	Rs_1	Rs_2	label	CJUMP(GT, •, •, label, •)
	Rs_1	I_{16}	label	CJUMP(GT, •, CONST_{16}, label, •)
ble	Rs_1	Rs_2	label	CJUMP(LE, •, •, label, •)
	Rs_1	I_{16}	label	CJUMP(LE, •, CONST_{16}, label, •)
bge	Rs_1	Rs_2	label	CJUMP(GE, •, •, label, •)
	Rs_1	I_{16}	label	CJUMP(GE, •, CONST_{16}, label, •)
bltu	Rs_1	Rs_2	label	CJUMP(ULT, •, •, label, •)
	Rs_1	I_{16}	label	CJUMP(ULT, •, CONST_{16}, label, •)
bleu	Rs_1	Rs_2	label	CJUMP(ULE, •, •, label, •)
	Rs_1	I_{16}	label	CJUMP(ULE, •, CONST_{16}, label, •)
bgtu	Rs_1	Rs_2	label	CJUMP(UGT, •, •, label, •)
	Rs_1	I_{16}	label	CJUMP(UGT, •, CONST_{16}, label, •)
bgeu	Rs_1	Rs_2	label	CJUMP(UGE, •, •, label, •)
	Rs_1	I_{16}	label	CJUMP(UGE, •, CONST_{16}, label, •)

Tiling

- *Tiles* are a set of tree patterns for the target machine
- Goal is to cover the IR tree with nonoverlapping tiles

e.g., a[i] := x



lw r_1 a($fp)	add r_1 $fp a
sll r_2 r_i 2	lw r_1 (r_1)
add r_1 r_1 r_2	sll r_2 r_i 2
lw r_2 x($fp)	add r_1 r_1 r_2
sw r_2 (r_1)	add r_2 $fp x
	lw r_2 (r_2)
	sw r_2 (r_1)

Optimal and optimum tilings

Optimum tiling: least cost instruction sequence

- shortest
- fewest cycles

Optimum tiling costs sum to lowest possible value

Optimal: no 2 adjacent tiles combine into 1 tile of lower cost

optimum $\Rightarrow$ optimal
optimal $\not\Rightarrow$ optimum

CISC instructions have complex tiles $\Rightarrow$ optimal $\not\approx$ optimum
RISC instructions have small tiles $\Rightarrow$ optimal $\approx$ optimum

Optimal tiling

Maximal "munch":

1. Start at root of tree
2. Tile root with largest tile that fits
3. Repeat for each subtree

Optimum tiling

Dynamic programming

- Assign a cost to every tree node: sum of instruction costs of best tiling for that node (including best tilings for children)

Example:



Tile	Instruction	Tile Cost	Leaves Cost	Total Cost
+(●, ●)	add	1	1+1	3
+(●, CONST 2)	add	1	1+0	2
+(CONST 1, ●)	add	1	0+1	2

CISC machines

- few registers (Pentium has 6 general, SP and FP)

  allocate TEMP nodes freely, assume good register allocation
- different register classes, some operations only on certain registers (Pentium allows mul/div only on eax, high-order bits into edx)

  $$t_1 \leftarrow t_2 \times t_3 \equiv \begin{array}{l} \text{eax} \leftarrow t_1 \\ \text{eax} \leftarrow \text{eax} \times t_2\text{; edx} \leftarrow \\ t_3 \quad \leftarrow \text{eax} \end{array}$$

  register allocator removes redundant moves
- 2-address instructions

  $$t_1 \leftarrow t_2 + t_3 \equiv \begin{array}{l} t_1 \leftarrow t_2 \\ t_1 \leftarrow t_1 + t_3 \end{array}$$

  register allocator removes redundant moves

CISC machines (cont.)

- arithmetic operations can address memory

  spill phase of register allocator will handle as

  $$\begin{array}{lll} \text{eax} & \leftarrow \text{[ebp-8]} & \\ \text{eax} & \leftarrow \text{eax} + \text{ecx} & \equiv \text{[ebp-8]} \leftarrow \text{[ebp-8]} + \text{ecx} \\ \text{[ebp-8]} & \leftarrow \text{eax} & \end{array}$$
- several memory addressing modes
- variable-length instructions
- instructions with side-effects such as “auto-increment” addressing