

# 6.035

Fall 2000

## Lectures 11 & 12: Program Analysis

Analysis and Transformations

## Analysis and Transformations

- Program Analysis
  - Discover properties of program
- Transformations
  - Use analysis results to transform program
  - Goal: improve some aspect of program
    - number of executed instructions, number of cycles
    - cache hit rate
    - memory space (code or data)
    - power


Martin Rogard

2

6.035 ©MIT Fall 1998

## Control Flow Graph

```
into add(n, k) {  
  s = 0; a = 4; i = 0;  
  if (k == 0) b = 1;  
  else b = 2;  
  while (i < n) {  
    s = s + a*b;  
    i = i + 1;  
  }  
  return s;  
}
```



Martin Rogard

3

6.035 ©MIT Fall 1998

## Control Flow Graph

- Nodes Represent Computation
  - Each Node is a Basic Block
  - Basic Block is a Sequence of Instructions with
    - No Branches Out Of Middle of Basic Block
    - No Branches Into Middle of Basic Block
    - Basic Blocks should be maximal
  - Execution of basic block starts with first instruction
  - Includes all instructions in basic block
- Edges Represent Control Flow

Martin Rogard

4

6.035 ©MIT Fall 1998

## Two Kinds of Variables

- Temporaries Introduced By Compiler
  - Transfer values only within basic block
  - Introduced as part of instruction flattening
  - Introduced by optimizations/transformations
- Program Variables
  - Declared in original program
  - May transfer values between basic blocks

Martin Rogard

5

6.035 ©MIT Fall 1998

## Basic Block Optimizations

- |   |  |
|---|--|
| • Common Sub-Expression Elimination <ul style="list-style-type: none"><li>– <math>a = (x+y)+z</math>; <math>b = x+y</math>;</li><li>– <math>t = x+y</math>; <math>a = t+z</math>; <math>b = t</math>;</li></ul> | • Copy Propagation <ul style="list-style-type: none"><li>– <math>a = x+y</math>; <math>b = a</math>; <math>c = b+z</math>;</li><li>– <math>a = x+y</math>; <math>b = a</math>; <math>c = a+z</math>;</li></ul> |
| • Constant Propagation <ul style="list-style-type: none"><li>– <math>x = 5</math>; <math>b = x+y</math>;</li><li>– <math>b = 5+y</math>;</li></ul>  | • Dead Code Elimination <ul style="list-style-type: none"><li>– <math>a = x+y</math>; <math>b = a</math>; <math>c = a+z</math>;</li><li>– <math>a = x+y</math>; <math>c = a+z</math></li></ul>                 |
| • Algebraic Identities <ul style="list-style-type: none"><li>– <math>a = x * 1</math>;</li><li>– <math>a = x</math>;</li></ul>  | • Strength Reduction <ul style="list-style-type: none"><li>– <math>t = i * 4</math>;</li><li>– <math>t = i &lt;&lt; 2</math>;</li></ul>  |

Martin Rogard

6

6.035 ©MIT Fall 1998

## Value Numbering

- Normalize basic block so that all statements are of the form
  - $\text{var} = \text{var op var}$  (where op is a binary operator)
  - $\text{var} = \text{op var}$  (where op is a unary operator)
  - $\text{var} = \text{var}$
- Simulate execution of basic block
  - Assign a virtual value to each variable
  - Assign a virtual value to each expression
  - Assign a temporary variable to hold value of each computed expression

Martin Riegard

7

6.035 ©MIT Fall 1998

## Value Numbering for CSE

- As simulate execution of program
- Generate a new version of program
  - Each new value assigned to temporary
    - $a = x+y$ ; becomes  $a = x+y$ ;  $t = a$ ;
  - Temporary preserves value for use later in program even if original variable rewritten
    - $a = x+y$ ;  $a = a+z$ ;  $b = x+y$  becomes
    - $a = x+y$ ;  $t = a$ ;  $a = a+z$ ;  $b = t$ ;

Martin Riegard

8

6.035 ©MIT Fall 1998

## CSE Example

- Original
  - $a = x+y$
  - $b = a+z$
  - $b = b+y$
  - $c = a+z$
- After CSE
  - $a = x+y$
  - $b = a+z$
  - $t = b$
  - $b = b+y$
  - $c = t$
- Issues
  - Temporaries store values for use later
  - CSE with different names
    - $a = x$ ;  $b = x+y$ ;  $c = a+y$ ;
  - Excessive Temp Generation and Use

Martin Riegard

9

6.035 ©MIT Fall 1998

Original Basic Block	New Basic Block	
$a = x+y$ $b = a+z$ $b = b+y$ $c = a+z$	$a = x+y$ $t1 = a$ $b = a+z$ $t2 = b$ $b = b+y$ $t3 = b$ $c = t2$	
Var to Val	Exp to Val	Exp to Tmp
$x \rightarrow v1$ $y \rightarrow v2$ $a \rightarrow v3$ $z \rightarrow v4$ $b \rightarrow v6$ $c \rightarrow v5$	$v1+v2 \rightarrow v3$ $v3+v4 \rightarrow v5$ $v5+v2 \rightarrow v6$	$v1+v2 \rightarrow t1$ $v3+v4 \rightarrow t2$ $v5+v2 \rightarrow t3$

Martin Riegard

10

6.035 ©MIT Fall 1998

## Problems

- Algorithm has a temporary for each new value
  - $a = x+y$ ;  $t1 = a$
- Introduces
  - lots of temporaries
  - lots of copy statements to temporaries
- In many cases, temporaries and copy statements are unnecessary
- So we eliminate them with copy propagation and dead code elimination

Martin Riegard

11

6.035 ©MIT Fall 1998

## Copy Propagation

- Once again, simulate execution of program
- If can, use original variable instead of temporary
  - $a = x+y$ ;  $b = x+y$ ;
  - After CSE becomes  $a = x+y$ ;  $t = a$ ;  $b = t$ ;
  - After CP becomes  $a = x+y$ ;  $b = a$ ;
- Key idea: determine when original variables are NOT overwritten between computation of stored value and use of stored value

Martin Riegard

12

6.035 ©MIT Fall 1998

## Copy Propagation Maps

- Maintain two maps
  - tmp to var: tells which variable to use instead of a given temporary variable
  - var to set: inverse of tmp to var. tells which temps are mapped to a given variable by tmp to var

Martin Ragard

13

6.035 ©MIT Fall 1998

## Copy Propagation Example

- Original
  - $a = x + y$
  - $b = a + z$
  - $c = x + y$
  - $a = b$
- After CSE
  - $a = x + y$
  - $t1 = a$
  - $b = a + z$
  - $t2 = b$
  - $c = t1$
  - $a = b$
- After CSE and Copy Propagation
  - $a = x + y$
  - $t1 = a$
  - $b = a + z$
  - $t2 = b$
  - $c = a$
  - $a = b$

Martin Ragard

14

6.035 ©MIT Fall 1998

## Copy Propagation Example

Basic Block  
After CSE

$a = x + y$   
 $t1 = a$

tmp to var  
 $t1 \mapsto a$

Basic Block After  
CSE and Copy Prop

$a = x + y$   
 $t1 = a$

var to set  
 $a \in \{t1\}$

Martin Ragard

15

6.035 ©MIT Fall 1998

## Copy Propagation Example

Basic Block  
After CSE

$a = x + y$   
 $t1 = a$   
 $b = a + z$   
 $t2 = b$

tmp to var  
 $t1 \mapsto a$   
 $t2 \mapsto b$

Basic Block After  
CSE and Copy Prop

$a = x + y$   
 $t1 = a$   
 $b = a + z$   
 $t2 = b$

var to set  
 $a \in \{t1\}$   
 $b \in \{t2\}$

Martin Ragard

16

6.035 ©MIT Fall 1998

## Copy Propagation Example

Basic Block  
After CSE

$a = x + y$   
 $t1 = a$   
 $b = a + z$   
 $t2 = b$   
 $c = t1$

tmp to var  
 $t1 \mapsto a$   
 $t2 \mapsto b$

Basic Block After  
CSE and Copy Prop

$a = x + y$   
 $t1 = a$   
 $b = a + z$   
 $t2 = b$

var to set  
 $a \in \{t1\}$   
 $b \in \{t2\}$

Martin Ragard

17

6.035 ©MIT Fall 1998

## Copy Propagation Example

Basic Block  
After CSE

$a = x + y$   
 $t1 = a$   
 $b = a + z$   
 $t2 = b$   
 $c = t1$

tmp to var  
 $t1 \mapsto a$   
 $t2 \mapsto b$

Basic Block After  
CSE and Copy Prop

$a = x + y$   
 $t1 = a$   
 $b = a + z$   
 $t2 = b$   
 $c = a$

var to set  
 $a \in \{t1\}$   
 $b \in \{t2\}$

Martin Ragard

18

6.035 ©MIT Fall 1998

## Copy Propagation Example

Basic Block  
After CSE

```
a = x+y
t1 = a
b = a+z
t2 = b
c = t1
a = b
```

tmp to var

```
t1 ← a
t2 ← b
```

Basic Block After  
CSE and Copy Prop

```
a = x+y
t1 = a
b = a+z
t2 = b
c = a
a = b
```

var to set

```
a ← {t1}
b ← {t2}
```

Martin Rogard

19

6.035 ©MIT Fall 1998

## Copy Propagation Example

Basic Block  
After CSE

```
a = x+y
t1 = a
b = a+z
t2 = b
c = t1
a = b
```

tmp to var

```
t1 ← t1
t2 ← b
```

Basic Block After  
CSE and Copy Prop

```
a = x+y
t1 = a
b = a+z
t2 = b
c = a
a = b
```

var to set

```
a ← {}
b ← {t2}
```

Martin Rogard

20

6.035 ©MIT Fall 1998

## Dead Code Elimination

- Copy propagation keeps all temps around
- May be temps that are never read
- Dead Code Elimination removes them

Basic Block After  
CSE and Copy Prop

```
a = x+y
t1 = a
b = a+z
t2 = b
c = a
a = b
```

Basic Block After  
CSE and Copy Prop

```
a = x+y
b = a+z
c = a
a = b
```

Martin Rogard

21

6.035 ©MIT Fall 1998

## Dead Code Elimination

- Basic Idea
  - Process Code In Reverse Execution Order
  - Maintain a set of variables that are needed later in computation
  - If encounter an assignment to a temporary that is not needed, remove assignment

Martin Rogard

22

6.035 ©MIT Fall 1998

Basic Block After  
CSE and Copy Prop

```
a = x+y
t1 = a
b = a+z
t2 = b
c = a
⇒ a = b
```

Needed Set  
{b}

Martin Rogard

23

6.035 ©MIT Fall 1998

Basic Block After  
CSE and Copy Prop

```
a = x+y
t1 = a
b = a+z
t2 = b
⇒ c = a
a = b
```

Needed Set  
{a, b}

Martin Rogard

24

6.035 ©MIT Fall 1998

Basic Block After  
CSE and Copy Prop

```
a = x+y
t1 = a
b = a+z
⇒ t2 = b
c = a
a = b
```

Needed Set  
{a, b}

Martin Regard

25

6.035 ©MIT Fall 1998

Basic Block After  
CSE and Copy Prop

```
a = x+y
t1 = a
b = a+z
⇒ c = a
a = b
```

Needed Set  
{a, b}

Martin Regard

26

6.035 ©MIT Fall 1998

Basic Block After  
CSE and Copy Prop

```
a = x+y
t1 = a
⇒ b = a+z

c = a
a = b
```

Needed Set  
{a, b, z}

Martin Regard

27

6.035 ©MIT Fall 1998

Basic Block After  
CSE and Copy Prop

```
⇒ a = x+y
t1 = a
b = a+z

c = a
a = b
```

Needed Set  
{a, b, z}

Martin Regard

28

6.035 ©MIT Fall 1998

Basic Block After  
CSE and Copy Prop

```
⇒ a = x+y
b = a+z

c = a
a = b
```

Needed Set  
{a, b, z}

Martin Regard

29

6.035 ©MIT Fall 1998

Basic Block After , CSE Copy Propagation,  
and Dead Code Elimination

```
⇒ a = x+y
b = a+z

c = a
a = b
```

Needed Set  
{a, b, z}

Martin Regard

30

6.035 ©MIT Fall 1998

## Interesting Properties

- Analysis and Transformation Algorithms  
Simulate Execution of Program
  - CSE and Copy Propagation go forward
  - Dead Code Elimination goes backwards
- Transformations stacked
  - Group of basic transformations
  - Work together to get good result
  - Often, one transformation creates inefficient code that is cleaned up by following transformations

Martin Rogard

31

6.035 ©MIT Fall 1998

## Other Basic Block Transformations

- Constant Propagation
  - $a \ll 2 = a * 4; a + a + a = 3 * a;$
- Strength Reduction
  - $a = a * 1; b = b + 0;$
- Algebraic Simplification
  - $a = a * 1; b = b + 0;$
- Do these in unified transformation framework, not in earlier or later phases

Martin Rogard

32

6.035 ©MIT Fall 1998

## Dataflow Analysis

- Used to determine properties of program that involve multiple basic blocks
- Typically used to enable transformations
  - common sub-expression elimination
  - constant and copy propagation
  - dead code elimination
- Analysis and transformation often come in pairs

Martin Rogard

33

6.035 ©MIT Fall 1998

## Reaching Definitions


- Concept of definition and use
  - $a = x + y$
  - is a definition of  $a$
  - is a use of  $x$  and  $y$
- A definition reaches a use if
  - value written by definition
  - may be read by use

Martin Rogard

34

6.035 ©MIT Fall 1998

## Reaching Definitions



Martin Rogard

35

6.035 ©MIT Fall 1998

## Reaching Definitions and Constant Propagation


- Is a use of a variable a constant?
  - Check all reaching definitions
  - If all assign variable to same constant
  - Then use is in fact a constant
- Can replace variable with constant

Martin Rogard

36

6.035 ©MIT Fall 1998

### Is a Constant in $s = s + a * b$ ?




**Yes!**  
On all reaching  
definitions  
 $a = 4$

Martin Ragard

37

6.035 ©MIT Fall 1998

### Constant Propagation Transform




**Yes!**  
On all reaching  
definitions  
 $a = 4$

Martin Ragard

38

6.035 ©MIT Fall 1998

### Is b Constant in $s = s + a * b$ ?



**No!**  
One reaching  
definition with  
 $b = 1$   
One reaching  
definition with  
 $b = 2$

Martin Ragard

39

6.035 ©MIT Fall 1998


### Computing Reaching Definitions

- Compute with sets of definitions
  - represent sets using bit vectors
  - each definition has a position in bit vector
- At each basic block, compute
  - definitions that reach start of block
  - definitions that reach end of block
- Do computation by simulating execution of program until reach fixed point

Martin Ragard

40

6.035 ©MIT Fall 1998



Martin Ragard

41

6.035 ©MIT Fall 1998

### Formalizing Analysis

- Each basic block has
  - IN - set of definitions that reach beginning of block
  - OUT - set of definitions that reach end of block
  - GEN - set of definitions generated in block
  - KILL - set of definitions killed in block
- $GEN[s = s + a * b; i = i + 1;] = 0000011$
- $KILL[s = s + a * b; i = i + 1;] = 1010000$
- Compiler scans each basic block to derive GEN and KILL sets

Martin Ragard

42

6.035 ©MIT Fall 1998

## Dataflow Equations

- $IN[b] = OUT[b_1] \cup \dots \cup OUT[b_n]$ 
  - where  $b_1, \dots, b_n$  are predecessors of  $b$  in CFG
- $OUT[b] = (IN[b] - KILL[b]) \cup GEN[b]$
- $IN[entry] = 0000000$
- Result: system of equations

Martin Ragar

43

6.035 ©MIT Fall 1998

## Solving Equations

- Use fixed point algorithm
- Initialize with solution of  $OUT[b] = 0000000$
- Repeatedly apply equations
  - $IN[b] = OUT[b_1] \cup \dots \cup OUT[b_n]$
  - $OUT[b] = (IN[b] - KILL[b]) \cup GEN[b]$
- Until reach fixed point
- Until equation application has no further effect
- Use a worklist to track which equation applications may have a further effect

Martin Ragar

44

6.035 ©MIT Fall 1998

## Reaching Definitions Algorithm

```
for all nodes n in N OUT[n] = emptyset; // OUT[n] = GEN[n];
Changed = D; // D = all definitions in graph
while (Changed != emptyset)
  choose a node n in Changed;
  Changed = Changed - { n };
  IN[n] = emptyset;
  for all nodes p in predecessors(n) IN[n] = IN[p] U OUT[p];
  OUT[n] = GEN[n] U (IN[n] - KILL[n]);
  if (OUT[n] changed)
    for all nodes s in successors(n) Changed = Changed U { s };
```

Martin Ragar

45

6.035 ©MIT Fall 1998

## Questions

- Does the algorithm halt?
  - yes, because transfer function is monotonic
  - if increase IN, increase OUT
  - in limit, all bits are 1
- If bit is 1, is there always an execution in which corresponding definition reaches basic block?
- If bit is 0, does the corresponding definition ever reach basic block?
- Concept of conservative analysis

Martin Ragar

46

6.035 ©MIT Fall 1998

## Available Expressions

- An expression  $x+y$  is available at a point  $p$  if
  - every path from the initial node to  $p$  evaluates  $x+y$  before reaching  $p$ ,
  - and there are no assignments to  $x$  or  $y$  after the evaluation but before  $p$ .
- Available Expression information can be used to do global (across basic blocks) CSE
- If expression is available at use, no need to reevaluate it

Martin Ragar

47

6.035 ©MIT Fall 1998

## Computing Available Expressions



- Represent sets of expressions using bit vectors
- Each expression corresponds to a bit
- Run dataflow algorithm similar to reaching definitions
- Big difference
  - definition reaches a basic block if it comes from ANY predecessor in CFG
  - expression is available at a basic block only if it is available from ALL predecessors in CFG

Martin Ragar

48

6.035 ©MIT Fall 1998





### Formalizing Analysis

- Each basic block has
  - IN - set of expressions available at start of block
  - OUT - set of expressions available at end of block
  - GEN - set of expressions computed in block
  - KILL - set of expressions killed in in block
- $GEN[x = z; b = x+y] = 1000$
- $KILL[x = z; b = x+y] = 1001$
- Compiler scans each basic block to derive GEN and KILL sets

Martin Ragard 51 6.035 ©MIT Fall 1998

### Dataflow Equations

- $IN[b] = OUT[b_1] \text{ intersect } \dots \text{ intersect } OUT[b_n]$ 
  - where  $b_1, \dots, b_n$  are predecessors of  $b$  in CFG
- $OUT[b] = (IN[b] - KILL[b]) \cup GEN[b]$
- $IN[\text{entry}] = 0000$
- Result: system of equations

Martin Ragard 52 6.035 ©MIT Fall 1998

### Solving Equations

- Use fixed point algorithm
- $IN[\text{entry}] = 0000$
- Initialize  $OUT[b] = 1111$
- Repeatedly apply equations
  - $IN[b] = OUT[b_1] \text{ intersect } \dots \text{ intersect } OUT[b_n]$
  - $OUT[b] = (IN[b] - KILL[b]) \cup GEN[b]$
- Use a worklist algorithm to reach fixed point

Martin Ragard 53 6.035 ©MIT Fall 1998

### Available Expressions Algorithm

for all nodes  $n$  in  $N$   $OUT[n] = E$ ; //  $OUT[n] = E - KILL[n]$ ;  
 $IN[\text{Entry}] = \text{emptyset}$ ;  $OUT[\text{Entry}] = GEN[\text{Entry}]$ ;  
 $\text{Changed} = N - \{ \text{Entry} \}$ ; //  $N$  = all nodes in graph  
 while ( $\text{Changed} \neq \text{emptyset}$ )  
   choose a node  $n$  in  $\text{Changed}$ ;  
    $\text{Changed} = \text{Changed} - \{ n \}$ ;  
    $IN[n] = E$ ; //  $E$  is set of all expressions  
   for all nodes  $p$  in  $\text{predecessors}(n)$   
      $IN[n] = IN[n] \text{ intersect } OUT[p]$ ;  
    $OUT[n] = GEN[n] \cup (IN[n] - KILL[n])$ ;  
   if ( $OUT[n]$  changed)  
     for all nodes  $s$  in  $\text{successors}(n)$   $\text{Changed} = \text{Changed} \cup \{ s \}$ ;

Martin Ragard 54 6.035 ©MIT Fall 1998

## Questions

- Does algorithm always halt?
- If expression is available in some execution, is it always marked as available in analysis?
- If expression is not available in some execution, can it be marked as available in analysis?
- In what sense is algorithm conservative?

Martin Ragard

55

6.035 ©MIT Fall 1998

## Duality In Two Algorithms

- Reaching definitions
  - Confluence operation is set union
  - OUT[b] initialized to empty set
- Available expressions
  - Confluence operation is set intersection
  - OUT[b] initialized to set of available expressions
- General framework for dataflow algorithms.
- Build parameterized dataflow analyzer once, use for all dataflow problems

Martin Ragard

56

6.035 ©MIT Fall 1998

## Liveness Analysis

- A variable  $v$  is live at point  $p$  if
  - $v$  is used along some path starting at  $p$ , and
  - no definition of  $v$  along the path before the use.
- When is a variable  $v$  dead at point  $p$ ?
  - No use of  $v$  on any path from  $p$  to exit node, or
  - If all paths from  $p$  redefine  $v$  before using  $v$ .

Martin Ragard

57

6.035 ©MIT Fall 1998

## What Use is Liveness Information?

- Register allocation.
  - If a variable is dead, can reassign its register
- Dead code elimination.
  - Eliminate assignments to variables not read later.
  - But must not eliminate last assignment to variable (such as instance variable) visible outside CFG.
  - Can eliminate other dead assignments.
  - Handle by making all externally visible variables live on exit from CFG

Martin Ragard

58

6.035 ©MIT Fall 1998

## Conceptual Idea of Analysis

- Simulate execution
- But start from exit and go backwards in CFG
- Compute liveness information from end to beginning of basic blocks


Martin Ragard

59

6.035 ©MIT Fall 1998

## Liveness Example

- Assume  $a, b, c$  visible outside method
- So are live on exit
- Assume  $x, y, z, t$  not visible
- Represent Liveness Using Bit Vector
  - order is  $abcxyz$




Martin Ragard

60

6.035 ©MIT Fall 1998

## Dead Code Elimination

- Assume a,b,c visible outside method
- So are live on exit
- Assume x,y,z,t not visible
- Represent Liveness Using Bit Vector
  - order is abxyz



Martin Rogard

61

6.035 ©MIT Fall 1998

## Formalizing Analysis

- Each basic block has
  - IN - set of variables live at start of block
  - OUT - set of variables live at end of block
  - USE - set of variables with upwards exposed uses in block
  - DEF - set of variables defined in block
- $USE[x = z; x = x+1;] = \{z\}$  (x not in USE)
- $DEF[x = z; x = x+1; y = 1;] = \{x, y\}$
- Compiler scans each basic block to derive GEN and KILL sets

Martin Rogard

62

6.035 ©MIT Fall 1998

## Algorithm

```

out[Exit] = emptyset; in[Exit] = use[n];
for all nodes n in N - { Exit } in[n] = emptyset;
Changed = N - { Exit };
while (Changed != emptyset)
    choose a node n in Changed;
    Changed = Changed - { n };
    out[n] = emptyset;
    for all nodes s in successors(n) out[s] = out[n] U in[p];
    in[n] = use[n] U (out[n] - def[n]);
    if (in[n] changed)
        for all nodes p in predecessors(n)
            Changed = Changed U { p };
    
```

Martin Rogard

63

6.035 ©MIT Fall 1998

## Similar to Other Dataflow Algorithms

- Backwards analysis, not forwards
- Still have transfer functions
- Still have confluence operators
- Can generalize framework to work for both forwards and backwards analyses

Martin Rogard

64

6.035 ©MIT Fall 1998

## Analysis Information Inside Basic Blocks

- One detail:
  - Given dataflow information at IN and OUT of node
  - Also need to compute information at each statement of basic block
  - Simple propagation algorithm usually works fine
  - Can be viewed as restricted case of dataflow analysis

Martin Rogard

65

6.035 ©MIT Fall 1998

## Loop Optimizations


- Important because lots of computation occurs in loops
- We will study two optimizations
  - Loop-invariant code motion
  - Induction variable elimination

Martin Rogard

66

6.035 ©MIT Fall 1998

## What is a Loop?




Martin Regard

67

6.035 ©MIT Fall 1998

## What is a Loop?

- Set of nodes
- Loop header
  - Single node
  - All iterations of loop go through header
- Back edge




Martin Regard

68

6.035 ©MIT Fall 1998

## Anamalous Situations

- Two back edges, two loops, one header
- Compiler merges loops
- No loop header, no loop



Martin Regard

69

6.035 ©MIT Fall 1998

## Defining Loops With Dominators

- Concept of dominator
  - Node  $n$  dominates a node  $m$  if all paths from start node to  $m$  go through  $n$
  - “The road to the Super Bowl goes through St. Louis”
  - Conclusion? St. Louis dominates the Super Bowl!
- If  $d_1$  and  $d_2$  both dominate  $n$ , then either
  - $d_1$  dominates  $d_2$ , or
  - $d_2$  dominates  $d_1$  (but not both – look at path from start)
- Immediate dominator  $n$  – last dominator of  $n$  on any path from start node

Martin Regard

70

6.035 ©MIT Fall 1998

## Dominator Tree


- Nodes are nodes of control flow graph
- Edge from  $d$  to  $n$  if  $d$  immediate dominator of  $n$
- This structure is a tree
- Rooted at start node

Martin Regard

71

6.035 ©MIT Fall 1998

## Example Dominator Tree



Martin Regard

72

6.035 ©MIT Fall 1998

## Defining Loops


- Unique entry point – header
- At least one path back to header
- Find edges whose heads dominate tails
  - These edges are back edges of loops
  - Given back edge  $d \rightarrow n$
  - Loop consists of  $d$  plus all nodes that can reach  $n$  without going through  $d$  (all nodes “between”  $d$  and  $n$ )
  - $d$  is loop header

Martin Regard

73

6.035 ©MIT Fall 1998

## Two Loops In Example



Martin Regard

74

6.035 ©MIT Fall 1998

## Loop Construction Algorithm

```

insert(m)
  if  $m \notin \text{loop}$  then
     $\text{loop} = \text{loop} \cup \{m\}$ 
    push  $m$  onto stack
loop(d,n)
   $\text{loop} = \emptyset$ ;  $\text{stack} = \emptyset$ ; insert( $n$ );
  while stack not empty do
     $m = \text{pop stack}$ ;
    for all  $p \in \text{pred}(m)$  do insert( $p$ )
  
```


Martin Regard

75

6.035 ©MIT Fall 1998

## Nested Loops

- If two loops do not have same header then
  - Either one loop (inner loop) contained in other (outer loop)
  - Or two loops are disjoint
- If two loops have same header, typically unioned and treated as one loop



Two loops:  
 $\{1,2\}$  and  $\{1,3\}$   
 Unioned:  $\{1,2,3\}$


Martin Regard

76

6.035 ©MIT Fall 1998

## Loop Preheader

- Many optimizations stick code before loop
- Put a special node (loop preheader) before loop to hold this code



Martin Regard

77

6.035 ©MIT Fall 1998

## Loop Optimizations


- Now that we have the loop, can optimize it!
- Loop invariant code motion
  - Stick loop invariant code in the header

Martin Regard

78

6.035 ©MIT Fall 1998

## Induction Variable Elimination



Martin Ragard

79

6.035 ©MIT Fall 1998

## Detecting Loop Invariant Code

- A statement is invariant if operands are
  - Constant,
  - Have all reaching definitions outside loop, or
  - Have exactly one reaching definition, and that definition comes from an invariant statement
- Concept of exit node of loop
  - node with successors outside loop

Martin Ragard

80

6.035 ©MIT Fall 1998

## Loop Invariant Code Detection Algorithm

for all statements in loop  
 if operands are constant or have all reaching definitions outside loop, mark statement as invariant  
do  
 for all statements in loop not already marked invariant  
 if operands are constant, have all reaching definitions outside loop, or have exactly one reaching definition from invariant statement then  
 mark statement as invariant  
until find no more invariant statements

Martin Ragard

81

6.035 ©MIT Fall 1998

## Loop Invariant Code Motion

- Conditions for moving a statement  $s: x := y + z$  into loop header:
  - $s$  dominates all exit nodes of loop
    - If it doesn't, some use after loop might get wrong value
    - Alternate condition: definition of  $x$  from  $s$  reaches no use outside loop (but moving  $s$  may increase run time)
  - No other statement in loop assigns to  $x$ 
    - If one does, assignments might get reordered
  - No use of  $x$  in loop is reached by definition other than  $s$ 
    - If one is, movement may change value read by use


Martin Ragard

82

6.035 ©MIT Fall 1998

## Order of Statements in Preheader

Preserve data dependences from original program  
 (can use order in which discovered by algorithm)



Martin Ragard

83

6.035 ©MIT Fall 1998

## What is an Induction Variable?


- Base induction variable
  - Only assignments in loop are of form  $i = i \pm c$
- Derived induction variables
  - Value is a linear function of a base induction variable
  - Within loop,  $j = c*i + d$ , where  $i$  is a base induction variable
  - Very common in array index expressions – an access to  $a[i]$  produces code like  $p = a + 4*i$

Martin Ragard

84

6.035 ©MIT Fall 1998

## Strength Reduction for Derived Induction Variables




Martin Ragard

85

6.035 ©MIT Fall 1998

## Elimination of Superfluous Induction Variables



Martin Ragard

86

6.035 ©MIT Fall 1998

## Three Algorithms

- Detection of induction variables
  - Find base induction variables
  - Each base induction variable has a family of derived induction variables, each of which is a linear function of base induction variable
- Strength reduction for derived induction variables
- Elimination of superfluous induction variables

Martin Ragard

87

6.035 ©MIT Fall 1998

## Output of Induction Variable Detection Algorithm

- Set of induction variables
  - base induction variables
  - derived induction variables
- For each induction variable  $j$ , a triple  $\langle i, c, d \rangle$ 
  - $i$  is a base induction variable
  - value of  $j$  is  $i * c + d$
  - $j$  belongs to family of  $i$

Martin Ragard

88

6.035 ©MIT Fall 1998

## Induction Variable Detection Algorithm

Scan loop to find all base induction variables  
do

Scan loop to find all variables  $k$  with one assignment of form  $k = j * b$  where  $j$  is an induction variable with triple  $\langle i, c, d \rangle$

make  $k$  an induction variable with triple  $\langle i, c * b, d \rangle$

Scan loop to find all variables  $k$  with one assignment of form  $k = j \pm b$  where  $j$  is an induction variable with triple  $\langle i, c, d \rangle$

make  $k$  an induction variable with triple  $\langle i, c, b \pm d \rangle$

until no more induction variables found

Martin Ragard

89

6.035 ©MIT Fall 1998

## Strength Reduction Algorithm

for all derived induction variables  $j$  with triple  $\langle i, c, d \rangle$

Create a new variable  $s$

Replace assignment  $j = i * c + d$  with  $j = s$

Immediately after each assignment  $i = i + e$ , insert statement  $s = s + c * e$  ( $c * e$  is constant)

place  $s$  in family of  $i$  with triple  $\langle i, c, d \rangle$


Insert  $s = c * i + d$  into preheader

Martin Ragard

90

6.035 ©MIT Fall 1998

## Strength Reduction for Derived Induction Variables



Martin Regard

91

6.035 ©MIT Fall 1998

## Induction Variable Elimination

Choose a base induction variable  $i$  such that only uses of  $i$  are in

termination condition of the form  $i < n$

assignment of the form  $i = i + m$

Choose a derived induction variable  $k$  with  $\langle i, c, d \rangle$

Replace termination condition with  $k < c*n + d$

Martin Regard

92

6.035 ©MIT Fall 1998

## Induction Variable Wrapup

- There is lots more to induction variables
  - more general classes of induction variables
  - more general transformations involving induction variables

Martin Regard

93

6.035 ©MIT Fall 1998

## Summary

- Wide range of analyses and optimizations
- Dataflow Analyses and Corresponding Optimizations
  - reaching definitions, constant propagation
  - live variable analysis, dead code elimination
- Induction variable analyses and optimizations
  - Strength Reduction
  - Induction variable elimination
  - Important because of time spent in loops

Martin Regard

94

6.035 ©MIT Fall 1998