µC

File: µC.kicad_sch

Power

File: power.kicad_sch

In_Out

File: in_out_puts.kicad_sch

By default, everything is configured for the Nerf Laser Ops Deltaburst Blaster.
By cutting off the solder jumpers and re-soldering, the board can also be configured for the Nerf Laser Ops Alphapoint Blaster.
In addition, there are some new features that are optional, such as the camera(OV5060), an Accelorometer or an OLED display (SSD1306).

made by Nico Hütter

Sheet: /

File: LaserOps_PCB.kicad_sch

Title: Nerf-ATG

Size: A4	Date: 2025-04-13	**Rev: 1.0**
KiCad E.D.A. 9.0.0		Id: 1/4



made by Nico Hütter

Sheet: /Power/

File: power.kicad_sch

Title: Nerf-ATG

Size: A4	Date: 2025-04-13	**Rev: 1.0**
KiCad E.D.A. 9.0.0		Id: 2/4



made by Nico Hütter

Sheet: /In_Out/

File: in_out_puts.kicad_sch

Title: Nerf−ATG

Size: A4	Date: 2025−04−13	Rev: 1.0
KiCad E.D.A. 9.0.0		Id: 3/4

ESP32-S3-wroom-u1-N16R8



Jumpers



USB-C



made by Nico Hütter

Sheet: /µC/

File: µC.kicad_sch

Title: Nerf-ATG

Size: A4	Date: 2025-04-13	Rev: 1.0
KiCad E.D.A. 9.0.0		Id: 4/4