Kiel Nicolai D. Orgas
BSIT 2-3
3/25/26

Object-Oriented Programming:
Midterm Seatwork #2 – Smart Wallet System

KIEL NICOLAI D. ORGAS BSIT 2-3 3/25/26

```
import java.util.Scanner;
public class SmartWalletSystemORGAS {
    public static void main (String [] args) {
        int ch = 0, bal = 5000, cashIn = 0, trans = 0, count = 1 ;
        Scanner input = new Scanner (system.in);
        while (ch != 4){
            System.out.println ("===== SMART WALLET =====");
            System.out.println ("1. View Balance");
            System.out.println ("2. Cash In");
            System.out.println ("3. Send Money");
            System.out.Exit ("4. Exit ");
            System.out.println ("transaction count : " + count);
            System.out.Print ("choice: ");

            ch = input.nextInt ();

            switch (ch) {
              case 1:
                System.out.println ("Your current balance is: " + bal);
                count ++ ;
            break;

            case 2:
              System.out.println ("current balance : " + bal ");
              System.out.print ("Type amount to cash-in: ");
              cashIn = input.nextint ();
              bal += cashIn;
              System.out.println("New Balance: " + bal);
                cashIn = 0;
            count ++;
            break;
```

```
case 3 :
    system.out.println ("Current balance : " + bal);
while (true) {
    System.out.print("Type amount to transfer (Minimum of 100,
Maximum of 1500): ");
    trans = input.nextInt ();

if (trans < 100) {
    System.out.println ("Amount is less than 100!");
} else if (trans > 1500) {
    System.out.println ("Amount is greater than 1500!");
} else if (trans > bal) {
    System.out.println("Amount exceeds current balance!");
} else {
    bal -= trans;
    System.out.println ("Transfer successful!");
    System.out.println ("New balance: " + bal);
    break;
  }
    }
    count++;
  break;
case 4:
    count = 1;
    System.out.println ("Session Terminated. Thank You!");
    break;
default:
    System.out.println ("Invalid option, please try again!");
    break;
  }
}
}
}
```

Kiel Nicolai D. Orgas
BSIT 2-3
3/25/26

Object-Oriented Programming:
Midterm Seatwork #2 – Smart Wallet System

2. Sample Execution

```
===== SMART WALLET MENU =====
1. View Balance
2. Cash In
3. Send Money
4. Exit
transaction count : 1
Choice : 1
Your current balance is : 5000
===== SMART WALLET MENU =====
1. View Balance
2. Cash In
3. Send Money
4. Exit
transaction count : 2
Choice : 2
Current balance : 5000
Type amount to cash in : 10000
New balance : 15000
===== SMART MENU =====
1. View Balance
2. Cash In
3. Send Money
4. Exit
Transaction count : 3
Choice : 3
current Balance : 15000
Type amount to transfer ( Minimum of 100, Maximum of 1500 ) : 99
Amount is less than 100!
Type amount to transfer (Minimum of 100, Maximum of 1500) : 150
Transfer successful!
New balance : 14850
```

```
===== SMART WALLET MENU =====
1. View Balance
2. Cash In
3. Send Money
4. Exit
transaction count : 4
Choice : 4
Session terminated. Thank you!
```

3. SHORT EXPLANATION

EXPLAIN:

- HOW THE WHILE LOOP KEEPS THE PROGRAM RUNNING.

  THE WHILE LOOP RUNS THE PROGRAM INDEFINITELY UNTIL THE CONDITION SET IS MET. FOR EXAMPLE IN THIS PROGRAM, THE PROGRAM WILL RUN AGAIN AFTER A TRANSACTION UNTIL THE USER ENTERS THE NUMBER 4, WHICH WILL TERMINATE OR END THE PROGRAM.

- HOW SWITCH-CASE CONTROLS MENU SELECTION

  SWITCH CASE CONTROLS MENU SELECTION BY CHOOSING WHAT VARIABLE TO USE IN DETERMING THE VALUE AND MAKING CASES BASED ON WHAT THAT VALUE IS AND EXECUTES THE BLOCK OF CODE UNDER THAT CASE.

- HOW IF-ELSE VALIDATES TRANSACTIONS

  IF-ELSE VALIDATES TRANSACTION BY CHECKING THROUGH THE CONDITION SET BY THE IF-ELSE LADDER. THE PROGRAM CHECKS THE CONDITION AND EXECUTES IT IF TRUE IF NO IS NOT, IT WILL MOVE ON TO THE NEXT CONDITION UNTIL IT ARRIVES TO THE ELSE BLOCK IF NONE OF THE CONDITIONS ARE MET.