

Legend

optimisation
algorithm
kernels
testbed
notes
post
processing

<<Interface>>
ITestbenchBase

#pde_string: string
#exec_time: float
#mem_consumption: int

+exact(x): float
+approx(x): float
+normL2(): float
+solve(): None

<<Interface>>
IOptAlgoBase

#init_guess: np.array
#max_fe: int
#min_err: float

+opt(function): (list, list, list list)

<<Interface>>
IKernelBase

#kernel_type: string
#kernel_size: int

+solution(kernels, x): float
+solution_x0(kernels, x): float
+solution_x1(kernels, x): float
+soluiton_x0_x0(kernels, x): float
+solution_x0_x1(kernels, x): float
+solution_x1_x1(kernels, x): float

OptAlgo{NAME}

-__init__(init_guess, max_fe, min_err)
+opt(function): (list,list,list,list)

KernelGauss

-__init__()

KernelGsin

-__init__()

FemPdeBase

+show_gui: bool
#_ngs_ex: ngs.fem.CoefficientFunction
#_fes: ngs.comp.H1
#_gfu: ngs.comp.GridFunction
#_a: ngs.comp.BilinearForm
#_f: ngs.comp.LinearForm
#_g: ngs.fem.CoefficientFunction
#_space_flux: ngs.comp.HDiv
#_gf_flux: ngs.comp.GridFunction
#_mesh: ngs.comp.Mesh

-__init__(show_gui)
#_solveStep(): None
#_estimateError(): None

CiPdeBase

+pop_histroy: list
+fit_history: list
+cr_history: list
+f_history: list
#_nc: list
#_nb: list
#_xi: list
#_kappa: float
#_weight_reference: float
#_phi: list
#_sol_kernel: np.array
#_lx: np.array
#_ux: np.array

-__init__(opt_alog, kernel, nb, nc)
+fitness_func(kernel): float
+nc_weight(xi): float
#_ly(float): float
#_uy(float): float

FemPde0

+max_ndof: int

-__init__(show_gui, max_ndof)
^+solve(): None

CiPde0

+ max_gen: int

-__init__(opt_alog, kernel, nb, nc)
^+ fitness_func(kernel): float
^+ exact (x): float

Note:
set of classes where
each class represents a
PDE 0...N of the testbed

for every run in the
experimnet a new object
is created

Note:

different implementation
of optimisation algorithms
that are abstracted to a level so
they only use 4 parameters:
initial guess, maximum
number of iteration, minimum
error to terminate and the
function to optimise

the name of the class is
distinct where {NAME} is
substituded

<<Module>>
PostProc

drawGaussKernel(parameter, ggb): bool
drawGsinKernel(parameter, ggb): bool
saveExpObject(obj, filename): bool
loadExpObject(filename): dict
loadExpObjectFast(filename): dict
plotApprox3D(kernel, parameter,
ID, uD, name=None): None
calcRMSE(solve_dict): float
statsWilcoxon(a, b, alpha=0.05): string
plotFEDynamic(FEDynamic,
name=None): None
plotABSError3D(kernel, parameter,
pdeName, ID, uD,
name=None): None
plotError3D(kernel, parameter,
pdeName, ID, uD,
name=None): None
plotKernelAdaption(obj_dict, title,
name=None): None
calcSingleERT(rundata,target):(float, float)