

Apply Filters to SQL Queries

Project description

I was tasked with using SQL queries with filters to perform security-related tasks and ensure the system is safe and secure.

Retrieve after hours failed login attempts

I first checked whether any failed login attempts occurred after business hours (6pm):

```
MariaDB [organization]> SELECT * FROM log_in_attempts WHERE login_time > '18:00' AND success = FALSE;
```

event_id	username	login_date	login_time	country	ip_address	success
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
20	tshah	2022-05-12	18:56:36	MEXICO	192.168.109.50	0
28	aestrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
34	drosas	2022-05-11	21:02:04	US	192.168.45.93	0
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
52	cjackson	2022-05-10	22:07:07	CAN	192.168.58.57	0
69	wjaffrey	2022-05-11	19:55:15	USA	192.168.100.17	0
82	abernard	2022-05-12	23:38:46	MEX	192.168.234.49	0
87	apatel	2022-05-08	22:38:31	CANADA	192.168.132.153	0
96	ivelasco	2022-05-09	22:36:36	CAN	192.168.84.194	0
104	asundara	2022-05-11	18:38:07	US	192.168.96.200	0
107	bisles	2022-05-12	20:25:57	USA	192.168.116.187	0
111	aestrada	2022-05-10	22:00:26	MEXICO	192.168.76.27	0
127	abellmas	2022-05-09	21:20:51	CANADA	192.168.70.122	0
131	bisles	2022-05-09	20:03:55	US	192.168.113.171	0
155	cgriffin	2022-05-12	22:18:42	USA	192.168.236.176	0
160	jclark	2022-05-10	20:49:00	CANADA	192.168.214.49	0
199	yappiah	2022-05-11	19:34:48	MEXICO	192.168.44.232	0

```
19 rows in set (0.003 sec)
```

The SQL query ***SELECT * FROM log_in_attempts WHERE login_time > '18:00' AND success = FALSE;*** retrieves all records from the ***log_in_attempts*** table where the login attempt occurred after 6:00 PM (***login_time > '18:00'***) and the attempt was unsuccessful (***success = FALSE***). The ***SELECT **** statement fetches all columns for the matching records, providing a complete view of the relevant failed login attempts.

Retrieve login attempts on specific dates

Next, I checked for suspicious logins over a one day period (May 8 - May 9):

```
MariaDB [organization]> SELECT * FROM log_in_attempts WHERE login_date = '2022-05-08' OR login_date = '2022-05-09';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
24	arusso	2022-05-09	06:49:39	MEXICO	192.168.171.192	1
25	sbaelish	2022-05-09	07:04:02	US	192.168.33.137	1
26	apatel	2022-05-08	17:27:00	CANADA	192.168.123.105	1
28	aestrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
30	yappiah	2022-05-09	03:22:22	MEX	192.168.124.48	1
32	acook	2022-05-09	02:52:02	CANADA	192.168.142.239	0
36	asundara	2022-05-08	09:00:42	US	192.168.78.151	1
38	sbaelish	2022-05-09	14:40:01	USA	192.168.60.42	1
39	yappiah	2022-05-09	07:56:40	MEXICO	192.168.57.115	1
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
43	mcouliba	2022-05-08	02:35:34	CANADA	192.168.16.208	0
44	daquino	2022-05-08	07:02:35	CANADA	192.168.168.144	0
47	dkot	2022-05-08	05:06:45	US	192.168.233.24	1
49	asundara	2022-05-08	14:00:01	US	192.168.173.213	0
53	nmason	2022-05-08	11:51:38	CAN	192.168.133.188	1
56	acook	2022-05-08	04:56:30	CAN	192.168.209.130	1
58	ivelasco	2022-05-09	17:20:54	CAN	192.168.57.162	0
61	dtanaka	2022-05-09	09:45:18	USA	192.168.98.221	1

The SQL query retrieves all columns (*) from the table **log_in_attempts** for records where the **login_date** is either 2022-05-08 or 2022-05-09. The **WHERE** clause is used to filter the rows based on the specified conditions. By combining the two conditions with the **OR** operator, the query ensures that any log-in attempt matching either of these dates will be included in the results.

Retrieve login attempts outside of Mexico

After that, I queried any potential suspicious logins that occurred outside the country of Mexico

```
MariaDB [organization]> SELECT * FROM log_in_attempts WHERE NOT country LIKE 'MEX%';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
5	jrafael	2022-05-11	03:05:59	CANADA	192.168.86.232	0
7	eraab	2022-05-11	01:45:14	CAN	192.168.170.243	1
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
10	jrafael	2022-05-12	09:33:19	CANADA	192.168.228.221	0
11	sgilmore	2022-05-11	10:16:29	CANADA	192.168.140.81	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
13	mrh	2022-05-11	09:29:34	USA	192.168.246.135	1
14	sbaelish	2022-05-10	10:20:18	US	192.168.16.99	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
16	mcouliba	2022-05-11	06:44:22	CAN	192.168.172.189	1
17	pwashing	2022-05-11	02:33:02	USA	192.168.81.89	1
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
19	jhill	2022-05-12	13:09:04	US	192.168.142.245	1
21	iuduike	2022-05-11	17:50:00	US	192.168.131.147	1
25	sbaelish	2022-05-09	07:04:02	US	192.168.33.137	1
26	apatel	2022-05-08	17:27:00	CANADA	192.168.123.105	1
29	bisles	2022-05-11	01:21:22	US	192.168.85.186	0
31	acook	2022-05-12	17:36:45	CANADA	192.168.58.232	0
32	acook	2022-05-09	02:52:02	CANADA	192.168.142.239	0

The SQL query ***SELECT * FROM log_in_attempts WHERE NOT country LIKE 'MEX%';*** retrieves all records from the ***log_in_attempts*** table where the country column does not begin with ***"MEX."*** The ***LIKE*** operator is used to perform pattern matching, and the ***%*** symbol acts as a wildcard, matching any sequence of characters following ***"MEX."*** The ***NOT*** keyword negates the condition, so the query filters out rows where the country starts with ***"MEX."***

Retrieve employees in Marketing

After checking for suspicious logins, I was instructed to list all employees in the Marketing department who worked in any one of the East office buildings.

```
MariaDB [organization]> SELECT * FROM employees WHERE department = 'Marketing' AND office LIKE 'East%';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1052	a192b174c940	jdarosa	Marketing	East-195
1075	x573y883z772	fbautist	Marketing	East-267
1088	k865l965m233	rgosh	Marketing	East-157
1103	NULL	randerss	Marketing	East-460
1156	a184b775c707	dellery	Marketing	East-417
1163	h679i515j339	cwilliam	Marketing	East-216

7 rows in set (0.001 sec)

The SQL query ***SELECT * FROM employees WHERE department = 'Marketing' AND office LIKE 'East%'***; retrieves all records from the employees table where two conditions are met: the department column has a value of 'Marketing' and the office column begins with the word 'East'. The ***LIKE*** operator is used for pattern matching, with the % symbol acting as a wildcard that represents zero or more characters. For example, this query would match offices named 'East-123' or 'East-456'.

Retrieve employees in Finance or Sales

Then, I was instructed to filter for employees that worked in the Finance or Sales department.

```
MariaDB [organization]> SELECT * FROM employees WHERE department = 'Finance' or department = 'Sales';
```

employee_id	device_id	username	department	office
1003	d394e816f943	sgilmore	Finance	South-153
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduike	Sales	South-215
1025	z381a365b233	jhill	Sales	North-115
1029	d336e475f676	ivelasco	Finance	East-156
1035	j236k303l245	bisles	Sales	South-171
1039	n253o917p623	cjackson	Sales	East-378
1041	p929q222r778	cgriffin	Sales	North-208
1044	s429t157u159	tbarnes	Finance	West-415
1045	t567u844v434	pwashing	Finance	East-115
1046	u429v921w138	daquino	Finance	West-280
1047	v109w587x644	cward	Finance	West-373
1048	w167x592y375	tmitchel	Finance	South-288
1049	NULL	jreckley	Finance	Central-295

The SQL query ***SELECT * FROM employees WHERE department = 'Finance' OR department = 'Sales'***; retrieves all records from the employees table where the department column matches either "Finance" or "Sales". The ***SELECT **** statement specifies that all columns from the matching rows should be included in the result. The ***WHERE*** clause filters the rows based on the condition, and the ***OR*** operator ensures that any employee belonging to either the "Finance" or "Sales" department is included in the output.

Retrieve all employees not in IT

Lastly, I was instructed to retrieve all employees that are not in the IT department.

```
MariaDB [organization]> SELECT * FROM employees WHERE NOT department = 'Information Technology';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1001	b239c825d303	bmoreno	Marketing	Central-276
1002	c116d593e558	tshah	Human Resources	North-434
1003	d394e816f943	sgilmore	Finance	South-153
1004	e218f877g788	eraab	Human Resources	South-127
1005	f551g340h864	gesparza	Human Resources	South-366
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1016	q793r736s288	sbaelish	Human Resources	North-229
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1020	u899v381w363	arutley	Marketing	South-351
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduike	Sales	South-215
1025	z381a365b233	jhill	Sales	North-115
1026	a998b568c863	apatel	Human Resources	West-320
1027	b806c503d354	mrah	Marketing	West-246
1028	c603d749e374	aestrada	Human Resources	West-121

The SQL query ***SELECT * FROM employees WHERE NOT department = 'Information Technology'***; retrieves all records from the employees table, excluding those where the department is 'Information Technology'. The ***SELECT **** statement specifies that all columns of the table should be included in the result, while the ***WHERE NOT*** clause filters out rows matching the condition `department = 'Information Technology'`.

Summary

I applied filters to SQL queries to extract specific information about login attempts and employee machines. Using the `log_in_attempts` and `employees` tables, I utilized the AND, OR, and NOT operators to refine the results according to the requirements of each task. Additionally, I incorporated the LIKE operator with the % wildcard to filter data based on specific patterns, ensuring precise and relevant query outputs.