

Linear Programming (Simplex LP) PuLP?

Asked 4 years, 2 months ago Active 4 years, 2 months ago Viewed 4k times

4

3

In Python only, and using data from a Pandas dataframe, how can I use [PuLP](#) to solve linear programming problems the same way I can in Excel? How much budget should be allocated to each Channel under the New Budget column so we maximize the total number of estimated successes? I'm really looking for a concrete **example** using data from a dataframe and not really high-level advice.

Problem Data Setup

	Channel	30-day Cost	Trials	Success	Cost Min	Cost Max	New Budget
0	Channel1	1765.21	9865	812	882.61	2647.82	0
1	Channel2	2700.00	15000	900	1350.00	4050.00	0
2	Channel3	2160.00	12000	333	1080.00	3240.00	0

This is a **Maximization** problem.

The *objective function* is:

```
objective_function = sum((df['New Budget'] / (df['30-day Cost'] / df['Trials'])) * (df['Success']
```

The *constraints* are:

1. The sum of `df['New Budget']` must equal `5000`
2. The `New Budget` for a given channel can go no *lower* than the `Cost Min`
3. The `New Budget` for a given channel can go no *higher* than the `Cost Max`

Any ideas how to translate this pandas dataframe solver linear problem using PuLP or any other solver approach? The end-result would be what you see in the image below.

	A	B	C	D	E	F	G	H
1	Channel	30-day Cost	Trials	Success	Cost Min	Cost Max	New Budget	Est. Successes
2	Channel1	\$1,765.21	9,865	812	\$882.61	\$2,647.82	\$2,570.00	1,182
3	Channel2	\$2,700.00	15,000	900	\$1,350.00	\$4,050.00	\$1,350.00	450
4	Channel3	\$2,160.00	12,000	333	\$1,080.00	\$3,240.00	\$1,080.00	167
5		\$6,625.21					\$5,000.00	1,799

Solver Parameters

Set Objective: \$H\$5

To: ☒ Max ☐ Min ☐ Value Of: 0.18

By Changing Variable Cells: \$G\$2:\$G\$4

Subject to the Constraints:

\$G\$2:\$G\$4 <= \$F\$2:\$F\$4

\$G\$2:\$G\$4 >= \$E\$2:\$E\$4

\$G\$5 = 5000

Add

Change

Delete

Reset All

Load/Save

☒ Make Unconstrained Variables Non-Negative

Select a Solving Method: Simplex LP

Solving Method
 Select the GRG Nonlinear engine for Solver Problems that are smooth nonlinear. Select the LP Simplex engine for linear Solver Problems, and select the Evolutionary engine for Solver problems that are non-smooth.

Help Solve Close

python pandas dataframe linear-programming pulp

share improve this question

edited Oct 15 '15 at 23:59

 TigerhawkT3
41.5k ● 5 ● 38 ● 69

asked Oct 15 '15 at 23:36

 Jarad
8,072 ● 8 ● 53 ● 80

add a comment





Introducing a new option
for Private Q&A featuring
single sign-on and
advanced features for
your business

1 Answer

active oldest votes

7

In general you create a dictionary of variables (`x` in this case) and a model variable (`mod` in this case). To create the objective you use `sum` over the variables times some scalars, adding that result to `mod`. You construct constraints by again computing linear combinations of variables, using `>=`, `<=`, or `==`, and adding that constraint to `mod`. Finally you use `mod.solve()` to get the solutions.

```
import pulp

# Create variables and model
x = pulp.LpVariable.dicts("x", df.index, lowBound=0)
mod = pulp.LpProblem("Budget", pulp.LpMaximize)

# Objective function
objvals = {idx: (1.0/(df['30-day Cost'][idx]/df['Trials'][idx]))*(df['Success'][idx]/float(
mod += sum([x[idx]*objvals[idx] for idx in df.index])

# Lower and upper bounds:
for idx in df.index:
    mod += x[idx] >= df['Cost Min'][idx]
    mod += x[idx] <= df['Cost Max'][idx]

# Budget sum
mod += sum([x[idx] for idx in df.index]) == 5000.0

# Solve model
mod.solve()

# Output solution
for idx in df.index:
    print idx, x[idx].value()
# 0 2570.0
# 1 1350.0
# 2 1080.0

print 'Objective', pulp.value(mod.objective)
# Objective 1798.70495012
```

Data:

```
import numpy as np
import pandas as pd
idx = [0, 1, 2]
d = {'channel': pd.Series(['Channel1', 'Channel2', 'Channel3'], index=idx),
     '30-day Cost': pd.Series([1765.21, 2700., 2160.], index=idx),
     'Trials': pd.Series([9865, 1500, 1200], index=idx),
```



```
df = pd.DataFrame(a)
```

```
df
```

#	30-day Cost	Cost Max	Cost Min	Success	Trials	channel
# 0	1765.21	2647.82	882.61	812	9865	Channel1
# 1	2700.00	4050.00	1350.00	900	1500	Channel2
# 2	2160.00	3240.00	1080.00	333	1200	Channel3

share improve this answer

edited Oct 16 '15 at 18:24

answered Oct 16 '15 at 1:01



josliber ♦

39.4k ● 11 ● 73 ● 109

In the same example what if I have two variables. For eg: currently, \$G\$2:\$G\$4 is there if want something like \$G\$2:\$H\$6 as changing the variable in pulp. – Bastin Robin Aug 27 '17 at 10:38

@josliber, I'm curious, why are you using 1.0 in your objective function where OP is using df['New Budget'] ? Is that because df['New Budget'] are the variable cells? I'm trying to map this to my own problem but can't figure out where to put my variable cells. Thanks! – tmthyjames Nov 1 '17 at 15:15

@tmthyjames I am using 1.0/(df['30-day Cost'][idx]/df['Trials'][idx]))*(df['Success'][idx]/float(df['Trials'][idx])) because this is the OP's objective function from their excel spreadsheet. If you have a different formula then you would use that instead. – josliber ♦ Nov 1 '17 at 15:25

Hi @josliber, is it possible for me to connect with you over mail? I have a similar problem that I want to discuss. Would be really grateful, if you could help me out. Thanks. Kindly, check this out : stackoverflow.com/questions/49194399/... – IndigoChild Mar 10 '18 at 17:19

add a comment

Your Answer

B *I*

Sign up or [log in](#)

Sign up using Google

Sign up using Facebook

Sign up using Email and Password



Name

Email

Required, but never shown


Post Your Answer


By clicking "Post Your Answer", you agree to our [terms of service](#), [privacy policy](#) and [cookie policy](#)


Not the answer you're looking for? Browse other questions tagged [python](#) [pandas](#) [dataframe](#)

[linear-programming](#) [pulp](#) or [ask your own question](#).

Featured on Meta





 [Update: an agreement with Monica Cellio](#)

 [We're lowering the close/reopen vote threshold from 5 to 3 for good](#)



Haven Connect
Affordable Housing

We have great benefits!

-  Medical/Dental/Vision
-  Ultrawide or 4K monitor
-  Macbook Pro laptop
-  401k with 5% match

+ 2 more benefits

[Learn more](#)

Linked

32 [linear programming in python?](#)

5 [Using Excel like solver in Python or SQL](#)



Related

- 1 How to configure temporal / time linear programming constraints using PuLP?
- 3 Linear Programming with Python (Pulp) - Scheduling
- 1 Python Pulp Integer Linear Program with dynamic constraint
- 0 Conditional Constraint Linear Program in Python's Pulp Module
- 2 Linear programming salad mixture optimization with PuLP
- 0 Formulating an Linear Programming Assignment in pulp
- 1 PuLP: Objective Function: Adding multiple lpSum in a loop
- 0 Python Pulp linear programming with dynamic constraint

Hot Network Questions

- 🌐 Does a Canadian permanent resident need a transit visa in Canada?
- 🔌 Buck Converter Feedback Circuitry
- 💡 What is the minimum die area of a chip?
- 🔧 What do you get when you sum over the smaller half of the harmonic series?
- 🗨️ Car won't start after sitting for 2 years even with a jump. Is it a starter or alternator issue?
- 📖 I don't recognize the symbol on top of this note. What is it, and how does it affect the note?
- 🔥 Which operation combines $\{f,g,h,\dots\}$ and $y[u,v,w,\dots]$ to get $y[f[u],g[v],h[w],\dots]$?
- 🔌 Replacing electrical wiring
- 🔨 Driving a nail with a light object?
- 🗡️ Justifications for Axe Bayonets
- 📅 Timeline of The Witcher tv series
- 🖨️ Tabletop saw stops midway through chipboard
- 🏠 Is there any significance to the earth's numbers?
- 💻 Why did the ZX80 CPU run at only 3.25 MHz?
- 🔌 Why volt instead of volta?
- 📊 Why does thinning work in Bayesian inference?
- 🏠 What are the potential risks of leaving a device in public, but locked?
- 🌐 A Riley riddle to end the year!



In C++ if the key is, the character requires an item yet starts with it confiscated. What should I do?



Finding all the binary bit strings of a given length



Construct the Array from HackerRank



Is 8.6.18 insecure? Will there be 8.6.19 etc.?



UN condemns Rohingya human rights abuses
134-9 with 28 abstentions. Which countries voted against?



Question feed

STACK OVERFLOW

Questions

Jobs

Developer Jobs Directory

Salary Calculator

Help

Mobile

Disable Responsiveness

PRODUCTS

Teams

Talent

Advertising

Enterprise

COMPANY

About

Press

Work Here

Legal

Privacy Policy

Contact Us

STACK EXCHANGE NETWORK

Technology >

Life / Arts >

Culture / Recreation >

Science >

Other >

[Blog](#) [Facebook](#) [Twitter](#) [LinkedIn](#)

site design / logo © 2020 Stack Exchange Inc; user contributions licensed under cc by-sa 4.0 with attribution required.
rev 2019.12.20.35703

