

## Display text

```
st.text('Fixed width text')
st.markdown('_Markdown_') # see **
st.caption('Balloons. Hundreds of them...')
st.latex(r''' e^{i\pi} + 1 = 0 ''')
st.write('Most objects') # df, err, func, keras!
st.write(['st', 'is <', 3]) # see *
st.title('My title')
st.header('My header')
st.subheader('My sub')
st.code('for i in range(8): foo()')

# * optional kwarg unsafe_allow_html = True
```

## Display data

```
st.dataframe(my_dataframe)
st.table(data.iloc[0:10])
st.json({'foo': 'bar', 'fu': 'ba'})
st.metric(label="Temp", value="273 K", delta="1.2 K")
```

## Display media

```
st.image('./header.png')
st.audio(data)
st.video(data)
```

## Columns

```
col1, col2 = st.columns(2)
col1.write('Column 1')
col2.write('Column 2')

# Three columns with different widths
col1, col2, col3 = st.columns([3,1,1])
# col1 is wider

# Using 'with' notation:
>>> with col1:
>>>     st.write('This is column 1')
```

## Tabs

```
# Insert containers separated into tabs:
>>> tab1, tab2 = st.tabs(["Tab 1", "Tab2"])
>>> tab1.write("this is tab 1")
>>> tab2.write("this is tab 2")

# You can also use "with" notation:
>>> with tab1:
>>>     st.radio('Select one:', [1, 2])
```

## Control flow

```
# Stop execution immediately:
st.stop()

# Rerun script immediately:
st.experimental_rerun()
```

## Display interactive widgets

```
st.button('Hit me')
st.data_editor('Edit data', data)
st.checkbox('Check me out')
st.radio('Pick one:', ['nose', 'ear'])
st.selectbox('Select', [1,2,3])
st.multiselect('Multiselect', [1,2,3])
st.slider('Slide me', min_value=0, max_value=100)
st.select_slider('Slide to select', options=[1, 2, 3, 4])
st.text_input('Enter some text')
st.number_input('Enter a number')
st.text_area('Area for textual entry')
st.date_input('Date input')
st.time_input('Time entry')
st.file_uploader('File uploader')
st.download_button('On the dl', data)
st.camera_input("一二三,茄子!")
st.color_picker('Pick a color')
```

```
# Use widgets' returned values in variables
>>> for i in range(int(st.number_input('Num:'))):
>>>     if st.sidebar.selectbox('I:', ['f']) == 'f':
>>>         my_slider_val = st.slider('Quinn Mallory', 0, 100)
>>>         st.write(my_slider_val)
```

```
# Disable widgets to remove interactivity:
>>> st.slider('Pick a number', 0, 100, disabled=True)
```

## Build chat-based apps

```
# Insert a chat message container.
>>> with st.chat_message("user"):
>>>     st.write("Hello 🍌")
>>>     st.line_chart(np.random.randn(30, 3))

# Display a chat input widget.
>>> st.chat_input("Say something")
```

Learn how to [build chat-based apps](#)

## Mutate data

```
# Add rows to a dataframe after
# showing it.
>>> element = st.dataframe(df1)
>>> element.add_rows(df2)

# Add rows to a chart after
# showing it.
>>> element = st.line_chart(df1)
>>> element.add_rows(df2)
```

## Display code

```
st.echo()
>>> with st.echo():
>>>     st.write('Code will be executed and printed')
```

```
# Group multiple widgets:
>>> with st.form(key='my_form'):
>>>     username = st.text_input('Username')
>>>     password = st.text_input('Password')
>>>     st.form_submit_button('Login')
```

## Personalize apps for users

```
# Show different content based on the user's email address.
>>> if st.user.email == 'jane@email.com':
>>>     display_jane_content()
>>> elif st.user.email == 'adam@foocorp.io':
>>>     display_adam_content()
>>> else:
>>>     st.write("Please contact us to get access!")
```

## Placeholders, help, and options

```
# Replace any single element.
>>> element = st.empty()
>>> element.line_chart(...)
>>> element.text_input(...) # Replaces previous element
```

```
# Insert out of order.
>>> elements = st.container()
>>> elements.line_chart(...)
>>> st.write("Hello")
>>> elements.text_input(...) # Appears above 'Hello'
```

```
st.help(pandas.DataFrame)
st.get_option(key)
st.set_option(key, value)
st.set_page_config(layout='wide')
st.experimental_show(objects)
st.experimental_get_query_params()
st.experimental_set_query_params(**params)
```