

Team Notebook

Universidad Mayor de San Simón - Wasos del Valle

1 1. Math	3	5.3 convex hull trick	9	8 5. Flow	18
1.1 fast fibonacci	3	5.4 knuths optimization	10	8.1 hungarian	18
1.2 floor sums	3	5.5 sos dp	10	8.2 max flow	19
1.3 subfactorial	3	5.6 divide and conquer optimization	10	8.3 blossom	19
1.4 catalan	3	5.7 multiple knacksack optimizacion	10	8.4 min cut	20
1.5 combinatorics	3	5.8 optimizing pragmas for bitset	10	8.5 min cost max flow	20
1.6 count primes with pi function	3	5.9 longest increasing subsequence	11	9 6. Tree	21
1.7 add josephus	4	5.10 sos dp reverse	11	9.1 block tree	21
1.8 optimized polard rho	4	5.11 linear recurrence matrix exponciation	11	9.2 isomorfismo	22
1.9 ternary search	4	5.12 separation optimization	11	9.3 heavy light	22
1.10 catalan convolution	5	6 3. Data Structures	11	9.4 online centroid	22
2 1. Math - Fft	5	6.1 multiororderedset	11	9.5 centroid descomposition	23
2.1 karatsuba	5	6.2 persistantsegmenttree	12	10 7. Strings	23
2.2 fft shifts trick	5	6.3 fenwick tree 2d	12	10.1 kmp	23
2.3 fast hadamard transform	5	6.4 fast hash map	13	10.2 micky hashing	23
2.4 fft	6	6.5 rope	13	10.3 manacher	23
2.5 ntt	6	6.6 fenwick tree	13	10.4 suffix array	24
3 1. Math - Mobius	6	6.7 dynamic connectivity	13	10.5 fast hashing	24
3.1 $\sum_{i=1}^n \frac{1}{\gcd(i,n)}$	7	6.8 min sparse table	14	10.6 kmp automaton	24
3.2 $[\gcd(a, i) == k] \text{ queries}$	7	6.9 orderedset	14	11 8. Geometry	25
3.3 linear sieve	7	6.10 lazy segment tree	14	11.1 ufps line	25
3.4 mobius	7	6.11 sqrt mod	15	11.2 closest pair of points sweep line	25
3.5 $[\gcd(i, j) == k]$	8	6.12 persistance segtree	15	11.3 heron formula	25
4 1. Math - Modular Arithmethics	8	6.13 mo's	15	11.4 point in convex polygon	25
4.1 discrete log	8	6.14 segment tree 2d	16	11.5 ufps circle	26
4.2 diophantine ecuations	8	6.15 custom hash	16	11.6 ufps polygon	26
4.3 chinease remainder	8	6.16 segment tree	16	11.7 ufps segment	27
4.4 big expontent modular exponentiation	8	7 4. Graphs	17	11.8 segment intersection	28
5 2. Dp	8	7.1 bellmanford find negative cycle	17	11.9 point in general polygon	28
5.1 linear recurrence cayley halmiton	8	7.2 strongly connected components	17	11.10 convex hull	29
5.2 dp mask over submasks	9	7.3 two sat	18	11.11 ufps point	30

11.12 polygon diameter	30
11.13 closest pair of points	31
12 9. Utils	31
12.1 bit tricks	31
12.2 pragmas	31
12.3 string streams	32
12.4 randoms	32
12.5 io int128	32
12.6 decimal precision python	32
13 A. To Order	32
13.1 polynomial sum lazy segtree problem	32
13.2 mo's in tree's	33
13.3 poly definitions	33
14 Problems	33
14.1 shift poly	33
14.2 big primes	33

1.1. Math

1.1 fast fibonacci

```
0(log n), fib(n).F = Fib at n-th position
pair<ll,ll> fib (ll n) {
    if (n == 0) return {0, 1};
    auto p = fib(n >> 1);
    ll c = (p.F * (2*p.S - p.F + MOD)%MOD)%MOD;
    ll d = (p.F * p.F + p.S * p.S)%MOD;
    if (n & 1) return {d, (c + d)%MOD};
    else return {c, d};
}
```

1.2 floor sums

```
// from atcoder
// floor_sum(n,m,a,b) = sum{0}to{n-1} [(a*i+b)/m]
// 0(log m), mod 2^64, n<2^32, m<2^32
constexpr long long safe_mod(long long x, long long m)
{
    x %= m;
    if (x < 0) x += m;
    return x;
}

unsigned long long floor_sum_unsigned(unsigned long
long n,
                                unsigned long
long m,
                                unsigned long
long a,
                                unsigned long
long b) {
    unsigned long long ans = 0;
    while (true) {
        if (a >= m) {
            ans += n * (n - 1) / 2 * (a / m);
            a %= m;
        }
        if (b >= m) {
            ans += n * (b / m);
            b %= m;
        }
        unsigned long long y_max = a * n + b;
        if (y_max < m) break;
        // y_max < m * (n + 1)
        // floor(y_max / m) <= n
        n = (unsigned long long)(y_max / m);
        b = (unsigned long long)(y_max % m);
        swap(m, a);
    }
}
```

```
return ans;
}
long long floor_sum(long long n, long long m, long long
a, long long b) {
    assert(0 <= n && n < (1LL << 32));
    assert(1 <= m && m < (1LL << 32));
    unsigned long long ans = 0;
    if (a < 0) {
        unsigned long long a2 = safe_mod(a, m);
        ans -= 1ULL * n * (n - 1) / 2 * ((a2 - a) / m);
        a = a2;
    }
    if (b < 0) {
        unsigned long long b2 = safe_mod(b, m);
        ans -= 1ULL * n * ((b2 - b) / m);
        b = b2;
    }
    return ans + floor_sum_unsigned(n, m, a, b);
}
```

1.3 subfactorial

```
const int mxN = 2e6 + 10;
vector<ll> subFact(mxN);
void init() {
    subFact[0] = 1, subFact[1] = 0;
    for (int i = 2; i < mxN; i++)
        subFact[i] = mul(add(subFact[i-1], subFact[i-2]), i-1);
}
```

1.4 catalan

Catalan, cuenta numero de formas
(A) B, donde |A|+|B| = N, para N+1

```
ll catalan(ll n) {
    if (n < 0) return 0;
    ll up = fact[2*n]; ll down = mul(fact[n], fact[n+1]);
    return mul(up, inv(down));
}
```

1.5 combinatorics

```
// 0(min(n, n-k)) lineal
ll nck(ll n, ll k) {
    if (k < 0 || n < k) return 0;
    k = min(k, n-k);
    ll ans = 1;
    for (int i = 1; i <= k; i++)
        ans = ans * (n-i+1) / i;
    return ans;
}
```

1.6 count primes with pi function

```
// sprime.count_primes(n);
// 0(n^(2/3))
// PI(n) = Count prime numbers until n inclusive
struct count_primers_struct {
    vector<int> primes;
    vector<int> mnprimes;
    ll ans;
    ll y;
    vector<pair<pair<ll, int>, char>> queries;
    ll count_primes(ll n) {
        // this y is actually n/y
        // also no logarithms, welcome to reality, this
        // y is the best for n=10^12 or n=10^13
        y = pow(n, 0.64);
        if (n < 100) y = n;
        // linear sieve
        primes.clear();
        mnprimes.assign(y + 1, -1);
        ans = 0;
        for (int i = 2; i <= y; ++i) {
            if (mnprimes[i] == -1) {
                mnprimes[i] = primes.size();
                primes.push_back(i);
            }
            for (int k = 0; k < primes.size(); ++k) {
                int j = primes[k];
                if (i * j > y) break;
                mnprimes[i * j] = k;
                if (i % j == 0) break;
            }
        }
        if (n < 100) return primes.size();
        ll s = n / y;
        for (int p : primes) {
            if (p > s) break;
            ans++;
        }
        // pi(n / y)
        int ssz = ans;
        // F with two pointers
        int ptr = primes.size() - 1;
        for (int i = ssz; i < primes.size(); ++i) {
            while (ptr >= i && (ll)primes[i] *
primes[ptr] > n)
                --ptr;
            if (ptr < i) break;
            ans -= ptr - i + 1;
        }
        // phi, store all queries
```

```

    phi(n, ssz - 1);
    sort(queries.begin(), queries.end());
    int ind = 2;
    int sz = primes.size();
    // the order in fenwick will be reversed,
    because prefix sum in a fenwick is just one query
    fenwick fw(sz);
    for (auto qq : queries) {
        auto na = qq.F;
        auto sign = qq.S;
        auto n = na.F;
        auto a = na.S;
        while (ind <= n)
            fw.add(sz - 1 - mnprimes[ind++], 1);
        ans += (fw.ask(sz - a - 2) + 1) * sign;
    }
    queries.clear();
    return ans - 1;
}

void phi(ll n, int a, int sign = 1) {
    if (n == 0) return;
    if (a == -1) {
        ans += n * sign;
        return;
    }
    if (n <= y) {
        queries.emplace_back(make_pair(n, a),
            sign);
        return;
    }
    phi(n, a - 1, sign);
    phi(n / primes[a], a - 1, -sign);
}

struct fenwick {
    vector<int> tree;
    int n;
    fenwick(int n = 0) : n(n) {
        tree.assign(n, 0);
    }
    void add(int i, int k) {
        for (; i < n; i = (i | (i + 1)))
            tree[i] += k;
    }
    int ask(int r) {
        int res = 0;
        for (; r >= 0; r = (r & (r + 1)) - 1)
            res += tree[r];
        return res;
    }
};

```

```

} ;
count_primers_struct sprime;

```

1.7 add josephus

1.8 optimized polard rho

```

// Fast factorization with big numbers, use fact method
// Seems to be O(log^3(n)) !!! Need revision
#define fore(i, b, e) for(int i = b; i < e; i++)
ll gcd(ll a, ll b){return a?gcd(b%a,a):b;}
ll mulmod(ll a, ll b, ll m) {
    ll r=a*b-(ll)((long double)a*b/m+.5)*m;
    return r<0?r+m:r;
}
ll expmod(ll b, ll e, ll m){
    if(!e)return 1;
    ll q=expmod(b,e/2,m);q=mulmod(q,q,m);
    return e&1?mulmod(b,q,m):q;
}
bool is_prime_prob(ll n, int a){
    if(n==a)return true;
    ll s=0,d=n-1;
    while(d%2==0)s++,d/=2;
    ll x=expmod(a,d,n);
    if((x==1)|| (x+1==n))return true;
    fore(_,0,s-1){
        x=mulmod(x,x,n);
        if(x==1)return false;
        if(x+1==n)return true;
    }
    return false;
}
bool rabin(ll n){ // true iff n is prime
    if(n==1)return false;
    int ar[]={2,3,5,7,11,13,17,19,23};
    fore(i,0,9)if(!is_prime_prob(n,ar[i]))return false;
    return true;
}
// optimized version: replace rho and fact with the
following:
const int MAXP=1e6+1; // sieve size
int sv[MAXP]; // sieve
ll add(ll a, ll b, ll m){return (a+b)<m?a+b-m;}
ll rho(ll n){
    static ll s[MAXP];
    while(1){
        ll x=rand()%n,y=x,c=rand()%n;
        ll *px=s,*py=s,v=0,p=1;
        while(1){

```

```

*py+=y=add(mulmod(y,y,n),c,n);
*py+=y=add(mulmod(y,y,n),c,n);
if((x=*px++)==y)break;
ll t=p;
p=mulmod(p,abs(y-x),n);
if(!p)return gcd(t,n);
if(++v==26){
    if((p=gcd(p,n))>1&&p<n)return p;
    v=0;
}
}
if(v&&(p=gcd(p,n))>1&&p<n)return p;
}
}
void init_sv(){
    fore(i,2,MAXP)if(!sv[i])for(ll
j=i;j<MAXP;j+=i)sv[j]=i;
}
void fact(ll n, map<ll,int>& f){ // call init_sv
first!!!
    for(auto&& p:f){
        while(n%p.F==0){
            p.S++; n/=p.F;
        }
    }
    if(n<MAXP)while(n>1)f[sv[n]]++,n/=sv[n];
    else if(rabin(n))f[n]++;
    else {ll q=rho(n);fact(q,f);fact(n/q,f);}
}

```

1.9 ternary search

```

// this is for find minimum point in a parabolic
// O(log3(n))
// TODO: Improve to generic!!!
ll left = 0;
ll right = n - 1;
while (left + 3 < right) {
    ll mid1 = left + (right - left) / 3;
    ll mid2 = right - (right - left) / 3;
    if (f(b, lines[mid1]) <= f(b, lines[mid2])) {
        right = mid2;
    } else {
        left = mid1;
    }
}
ll target = -4 * a * c;
ll ans = -1; // find the answer, in this case any
works.
for (ll mid = left; mid <= right; mid++) {
    if (f(b, lines[mid]) + target < 0) {

```

```

        ans = mid;
    }
}

```

1.10 catalan convolution

```

/*
Catalan Convolution.
Convolution for k=3
((( A ) B ) C ) D
Where A + B + C + D = N, for N + 1
*/
ll cnk(ll n, ll k);
// for parenthesis example
// number of n+k pairs having k open parenthesis at
beginning
// (cnk(2n+k,n)*(k+1))/(n+k+1)
ll catalanCov(ll n, ll k) {
    ll up = mul(cnk(2*n+k,n),(k+1)%MOD);
    ll down = (n+k+1)%MOD;
    return mul(up,inv(down));
}
/*
6
((
ans: 2
*/
// size, and prefix
ll countParenthesisWithPrefix(ll n, string &p) {
    if (n&1) return 0;
    ll k = 0;
    for (auto c : p) {
        if (c=='(') k++;
        else k--;
        if (k<0) return 0;
    }
    n=(n-(ll)p.size()-k)/2;
    return catalanCov(n,k);
}

```

2 1. Math - Fft

2.1 karatsuba

```

// Multiplication of Polynomials in  $O(n^{1.58})$ 
// with any Module that you want
#define ll long long
const int MOD = 1e9+7;
#define poly vector<ll>
#define fore(i,a,b) for(int i=a,ThxDem=b;i<ThxDem;++i)
typedef int tp;

```

```

ll sum(ll x, ll y) {
    ll ans = (x + y) % MOD;
    if (ans < 0) ans += MOD;
    return ans;
}
ll mult(ll x, ll y) {
    ll ans = (x % MOD) * (y % MOD);
    ans %= MOD;
    if (ans < 0) ans += MOD;
    return ans;
}
#define add(n,s,d,k) \
    fore(i,0,n)(d)[i] = sum((d)[i],mult((s)[i],k))
tp* ini(int n){
    tp *r=new tp[n];fill(r,r+n,0);
    return r;
}
void karatsura(int n, tp* p, tp* q, tp* r){
    if(n<=0)return;
    if(n<35)
        fore(i,0,n)
        fore(j,0,n)
            r[i+j]=sum(r[i+j], mult(p[i],q[j]));
    else {
        int nac=n/2,nbd=n-n/2;
        tp *a=p,*b=p+nac,*c=q,*d=q+nac;
        tp *ab=ini(nbd+1),*cd=ini(nbd+1),
            *ac=ini(nac*2),*bd=ini(nbd*2);
        add(nac,a,ab,1);add(nbd,b,ab,1);
        add(nac,c,cd,1);add(nbd,d,cd,1);
        karatsura(nac,a,c,ac);karatsura(nbd,b,d,bd);
        add(nac*2,ac,r+nac,-1);add(nbd*2,bd,r+nac,-1);
        add(nac*2,ac,r,1);add(nbd*2,bd,r+nac*2,1);
        karatsura(nbd+1,ab,cd,r+nac);
        free(ab);free(cd);free(ac);free(bd);
    }
}
vector<tp> multiply(vector<tp> p0, vector<tp> p1){
    int n=max(p0.size(),p1.size());
    tp *p=ini(n),*q=ini(n),*r=ini(2*n);
    fore(i,0,p0.size())p[i]=p0[i];
    fore(i,0,p1.size())q[i]=p1[i];
    karatsura(n,p,q,r);
    vector<tp> rr(r,r+p0.size()+p1.size()-1);
    free(p);free(q);free(r);
    return rr;
}

```

2.2 fft shifts trick

```

//FFT Trick, it very useful for shifts in the
following:
// Sum j_0_to_n-1 a[j]*a[j+i]
// where i is the number of shifts, and 'a' is some
array.
auto copy = actual;
reverse(all(copy));
// be careful with doubles precision, so maybe NTT
could be useful here.
// multiply is the method of FTT or NTT
auto polinomy = multiply(actual, copy);
ll m = actual.size();
answer[0] = polinomy[m-1]; // 0 with m-1, 1 with m-2
=m-1
for (int i = 1; i <= m-1; i++) { // 1 step no m-1 steps
    // 0 with m-2 is 1 step, 1 with m-3 is one then
m-1-1, also the last one m-1 is with m-1
    // 0 with m-3 is 2 step, m-1 with m-1-1
    answer[i] = polinomy[m-1-i] + polinomy[2*(m-1)-
i+1];
}

```

2.3 fast hadamard transform

```

// like polynomial multiplication, but XORing exponents
// instead of adding them (also ANDing, ORing)
const int MAXN=1<<18;
#define fore(i,l,r) for(int i=int(l);i<int(r);++i)
#define SZ(x) ((int)(x).size())
ll c1[MAXN+9],c2[MAXN+9];//MAXN must be power of 2!
void fht(ll* p, int n, bool inv){
    for(int l=1;2*l<=n;l*=2)
        for(int i=0;i<n;i+=2*l)
            fore(j,0,l){
                ll u=p[i+j],v=p[i+l+j];
                // if(!inv)p[i+j]=u+v,p[i+l+j]=u-v; // XOR
                // else p[i+j]=(u+v)/2,p[i+l+j]=(u-v)/2;
                //if(!inv)p[i+j]=v,p[i+l+j]=u+v; // AND
                //else p[i+j]=-u+v,p[i+l+j]=u;
                if(!inv)p[i+j]=u+v,p[i+l+j]=u; // OR
                else p[i+j]=v,p[i+l+j]=u-v;
            }
}
// like polynomial multiplication, but XORing exponents
// instead of adding them (also ANDing, ORing)
vector<ll> multiply(vector<ll>& p1, vector<ll>& p2){
    int n=1<<(32-__builtin_clz(max(SZ(p1),SZ(p2))-1));
    fore(i,0,n)c1[i]=0,c2[i]=0;
    fore(i,0,SZ(p1))c1[i]=p1[i];
    fore(i,0,SZ(p2))c2[i]=p2[i];
    fht(c1,n,false);fht(c2,n,false);
}

```

```

    fore(i,0,n)c1[i]*=c2[i];
    fht(c1,n,true);
    return vector<ll>(c1,c1+n);
}
// maxime the OR of a pair of given nums and count
// how many pairs can get that maximum OR
// tested: csacademy.com/contest/archive/task/maxor
void test_case() {
    ll n; cin >> n;
    vl a(MAXN),b(MAXN);
    for (int i =0;i<n;i++) {
        ll x; cin >> x; a[x]++; b[x]++;
    }
    vl c = multiply(a,b);
    pair<ll,ll> best = {0, c[0]};
    for (int i = 0;i<MAXN;i++)
        if (c[i]) best = {i,c[i]-a[i]]/2};
    cout <<best.F << " " << best.S << endl;
}

```

2.4 fft

```

// FFT multiplies polinomial 'a' and 'b' in O(n log n)
// you can define double as long double, but maybe TLE
using cd = complex<double>;
void fft(vector<cd> &a, bool invert) {
    ll n = a.size();
    for (ll i = 1, j = 0; i < n; i++) {
        ll bit = n >> 1;
        for (; j & bit; bit >>= 1)
            j ^= bit;
        j ^= bit;
        if (i < j)
            swap(a[i], a[j]);
    }
    for (ll len = 2; len <= n; len <= 1) {
        double ang = 2 * PI / len * (invert ? -1 : 1);
        cd wlen(cos(ang), sin(ang));
        for (ll i = 0; i < n; i += len) {
            cd w(1);
            for (ll j = 0; j < len / 2; j++) {
                cd u = a[i+j], v = a[i+j+len/2] * w;
                a[i+j] = u + v;
                a[i+j+len/2] = u - v;
                w *= wlen;
            }
        }
    }
    if (invert) {
        for (cd &x : a)
            x /= n;
    }
}

```

```

    }
}
vector<ll> multiply(vector<ll> &a, vector<ll> &b) {
    vector<cd> fa(a.begin(), a.end()),
                fb(b.begin(), b.end());

    ll n = 1;
    while (n < a.size() + b.size())
        n <= 1;
    fa.resize(n);
    fb.resize(n);
    fft(fa, false);
    fft(fb, false);
    for (ll i = 0; i < n; i++)
        fa[i] *= fb[i];
    fft(fa, true);
    vector<ll> result(n);
    for (ll i = 0; i < n; i++)
        result[i] = round(fa[i].real());
    // fa[i].real() + 0.5 is faster
    return result;
}

```

2.5 ntt

```

// Multiply Poly with special Modules
// MAXN must be power of 2 !!
// MOD-1 needs to be a multiple of MAXN !!
// #define int long long
#define fore(i,a,b) for(ll i=a,ThxDem=b;i<ThxDem;++i)
// const ll MOD=998244353,RT=3,MAXN=1<<18;
const ll MOD=2305843009255636993ll,RT=5,MAXN=1<<18;
typedef vector<ll> poly;
ll mulmod(__int128 a, __int128 b){
    return ((a%MOD)*(b%MOD)) % MOD;
}
ll addmod(ll a, ll b){
    ll r=a+b;if(r>=MOD)r-=MOD;return r;
}
ll submod(ll a, ll b){ll r=a-b;if(r<0)r+=MOD;return r;}
ll pm(ll a, ll e){
    ll r=1;
    while(e){
        if(e&1)r=mulmod(r,a);
        e>>=1;a=mulmod(a,a);
    }
    return r;
}
struct CD {
    ll x;
    CD(ll x):x(x){}
    CD(){}
    ll get()const{return x;}
};

```

```

CD operator*(const CD& a, const CD& b){
    return CD(mulmod(a.x,b.x));
}
CD operator+(const CD& a, const CD& b){
    return CD(addmod(a.x,b.x));
}
CD operator-(const CD& a, const CD& b){
    return CD(submod(a.x,b.x));
}
vector<ll> rts(MAXN+9,-1);
CD root(ll n, bool inv){
    ll r=rts[n]<0?rts[n]=pm(RT,(MOD-1)/n):rts[n];
    return CD(inv?pm(r,MOD-2):r);
}
CD cp1[MAXN+9],cp2[MAXN+9];
ll R[MAXN+9];
void dft(CD* a, ll n, bool inv){
    fore(i,0,n)if(R[i]<i)swap(a[R[i]],a[i]);
    for(ll m=2;m<=n;m*=2){
        CD wi=root(m,inv); // NTT
        for(ll j=0;j<n;j+=m){
            CD w(1);
            for(ll k=j,k2=j+m/2;k2<j+m;k++,k2++){
                CD u=a[k];CD v=a[k2]*w;a[k]=u+v;
                a[k2]=u-v;w=w*wi;
            }
        }
    }
    if(inv){
        CD z(pm(n,MOD-2)); // pm: modular exponentiation
        fore(i,0,n)a[i]=a[i]*z;
    }
}
poly multiply(poly& p1, poly& p2){
    ll n=p1.size()+p2.size()+1;
    ll m=1,cnt=0;
    while(m<=n)m+=m,cnt++;
    fore(i,0,m){R[i]=0;
        fore(j,0,cnt) R[i]=(R[i]<<1)|((i>>j)&1);
    }
    fore(i,0,m)cp1[i]=0,cp2[i]=0;
    fore(i,0,p1.size())cp1[i]=p1[i];
    fore(i,0,p2.size())cp2[i]=p2[i];
    dft(cp1,m,false);dft(cp2,m,false);
    fore(i,0,m)cp1[i]=cp1[i]*cp2[i];
    dft(cp1,m,true);
    poly res;
    n-=2;
    fore(i,0,n)res.pb(cp1[i].x); // NTT
    return res;
}

```

3 1. Math - Mobius

3.1 $\sum_{i=1}^n \frac{n}{\gcd(i,n)}$

```
// Multiplicative Function
// Calc f(n), f(n) = sum_{1 to n} n / gcd(n,i)
// f(p) = (p-1)*p + 1
// f(p^k) = f(p^(k-1)) + p^k*p^(k-1)*(p-1)
const int mxN = 1e7 + 10;
vl lp(mxN); // least prime factor
vl pw(mxN); // power of least prime factor
vl fn(mxN); // answer of f(n)
vl primes;
void init() { // O(n), Call init first !!!!
    fn[1] = pw[1] = lp[1] = 1;
    for (ll i = 2; i < mxN; i++) {
        if (lp[i] == 0) {
            lp[i] = pw[i] = i;
            fn[i] = (i-1)*i + 1;
            primes.pb(i);
        }
        for (auto p : primes) {
            ll j = i*p;
            if (j >= mxN) break;
            if (lp[i] != p) {
                lp[j] = pw[j] = p;
                fn[j] = fn[i] * fn[p];
            } else {
                lp[j] = p;
                pw[j] = pw[i] * p;
                ll fk = fn[pw[i]] + pw[j] * pw[i] *
                (p-1);
                fn[j] = fn[i/pw[i]] * fk;
                break;
            }
        }
    }
}
```

3.2 $\gcd(a, i, a, j) == k$ text{ queries}

```
// Given an array and q queries of count pairs
gcd(a_i, a_j) == k
// i < j, a_i < 1e5, q < 1e5, n < 1e5
// Complexity O(n * log n + q)
// Tested: https://www.hackerrank.com/contests/ab-yeh-
kar-ke-dikhao-returns/challenges/gcd-pairs
const int mxN = 1e5 + 10;
vl mo(mxN);
void init() { // Call init() first !!!
    mo[1] = 1;
    for (int i = 1; i < mxN; i++)
```

```
        for (int j = i+i; j < mxN; j += i) mo[j] -= mo[i];
    }
    vl cnt(mxN), dcnt(mxN), ans(mxN);
    void test_case() {
        ll n, q; cin >> n >> q;
        for (int i = 0; i < n; i++) {
            ll x; cin >> x;
            cnt[x]++; // cnt[x] = quantity of X's in array
        }
        for (int i = 1; i < mxN; i++)
            for (int j = i; j < mxN; j += i)
                dcnt[i] += cnt[j];
        // dcnt[x] = quantity of a_i divisible by x
        for (int k = 1; k < mxN; k++) {
            for (int d = 1; d <= mxN/k; d++) {
                ll totalCnt = d*k < mxN ? dcnt[d*k] : 0;
                ans[k] += mo[d] * totalCnt * totalCnt;
            }
            ans[k] += cnt[k]; // subtracting j>=i
            ans[k] /= 2;
        }
        while (q--) {
            ll k; cin >> k;
            if (k < mxN) cout << ans[k] << "\n";
            else cout << 0 << "\n";
        }
    }
}
```

3.3 linear sieve

```
/* For getting the primes less than mxN in O(mxN)*/
const int mxN = 1e6 + 10;
vl sv(mxN); // if prime sv[i]==i, it stores the lowest
prime of 'i'
vl primes;
void init() { // O(n)
    for (int i = 2; i < mxN; i++) {
        if (sv[i] == 0) {
            sv[i] = i;
            primes.pb(i);
        }
        for (int j = 0; j < primes.size() &&
            primes[j]*i < mxN; j++) {
            sv[primes[j]*i] = primes[j];
            if (primes[j] == sv[i]) break;
        }
    }
    // factorization using linear sieve, O(prime_count(n))
    // Very fast factorization but only for (n < mxN) !!!
    void fact(map<ll, int> &f, ll num) {
```

```
        while (num > 1) {
            ll p = sv[num];
            while (num % p == 0) num /= p, f[p]++;
        }
    }
```

3.4 mobius

```
/*
Mobius Function.
Multiplicative function that is useful to inclusion/
exclusion with
prime numbers (it gives the coefficient). Also you can
reduce some
sumatories using its equality with unit(n) function
(see the key below)
unit(n) = [ n == 1 ]
unit(1) = 1, unit(2) = 0, unit(0) = 0
(This is the key!!)
unit(n) = sum_{ d divides n } mobius(d)
mobius(1) = 1
mobius(quantity of primes is odd) = -1
mobius(quantity of primes is even) = 1
mobius(n is divisible by a square prime) = 0
Check https://codeforces.com/blog/entry/53925 for more
information.
Check mobius examples
*/
// This is shorter code and O(n log n)
const int mxN = 1e5 + 10;
vl mo(mxN);
void init() { // Call init() first !!!
    mo[1] = 1;
    for (int i = 1; i < mxN; i++)
        for (int j = i+i; j < mxN; j += i) mo[j] -= mo[i];
}
// This is O(n), but not too much difference of speed
with the other
const int mxN = 1e6 + 10;
vl sv(mxN); // prime if sv[i]==i, it stores the lowest
prime of i
vl primes; // Primes less than mxN
vl mo(mxN); // Mobius
void init() {
    // sv[1] = 1; // Check if needed
    for (int i = 2; i < mxN; i++) { // Linear Sieve
        if (sv[i] == 0) { sv[i] = i; primes.pb(i); }
        for (int j = 0; j < primes.size() &&
            primes[j]*i < mxN; j++) {
            sv[primes[j]*i] = primes[j];
            if (primes[j] == sv[i]) break;
        }
    }
}
```

```

    }
}
mo[1] = 1; // Mobius
for (int i=2;i<=m*N;i++) {
    if (sv[i/sv[i]] == sv[i]) mo[i] = 0;
    else mo[i] = -1*mo[i/sv[i]];
}
}

```

3.5 [gcd(i, j) == k]

```

// Counts pairs gcd(i,j) == k
// 1 <= i <= a, 1 <= j <= b, where (1,2) equals to
// (2,1)
// Call Mobius First !!!
// 0(min(a,b)/K)
// Tested: https://vjudge.net/problem/HDU-1695
ll solve(ll a, ll b, ll k) {
    if (k==0) return 0;
    a/=k;
    b/=k;
    if (a > b) swap(a,b);
    if (a == 0) return 0;
    ll ans = 0;
    for (ll d = 1; d <= a; d++) {
        ans += (a/d) * (b/d) * mo[d];
    }
    ll sub = 0; // Subtracting equals, e.g. (1,2) to
    // (2,1)
    for (ll d = 1; d <= a; d++) {
        sub += (a/d)*(b/d) * mo[d];
    }
    ans -= (sub-1)/2;
    return ans;
}

```

4 1. Math - Modular Arithmethics

4.1 discrete log

Devuelve un entero x tal que $a^x = b \pmod{m}$ or -1 si no existe tal x.

// Always check if change int to ll !!!

```

int expmod(int b, int e, int m) {
    int ans = 1;
    while (e) {
        if (e&1) ans = (1ll*ans*b) % m;
        b = (1ll*b*b) % m;
        e /= 2;
    }
}

```

```

}
return ans;
}
ll discrete_log(ll a, ll b, ll m) {
    a %= m, b %= m;
    if (b == 1) return 0;
    int cnt = 0;
    ll tmp = 1;
    for (int g = __gcd(a, m); g != 1; g = __gcd(a, m)) {
        if (b%g) return -1;
        m /= g, b /= g;
        tmp = tmp*a / g % m;
        ++cnt;
        if (b == tmp) return cnt;
    }
    map<ll, int> w;
    int s = ceil(sqrt(m));
    ll base = b;
    for (int i = 0; i < s; i++) {
        w[base] = i;
        base = base*a % m;
    }
    base = expmod(a, s, m);
    ll key = tmp;
    for (int i = 1; i <= s+1; i++) {
        key = key*base % m;
        if (w.count(key)) return i*s - w[key] + cnt;
    }
    return -1;
}

```

4.2 diophantine ecuations

Encuentra x, y en la ecuación de la forma $ax + by = c$

Agregar Extended Euclides.

```

ll g;
bool diophantine(ll a, ll b, ll c) {
    x = y = 0;
    if (!a && !b) return (!c); // sólo hay solución si c=0
    g = euclid(abs(a), abs(b));
    if (c % g) return false;
    a /= g; b /= g; c /= g;
    if (a < 0) x *= -1;
    x = (x % b) * (c % b) % b;
    if (x < 0) x += b;
    y = (c - a*x) / b;
    return true;
}

```

4.3 chinese remainder

```

/*
Finds this system congruence
X = a_1 (mod m_1)
X = a_2 (mod m_2)
...
X = a_k (mod m_k)
*/
ll x, y;
ll euclid(ll a, ll b) {
    if (b == 0) { x = 1; y = 0; return a; }
    ll d = euclid(b, a%b);
    ll aux = x;
    x = y;
    y = aux - a/b*y;
    return d;
}
pair<ll, ll> crt(vector<ll> A, vector<ll> M) {
    ll n = A.size(), ans = A[0], lcm = M[0];
    for (int i = 1; i < n; i++) {
        ll d = euclid(lcm, M[i]);
        if ((A[i] - ans) % d) return {-1, -1};
        ll mod = lcm / d * M[i];
        ans = (ans*x*(A[i] - ans)/d % (M[i]/d)*lcm) % mod;
        if (ans < 0) ans += mod;
        lcm = mod;
    }
    return {ans, lcm};
}

```

4.4 big exponent modular exponentiation

```

// Calc a^b^c % MOD
// MOD is prime
ll pot(ll x, ll y, ll mod);
void test_case() {
    ll a, b, c;
    cin >> a >> b >> c;
    // fermat theorem
    // a^(p-1) = 1 (mod p)
    b = pou(b, c, MOD - 1);
    a = pou(a, b, MOD);
    cout << a << "\n";
}

```

5 2. Dp

5.1 linear recurrence cayley halmiton


```
// O(N^2 log K)
const int mod = 1e9 + 7;
template <int32_t MOD>
struct modint {
    int32_t value;
    modint() = default;
    modint(int32_t value_) : value(value_) {}
    inline modint<MOD> operator + (modint<MOD> other)
    const { int32_t c = this->value + other.value; return
    modint<MOD>(c >= MOD ? c - MOD : c); }
    inline modint<MOD> operator * (modint<MOD> other)
    const { int32_t c = (int64_t)this->value * other.value
    % MOD; return modint<MOD>(c < 0 ? c + MOD : c); }
    inline modint<MOD> & operator += (modint<MOD> other)
    { this->value += other.value; if (this->value >= MOD)
    this->value -= MOD; return *this; }
    modint<MOD> pow(uint64_t k) const {
        modint<MOD> x = *this, y = 1;
        for (; k >= 1) {
            if (k & 1) y *= x;
            x *= x;
        }
        return y;
    }
    modint<MOD> inv() const { return pow(MOD - 2); } //
    MOD must be a prime
};
using mint = modint<mod>;
vector<mint> combine (int n, vector<mint> &a,
vector<mint> &b, vector<mint> &tr) {
    vector<mint> res(n * 2 + 1, 0);
    for (int i = 0; i < n + 1; i++) {
        for (int j = 0; j < n + 1; j++) res[i + j] += a[i]
        * b[j];
    }
    for (int i = 2 * n; i > n; --i) {
        for (int j = 0; j < n; j++) res[i - 1 - j] +=
        res[i] * tr[j];
    }
    res.resize(n + 1);
    return res;
};
// transition -> for(i = 0; i < x; i++) f[n] += tr[i] *
f[n-i-1]
// S contains initial values, k is 0 indexed
mint LinearRecurrence(vector<mint> &S, vector<mint>
&tr, long long k) {
    int n = S.size(); assert(n == (int)tr.size());
    if (n == 0) return 0;
    if (k < n) return S[k];
    vector<mint> pol(n + 1), e(pol);
```

```
pol[0] = e[1] = 1;
for (++k; k; k /= 2) {
    if (k % 2) pol = combine(n, pol, e, tr);
    e = combine(n, e, e, tr);
}
mint res = 0;
for (int i = 0; i < n; i++) res += pol[i + 1] * S[i];
return res;
}
void test_case() {
    ll n;
    cin >> n; // Fibonacci
    vector<mint> initial = {0, 1}; // F0, F1
    vector<mint> tr = {1, 1};
    cout << LinearRecurrence(initial, tr, n).value <<
    "\n";
}
```

5.2 dp mask over submasks

```
// DP of submask over submasks
// O(3^n)
// j & (-j); get a '1' bit of j
// for (int j=i;j;j = (j-1)&i){...} j is submask of 'i'
the mask
ll dp[1<<18]; // answer of mask
ll cst[1<<18]; // cost of use a submask
ll a[18][18]; // elements
ll pos[1<<18]; // trick to get fast the pos
void test_case() {
    ll n;
    cin >> n;
    for (int i=0;i<n;i++) {
        for (int j=0;j<n;j++) {
            cin >> a[i][j];
        }
    }
    for (int i=0;i<n;i++) {
        pos[1<<i] = i;
    }
    for (int i = 0; i < (1<<n); i++) {
        ll j = i;
        vl idxs;
        while (j) {
            ll k = j & (-j);
            idxs.pb(pos[k]);
            j ^= k;
        }
        for (int j = 0; j < idxs.size(); j++) {
            for (int k = j+1; k < idxs.size(); k++) {
                cst[i] += a[idxs[j]][idxs[k]];
            }
        }
    }
}
```

```
    }
    }
    dp[i] = cst[i];
    for (int j=i;j;j = (j-1)&i) {
        dp[i] = max(dp[i],cst[j]+dp[i^j]);
    }
    }
    cout << dp[(1<<n)-1] << "\n";
}
```

5.3 convex hull trick

```
/**
 * Author: Simon Lindholm
 * Description: Container where you can add lines of the
 * form kx+m, and query maximum values at points x.
 * Useful for dynamic programming ('`convex hull trick`').
 * Time: O(log N)
 * Status: stress-tested
 */
// For minimum you can multiply by -1 'k' and 'm'
// when adding, and the answer when querying.
// Tested atcoder.jp/contests/dp/submissions/55836691
#pragma once
struct Line {
    mutable ll k, m, p;
    bool operator<(const Line& o) const {return k < o.k;}
    bool operator<(ll x) const { return p < x; }
};
struct LineContainer : multiset<Line, less<>> {
    // (for doubles, use inf = 1/.0, div(a,b) = a/b)
    static const ll inf = LLONG_MAX;
    ll div(ll a, ll b) { // floored division
        return a / b - ((a ^ b) < 0 && a % b); }
    bool isect(iterator x, iterator y) {
        if (y == end()) return x->p = inf, 0;
        if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
        else x->p = div(y->m - x->m, x->k - y->k);
        return x->p >= y->p;
    }
    void add(ll k, ll m) {
        auto z = insert({k, m, 0}), y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y))
            isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            isect(x, erase(y));
    }
    ll query(ll x) {
        assert(!empty());
        auto l = *lower_bound(x);
```

```

return l.k * x + l.m;
}
};

```

5.4 knuths optimization

```

/*
Knuth's Optimization
For dp[i][j] = min_{i<=k<=j} dp[i][k] + dp[k+1][j] +
cost[i][j]
Optimizing that from O(n^3) to O(n^2), it's required to
hold the following:
opt[i][j] = optimal splitting point of dp[i][j], the
'k' the minimizes the above definition
opt[i][j-1] <= opt[i][j] <= opt[i+1][j]
You can demonstrate that by the following:
a<=b<=c<=d
cost(b,c) <= cost(a,d), // an contained interval is <=
of the interval
cost(a,c)+cost(b,d) <= cost(a,d)+cost(b,c) // partial
intersection <= total intersection
Complexity: O(n^2)
*/
void test_case() {
    cin >> n; nums.assign(n,0); pf.assign(n+1,0); // READ
input!!!
    for (int i = 0; i < n; i++) cin >> nums[i], pf[i+1] =
pf[i] + nums[i];
    for (int i = 0; i < n; i++) { // base case
        dp[i][i] = 0; // depends of the dp!!!!
        opt[i][i] = i;
    }
    for (int i = n-2; i >= 0; i--) {
        for (int j = i+1; j < n; j++) {
            dp[i][j] = inf; // set to inf, any option
is better, or use -1 or a flag!!
            //note about dp[i][j] is that I set inf instead of
cost(i,j) and it got accepted, not sure why
            ll cost = sum(i,j); // depends of problem
            for (int k = opt[i][j-1]; k <=
min(j-1, opt[i+1][j]); k++) {
                ll actual = dp[i][k] + dp[k+1][j] +
cost;
                if (actual < dp[i][j]) { // if flag
'-1' used, change here!!
                    dp[i][j] = actual;
                    opt[i][j] = k;
                }
            }
        }
    }
}

```

```

cout << dp[0][n-1] << "\n";
}
// https://cses.fi/problemset/task/2088
// https://www.spoj.com/problems/BRKSTRNG/

```

5.5 sos dp

```

// F(mask) = op(F(x_1), F(x_2), ...) where x is submask
of mask
// init sos[z]
for (int i = 0; i < M; i++) {
    for (int mask = 0; mask < (1 << M); mask++) {
        if (mask & (1 << i)) {
            sos[mask] += sos[mask ^ (1 << i)];
        }
    }
}

```

5.6 divide and conquer optimization

```

/*
Dividir un arreglo en k segmentos contiguos minimizando
(suma del segmento)^2
dp(i,j) = min 0<=k<=j such that dp(i-1,k-1) + cost(k,j)
Only works when cost(a,c)+cost(b,d) <=
cost(a,d)+cost(b,c)
dp(i,j) = 0 when j < 0
*/
const int mxn = 3005;
int nums[mxn], pf[mxn];
vector<ll> dp_cur, dp_before;
ll cost(ll i, ll j) {
    return (pf[j+1]-pf[i])*(pf[j+1]-pf[i]);
}
void solve(ll l, ll r, ll optl, ll optr) {
    if (r < l) return;
    ll mid = (l+r)>>1;
    pair<ll,int> best = {INT64_MAX, -1};
    for (int i = optl; i <= min(optr,mid); i++) {
        // check if dp_before[-1] should be 0
        ll nxt = (i ? dp_before[i-1] : 0) + cost(i,mid);
        best = min(best, {nxt,i});
    }
    dp_cur[mid] = best.first;
    ll p = best.second;
    solve(l,mid-1,optl,p);
    solve(mid+1,r,p,optr);
}
void test_case() {
    ll n, k; cin >> n >> k;
    dp_before.assign(n,0);
    dp_cur.assign(n,0);
}

```

```

for (int i = 0; i < n; i++)
    cin >> nums[i], pf[i+1] = pf[i] + nums[i];
for (int i = 0; i < n; i++) dp_before[i] = cost(0,i);
for (int i = 2; i <= k; i++) {
    solve(0,n-1,0,n-1);
    dp_before = dp_cur;
}
cout << dp_before[n-1] << "\n";
} // https://cses.fi/problemset/task/2086/

```

5.7 multiple knapsack optimization

```

/*
Multiple Knapsack
Time complexity is O(W*N*sum)
W = capacity, N = number of objects,
sum is: for (int i = 0; i < n; i++) sum +=
log2(copies[i])
Tested in https://cses.fi/problemset/task/1159/
n<=100, capacity<=10^5, copies[i]<=1000
*/
ll multipleKnapsack(vl &value, vl& weight,
                    vl&copies, ll capacity) {
    vl vs, ws;
    ll n = value.size();
    for (int i = 0; i < n; i++) {
        ll h = value[i], s = weight[i], k = copies[i];
        ll p = 1;
        while (k > p) {
            k -= p; // Binary Grouping Optimization
            vs.pb(s*p); ws.pb(h*p); p *= 2;
        }
        if (k) {
            vs.pb(s*k); ws.pb(h*k);
        }
    }
    vl dp(capacity+1);
    // 0-1 knapsack
    for (int i = 0; i < ws.size(); i++) {
        for (int j = capacity; j >= ws[i]; j--) {
            dp[j] = max(dp[j], dp[j-ws[i]] + vs[i]);
        }
    }
    return dp[capacity];
}

```

5.8 optimizing pragmas for bitset

```

#pragma GCC optimize("O3,unroll-loops")
#pragma GCC target("avx2,bmi,bmi2,lzcnt,popcnt")
// without popcnt is TLE in cses /task/2137/

```

5.9 longest increasing subsequence

```
// Find the Longest Increasing Subsequence of an array
in O(n log n)
int lis(vl &nums) {
    vl best;
    int n = nums.size();
    for (int i = 0; i < n; i++) {
        // For non-decreasing
        // int idx=upper_bound(all(best),nums[i])- bst.be()
        // For increasing
        int idx =
            lower_bound(all(best),nums[i])-best.begin();
        if (idx == best.size()) best.pb(nums[i]);
        else best[idx] = min(best[idx], nums[i]);
    }
    return best.size();
}
```

5.10 sos dp reverse

```
// Useful to calculate reverse sos DP.
// DP[x] = op(DP[y_1], DP[y_2], ...), where x is
submask of y_i
vector<ll> nums(n);
for (int i = 0; i < n; i++) {
    nums[i] = rd(); // read submask, and set init
state
    dp[nums[i]] = min(dp[nums[i]], {0, i});
}
for (int mask = (1<<m)-1; mask >= 0; mask--) { //
You can switch fors depends of the problem
    if (dp[mask].first > 0) continue; // Don't
propagate
    for (int i = 0; i < m; i++) {
        if ((mask >> i) & 1) { // Propagate to all
submasks
            auto nxt = dp[mask]; nxt.first--;
            dp[mask^(1ll<<i)] =
min(dp[mask^(1ll<<i)], nxt);
        }
    }
}
```

5.11 linear recurrence matrix exponciation

```
// Solves  $F_n = C_{n-1} * F_{n-1} + \dots + C_0 * F_0 + p + q * n + r * n^2$ 
// O((n+3)^3 * log(k))
// Also solves (k steps)-min path of a matrix in same
```

```
complexity
// Tested and for more details see: https://codeforces.
com/blog/entry/80195
const int MOD = 1e9 + 7;
const int N = 10 + 3; // 10 is MAX N, 3 is for p,q,r
inline ll add(ll x, ll y) { return (x+y)%MOD; }
inline ll mul(ll x, ll y) { return (x*y)%MOD; }
// const ll inf = 1ll(1e18) + 5; // for k-min path
struct Mat {
    array<array<ll,N>,N> mt;
    Mat(bool id=false) {
        for (auto &x : mt) fill(all(x),0);
        if (id) for (int i=0;i<N;i++) mt[i][i]=1;
        //for (auto &x : mt) fill(all(x),inf); // For k-min
path
        //if (id) for (int i =0;i<N;i++) mt[i][i]=0;
    }
    inline Mat operator * (const Mat &b) {
        Mat ans;
        for (int k=0;k<N;k++)for(int i=0;i<N;i+
+)for(int j=0;j<N;j++)
            ans.mt[i][j]=add(ans.mt[i][j],mul(mt[i]
[k],b.mt[k][j]));
        //ans.mt[i][j] = min(ans.mt[i][j],mt[i]
[k]+b.mt[k][j]); // For K-min Path
        return ans;
    }
    inline Mat pow(ll k) {
        Mat ans(true),p=*this; // Note '*!!'
        while (k) {
            if (k&1) ans = ans*p;
            p=p*p;
            k>>=1;
        }
        return ans;
    }
    string db() { // Optional for debugging
        string ans;
        for (int i =0;i<mt.size();i++)for (int
j=0;j<mt.size();j++)
            ans +=to_string(mt[i][j]),ans+="
\n"[j==N-1];
        return "\n"+ans;
    }
};
// Important!!! Remember to set N = MAX_N + 3
// Solves  $F_n = C_{n-1} * F_{n-1} + \dots + C_0 * F_0 + p + q * n + r * n^2$ 
// f = {f_0,f_1,f_2,f_3,...,f_n}
// c = {c_0,c_1,c_2,c_3,...,c_n}
ll fun(vl f, vl c, ll p, ll q, ll r, ll k) {
```

```
ll n = c.size();
if (k < n) return f[k];
reverse(all(c)),reverse(all(f));
Mat mt,st;
for (int i = 0;i<n;i++) mt.mt[0][i]=c[i];
for (int i = 1;i<n;i++) mt.mt[i][i-1]=1;
for (int i = 0;i<n;i++) st.mt[i][0]=f[i];
vl extra = {p,q,r}; // To extend here with
1*p,i*q,i*i*r,etc
for (int i=0;i<extra.size();i++) {
    st.mt[n+i][0]=1; //1,i,i*i,i*i*i
    mt.mt[0][n+i]=extra[i]; //p,q,r
    mt.mt[n+i][n]=1; //pascal
    for (int j=1;j<=i;j++) { //pascal
        st.mt[n+i][0]*=n; //1,i*i,i*i*i
        mt.mt[n+i][n+j]=mt.mt[n+i-1]
[n+j]+mt.mt[n+i-1][n+j-1];
    }
    return (mt.pow(k-(n-1))*st).mt[0][0];
}
```

5.12 separation optimization

No se si tiene un nombre, pero en varios problemas vi este truco:
 $dp[x] = f(x,y)$ donde se necesita un optimo 'y'.
 Truco: si puedes separarlo en $f(x,y)$ en $f(x)$ (+) $f(y)$, puedes guardar en una estructura optima $f(y)$ como un segment tree.

6 3. Data Structures

6.1 multioorderedset

```
#include <bits/stdc++.h>
#include <ext/pb_ds/tree_policy.hpp>
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
struct multioordered_set {
    tree<ll,
        null_type,
        less_equal<ll>, // this is the trick
        rb_tree_tag,
        tree_order_statistics_node_update> oset;
    //this function inserts one more occurrence of (x)
into the set.
    void insert(ll x) {
        oset.insert(x);
    }
    //this function checks weather the value (x) exists
```

```

in the set or not.
bool exists(ll x) {
    auto it = oset.upper_bound(x);
    if (it == oset.end()) {
        return false;
    }
    return *it == x;
}
//this function erases one occurrence of the value
(x).
void erase(ll x) {
    if (exists(x)) {
        oset.erase(oset.upper_bound(x));
    }
}
//this function returns the value at the index
(idx)..(0 indexing).
ll find_by_order(ll pos) {
    return *(oset.find_by_order(pos));
}
//this function returns the first index of the
value (x)..(0 indexing).
int first_index(ll x) {
    if (!exists(x)) {
        return -1;
    }
    return (oset.order_of_key(x));
}
//this function returns the last index of the value
(x)..(0 indexing).
int last_index(ll x) {
    if (!exists(x)) {
        return -1;
    }
    if (find_by_order(size() - 1) == x) {
        return size() - 1;
    }
    return first_index(*oset.lower_bound(x)) - 1;
}
//this function returns the number of occurrences
of the value (x).
int count(ll x) {
    if (!exists(x)) {
        return -1;
    }
    return last_index(x) - first_index(x) + 1;
}
// Count the numbers between [l, r]
int count(ll l, ll r) {
    auto left = oset.upper_bound(l);
    if (left == oset.end() || *left > r) {

```

```

        return 0;
    }
    auto right = oset.upper_bound(r);
    if (right != oset.end()) {
        right =
oset.find_by_order(oset.order_of_key(*right));
    }
    if (right == oset.end() || *right > r) {
        if (right == oset.begin()) return 0;
        right--;
    }
    return last_index(*right) - first_index(*left) + 1;
}
//this function clears all the elements from the
set.
void clear() {
    oset.clear();
}
//this function returns the size of the set.
ll size() {
    return (ll)oset.size();
}
};

```

6.2 persistant segment tree

```

struct Vertex {
    Vertex *l, *r;
    ll sum;
    Vertex(int val) : l(nullptr), r(nullptr), sum(val)
{}
    Vertex(Vertex *l, Vertex *r) : l(l), r(r), sum(0) {
        if (l) sum += l->sum;
        if (r) sum += r->sum;
    }
};
Vertex* build(vector<ll>& a, int tl, int tr) {
    if (tl == tr)
        return new Vertex(a[tl]);
    int tm = (tl + tr) / 2;
    return new Vertex(build(a, tl, tm), build(a, tm+1,
tr));
}
ll get_sum(Vertex* v, int tl, int tr, int l, int r) {
    if (l > r)
        return 0;
    if (l == tl && tr == r)
        return v->sum;
    int tm = (tl + tr) / 2;
    return get_sum(v->l, tl, tm, l, min(r, tm))
        + get_sum(v->r, tm+1, tr, max(l, tm+1), r);
}

```

```

}
Vertex* update(Vertex* v, int tl, int tr, int pos, int
new_val) {
    if (tl == tr)
        return new Vertex(new_val);
    int tm = (tl + tr) / 2;
    if (pos <= tm)
        return new Vertex(update(v->l, tl, tm, pos,
new_val), v->r);
    else
        return new Vertex(v->l, update(v->r, tm+1, tr,
pos, new_val));
}
Vertex* build(vector<ll> &a) {
    return build(a, 0, a.size() - 1);
}
ll get_sum(Vertex *v, ll n, int l, int r) {
    return get_sum(v, 0, n - 1, l, r);
}
Vertex* update(Vertex* v, ll n, int pos, int newV) {
    return update(v, 0, n - 1, pos, newV);
}
Vertex* copy(Vertex* v) {
    return new Vertex(v->l, v->r);
}
}

```

6.3 fenwick tree 2d

```

struct BIT2D { // 1-indexed
    vector<v> bit;
    ll n, m;
    BIT2D(ll n, ll m) : bit(n+1, v(m+1)), n(n), m(m){}
    ll lsb(ll i) { return i & -i; }
    void add(int row, int col, ll x) {
        for (int i = row; i <= n; i += lsb(i))
            for (int j = col; j <= m; j += lsb(j))
                bit[i][j] += x;
    }
    ll sum(int row, int col) {
        ll res = 0;
        for (int i = row; i > 0; i -= lsb(i))
            for (int j = col; j > 0; j -= lsb(j))
                res += bit[i][j];
        return res;
    }
    ll sum(int x1, int y1, int x2, int y2) {
        return sum(x2, y2) - sum(x1-1, y2)
            - sum(x2, y1-1) + sum(x1-1, y1-1);
    }
    void set(int x, int y, ll val) {
        add(x, y, val - sum(x, y, x, y));
    }
}

```

```
}
};
```

6.4 fast hash map

```
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
const int RANDOM =
chrono::high_resolution_clock::now().time_since_epoch().count();
struct chash {
    long long operator()(const ll &x) const {
        return x ^ RANDOM;
    };
};
// There is no mp.count(x), so use mp.find(x) !=
mp.end()
gp_hash_table<ll,ll,chash> mp;
```

6.5 rope

```
/**
 * Description: insert element at $i$-th position, cut
a substring and
 * re-insert somewhere else. At least 2 times slower
than handwritten treap.
 * Time:  $O(\log N)$  per operation? not well tested
 * Source: https://codeforces.com/blog/entry/10355
 * Verification: CEOI 2018 Day 2 Triangles
 * https://szkopul.edu.pl/problemset/problem/AzKAZ2RDIVTjEWSBolwoC5zL/site/?key=statement
 * vector is faster for this problem ...
 */
#include <ext/rope>
using namespace __gnu_cxx;
void ropeExample() {
    rope<int> v(5,0); // initialize with 5 zeroes
    FOR(i,sz(v)) v.mutable_reference_at(i) = i+1;
    FOR(i,5) v.pb(i+1); // constant time pb
    rope<int> cur = v.substr(1,2);
    v.erase(1,3); // erase 3 elements starting from 1st
element
    for (rope<int>::iterator it = v.mutable_begin();
        it != v.mutable_end(); ++it) pr((int)*it, ' ');
    ps(); // 1 5 1 2 3 4 5
    v.insert(v.mutable_begin()+2,cur); // or just 2
    v += cur; FOR(i,sz(v)) pr(v[i], ' ');
    ps(); // 1 5 2 3 1 2 3 4 5 2 3
}
/*
Tested in cses https://cses.fi/problemset/task/1749/
https://cses.fi/problemset/result/10105636/ 2 times
slower than ordered set
```

It's better to create rope with an given size and value
TLE with $2 \cdot 10^5$
Need revision!!
push_back() - $O(\log N)$.
pop_back() - $O(\log N)$
insert(int x, crope rl): $O(\log N)$ and Worst $O(N)$
substr(int x, int l): $O(\log N)$
replace(int x, int l, crope rl): $O(\log N)$.

6.6 fenwick tree

```
struct FenwickTree {
    vector<int> bit;
    int n;
    FenwickTree(int n) {
        this->n = n;
        bit.assign(n, 0);
    }
    FenwickTree(vector<int> a) : FenwickTree(a.size())
{
    for (size_t i = 0; i < a.size(); i++)
        add(i, a[i]);
}
    int sum(int r) {
        int ret = 0;
        for (; r >= 0; r = (r & (r + 1)) - 1)
            ret += bit[r];
        return ret;
    }
    int sum(int l, int r) {
        return sum(r) - sum(l - 1);
    }
    void add(int idx, int delta) {
        for (; idx < n; idx = idx | (idx + 1))
            bit[idx] += delta;
    }
    // TODO: Lower Bound
};
```

6.7 dynamic connectivity

```
struct union_find {
    struct uf_save { ll a, rnka, b, rnkb; };
    vector<uf_save> saves;
    vector<ll> p, rnk;
    ll n, comps;
    union_find(ll _n) : n(_n), p(_n), rnk(_n) {
        for (int i = 0; i < n; i++) p[i] = i;
        comps = n;
    };
    ll find(ll x) { return p[x] == x ? x : find(p[x]); }
```

```
int merge(ll a, ll b) {
    a = find(a);
    b = find(b);
    if (a == b) return 0;
    if (rnk[b] > rnk[a]) swap(a,b);
    comps--;
    saves.pb({a, rnk[a], b, rnk[b]});
    p[b] = a;
    if (rnk[a] == rnk[b]) rnk[a]++;
    return 1;
};
void rollback() {
    if (saves.empty()) return;
    uf_save lst = saves.back();
    saves.pop_back();
    comps++;
    p[lst.a] = lst.a, rnk[lst.a] = lst.rnka;
    p[lst.b] = lst.b, rnk[lst.b] = lst.rnkb;
}
};
struct query { ll a, b; };
struct segtree {
    int n; // size of queries!!!
    vector<vector<query>> t; // node si a vector<query>
    segtree(int queries_n) : n(queries_n), t(2*n) {}
    void addQuery(int l, int r, const query &q) {
        l += n, r += n+1;
        for (; l < r; l >>= 1, r >>= 1) {
            if (l&1) t[l++].pb(q);
            if (r&1) t[--r].pb(q);
        }
    }
    void dfs(int id, vector<ll> &ans, union_find &uf) {
        ll cnt = 0;
        for (auto &q : t[id]) cnt+=uf.merge(q.a, q.b);
        if (id < n)
            dfs(id*2, ans, uf), dfs(id*2+1,ans,uf);
        else ans[id-n] = uf.comps;
        for (int i =0;i<cnt;i++) uf.rollback();
    }
    vector<ll> solve(union_find &uf) {
        vector<ll> ans(n);
        dfs(1, ans, uf);
        return ans;
    }
};
void test_case() {
    ll n, m, q; cin >> n >> m >> q;
    segtree tree(q+1);
    vector<map<int,int>> lst(n); // to manage living
time!
```



```

auto addEdge = [&](int x, int y, int time) {
    if (y<x) swap(x,y);
    lst[x][y] = time;
};

auto erEdge = [&](int x, int y, int time) {
    if (y<x) swap(x,y);
    tree.addQuery(lst[x][y], time-1, {x,y});
    lst[x].erase(y);
};

for (int i = 0; i<m; i++) {
    ll x, y; cin >> x >> y; x--, y--;
    addEdge(x,y,0);
}

for (int time = 1; time<=q; time++) {
    ll t, x, y; cin >> t >> x >> y;
    x--, y--;
    if (t==1) addEdge(x,y,time);
    else erEdge(x,y,time);
}

for (int i = 0; i < n; i++)
    for (auto &[j,v] : lst[i]) // be carefull with
it and erasing
        tree.addQuery(v,q,{i,j});
union_find uf(n);
auto ans = tree.solve(uf);
for (int i = 0; i < ans.size(); i++) {
    cout << ans[i] << " \n" [i+1 == ans.size()];
}
} // https://cses.fi/problemset/task/2133/

```

6.8 min sparse table

```

using Type = int;
// Gets the minimum in a range [l,r] in O(1)
// Preprocessing is O(n log n)
struct min_sparse {
    int log;
    vector<vector<Type>> sparse;
    void init(vector<Type> &nums) {
        int n = nums.size();
        log = 0;
        while (n) log++, n/=2;
        n = nums.size();
        sparse.assign(n, vector<Type>(log, 0));
        for (int i = 0; i < n; i++) sparse[i][0] = nums[i];
        for (int l = 1; l < log; l++) {
            for (int j = 0; j + (1 << l) - 1 < n; j++) {
                sparse[j][l] = min(sparse[j][l-1],
                    sparse[j+(1 << (l-1))][l-1]);
            }
        }
    }
};

```

```

}
Type query(int x, int y) {
    int n = y - x + 1;
    int logg = -1;
    while (n) logg++, n/=2; // TODO: improve this
with fast builtin
    return min(sparse[x][logg], sparse[y-(1 <<
logg)+1][logg]);
}
};

```

6.9 orderedset

```

// Same as set, but you can get the order of an element
or the
// element in given sorted position in O(log n)
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
#define oset tree<ll, null_type, less<ll>,
rb_tree_tag, tree_order_statistics_node_update>
//find_by_order(k) order_of_key(k)

```

6.10 lazy segment tree

```

/*
Lazy Iterative Seg Tree.
This example is for cses 1735
*/
struct Node { ll x; };
const ll SET = 1;
const ll ADD = 2;
struct Func { ll type, val; }; // applied Function
Node e() { return { 0 }; }; // op(x, e()) = x
Func id() { return {ADD, 0}; } // mapping(x, id()) = x
Node op(Node &a, Node &b) { // associative property
    return {a.x + b.x};
}
Node mapping(Node node, ll sz, const Func &lazy) {
    if (lazy.type == SET) node.x = lazy.val * sz;
    else node.x += lazy.val * sz;
    return node;
}
Func comp(Func prev, const Func &actual) {
    if (actual.type==SET) return actual;
    if (prev.type == SET)
        return {SET, prev.val+actual.val};
    return {ADD, prev.val + actual.val};
}
struct lazyseg {
    ll n, h;
    vector<Node> t;
};

```

```

vector<Func> lz;
vector<int> sz; // if sz of node needed
lazyseg(ll n) : n(n), t(2*n, e()), lz(n, id()), sz(2*n, 1) {
    h = 32-__builtin_clz(n);
    for (int i = n-1; i>0; i--) sz[i]=sz[i*2]+sz[i*2+1];
}

void all_apply(ll x, const Func & f) {
    t[x] = mapping(t[x], sz[x], f);
    if (x<n) lz[x] = comp(lz[x], f);
}

void push(ll x) {
    all_apply(x*2, lz[x]);
    all_apply(x*2+1, lz[x]);
    lz[x] = id();
}

void build(ll x) {
    t[x] = op(t[x*2], t[x*2+1]);
}

bool ok(ll x, ll i) {
    return ((x>>i)<<i)!=x;
}

void update(ll p, Node v) {
    p += n;
    for (int i = h; i>0; i--) push(p>>i);
    t[p] = v;
    for (int i = 1; i<=h; i++) build(p>>i);
}

Node query(ll l, ll r) {
    if (l>r) return e();
    l += n, r += n+1;
    for (int i=h; i>0; i--) {
        if (ok(l,i)) push(l>>i);
        if (ok(r,i)) push((r-1)>>i);
    }
    Node ansL = e(), ansR = e();
    for (; l<r; l>=1, r>=1) {
        if (l&1) ansL = op(ansL, t[l++]);
        if (r&1) ansR = op(t[--r], ansR);
    }
    return op(ansL, ansR);
}

void apply(ll l, ll r, const Func &f) {
    if (l>r) return;
    l += n, r += n+1;
    for (int i = h; i>0; i--) {
        if (ok(l,i)) push(l>>i);
        if (ok(r,i)) push((r-1)>>i);
    }
    {
        int l2 = l, r2 = r;
        for (; l<r; l>=1, r>=1) {

```

```

        if (l&l) all_apply(l++, f);
        if (r&l) all_apply(--r,f);
    }
    l = l2, r = r2;
}
for (int i = l; i <= h; i++) {
    if (ok(l,i)) build(l>>i);
    if (ok(r,i)) build((r-1)>>i);
}
};
// Maximum r that satisfy g(op(t[l], t[l+1], ...,
t[r-1])) = True
// if there's no g() that returns true, then r = l
template <class G> int max_right(int l, G g) {
    assert(0 <= l && l <= n);
    assert(g(e()));
    if (l == n) return n;
    l += n;
    for (int i = h; i >= 1; i--) push(l >> i);
    Node sm = e();
    do {
        while (l % 2 == 0) l >>= 1;
        if (!g(op(sm, t[l]))) {
            while (l < n) {
                push(l);
                l = (2 * l);
                if (g(op(sm, t[l]))) {
                    sm = op(sm, t[l]);
                    l++;
                }
            }
            return l - n;
        }
        sm = op(sm, t[l]);
        l++;
    } while ((l & -l) != l);
    return n;
}
// If g is monotone, this is the minimum l that
satisfies
// g(op(a[l], a[l + 1], ..., a[r - 1])) = true.
template <class G> int min_left(int r, G g) {
    assert(0 <= r && r <= n);
    assert(g(e()));
    if (r == 0) return 0;
    ll size = n;
    r += size;
    for (int i = h; i >= 1; i--) push((r - 1) >> i);
    Node sm = e();
    do {
        r--;
    }

```

```

        while (r > 1 && (r % 2)) r >>= 1;
        if (!g(op(t[r], sm))) {
            while (r < size) {
                push(r);
                r = (2 * r + 1);
                if (g(op(t[r], sm))) {
                    sm = op(t[r], sm);
                    r--;
                }
            }
            return r + 1 - size;
        }
        sm = op(t[r], sm);
    } while ((r & -r) != r);
    return 0;
}
};

```

6.11 sqrt mod

```

/*
Trick using SQRT for problems using de diferent floor
values o a num.
A num has only around SQRT(n) possible values when
it is floor divided, for 2e5 is around 890
e.g. floor(n/i)=j. j has around sqrt(n) values.
e.g. floor(10/i)=j. j only can be 1,2,3,5,10 for any i
The following function calculates when a n/i changes
if you iterate over i increasing.
You can solve CF GYM 105009/L using this.
*/
const int MXN = 2e5 + 10;
int nums[MXN];
vector<int> ch[MXN];
for (int i = 0; i < n; i++) {
    for (int d = 1; d <= nums[i]; d = nums[i] / (nums[i] / d) + 1) {
        ch[d].pb(i);
    }
    ch[nums[i] + 1].pb(i);
}

```

6.12 persistance segtree

```

const int mxn = 2e5;
struct Node { int l=0,r=0; ll sum=0; }; //Elem Neutro
int T = 0; // st[0] siempre neutro
Node st[mxn*30]; //!!!! Check
struct PST {
    inline int nn(ll s) {
        ++T, st[T] = {0,0,s};
        return T;
    }
}

```

```

inline int nn(int l, int r) {
    ++T, st[T] = {l,r,0};
    if (l) st[T].sum += st[l].sum;
    if (r) st[T].sum += st[r].sum;
    return T;
}
int build(int tl, int tr, vector<ll> &a) {
    if (tl==tr) return nn(a[tr]);
    int m = (tl+tr)>>1;
    return nn(build(tl,m,a), build(m+1,tr,a));
}
ll qry(int v, int tl, int tr, int l, int r) {
    if (!v || r < tl || tr < l) return 0;
    if (l <= tl && tr <= r) return st[v].sum;
    int tm = (tl+tr)>>1;
    return qry(st[v].l, tl, tm, l, r)
        + qry(st[v].r, tm+1, tr, l, r);
}
int upd(int v, int tl, int tr, int pos, ll val) {
    if (tl==tr) return nn(val);
    int tm = (tl+tr)>>1;
    if (pos <= tm)
        return nn(upd(st[v].l, tl, tm, pos, val), st[v].r);
    return nn(st[v].l, upd(st[v].r, tm+1, tr, pos, val));
}
int build(vector<ll> &a) {
    return build(0, (int)a.size()-1, a);
}
ll query(int v, int n, int l, int r) {
    return qry(v, 0, n-1, l, r);
}
int upd(int v, int n, int pos, int val) {
    return upd(v, 0, n-1, pos, val);
}
int copy(int v) { return v; }
};

```

6.13 mo's

```

/*
Mo's algorithm O((N + Queries)*SQRT(N))
It answers queries offline using SQRT Descomposition,
sometimes get TLE when you have Set, Map, various
iteration when adding, So you need to implement
efficiently (with arrays) in O(1). You can answer
questions like in a range, the number of distincts
values.
*/
// For se 1e5=310, for 2e5=430
const int BLOCK_SIZE = 430;
struct query {

```

```

int l, r, idx;
bool operator <(query &other) const {
    return MP(l / BLOCK_SIZE, r) <
        MP(other.l / BLOCK_SIZE, other.r);
}
};
void add(int idx);
void remove(int idx);
ll getAnswer();
vector<ll> mo(vector<query> queries) {
    vector<ll> answers(queries.size());
    int l = 0;
    int r = -1;
    sort(all(queries));
    each(q, queries) {
        while (q.l < l) add(--l);
        while (r < q.r) add(++r);
        while (l < q.l) remove(l++);
        while (q.r < r) remove(r--);
        answers[q.idx] = getAnswer();
    }
    return answers;
}
v1 nums; //init
ll ans = 0;
int cnt[1000001];
void add(int idx) {
    // update ans, when adding an element
}
void remove(int idx) {
    // update ans, when removing an element
}
ll getAnswer() { return ans; }
    
```

6.14 segment tree 2d

```

// Tested: https://www.spoj.com/problems/MATSUM/
struct Node { ll x = 0; };
Node e() { return Node(); } // Identity element,
op(x,e()) = x
// Binary Operation, Associative. (a+b)+c = a+(b+c)
Node op(const Node &a, const Node &b) {
    Node c;
    c.x = a.x + b.x;
    return c;
}
struct segtree2d {
    int n, m;
    vector<vector<Node>> t;
    void init(int n, int m) {
        this->n = n;
    }
}
    
```

```

this->m = m;
t.assign(n*2, vector<Node>(m*2, e()));
}
void init(int n, int m, vector<vector<Node>> &nums) {
    init(n, m);
    for (int i = 0; i < n; i++) { // build leaf segtrees
        for (int j = 0; j < m; j++) t[i+n][j+m] = nums[i][j];
        for (int j = m-1; j > 0; j--)
            t[i+n][j] = op(t[i+n][j*2], t[i+n][j*2+1]);
    }
    // build non leaf segtrees
    for (int i = n-1; i > 0; i--) {
        for (int j = 0; j < 2*m; j++)
            t[i][j] = op(t[i*2][j], t[i*2+1][j]);
    }
}
Node query_y(int x, int l, int r) {
    l += m, r += m+1;
    Node resl = e(), resr = e();
    for (; l < r; l >>= 1, r >>= 1) {
        if (l&1) resl = op(resl, t[x][l++]);
        if (r&1) resr = op(t[x][--r], resr);
    }
    return op(resl, resr);
}
Node query(int x1, int y1, int x2, int y2) {
    ll l = x1+n, r = x2+n+1;
    Node resl = e(), resr = e();
    for (; l < r; l >>= 1, r >>= 1) {
        if (l&1) resl = op(resl, query_y(l++, y1, y2));
        if (r&1) resr = op(query_y(--r, y1, y2), resr);
    }
    return op(resl, resr);
}
void update(int x, int y, const Node &v) {
    x += n, y += m;
    t[x][y] = v; // fix leaf segtrees
    for (int j = y; j >>= 1; ) {
        t[x][j] = op(t[x][j*2], t[x][j*2+1]);
    }
    for (; x >>= 1; ) { // fix non leaf segtree
        t[x][y] = op(t[x*2][y], t[x*2+1][y]);
        for (int j = y; j >>= 1; ) {
            t[x][j] = op(t[x*2][j], t[x*2+1][j]);
        }
    }
}
Node get(int x, int y) { return t[x+n][y+m]; }
}
    
```

6.15 custom hash

```

// Avoid hashing hacks and improve performance of hash
structures
// e.g. unordered_map<ll,ll,custom_hash>
// use a fixed ll FIXED_RANDOM =
chrono::steady_clock::now().time_since_epoch().count();
struct custom_hash {
    size_t operator()(uint64_t x) const {
        x ^= FIXED_RANDOM;
        return x ^ (x >> 16);
    }
};
// pair
struct chash {
    size_t operator()(const pair<ll,ll>&x) const {
        return ...;
    }
};
    
```

6.16 segment tree

```

const int inf = 1e9;
// >>>>>>> Implement
struct Node { ll mn = inf, mx = -inf; };
Node e() { return Node(); } // op(a, e()) = a
Node op(const Node &a, const Node &b) { // asoc property
    Node c;
    c.mn = min(a.mn, b.mn); c.mx = max(a.mx, b.mx);
    return c;
}
// <<<<<<<
struct segtree {
    vector<Node> t;
    ll n;
    void init(int n) {
        t.assign(n * 2, e());
        this->n = n;
    }
    void init(vector<Node> &s) {
        n = s.size();
        t.assign(n * 2, e());
        for (int i = 0; i < n; i++) t[i+n] = s[i];
        build();
    }
    void build() { // build the tree
        for (int i = n - 1; i > 0; --i)
            t[i] = op(t[i*2], t[i*2+1]);
    }
    // set value at position p
    void update(int p, const Node &value) {
        for (t[p += n] = value; p >>= 1; )
            t[p] = op(t[p*2], t[p*2+1]);
    }
}
    
```



```

}
// sum on interval [l, r]
Node query(int l, int r) {
    r++; // make this inclusive
    Node resl=e(), resr=e(); // null element
    for (l += n, r += n; l < r; l >>= 1, r >>= 1) {
        if (l&1) resl = op(resl, t[l++]);
        if (r&1) resr = op(t[--r], resr);
    }
    return op(resl, resr);
}
Node get(int i) {
    return t[i+n];
}
// Maximum r that satisfy g(op(t[l], t[l+1], ...,
t[r-1])) = True
// if there's no g() that returns true, then r = l
template <class F> int max_right(int l, F f) const
{
    assert(0 <= l && l <= n);
    assert(f(e()));
    if (l == n) return n;
    ll size = n;
    l += size;
    Node sm = e();
    do {
        while (l % 2 == 0) l >>= 1;
        if (!f(op(sm, t[l]))) {
            while (l < size) {
                l = (2 * l);
                if (f(op(sm, t[l]))) {
                    sm = op(sm, t[l]);
                    l++;
                }
            }
            return l - size;
        }
        sm = op(sm, t[l]);
        l++;
    } while ((l & -l) != l);
    return n;
}
// If g is monotone, this is the minimum l that
satisfies
// g(op(a[l], a[l + 1], ..., a[r - 1])) = true.
template <class F> int min_left(int r, F f) const {
    assert(0 <= r && r <= n);
    assert(f(e()));
    if (r == 0) return 0;
    ll size = n;
    r += size;

```

```

Node sm = e();
do {
    r--;
    while (r > 1 && (r % 2)) r >>= 1;
    if (!f(op(t[r], sm))) {
        while (r < size) {
            r = (2 * r + 1);
            if (f(op(t[r], sm))) {
                sm = op(t[r], sm);
                r--;
            }
        }
        return r + 1 - size;
    }
    sm = op(t[r], sm);
} while ((r & -r) != r);
return 0;
}
};

```

7 4. Graphs

7.1 bellmanford find negative cycle

```

// This uses Bellmanford algorithm to find a negative
cycle
// 0(n*m) m=edges, n=nodes
void test_case() {
    ll n, m;
    cin >> n >> m;
    vector<ll> dist(n+1);
    vector<ll> p(n+1);
    vector<tuple<ll,ll,ll>> edges(m);
    for (int i =0; i < m; i++) {
        ll x, y, z;
        cin >> x >> y >> z;
        edges[i] = {x, y, z};
    }
    ll efe = -1;
    for (int i = 0; i < n; i++) {
        efe = -1;
        for (auto pp : edges) {
            ll x,y,z;
            tie(x,y,z) = pp;
            if (dist[x] + z < dist[y]) {
                dist[y] = dist[x] + z;
                p[y] = x;
                efe = y;
            }
        }
    }
}

```

```

}
if (efe == -1) {
    cout << "NO\n";
} else {
    cout << "YES\n";
    ll x = efe;
    for (int i = 0; i < n; i++) {
        x = p[x];
    }
    vector<ll> cycle;
    ll y = x;
    while (cycle.size() == 0 || y != x) {
        cycle.pb(y);
        y = p[y];
    }
    cycle.pb(x);
    reverse(all(cycle));
    for (int i =0; i < cycle.size(); i++) {
        cout << cycle[i] << " \n" [i == cycle.size() -1];
    }
}
}
}

```

7.2 strongly connected components

```

/*
Tarjan t(graph); provides you the SCC of that graph
passing the adjacency listof the graph(as vector<vl>)
This is 0-indexed,(butyou can have node0as dummy-node)
Use t.comp[x] to get the component of node x
SCC is the total number of components
adjComp()
gives you the adjacency list of strongly components
*/
struct Tarjan {
    vl low, pre, comp;
    ll cnt, SCC, n;
    vvl g;
    const int inf = 1e9;
    Tarjan(vvl &adj) {
        n = adj.size();
        g = adj;
        low = vl(n);
        pre = vl(n,-1);
        cnt = SCC = 0;
        comp = vl(n,-1);
        for (int i = 0;i<n;i++)
            if (pre[i] == -1) tarjan(i);
    }
    stack<int> st;
    void tarjan(int u) {

```

```

low[u] = pre[u] = cnt++;
st.push(u);
for (auto &v : g[u]) {
    if (pre[v] == -1) tarjan(v);
    low[u] = min(low[u], low[v]);
}
if (low[u] == pre[u]) {
    while (true) {
        int v = st.top(); st.pop();
        low[v] = inf;
        comp[v] = SCC;
        if (u == v) break;
    }
    SCC++;
}
}
vvl adjComp() {
    vvl adj(SCC);
    for (int i = 0; i < n; i++) {
        for (auto j : g[i]) {
            if (comp[i] == comp[j]) continue;
            adj[comp[i]].pb(comp[j]);
        }
    }
    for (int i = 0; i < SCC; i++) {
        sort(all(adj[i]));
        adj[i].erase(
            unique(all(adj[i])),
            adj[i].end());
    }
    return adj;
}
};
/* Another way is with with Kosaraju:
1. Find topological order of G
2. Run dfs in topological order in reverse Graph
to find o connected component
*/

```

7.3 two sat

```

/*
2-Sat (Boolean satisfiability problem with 2-clause
literals)
Complexity: O(n)
Tested: https://cses.fi/problemset/task/1684
To find a solution that makes this true with N boolean
vars as form:
(x or y) and (~x or y) and (z or ~x) and d and (x ==>
y)
Call s.satisfiable() to see if solution, and sat2.value

```

```

to see
values of variables
*/
struct sat2 {
    int n;
    vector<vector<vector<int>>> g;
    vector<int> tag;
    vector<bool> seen, value;
    stack<int> st;
    sat2(int n) : n(n), g(2, vector<vector<int>>(2*n)),
        tag(2*n), seen(2*n), value(2*n) {}
    int neg(int x) { return 2*n-x-1; }
    void add_or(int u, int v) { implication(neg(u), v); }
    void make_true(int u) { add_edge(neg(u), u); }
    void make_false(int u) { make_true(neg(u)); }
    void eq(int u, int v) {
        implication(u, v);
        implication(v, u);
    }
    void diff(int u, int v) { eq(u, neg(v)); }
    void implication(int u, int v) {
        add_edge(u, v);
        add_edge(neg(v), neg(u));
    }
    void add_edge(int u, int v) {
        g[0][u].push_back(v);
        g[1][v].push_back(u);
    }
    void dfs(int id, int u, int t = 0) {
        seen[u] = true;
        for (auto &v : g[id][u])
            if (!seen[v])
                dfs(id, v, t);
        if (id == 0) st.push(u);
        else tag[u] = t;
    }
    void kosaraju() {
        for (int u = 0; u < n; u++) {
            if (!seen[u]) dfs(0, u);
            if (!seen[neg(u)]) dfs(0, neg(u));
        }
        fill(seen.begin(), seen.end(), false);
        int t = 0;
        while (!st.empty()) {
            int u = st.top(); st.pop();
            if (!seen[u]) dfs(1, u, t++);
        }
    }
    bool satisfiable() {
        kosaraju();
        for (int i = 0; i < n; i++) {

```

```

            if (tag[i] == tag[neg(i)]) return false;
            value[i] = tag[i] > tag[neg(i)];
        }
        return true;
    }
};

```

8 5. Flow

8.1 hungarian

```

// Halla el maximo match en un grafo bipartito con
pesos (min cost) O(V ^ 3)
typedef ll T;
const T inf = 1e18;
struct hung {
    int n, m;
    vector<T> u, v; vector<int> p, way;
    vector<vector<T>> g;
    hung(int n, int m):
        n(n), m(m), g(n+1, vector<T>(m+1, inf-1)),
        u(n+1), v(m+1), p(m+1), way(m+1) {}
    void set(int u, int v, T w) { g[u+1][v+1] = w; }
    T assign() {
        for (int i = 1; i <= n; ++i) {
            int j0 = 0; p[0] = i;
            vector<T> minv(m+1, inf);
            vector<char> used(m+1, false);
            do {
                used[j0] = true;
                int i0 = p[j0], j1; T delta = inf;
                for (int j = 1; j <= m; ++j) if (!
                    used[j]) {
                        T cur = g[i0][j] - u[i0] - v[j];
                        if (cur < minv[j]) minv[j] = cur,
                            j1 = j;
                    }
                if (minv[j1] < delta) delta =
                    minv[j1], j1 = j1;
            } while (j1 != 0);
            for (int j = 0; j <= m; ++j)
                if (used[j]) u[p[j]] += delta, v[j]
                    -= delta;
            else minv[j] -= delta;
            j0 = j1;
        } while (p[j0]);
        do {
            int j1 = way[j0]; p[j0] = p[j1]; j0 =
                j1;
        } while (j0);
    }
};

```

```

        return -v[0];
    }
};

```

8.2 max flow

```

// #define int long long // take care int overflow with this
// #define vi vector<long long>
struct Dinitz {
    const int INF = 1e9 + 7;
    Dinitz() {}
    Dinitz(int n, int s, int t) { init(n, s, t); }
    void init(int n, int s, int t) {
        {
            S = s, T = t;
            nodes = n;
            G.clear(), G.resize(n);
            Q.resize(n);
        }
        struct flowEdge {
            int to, rev, f, cap;
        };
        vector<vector<flowEdge>> G;
        // Añade arista (st -> en) con su capacidad
        void addEdge(int st, int en, int cap) {
            flowEdge A = {en, (int)G[en].size(), 0, cap};
            flowEdge B = {st, (int)G[st].size(), 0, 0};
            G[st].pb(A);
            G[en].pb(B);
        }
        int nodes, S, T; // asignar estos valores al armar el grafo G
        // nodes = nodos en red de flujo.
        Hacer G.clear(); G.resize(nodes);
        vi work, lvl;
        vi Q;
        bool bfs() {
            int qt = 0;
            Q[qt++] = S;
            lvl.assign(nodes, -1);
            lvl[S] = 0;
            for (int qh = 0; qh < qt; qh++) {
                int v = Q[qh];
                for (flowEdge &e : G[v]) {
                    int u = e.to;
                    if (e.cap <= e.f || lvl[u] != -1)
                        continue;
                    lvl[u] = lvl[v] + 1;
                    Q[qt++] = u;
                }
            }
            return lvl[T] != -1;
        }
        int dfs(int v, int f) {
            if (v == T || f == 0) return f;
            for (int &i = work[v]; i < G[v].size(); i++) {
                flowEdge &e = G[v][i];
                int u = e.to;
                if (e.cap <= e.f || lvl[u] != lvl[v] + 1)
                    continue;
                int df = dfs(u, min(f, e.cap - e.f));
                if (df) {
                    e.f += df;
                    G[u][e.rev].f -= df;
                    return df;
                }
            }
            return 0;
        }
        int maxFlow() {
            int flow = 0;
            while (bfs()) {
                work.assign(nodes, 0);
                while (true) {
                    int df = dfs(S, INF);
                    if (df == 0) break;
                    flow += df;
                }
            }
            return flow;
        }
};

void test_case() {
    ll n, m, s, t;
    cin >> n >> m >> s >> t;
    Dinitz flow;
    flow.init(n, s, t);
    for (int i = 0; i < m; i++) {
        ll a, b, c;
        cin >> a >> b >> c;
        flow.addEdge(a, b, c);
    }
    ll f = flow.maxFlow(); // max flow
    vector<tuple<ll, ll, ll>> edges; // edges used with flow
    for (int i = 0; i < n; i++) {
        for (auto edge : flow.G[i]) {
            if (edge.f > 0) {
                edges.pb({i, edge.to, edge.f});
            }
        }
    }
}

```

```

    }
    return lvl[T] != -1;
}

int dfs(int v, int f) {
    if (v == T || f == 0) return f;
    for (int &i = work[v]; i < G[v].size(); i++) {
        flowEdge &e = G[v][i];
        int u = e.to;
        if (e.cap <= e.f || lvl[u] != lvl[v] + 1)
            continue;
        int df = dfs(u, min(f, e.cap - e.f));
        if (df) {
            e.f += df;
            G[u][e.rev].f -= df;
            return df;
        }
    }
    return 0;
}

int maxFlow() {
    int flow = 0;
    while (bfs()) {
        work.assign(nodes, 0);
        while (true) {
            int df = dfs(S, INF);
            if (df == 0) break;
            flow += df;
        }
    }
    return flow;
}

};

void test_case() {
    ll n, m, s, t;
    cin >> n >> m >> s >> t;
    Dinitz flow;
    flow.init(n, s, t);
    for (int i = 0; i < m; i++) {
        ll a, b, c;
        cin >> a >> b >> c;
        flow.addEdge(a, b, c);
    }
    ll f = flow.maxFlow(); // max flow
    vector<tuple<ll, ll, ll>> edges; // edges used with flow
    for (int i = 0; i < n; i++) {
        for (auto edge : flow.G[i]) {
            if (edge.f > 0) {
                edges.pb({i, edge.to, edge.f});
            }
        }
    }
}

```

```

    }
}

```

8.3 blossom

Halla el máximo match en un grafo general $O(E * v^2)$

```

struct network {
    struct struct_edge {
        int v; struct_edge * n;
    };
    typedef struct_edge* edge;
    int n;
    struct_edge pool[MAXE]; // 2*n*n;
    edge top;
    vector<edge> adj;
    queue<int> q;
    vector<int> f, base, inq, inb, inp, match;
    vector<vector<int>> ed;
    network(int n) : n(n), match(n, -1), adj(n),
        top(pool), f(n), base(n),
        inq(n), inb(n), inp(n), ed(n, vector<int>(n)) {}

    void add_edge(int u, int v) {
        if (ed[u][v]) return;
        ed[u][v] = 1;
        top->v = v, top->n = adj[u], adj[u] = top++;
        top->v = u, top->n = adj[v], adj[v] = top++;
    }

    int get_lca(int root, int u, int v) {
        fill(inp.begin(), inp.end(), 0);
        while (1) {
            inp[u = base[u]] = 1;
            if (u == root) break;
            u = f[match[u]];
        }
        while (1) {
            if (inp[v = base[v]]) return v;
            else v = f[match[v]];
        }
    }

    void mark(int lca, int u) {
        while (base[u] != lca) {
            int v = match[u];
            inb[base[u]] = 1;
            inb[base[v]] = 1;
            u = f[v];
            if (base[u] != lca) f[u] = v;
        }
    }

    void blossom_contraction(int s, int u, int v) {

```

```

int lca = get_lca(s, u, v);
fill(inb.begin(), inb.end(), 0);
mark(lca, u); mark(lca, v);
if (base[u] != lca) f[u] = v;
if (base[v] != lca) f[v] = u;
for (int u = 0; u < n; u++) {
    if (inb[base[u]]) {
        base[u] = lca;
        if (!inq[u]) {
            inq[u] = 1;
            q.push(u);
        }
    }
}
}

int bfs(int s) {
    fill(inq.begin(), inq.end(), 0);
    fill(f.begin(), f.end(), -1);
    for (int i = 0; i < n; i++) base[i] = i;
    q = queue<int>();
    q.push(s);
    inq[s] = 1;
    while (q.size()) {
        int u = q.front(); q.pop();
        for (edge e = adj[u]; e; e = e->n) {
            int v = e->v;
            if (base[u] != base[v] && match[u] !=
                if ((v == s) || (match[v] != -1 &&
f[match[v]] != -1)) {
                    blossom_contraction(s, u, v);
                } else if (f[v] == -1) {
                    f[v] = u;
                    if (match[v] == -1) return v;
                } else if (!inq[match[v]]) {
                    inq[match[v]] = 1;
                    q.push(match[v]);
                }
            }
        }
    }
}

return -1;
}

int doit(int u) {
    if (u == -1) return 0;
    int v = f[u];
    doit(match[v]);
    match[v] = u; match[u] = v;
    return u != -1;
}
}

```

```

// (i < net.match[i]) => means match
int maximum_matching() {
    int ans = 0;
    for (int u = 0; u < n; u++)
        ans += (match[u] == -1) && doit(bfs(u));
    return ans;
}
};

```

8.4 min cut

```

/*
Minimum Cut, need revision for general cases!!!
Tested in https://cses.fi/problemset/task/1695/
with undirected graph with capacity 1
1. Run Max Flow Algorithm
2. Get reachable vertices from source in the residual
graph!
   using BFS or DFS, call this reachable vertices = S
3. Iterate S, iterate edges of S in normal graph that
not belongs to S,
   thats the mincut edges of the answer.
*/
void test_case() {
    ll n, m; cin >> n >> m;
    vvl g(n);
    Dinitz f(n, 0, n-1); // add Dinitz for maxFlow!!
    for (int i = 0; i < m; i++) {
        ll x, y; cin >> x >> y; x--; y--;
        g[x].pb(y); g[y].pb(x); //this example the
graph is bidirectional
        f.addEdge(x, y, 1); f.addEdge(y, x, 1);
    }
    f.maxFlow(); // step 1
    vvl residual(n); // Step 2
    for (int i = 0; i < n; i++) for (auto j: f.G[i])
        if ((j.f < 0 && j.cap == 0) || (j.f == 0 && j.cap >
0))
            residual[i].pb(j.to); // residual graph
    set<ll> vis;
    function<void(int)> dfs = [&](int x) {
        vis.insert(x); // dfs on residual from source
        for (auto y : residual[x]) if (!vis.count(y))
            dfs(y);
    };
    dfs(0);
    vector<pair<ll, ll>> ans; // step 3
    for (auto x : vis)
        for (auto y : g[x])
            if (!vis.count(y))
                ans.pb({x, y});
}

```

```

cout << ans.size() << "\n";
for (auto e : ans) {
    cout << e.F + 1 << " " << e.S + 1 << "\n";
}
}

```

8.5 min cost max flow

```

// 0(min(E^2*V^2, E*V*FLOW))
// Min Cost Max Flow Dinitz
struct CheapDinitz{
    const int INF = 1e9 + 7;
    CheapDinitz() {}
    CheapDinitz(int n, int s, int t) {init(n, s, t);}
    int nodes, S, T;
    vi dist;
    vi pot, curFlow, prevNode, prevEdge, Q, inQue;
    struct flowEdge{
        int to, rev, flow, cap, cost;
    };
    vector<vector<flowEdge>> G;
    void init(int n, int s, int t)
    {
        nodes = n, S = s, T = t;
        curFlow.assign(n, 0), prevNode.assign(n, 0),
prevEdge.assign(n, 0);
        Q.assign(n, 0), inQue.assign(n, 0);
        G.clear();
        G.resize(n);
    }
    void addEdge(int s, int t, int cap, int cost)
    {
        flowEdge a = {t, (int)G[t].size(), 0, cap,
cost};
        flowEdge b = {s, (int)G[s].size(), 0, 0, -
cost};
        G[s].pb(a);
        G[t].pb(b);
    }
    void bellmanFord()
    {
        pot.assign(nodes, INF);
        pot[S] = 0;
        int qt = 0;
        Q[qt++] = S;
        for (int qh = 0; (qh - qt) % nodes != 0; qh++)
        {
            int u = Q[qh % nodes];
            inQue[u] = 0;
            for (int i = 0; i < (int)G[u].size(); i++)
            {

```

```

        flowEdge &e = G[u][i];
        if (e.cap <= e.flow) continue;
        int v = e.to;
        int newDist = pot[u] + e.cost;
        if (pot[v] > newDist)
        {
            pot[v] = newDist;
            if (!inQue[v])
            {
                Q[qt++ % nodes] = v;
                inQue[v] = 1;
            }
        }
    }
}

ii MinCostFlow()
{
    bellmanFord();
    int flow = 0;
    int flowCost = 0;
    while (true) // always a good start for an
algorithm :v
    {
        set<ii> s;
        s.insert({0, S});
        dist.assign(nodes, INF);
        dist[S] = 0;
        curFlow[S] = INF;
        while (s.size() > 0)
        {
            int u = s.begin() -> s;
            int actDist = s.begin() -> f;
            s.erase(s.begin());
            if (actDist > dist[u]) continue;
            for (int i = 0; i < (int)G[u].size();
i++)
            {
                flowEdge &e = G[u][i];
                int v = e.to;
                if (e.cap <= e.flow) continue;
                int newDist = actDist + e.cost +
pot[u] - pot[v];

                if (newDist < dist[v])
                {
                    dist[v] = newDist;
                    s.insert({newDist, v});
                    prevNode[v] = u;
                    prevEdge[v] = i;
                    curFlow[v] = min(curFlow[u],
e.cap - e.flow);

```

```

                }
            }
        }
        if (dist[T] == INF)
            break;
        for (int i = 0; i < nodes; i++)
            pot[i] += dist[i];
        int df = curFlow[T];
        flow += df;
        for (int v = T; v != S; v = prevNode[v])
        {
            flowEdge &e = G[prevNode[v]]
[prevEdge[v]];

            e.flow += df;
            G[v][e.rev].flow -= df;
            flowCost += df * e.cost;
        }
    }
    return {flow, flowCost};
};

```

9 6. Tree

9.1 block tree

```

/*
SQRT on Trees.
For having queries and updates online to subtrees or
sub forests.
See: https://codeforces.com/blog/entry/46843
Solution to: https://codeforces.com/gym/100589/problem/A
Properties:
- Each node will have atmost SQRT children nodes in
Block Tree
- There will be atmost SQRT Blocks
- There will be atmost SQRT nodes belongs to a block
- Not completely sure, but for merging answers of
childs it should be fast
*/
struct Block { // Block storing info depending of
problem!!!
    // O(n) memory here is possible, but better O(sqrt
n) to BlockTree creation be O(n)
    vector<int> depthCnt;
    ll sum = 0;
    void update(int lvl, ll v) { // !!! depends of
problem
        assert(lvl < depthCnt.size());

```

```

        if (lvl >= depthCnt.size()) return;
        sum += v * depthCnt[lvl];
    }
    ll query() { return sum; }
};

struct BlockTree {
    const int SQRT = 320; // sqrt of max N
    ll n;
    vector<Block> blocks;
    vector<vector<int>>> child; // if node < n, then
normal node, otherwise block node
    vector<int> depth;
    vector<int> leader; // for the sqrt group of nodes
the first ancestor that is not in the group
    vector<int> blockId;
    // ===== depends of the problem!!!
    vector<ll> sum;
    // =====
    BlockTree(ll n, vector<vector<ll>>> &adj) : n(n),
child(2*n+5), depth(2*n+5),

leader(2*n+5), blockId(2*n+5) {
        sum = vector<ll>(n);
        build(adj); // adjacency should be x -> y, and
y -> x
    }

    bool is_block(ll x) { return x >= n; }
    void build(vector<vector<ll>>> &adj, ll root = 0) {
        auto dfs = [&](ll x, ll p, auto &&dfs) -> void
{
            for (auto y : adj[x]) if (y != p) {
                depth[y] = depth[x]+1;
                dfs(y,x,dfs);
            }
        };
        dfs(root, -1, dfs); // !!! Don't forget
        ll idNewBlock = n;
        auto createBlock = [&](int parent, const
vector<ll> &nodes) {
            ll id = idNewBlock++;
            if (parent != -1) {
                child[parent].push_back(id);
                depth[id] = depth[parent]+1;
            }
            Block block; // Modify the creation of your
block here!!!
            leader[id] = parent;
            blockId[id] = id;
            block.depthCnt = vector<int>(n);
            auto dfsOverBlock = [&](ll x, auto
&&dfsOverBlock)->void {

```

```

        leader[x] = parent;
        blockId[x] = id;
        block.depthCnt[depth[x]]++;
        for (auto y : child[x]) {
            if (!is_block(y)) dfsOverBlock(y,
dfsOverBlock);
            else child[id].push_back(y); //
depending of the problem, you can add
// relationship between block node
-> node or block node -> block node, like this
        }
    };
    for (auto & x : nodes) dfsOverBlock(x,
dfsOverBlock);
    blocks.push_back(block);
};
vector<vector<ll>> byDepth(n); // counting sort
for (int i = 0; i < n; i++) byDepth[n-1-
depth[i]].pb(i);
vector<ll> sz(n);
for (auto & nodes : byDepth) {
    for (int x : nodes) {
        ll blockSz = 0;
        vector<ll> curBlock;
        sz[x] = 1;
        for (int y : adj[x]) if (depth[x] <
depth[y]) {
            sz[x] += sz[y];
            blockSz += sz[y];
            curBlock.pb(y);
            if (blockSz > Sqrt) {
                createBlock(x, curBlock);
                sz[x] -= blockSz;
                blockSz = 0;
                curBlock.clear();
            }
        }
        child[x].insert(child[x].end(),
curBlock.begin(), curBlock.end());
    }
    createBlock(-1, { root });
}
void update(int lvl, ll v) {
    sum[lvl] += v;
    for (auto & block : blocks) {
        block.update(lvl, v);
    }
}
ll query(ll x) { // dfs over node blocks and non
node blocks

```

```

        ll ans = is_block(x) ? blocks[x-n].query() :
sum[depth[x]];
        for (auto & y : child[x])
            ans += query(y);
        return ans;
    }
};

```

9.2 isomorfismo

Permite hashear árboles para comparar su estructura rápidamente.

Agregar Random Integer para ll

```

map<ll, ll> table;
ll get(ll x) {
    if (table.count(x)) return table[x];
    return table[x] = rand(0, 1e18);
}
ll hashes[N], sum[N];
void dfs(int u, int p) {
    sum[u] = 0;
    for (auto &v : g[u]) {
        if (v == p) continue;
        dfs(v, u);
        sum[u] += hashes[v];
    }
    hashes[u] = get(sum[u]);
}

```

9.3 heavy light

```

vector<vector<int>> adj; // INIT this, use init()!!!
vector<int> parent, depth, heavy, head, pos;
int cur_pos;
int dfs(int v) {
    int size = 1, max_size = 0;
    for (int c : adj[v]) if (c != parent[v]) {
        parent[c] = v, depth[c] = depth[v] + 1;
        int c_size = dfs(c);
        size += c_size;
        if (c_size > max_size)
            max_size = c_size, heavy[v] = c;
    }
    return size;
}
void decompose(int v, int h) {
    head[v] = h, pos[v] = cur_pos++;
    if (heavy[v] != -1) // check when copy head and
heavy
        decompose(heavy[v], h);
    for (int c : adj[v]) {
        if (c != parent[v] && c != heavy[v])

```

```

        decompose(c, c);
    }
}
segtree tree; // !!ADD SegTree
vector<ll> values;
void init() {
    int n = adj.size();
    parent = depth = head = pos = vector<int>(n);
    heavy = vector<int>(n, -1);
    cur_pos = 0;
    dfs(0);
    decompose(0, 0);
    tree.init(n);
    for (int i = 0; i < n; i++) tree.update(pos[i],
{ values[i] });
}
int seg_query(int a, int b) {
    return tree.query(a, b).x; // !! depends of segtree
}
void update_query(int node, int val) {
    tree.update(pos[node], { val }); // depends of
segtree
}
int query(int a, int b) {
    int res = 0;
    for (; head[a] != head[b]; b = parent[head[b]]) {
        if (depth[head[a]] > depth[head[b]])
            swap(a, b);
        int cur_heavy_path_max =
seg_query(pos[head[b]], pos[b]);
        res = max(res, cur_heavy_path_max);
    }
    if (depth[a] > depth[b])
        swap(a, b);
    int last_heavy_path_max = seg_query(pos[a],
pos[b]); // consider pos[a]+1 when query edges
    res = max(res, last_heavy_path_max); // Change to
Segment Tree Operation
    return res;
}

```

9.4 online centroid

```

// !!! Add centroid Descomposition
// When you can get Answers for fixed root
// When you can get answer for all paths for fixed root
struct centroid_data {
    ll idx = 0, best_red = -1;
    void mark_red(int x, ll d) {
        if (best_red == -1) best_red = d;
        best_red = min(best_red, d);
    }
}

```



```

    }
    int query(int x, ll d) {
        if (best_red == -1) return inf;
        return best_red + d;
    }
};
vector<vector<pair<ll,ll>>> belongs; // idx centroid,
extra data, init this!!
vector<centroid_data> centroids;
int id_centroid = 0;
void process_centroid(int root, int sz) { // creates
centroids
    centroids.push_back({id_centroid++, -1});
    auto & c = centroids.back();
    auto dfs = [&](int x, int p, ll dist, auto &&dfs) -
> void {
        belongs[x].pb({c.idx, dist});
        for (auto & y : adj[x]) if (y != p && alive[y])
            dfs(y, x, dist+1, dfs);
    };
    dfs(root, -1, 0, dfs);
}
void mark_red(int x) { // UPDATE O(log n) centroids
belongs to node
    for (auto [idx, dist] : belongs[x])
        centroids[idx].mark_red(x, dist);
}
int query(int x) { // iterates over each centroid
belongs to node O(logn)
    int best = 1e9;
    for (auto [idx, dist] : belongs[x])
        best = min(best, centroids[idx].query(x,
dist));
    return best;
}

```

9.5 centroid descomposition

```

vector<vector<ll>> adj;
vector<bool> alive;
vector<int> sz;
void init(int n) {
    alive = vector<bool>(n+1, true);
    sz = vector<int>(n+1);
    adj = vector<vector<ll>>(n+1);
    // belongs =
vector<vector<pair<ll,ll>>>(n+1); // !! for online
}
int get_sz(int x, int p) {
    sz[x] = 1;
    for (auto y : adj[x]) if (y != p && alive[y])

```

```

        sz[x] += get_sz(y, x);
    return sz[x];
}
int find_centroid(int x, int p, int tree_sz) {
    for (auto y : adj[x]) if (y != p && alive[y]) {
        if (sz[y] * 2 > tree_sz) {
            return find_centroid(y, x, tree_sz);
        }
    }
    return x;
}
//!!! Implement O(sz) solution, use adj, only use alive
nodes check with alive[x]
// dont sz[x] because it is not rerooted to centroid
void process_centroid(int root, int sz);
void centroid_decomp(ll x) {
    int sz = get_sz(x, -1);
    int centroid = find_centroid(x, -1, sz);
    process_centroid(centroid, sz); // implement!!!
    alive[centroid] = false;
    for (auto y : adj[centroid]) if (alive[y]) {
        centroid_decomp(y);
    }
}

```

10 7. Strings

10.1 kmp

```

// Given string s, and patter p, count and find
// occurrences of p in s. O(n)
struct KMP {
    int kmp(vector<ll> &s, vector<ll> &p) {
        int n = s.size(), m = p.size(), cnt = 0;
        vector<int> pf = prefix_function(p);
        for(int i = 0, j = 0; i < n; i++) {
            while(j && s[i] != p[j]) j = pf[j-1];
            if(s[i] == p[j]) j++;
            if(j == m) {
                cnt++;
                j = pf[j-1];
            }
        }
        return cnt;
    }
}
vector<int> prefix_function(vector<ll> &s) {
    int n = s.size();
    vector<int> pf(n);
    pf[0] = 0;
    for (int i = 1, j = 0; i < n; i++) {

```

```

        while (j && s[i] != s[j]) j = pf[j-1];
        if (s[i] == s[j]) j++;
        pf[i] = j;
    }
    return pf;
}
};

```

10.2 micky hashing

```

ll pot(ll x, ll y, ll m) {
    if (y==0) return 1;
    ll ans = pot(x,y/2,m);
    ans = (ans*ans)%m;
    if (y&1) ans = (ans*x)%m;
    return ans;
}
struct Hash {
    int p = 997, m[2], in[2];
    vl h[2], inv[2];
    Hash(string s) {
        m[0] = 998244353, m[1]=1e9+9;
        for (int i = 0; i<2; i++) {
            in[i] = pot(p,m[i]-2,m[i]);
            h[i].resize(s.size()+1);
            inv[i].resize(s.size()+1);
            ll acu = 1;
            h[i][0]=0, inv[i][0]=1;
            for (int j = 0; j<s.size(); j++) {
                h[i][j+1]=(h[i][j]+acu*s[j])%m[i];
                inv[i][j+1]=(1ll*inv[i][j]*in[i])%m[i];
                acu = (acu * p) % m[i];
            }
        }
    }
    ll get(int b, int e) {
        e++;
        ll ha[2];
        for (int i =0; i<2; i++) {
            ha[i] = (((h[i][e] - h[i][b]) * (ll)inv[i][b]) %
m[i]) + m[i]) % m[i];
        }
        return ((ha[0]<<32)|ha[1]);
    }
};

```

10.3 manacher

Devuelve un vector p donde, para cada i, p[i] es igual al largo del palindromo mas largo con centro en i.

```

string parse(string &s) {
    string t = "%";

```

```

    for (auto &c : s) t.pb('#'), t.pb(c);
    t += "$";
    return t;
}

vector<int> manacher(string &s) {
    string t = parse(s);
    int n = t.size(), c = 0, r = 0;
    vector<int> p(n, 0);
    for (int i = 1; i < n-1; i++) {
        int j = c - (i-c);
        if (r > i) p[i] = min(r-i, p[j]);
        while (t[i+1+p[i]] == t[i-1-p[i]])
            p[i]++;
        if (i+p[i] > r) {
            c = i;
            r = i+p[i];
        }
    }
    return p;
    // si p[i] > 0 entonces, s[l, r) es palíndromo
    // donde l = (i-1-p[i])/2 y r = l+p[i];
}

```

10.4 suffix array

```

#define fore(i,a,b) for(int i=a,ThxDem=b;i<ThxDem;++i)
#define SZ(s) int(s.size())
#define RB(x) (x<n?r[x]:0)
void csort(vector<int> &sa, vector<int> &r, int k){
    int n=SZ(sa);
    vector<int> f(max(255,n+1)),t(n);
    fore(i,0,n) f[RB(i+k)]++;
    int sum=0;
    fore(i,0,max(255,n+1))f[i]=(sum+=f[i])-f[i];
    fore(i,0,n)t[f[RB(sa[i]+k)]++] = sa[i];
    sa=t;
}

vector<int> constructSA(vector<int> &s){
    int n=SZ(s),rank;
    vector<int> sa(n),r(n),t(n);
    fore(i,0,n)sa[i]=i,r[i]=s[i];
    for(int k=1;k<n;k*=2){
        csort(sa,r,k);csort(sa,r,0);
        t[sa[0]]=rank=0;
        fore(i,1,n){
            if(r[sa[i]]!=r[sa[i-1]]||RB(sa[i]+k)!
            =RB(sa[i-1]+k))rank++;
            t[sa[i]]=rank;
        }
        r=t;
        if(r[sa[n-1]]==n-1)break;
    }
}

```

```

}
return sa;
}

vector<int> computeLCP(vector<int> &s, vector<int> &sa)
{
    int n=SZ(s),L=0;
    vector<int> lcp(n),plcp(n),phi(n);
    phi[sa[0]]=-1;
    fore(i,1,n)phi[sa[i]]=sa[i-1];
    fore(i,0,n){
        if(phi[i]<0){plcp[i]=0;continue;}
        while(s[i+L]==s[phi[i]+L])L++;
        plcp[i]=L;
        L=max(L-1,0);
    }
    fore(i,0,n)lcp[i]=plcp[sa[i]];
    return lcp;
}

void test_case() { // max element <= n
    ll n; cin >> n; vector<int> nums(n);
    for (int i = 0; i < n; i++) cin >> nums[i];
    nums.pb(0); // min element
    auto sa = constructSA(nums);
    auto lcp = computeLCP(nums, sa); // lcp[i] =
    lcp[sa[i-1],sa[i]]
    sa.erase(sa.begin());
    lcp.erase(lcp.begin());
    nums.pop_back();
}

```

10.5 fast hashing

```

const int N = 1e6 + 9; // Max size
int power(long long n, long long k, const int mod) {
    int ans = 1 % mod;
    n %= mod;
    if (n < 0) n += mod;
    while (k) {
        if (k & 1) ans = (long long) ans * n % mod;
        n = (long long) n * n % mod;
        k >>= 1;
    }
    return ans;
}

const int MOD1 = 127657753, MOD2 = 987654319;
const int p1 = 137, p2 = 277;
int ip1, ip2;
pair<int, int> pw[N], ipw[N];
void init() { // Call init() first!!!
    pw[0] = {1, 1};
    for (int i = 1; i < N; i++) {

```

```

        pw[i].first = 1LL * pw[i - 1].first * p1 % MOD1;
        pw[i].second = 1LL * pw[i - 1].second * p2 % MOD2;
    }
    ip1 = power(p1, MOD1 - 2, MOD1);
    ip2 = power(p2, MOD2 - 2, MOD2);
    ipw[0] = {1, 1};
    for (int i = 1; i < N; i++) {
        ipw[i].first = 1LL * ipw[i - 1].first * ip1 % MOD1;
        ipw[i].second = 1LL * ipw[i - 1].second * ip2 %
        MOD2;
    }
}

struct Hashing {
    int n;
    string s; // 0 - indexed
    vector<pair<int, int>> hs; // 1 - indexed
    Hashing() {}
    Hashing(string _s) {
        n = _s.size();
        s = _s;
        hs.emplace_back(0, 0);
        for (int i = 0; i < n; i++) {
            pair<int, int> p;
            p.first = (hs[i].first + 1LL * pw[i].first * s[i]
            % MOD1) % MOD1;
            p.second = (hs[i].second + 1LL * pw[i].second *
            s[i] % MOD2) % MOD2;
            hs.push_back(p);
        }
        pair<int, int> get_hash(int l, int r) { // 1-indexed
            assert(1 <= l && l <= r && r <= n);
            pair<int, int> ans;
            ans.first = (hs[r].first - hs[l - 1].first + MOD1)
            * 1LL * ipw[l - 1].first % MOD1;
            ans.second = (hs[r].second - hs[l - 1].second +
            MOD2) * 1LL * ipw[l - 1].second % MOD2;
            return ans;
        }
        pair<int, int> get(int l, int r) { // 0-indexed
            return get_hash(l+1,r+1);
        }
        pair<int, int> get_hash() {
            return get_hash(1, n);
        }
    };
};

```

10.6 kmp automaton

```

// Very useful for some DP's with strings
// aut[i][j], you are in 'i' position, and choose

```

```

character 'j', the next position.
const int MAXN = 1e5 + 5, alpha = 26;
const char L = 'A';
int aut[MAXN][alpha]; // aut[i][j] = a donde vuelvo si
estoy en i y pongo una j
void build(string &s) {
    int lps = 0;
    aut[0][s[0]-L] = 1;
    int n = s.size();
    for (int i = 1; i < n+1; i++) {
        for (int j = 0; j < alpha; j++) aut[i][j] =
aut[lps][j];
        if (i < n) {
            aut[i][s[i]-L] = i + 1;
            lps = aut[lps][s[i]-L];
        }
    }
}

```

11 8. Geometry

11.1 ufps line

```

struct line {
    pt v; T c; // v:direction c: pos in y axis
    line(pt v, T c) : v(v), c(c) {}
    line(T a, T b, T c) : v({b, -a}), c(c) {} // ax +
by = c
    line(pt p, pt q) : v(q-p), c(cross(v, p)) {}
    T side(pt p) { return cross(v, p)-c; }
    lf dist(pt p) { return abs(side(p)) / abs(v); }
    lf sq_dist(pt p) { return side(p)*side(p) /
(lf)norm(v); }
    line perp_through(pt p) { return {p, p +
rot90ccw(v)}; } // line perp to v passing through p
    bool cmp_proj(pt p, pt q) { return dot(v, p) <
dot(v, q); } // order for points over the line
    line translate(pt t) { return {v, c + cross(v,
t)}; }
    line shift_left(double d) { return {v, c +
d*abs(v)}; }
    pt proj(pt p) { return p - rot90ccw(v)*side(p)/
norm(v); } // pt projected on the line
    pt refl(pt p) { return p - rot90ccw(v)*2*side(p)/
norm(v); } // pt reflected on the other side of the
line
};
bool inter_ll(line l1, line l2, pt &out) {
    T d = cross(l1.v, l2.v);
    if (d == 0) return false;

```

```

    out = (l2.v*l1.c - l1.v*l2.c) / d; // floating
points
    return true;
}
// bisector divides the angle in 2 equal angles
// interior line goes on the same direction as l1 and
l2
line bisector(line l1, line l2, bool interior) {
    assert(cross(l1.v, l2.v) != 0); // l1 and l2 cannot
be parallel!
    lf sign = interior ? 1 : -1;
    return {l2.v/abs(l2.v) + l1.v/abs(l1.v) * sign,
l2.c/abs(l2.v) + l1.c/abs(l1.v) * sign};
}

```

11.2 closest pair of points sweep line

```

#define x first
#define y second
ll dist2(pair<int,int> a, pair<int,int> b) {
    return 1LL * (a.x-b.x)*(a.x-b.x) + 1LL * (a.y-
b.y)*(a.y-b.y);
}
pair<pair<ll,ll>,pair<ll,ll>>
ClosestPair(vector<pair<int, int>> pts) {
    int n = pts.size();
    sort(pts.begin(), pts.end());
    set<pair<ll, ll>> s;
    long long best_dist = 8e18;
    int last_best = 0; // if you need the points
    int j = 0;
    for (int i = 0; i < n; ++i) {
        ll d = ceil(sqrtll(best_dist));
        while (pts[i].first - pts[j].first >= d) {
            s.erase({pts[j].second, pts[j].first});
            j += 1;
        }
        auto it1 = s.lower_bound({pts[i].second - d,
pts[i].first});
        auto it2 = s.upper_bound({pts[i].second + d,
pts[i].first});
        for (auto it = it1; it != it2; ++it) {
            ll dx = pts[i].first - it->second;
            ll dy = pts[i].second - it->first;
            ll distance = 1LL * dx * dx + 1LL * dy *
dy;
            if (distance <= best_dist) { // must be <=
otherwise got WA
                best_dist = distance;
                last_best = i; // if you need the
points

```

```

            }
        }
        s.insert({pts[i].second, pts[i].first});
    }
    // If you need the points otherwise return
best_dist;
    for (int i = 0; i < last_best; i++) {
        if (dist2(pts[i],pts[last_best])==best_dist) {
            return {pts[i],pts[last_best]};
        }
    }
    assert(false);
    return {{0,0},{0,0}};
}
void test_case() {
    ll n;
    cin >> n;
    vector<pair<int,int>> points(n);
    for (int i =0;i<n;i++) {
        ll x, y;
        cin >> x >> y;
        points[i] = {x,y};
    }
    auto ans = ClosestPair(points);
    cout << dist2(ans.F, ans.S) << "\n";
}
// AC https://cses.fi/problemset/task/2194/

```

11.3 heron formula

```

ld triangle_area(ld a, ld b, ld c) {
    ld s = (a + b + c) / 2;
    return sqrtl(s * (s - a) * (s - b) * (s - c));
}

```

11.4 point in convex polygon

```

// Check if a point is in, on, or out a convex Polygon
// in O(log n)
ll IN = 0;
ll ON = 1;
ll OUT = 2;
vector<string> ANS = {"IN", "ON", "OUT"};
#define pt pair<ll,ll>
#define x first
#define y second
pt sub(pt a, pt b) { return {a.x - b.x, a.y - b.y}; }
ll cross(pt a, pt b) { return a.x*b.y - a.y*b.x; } // x
= 180 -> sin = 0
ll orient(pt a, pt b, pt c) { return
cross(sub(b,a),sub(c,a)); } // clockwise = -
// poly is in clock wise order

```

```

ll insidePoly(vector<pt> &poly, pt query) {
    ll n = poly.size();
    ll left = 1;
    ll right = n - 2;
    ll ans = -1;
    if (!(orient(poly[0], poly[1], query) <= 0
        && orient(poly[0], poly[n-1], query) >= 0)) {
        return OUT;
    }
    while (left <= right) {
        ll mid = (left + right) / 2;
        if (orient(poly[0], poly[mid], query) <= 0) {
            left = mid + 1;
            ans = mid;
        } else {
            right = mid - 1;
        }
    }
    left = ans;
    right = ans + 1;
    if (orient(poly[left], query, poly[right]) < 0) {
        return OUT;
    }
    if (orient(poly[left], poly[right], query) == 0
        || (left == 1 && orient(poly[0], poly[left],
            query) == 0)
        || (right == n-1 && orient(poly[0], poly[right],
            query) == 0)) {
        return ON;
    }
    return IN;
}
    
```

11.5 ufps circle

```

struct circle {
    pt c; T r;
};
// (x-xo)^2 + (y-yo)^2 = r^2
// circle that passes through abc
circle center(pt a, pt b, pt c) {
    b = b-a, c = c-a;
    assert(cross(b, c) != 0); // no circumcircle if A,
    B, C aligned
    pt cen = a + rot90ccw(b*norm(c) - c*norm(b))/
    cross(b, c)/2;
    return {cen, abs(a-cen)};
}
// centers of the circles that pass through ab and have
radius r
vector<pt> centers(pt a, pt b, T r) {
    
```

```

    if (abs(a-b) > 2*r + eps) return {};
    pt m = (a+b)/2;
    double f = sqrt(r*r/norm(a-m) - 1);
    pt c = rot90ccw(a-m)*f;
    return {m-c, m+c};
}
int inter_cl(circle c, line l, pair<pt, pt> &out) {
    lf h2 = c.r*c.r - l.sq_dist(c.c);
    if (h2 >= 0) { // line touches circle
        pt p = l.proj(c.c);
        pt h = l.v*sqrt(h2)/abs(l.v); // vector of len
        h parallel to line
        out = {p-h, p+h};
    }
    return 1 + sign(h2); // if 1 -> out.F == out.S
}
int inter_cc(circle c1, circle c2, pair<pt, pt> &out) {
    pt d = c2.c-c1.c;
    double d2 = norm(d);
    if (d2 == 0) { assert(c1.r != c2.r); return 0; } //
    concentric circles (identical)
    double pd = (d2 + c1.r*c1.r - c2.r*c2.r)/2; // = |
    0_1p| * d
    double h2 = c1.r*c1.r - pd*pd/d2; // = h^2
    if (h2 >= 0) {
        pt p = c1.c + d*pd/d2, h = rot90ccw(d)*sqrt(h2/
        d2);
        out = {p-h, p+h};
    }
    return 1 + sign(h2);
}
// circle-line inter = 1
int tangents(circle c1, circle c2, bool inner,
    vector<pair<pt, pt>> &out) {
    if (inner) c2.r = -c2.r; // inner tangent
    pt d = c2.c-c1.c;
    double dr = c1.r-c2.r, d2 = norm(d), h2 = d2-dr*dr;
    if (d2 == 0 || h2 < 0) { assert(h2 != 0); return
    0; } // (identical)
    for (double s : {-1, 1}) {
        pt v = (d*dr + rot90ccw(d)*sqrt(h2)*s)/d2;
        out.pb({c1.c + v*c1.r, c2.c + v*c2.r});
    }
    return 1 + (h2 > 0); // if 1: circle are tangent
}
// circle tangent passing through pt p
int tangent_through_pt(pt p, circle c, pair<pt, pt>
    &out) {
    double d = abs(p - c.c);
    if (d < c.r) return 0;
    pt base = c.c-p;
    
```

```

    double w = sqrt(norm(base) - c.r*c.r);
    pt a = {w, c.r}, b = {w, -c.r};
    pt s = p + base*a/norm(base)*w;
    pt t = p + base*b/norm(base)*w;
    out = {s, t};
    return 1 + (abs(c.c-p) == c.r);
}
    
```

11.6 ufps polygon

```

enum {IN, OUT, ON};
struct polygon {
    vector<pt> p;
    polygon(int n) : p(n) {}
    int top = -1, bottom = -1;
    void delete_repeated() {
        vector<pt> aux;
        sort(p.begin(), p.end());
        for (pt &i : p)
            if (aux.empty() || aux.back() != i)
                aux.pb(i);
        p.swap(aux);
    }
    bool is_convex() {
        bool pos = 0, neg = 0;
        for (int i = 0, n = p.size(); i < n; i++) {
            int o = orient(p[i], p[(i+1)%n],
                p[(i+2)%n]);
            if (o > 0) pos = 1;
            if (o < 0) neg = 1;
        }
        return !(pos && neg);
    }
    lf area(bool s = false) { // better on clockwise
    order
        lf ans = 0;
        for (int i = 0, n = p.size(); i < n; i++)
            ans += cross(p[i], p[(i+1)%n]);
        ans /= 2;
        return s ? ans : abs(ans);
    }
    lf perimeter() {
        lf per = 0;
        for (int i = 0, n = p.size(); i < n; i++)
            per += abs(p[i] - p[(i+1)%n]);
        return per;
    }
    bool above(pt a, pt p) { return p.y >= a.y; }
    bool crosses_ray(pt a, pt p, pt q) { // pq crosses
    ray from a
        return (above(a, q)-above(a, p))*orient(a, p,
    
```

```

q) > 0;
}
int in_polygon(pt a) {
    int crosses = 0;
    for (int i = 0, n = p.size(); i < n; i++) {
        if (on_segment(p[i], p[(i+1)%n], a)) return
ON;
        crosses += crosses_ray(a, p[i],
p[(i+1)%n]);
    }
    return (crosses & 1 ? IN : OUT);
}
void normalize() { // polygon is CCW
    bottom = min_element(p.begin(), p.end()) -
p.begin();
    vector<pt> tmp(p.begin()+bottom, p.end());
    tmp.insert(tmp.end(), p.begin(),
p.begin()+bottom);
    p.swap(tmp);
    bottom = 0;
    top = max_element(p.begin(), p.end()) -
p.begin();
}
int in_convex(pt a) {
    assert(bottom == 0 && top != -1);
    if (a < p[0] || a > p[top]) return OUT;
    T orientation = orient(p[0], p[top], a);
    if (orientation == 0) {
        if (a == p[0] || a == p[top]) return ON;
        return top == 1 || top + 1 == p.size() ?
ON : IN;
    } else if (orientation < 0) {
        auto it = lower_bound(p.begin()+1,
p.begin()+top, a);
        T d = orient(*prev(it), a, *it);
        return d < 0 ? IN : (d > 0 ? OUT : ON);
    } else {
        auto it = upper_bound(p.rbegin(), p.rend()-
top-1, a);
        T d = orient(*it, a, it == p.rbegin() ?
p[0] : *prev(it));
        return d < 0 ? IN : (d > 0 ? OUT : ON);
    }
}
polygon cut(pt a, pt b) { // cuts polygon on line
ab
    line l(a, b);
    polygon new_polygon(0);
    for (int i = 0, n = p.size(); i < n; ++i) {
        pt c = p[i], d = p[(i+1)%n];
        lf abc = cross(b-a, c-a), abd = cross(b-a,

```

```

d-a);
        if (abc >= 0) new_polygon.p.pb(c);
        if (abc*abd < 0) {
            pt out; inter_ll(l, line(c, d), out);
            new_polygon.p.pb(out);
        }
    }
    return new_polygon;
}
void convex_hull() {
    sort(p.begin(), p.end());
    vector<pt> ch;
    ch.reserve(p.size()+1);
    for (int it = 0; it < 2; it++) {
        int start = ch.size();
        for (auto &a : p) {
            // if colinear are needed, use < and
remove repeated points
            while (ch.size() >= start+2 &&
orient(ch[ch.size()-2], ch.back(), a) <= 0)
                ch.pop_back();
            ch.pb(a);
        }
        ch.pop_back();
        reverse(p.begin(), p.end());
        if (ch.size() == 2 && ch[0] == ch[1])
            ch.pop_back();
        // be careful with CH of size < 3
        p.swap(ch);
    }
    vector<pii> antipodal() {
        vector<pii> ans;
        int n = p.size();
        if (n == 2) ans.pb({0, 1});
        if (n < 3) return ans;
        auto nxt = [&](int x) { return (x+1 == n ? 0 :
x+1); };
        auto area2 = [&](pt a, pt b, pt c) { return
cross(b-a, c-a); };
        int b0 = 0;
        while (abs(area2(p[n-1], p[0], p[nxt(b0)])) >
abs(area2(p[n-1], p[0], p[b0]))) ++b0;
        for (int b = b0, a = 0; b != 0 && a <= b0; ++a)
        {
            ans.pb({a, b});
            while (abs(area2(p[a], p[nxt(a)],
p[nxt(b)])) > abs(area2(p[a], p[nxt(a)], p[b]))) {
                b = nxt(b);
                if (a != b0 || b != 0) ans.pb({ a,
b });
            }
        }
    }
}

```

```

        else return ans;
    }
    if (abs(area2(p[a], p[nxt(a)], p[nxt(b)]))
== abs(area2(p[a], p[nxt(a)], p[b]))) {
        if (a != b0 || b != n-1) ans.pb({ a,
nxt(b) });
        else ans.pb({ nxt(a), b });
    }
}
return ans;
}
pt centroid() {
    pt c{0, 0};
    lf scale = 6. * area(true);
    for (int i = 0, n = p.size(); i < n; ++i) {
        int j = (i+1 == n ? 0 : i+1);
        c = c + (p[i] + p[j]) * cross(p[i], p[j]);
    }
    return c / scale;
}
ll pick() {
    ll boundary = 0;
    for (int i = 0, n = p.size(); i < n; i++) {
        int j = (i+1 == n ? 0 : i+1);
        boundary += __gcd((ll)abs(p[i].x - p[j].x),
(ll)abs(p[i].y - p[j].y));
    }
    return area() + 1 - boundary/2;
}
pt& operator [] (int i) { return p[i]; }
};

```

11.7 ufps segment

```

bool in_disk(pt a, pt b, pt p) { // pt p inside ab disk
    return dot(a-p, b-p) <= 0;
}
bool on_segment(pt a, pt b, pt p) { // p on ab
    return orient(a, b, p) == 0 && in_disk(a, b, p);
}
// ab crossing cd
bool proper_inter(pt a, pt b, pt c, pt d, pt &out) {
    T oa = orient(c, d, a),
    ob = orient(c, d, b),
    oc = orient(a, b, c),
    od = orient(a, b, d);
    // Proper intersection exists iff opposite signs
    if (oa*ob < 0 && oc*od < 0) {
        out = (a*ob - b*oa) / (ob-oa);
        return true;
    }
}

```

```

    return false;
}
// intersection bwn segments
set<pt> inter_ss(pt a, pt b, pt c, pt d) {
    pt out;
    if (proper_inter(a, b, c, d, out)) return {out}; //
    if cross -> 1
    set<pt> s;
    if (on_segment(c, d, a)) s.insert(a); // a in cd
    if (on_segment(c, d, b)) s.insert(b); // b in cd
    if (on_segment(a, b, c)) s.insert(c); // c in ab
    if (on_segment(a, b, d)) s.insert(d); // d in ab
    return s; // 0, 2
}
lf pt_to_seg(pt a, pt b, pt p) { // p to ab
    if (a != b) {
        line l(a, b);
        if (l.cmp_proj(a, p) && l.cmp_proj(p, b)) // if
        closest to projection = (a, p, b)
            return l.dist(p); // output distance to
        line
    }
    return min(abs(p-a), abs(p-b)); // otherwise
    distance to A or B
}
lf seg_to_seg(pt a, pt b, pt c, pt d) {
    pt dummy;
    if (proper_inter(a, b, c, d, dummy)) return 0; //
    ab intersects cd
    return min({pt_to_seg(a, b, c), pt_to_seg(a, b, d),
    pt_to_seg(c, d, a), pt_to_seg(c, d, b)}); // try the 4
    pts
}

```

11.8 segment intersection

```

// No the best algorithm, find a better one!!
// Given two segment, finds the intersection point.
// LINE if they are parallel and mulitple
// intersection??
// POINT with the intersection point
// NONE if not intersection
struct line {
    ld a, b; // first point
    ld x, y; // second point
    ld m() { return (a - x)/(b - y); }
    bool horizontal() { return b == y; }
    bool vertical() { return a == x; }
    void intersects(line &o) {
        if (horizontal() && o.horizontal()) {
            if (y == o.y) cout << "LINE\n";

```

```

        else cout << "NONE\n";
        return;
    }
    if (vertical() && o.vertical()) {
        if (x == o.x) cout << "LINE\n";
        else cout << "NONE\n";
        return;
    }
    if (!horizontal() && !o.horizontal()) {
        ld ma = m();
        ld mb = o.m();
        if (ma == mb) {
            ld someY = (o.x - x)/ma + y;
            if (abs(someY - o.y) <= 0.000001) {
                cout << "LINE\n";
            } else {
                cout << "NONE\n";
            }
        } else {
            ld xx = (x*mb - o.x*ma + ma*mb*(o.y -
            y))/(mb - ma);
            ld yy = (xx - x)/ma + y;
            cout << "POINT " << fixed <<
            setprecision(2) << xx << " " << yy << "\n";
        }
    } else {
        if (!horizontal()) {
            ld xx;
            if (x == a) {
                xx = x;
            } else {
                xx = (o.y - y)/m() + x;
            }
            ld yy = o.y;
            cout << "POINT " << fixed <<
            setprecision(2) << xx << " " << yy << "\n";
        } else {
            ld xx;
            if (x == a) {
                xx = x;
            } else {
                xx = (y - o.y)/o.m() + o.x;
            }
            ld yy = y;
            cout << "POINT " << fixed <<
            setprecision(2) << xx << " " << yy << "\n";
        }
    }
}
};
void test_case() {

```

```

    line l[2];
    for (int i = 0; i < 2; i++) {
        ld x, y, a, b;
        cin >> x >> y >> a >> b;
        l[i].a = x;
        l[i].b = y;
        l[i].x = a;
        l[i].y = b;
    }
    l[0].intersects(l[1]);
}

```

11.9 point in general polygon

```

// Use insidepoly(poly, point)
// Returns if a point is inside=0, outside=1, onedge=2
// tested https://vjudge.net/solution/45869791/
BIPDAUMWyupUW18AlWgd
// Seems to be O(n)??
int inf = 1 << 30;
int INSIDE = 0;
int OUTSIDE = 1;
int ONEDGE = 2;
int COLINEAR = 0;
int CW = 1;
int CCW = 2;
typedef long double ld;
struct point {
    ld x, y;
    point(ld xloc, ld yloc) : x(xloc), y(yloc) {}
    point() {}
    point& operator= (const point& other) {
        x = other.x, y = other.y;
        return *this;
    }
    int operator == (const point& other) const {
        return (abs(other.x - x) < .00001 &&
        abs(other.y - y) < .00001);
    }
    int operator != (const point& other) const {
        return !(abs(other.x - x) < .00001 &&
        abs(other.y - y) < .00001);
    }
    bool operator< (const point& other) const {
        return (x < other.x ? true : (x == other.x && y
        < other.y));
    }
};
struct vect { ld i, j; };
struct segment {
    point p1, p2;

```



```

segment(point a, point b) : p1(a), p2(b) {}
segment() {}
};
long double crossProduct(point A, point B, point C) {
    vect AB, AC;
    AB.i = B.x - A.x;
    AB.j = B.y - A.y;
    AC.i = C.x - A.x;
    AC.j = C.y - A.y;
    return (AB.i * AC.j - AB.j * AC.i);
}
int orientation(point p, point q, point r) {
    int val = int(crossProduct(p, q, r));
    if(val == 0) {
        return COLINEAR;
    }
    return (val > 0) ? CW : CCW;
}
bool onSegment(point p, segment s) {
    return (p.x <= max(s.p1.x, s.p2.x) && p.x >=
min(s.p1.x, s.p2.x) &&
        p.y <= max(s.p1.y, s.p2.y) && p.y >=
min(s.p1.y, s.p2.y));
}
vector<point> intersect(segment s1, segment s2) {
    vector<point> res;
    point a = s1.p1, b = s1.p2, c = s2.p1, d = s2.p2;
    if(orientation(a, b, c) == 0 && orientation(a, b,
d) == 0 &&
        orientation(c, d, a) == 0 && orientation(c, d,
b) == 0) {
        point min_s1 = min(a, b), max_s1 = max(a, b);
        point min_s2 = min(c, d), max_s2 = max(c, d);
        if(min_s1 < min_s2) {
            if(max_s1 < min_s2) {
                return res;
            }
        }
        else if(min_s2 < min_s1 && max_s2 < min_s1) {
            return res;
        }
        point start = max(min_s1, min_s2), end =
min(max_s1, max_s2);
        if(start == end) {
            res.push_back(start);
        }
        else {
            res.push_back(min(start, end));
            res.push_back(max(start, end));
        }
    }
    return res;
}

```

```

}
ld x1 = (b.x - a.x);
ld y1 = (b.y - a.y);
ld x2 = (d.x - c.x);
ld y2 = (d.y - c.y);
ld u1 = (-y1 * (a.x - c.x) + x1 * (a.y - c.y)) / (-
x2 * y1 + x1 * y2);
ld u2 = (x2 * (a.y - c.y) - y2 * (a.x - c.x)) / (-
x2 * y1 + x1 * y2);
if(u1 >= 0 && u1 <= 1 && u2 >= 0 && u2 <= 1) {
    res.push_back(point((a.x + u2 * x1), (a.y + u2
* y1)));
}
return res;
}
int insidepoly(vector<point> poly, point p) {
    bool inside = false;
    point outside(inf, p.y);
    vector<point> intersection;
    for(unsigned int i = 0, j = poly.size()-1; i <
poly.size(); i++, j = i-1) {
        if(p == poly[i] || p == poly[j]) {
            return ONEDGE;
        }
        if(orientation(p, poly[i], poly[j]) == COLINEAR
&& onSegment(p, segment(poly[i], poly[j]))) {
            return ONEDGE;
        }
        intersection = intersect(segment(p, outside),
segment(poly[i], poly[j]));
        if(intersection.size() == 1) {
            if(poly[i] == intersection[0] && poly[j].y
<= p.y) {
                continue;
            }
            if(poly[j] == intersection[0] && poly[i].y
<= p.y) {
                continue;
            }
            inside = !inside;
        }
    }
    return inside ? INSIDE : OUTSIDE;
}
//

```

11.10 convex hull

```

// Given a Polygon, find its convex hull polygon
// O(n)
struct pt {

```

```

ll x, y;
pt operator - (pt p) { return {x-p.x, y-p.y}; }
bool operator == (pt b) { return x == b.x && y ==
b.y; }
bool operator != (pt b) { return !((*this) == b); }
bool operator < (const pt &o) const { return y <
o.y || (y == o.y && x < o.x); }
};
ll cross(pt a, pt b) { return a.x*b.y - a.y*b.x; } // x
= 180 -> sin = 0
ll orient(pt a, pt b, pt c) { return cross(b-a,c-
a); } // clockwise = -
ld norm(pt a) { return a.x*a.x + a.y*a.y; }
ld abs(pt a) { return sqrt(norm(a)); }
struct polygon {
    vector<pt> p;
    polygon(int n) : p(n) {}
    void delete_repetead() {
        vector<pt> aux;
        sort(p.begin(), p.end());
        for(pt &i : p)
            if(aux.empty() || aux.back() != i)
                aux.push_back(i);
        p.swap(aux);
    }
    int top = -1, bottom = -1;
    void normalize() { // polygon is CCW
        bottom = min_element(p.begin(), p.end()) -
p.begin();
        vector<pt> tmp(p.begin()+bottom, p.end());
        tmp.insert(tmp.end(), p.begin(),
p.begin()+bottom);
        p.swap(tmp);
        bottom = 0;
        top = max_element(p.begin(), p.end()) -
p.begin();
    }
    void convex_hull() {
        sort(p.begin(), p.end());
        vector<pt> ch;
        ch.reserve(p.size()+1);
        for(int it = 0; it < 2; it++) {
            int start = ch.size();
            for(auto &a : p) {
                // if colinear are needed, use < and
remove repeated points
                while(ch.size() >= start+2 &&
orient(ch[ch.size()-2], ch.back(), a) <= 0)
                    ch.pop_back();
                ch.push_back(a);
            }
        }
    }
}

```

```

        ch.pop_back();
        reverse(p.begin(), p.end());
    }
    if(ch.size() == 2 && ch[0] == ch[1])
ch.pop_back();
    // be careful with CH of size < 3
    p.swap(ch);
}
ld perimeter() {
    ld per = 0;
    for(int i = 0, n = p.size(); i < n; i++)
        per += abs(p[i] - p[(i+1)%n]);
    return per;
}
};

```

11.11 ufps point

```

// esto me pidio alex agregar
lf angle(pt a) {
    return atan2(a.y,a.x);
}
lf angle(pt a) {
    lf r = abs(a);
    return (a.y < 0? -1: 1)*acos(a.x / r);
}
lf angle(pt a, pt b) {
    lf aa = angle(a);
    lf bb = angle(b);
    lf dif = abs(aa - bb);
    return min(dif, 2*PI - dif);
}
// esto pidio alex agregar
typedef double lf;
const lf eps = 1e-9;
const lf PI = acos(-1.0);
typedef double T;
struct pt {
    T x, y;
    pt operator + (pt p) { return {x+p.x, y+p.y}; }
    pt operator - (pt p) { return {x-p.x, y-p.y}; }
    pt operator * (pt p) { return {x*p.x-y*p.y,
x*p.y+y*p.x}; }
    pt operator * (T d) { return {x*d, y*d}; }
    pt operator / (lf d) { return {x/d, y/d}; } // only
for floating point
    bool operator == (pt b) { return x == b.x && y ==
b.y; }
    bool operator != (pt b) { return !(*this == b); }
    bool operator < (const pt &o) const { return y <
o.y || (y == o.y && x < o.x); }
}

```

```

    bool operator > (const pt &o) const { return y >
o.y || (y == o.y && x > o.x); }
};
int cmp(lf a, lf b) { return (a + eps < b ? -1 : (b +
eps < a ? 1 : 0)); } // double comparator
T norm(pt a) { return a.x*a.x + a.y*a.y; }
lf abs(pt a) { return sqrt(norm(a)); }
lf arg(pt a) { return atan2(a.y, a.x); }
pt unit(pt a) { return a/abs(a); }
T dot(pt a, pt b) { return a.x*b.x + a.y*b.y; } // x =
90 -> cos = 0
T cross(pt a, pt b) { return a.x*b.y - a.y*b.x; } // x
= 180 -> sin = 0
T orient(pt a, pt b, pt c) { return cross(b-a, c-
a); } // clockwise = -
pt rot(pt p, lf a) { return {p.x*cos(a) - p.y*sin(a),
p.x*sin(a) + p.y*cos(a)}; }
pt rotate_to_b(pt a, pt b, lf ang) { return rot(a-b,
ang)+b; } // rotate by ang center b
pt rot90ccw(pt p) { return {-p.y, p.x}; }
pt rot90cw(pt p) { return {p.y, -p.x}; }
pt translate(pt p, pt v) { return p+v; }
pt scale(pt p, double f, pt c) { return c + (p-
c)*f; } // c-center
bool are_perp(pt v, pt w) { return dot(v, w) == 0; }
int sign(T x) { return (T(0) < x) - (x < T(0)); }
bool in_angle(pt a, pt b, pt c, pt x) { // x inside
angle abc (center in a)
    assert(orient(a, b, c) != 0);
    if (orient(a, b, c) < 0) swap(b, c);
    return orient(a, b, x) >= 0 && orient(a, c, x) <=
0;
}
// angle bwn 2 vectors [0, pi] -> [0, 180] and (-pi, 0)
-> (180, 360)
lf angle(pt a, pt b) { return acos(max(-1.0, min(1.0,
dot(a, b)/abs(a)/abs(b)))); }
lf angle(pt a, pt b) { return atan2(cross(a, b), dot(a,
b)); }
lf angle360(pt a, pt b) { // [0, 360)
    lf ang = angle(a, b); return (ang < 0 ? ang+2*PI :
ang) * 360/(2*PI);
}
// returns vector to transform points
pt get_linear_transformation(pt p, pt q, pt r, pt fp,
pt fq) {
    pt pq = q-p, num{cross(pq, fq-fp), dot(pq, fq-fp)};
    return fp + pt{cross(r-p, num), dot(r-p, num)} /
norm(pq);
}
bool half(pt p) { // true if is in (0, 180] (line is x

```

```

axis)
    assert(p.x != 0 || p.y != 0); // the argument of
(0, 0) is undefined
    return p.y > 0 || (p.y == 0 && p.x < 0);
}
bool half_from(pt p, pt v = {1, 0}) { // line is v
(above v is true)
    return cross(v, p) < 0 || (cross(v, p) == 0 &&
dot(v, p) < 0);
}
bool polar_cmp(const pt &a, const pt &b) { // polar
sort
    return make_tuple(half(a), 0) < make_tuple(half(b),
cross(a, b));
    // return make_tuple(half(a), 0, sq(a)) <
make_tuple(half(b), cross(a, b), sq(b)); // further
ones appear later
}

```

11.12 polygon diameter

```

// Given a set of points, it returns
// the diameter (the biggest distance between 2 points)
// tested: https://open.kattis.com/submissions/13937489
const double eps = 1e-9;
int sign(double x) { return (x > eps) - (x < -eps); }
struct PT {
    double x, y;
    PT() { x = 0, y = 0; }
    PT(double x, double y) : x(x), y(y) {}
    PT operator - (const PT &a) const { return PT(x -
a.x, y - a.y); }
    bool operator < (PT a) const { return sign(a.x - x)
== 0 ? y < a.y : x < a.x; }
    bool operator == (PT a) const { return sign(a.x -
x) == 0 && sign(a.y - y) == 0; }
};
inline double dot(PT a, PT b) { return a.x * b.x + a.y
* b.y; }
inline double dist2(PT a, PT b) { return dot(a - b, a -
b); }
inline double dist(PT a, PT b) { return sqrt(dot(a - b,
a - b)); }
inline double cross(PT a, PT b) { return a.x * b.y -
a.y * b.x; }
inline int orientation(PT a, PT b, PT c) { return
sign(cross(b - a, c - a)); }
double diameter(vector<PT> &p) {
    int n = (int)p.size();
    if (n == 1) return 0;
    if (n == 2) return dist(p[0], p[1]);
}

```

```

double ans = 0;
int i = 0, j = 1;
while (i < n) {
    while (cross(p[(i + 1) % n] - p[i], p[(j + 1) % n] - p[j]) >= 0) {
        ans = max(ans, dist2(p[i], p[j]));
        j = (j + 1) % n;
    }
    ans = max(ans, dist2(p[i], p[j]));
    i++;
}
return sqrt(ans);
}

vector<PT> convex_hull(vector<PT> &p) {
    if (p.size() <= 1) return p;
    vector<PT> v = p;
    sort(v.begin(), v.end());
    vector<PT> up, dn;
    for (auto& p : v) {
        while (up.size() > 1 &&
orientation(up[up.size() - 2], up.back(), p) >= 0) {
            up.pop_back();
        }
        while (dn.size() > 1 &&
orientation(dn[dn.size() - 2], dn.back(), p) <= 0) {
            dn.pop_back();
        }
        up.push_back(p);
        dn.push_back(p);
    }
    v = dn;
    if (v.size() > 1) v.pop_back();
    reverse(up.begin(), up.end());
    up.pop_back();
    for (auto& p : up) {
        v.push_back(p);
    }
    if (v.size() == 2 && v[0] == v[1]) v.pop_back();
    return v;
}

void test_case() {
    ll n;
    cin >> n;
    vector<PT> p(n);
    for (int i = 0; i < n; i++) cin >> p[i].x >> p[i].y;
    p = convex_hull(p);
    cout << fixed<<setprecision(10) << diameter(p) <<
"\n";
}
    
```

11.13 closest pair of points

```

// It seems O(n log n), not sure but it worked for
50000
// This algorithms is not the best, TLE in CSES
// https://cses.fi/problemset/task/2194
#define x first
#define y second
long long dist2(pair<int, int> a, pair<int, int> b) {
    return 1LL * (a.x - b.x) * (a.x - b.x) + 1LL * (a.y -
b.y) * (a.y - b.y);
}
pair<int, int> closest_pair(vector<pair<int, int>> a) {
    int n = a.size();
    assert(n >= 2);
    vector<pair<pair<int, int>, int>> p(n);
    for (int i = 0; i < n; i++) p[i] = {a[i], i};
    sort(p.begin(), p.end());
    int l = 0, r = 2;
    long long ans = dist2(p[0].x, p[1].x);
    pair<int, int> ret = {p[0].y, p[1].y};
    while (r < n) {
        while (l < r && 1LL * (p[r].x.x - p[l].x.x) *
(p[r].x.x - p[l].x.x) >= ans) l++;
        for (int i = l; i < r; i++) {
            long long nw = dist2(p[i].x, p[r].x);
            if (nw < ans) {
                ans = nw;
                ret = {p[i].y, p[r].y};
            }
        }
        r++;
    }
    return ret;
}

// Tested: https://vjudge.net/solution/52922194/
ccPUXODAMWTzpZCEvXbV
void test_case() {
    ll n;
    cin >> n;
    vector<pair<int, int>> points(n);
    for (int i = 0; i < n; i++) cin >> points[i].x >>
points[i].y;
    auto ans = closest_pair(points);
    cout << fixed << setprecision(6);
    if (ans.F > ans.S) swap(ans.F, ans.S);
    ld dist =
sqrtl(dist2(points[ans.F], points[ans.S]));
    cout << ans.F << " " << ans.S << " " << dist <<
endl;
}
    
```

12 9. Utils

12.1 bit tricks

```

y = x & (x-1) // Turn off rightmost lbit
y = x & (-x) // Isolate rightmost lbit
y = x | (x-1) // Right propagate rightmost lbit(fill
in 1s)
y = x | (x+1) // Turn on rightmost 0bit
y = ~x & (x+1) // Isolate rightmost 0bit
// If x is of long type, use __builtin_popcountl(x)
// If x is of long long type, use
__builtin_popcountll(x)
// 1. Counts the number of one's(set bits) in an
integer.
__builtin_popcount(x)
// 2. Checks the Parity of a number. Returns true(1) if
the
// number has odd number of set bits, else it returns
// false(0) for even number of set bits.
__builtin_parity(x)
// 3. Counts the leading number of zeros of the
integer.
__builtin_clz(x)
// 4. Counts the trailing number of zeros of the
integer.
__builtin_ctz(x)
// 5. Returns 1 + the index of the least significant 1-
bit.
__builtin_ffs(x) // If x == 0, returns 0.
// Iterate over non empty subsets of bitmask
for(int s=m;s=s-1&m) // Decreasing order
for(int s=0;s=s-m&m;) // Increasing order
    
```

12.2 pragmas

```

//#pragma GCC target("popcnt")
//It's worth noting that after adding
__builtin_popcount() is replaced to corresponding
machine instruction (look at the difference). In my
test this maked x2 speed up. bitset::count() use
__builtin_popcount() call in implementation, so it's
also affected by this.
#pragma GCC target ("avx2")
#pragma GCC optimization ("O3")
#pragma GCC optimization ("unroll-loops")
#pragma GCC target("popcnt")
#pragma GCC
target("avx,avx2,sse3,ssse3,sse4.1,sse4.2,tune=native")
#pragma GCC optimize(3)
#pragma GCC optimize("O3")
    
```

```
#pragma GCC optimize("inline")
#pragma GCC optimize("-fgcse")
#pragma GCC optimize("-fgcse-lm")
#pragma GCC optimize("-fipa-sra")
#pragma GCC optimize("-ftree-pre")
#pragma GCC optimize("-ftree-vec")
#pragma GCC optimize("-fpeephole2")
#pragma GCC optimize("-fsched-spec")
#pragma GCC optimize("-falign-jumps")
#pragma GCC optimize("-falign-loops")
#pragma GCC optimize("-falign-labels")
#pragma GCC optimize("-fdevirtualize")
#pragma GCC optimize("-fcaller-saves")
#pragma GCC optimize("-fcrossjumping")
#pragma GCC optimize("-fthread-jumps")
#pragma GCC optimize("-freorder-blocks")
#pragma GCC optimize("-fschedule-insns")
#pragma GCC optimize("inline-functions")
#pragma GCC optimize("-ftree-tail-merge")
#pragma GCC optimize("-fschedule-insns2")
#pragma GCC optimize("-fststrict-aliasing")
#pragma GCC optimize("-falign-functions")
#pragma GCC optimize("-fcse-follow-jumps")
#pragma GCC optimize("-fsched-interblock")
#pragma GCC optimize("-fpartial-inlining")
#pragma GCC optimize("no-stack-protector")
#pragma GCC optimize("-freorder-functions")
#pragma GCC optimize("-findirect-inlining")
#pragma GCC optimize("-fhoist-adjacent-loads")
#pragma GCC optimize("-frerun-cse-after-loop")
#pragma GCC optimize("inline-small-functions")
#pragma GCC optimize("-finline-small-functions")
#pragma GCC optimize("-ftree-switch-conversion")
#pragma GCC optimize("-foptimize-sibling-calls")
#pragma GCC optimize("-fexpensive-optimizations")
#pragma GCC optimize("inline-functions-called-once")
#pragma GCC optimize("-fdelete-null-pointer-checks")
```

12.3 string streams

```
// For some complex reading of input
// st is the same as a cin, but you pass the string
string line;
getline(cin, line);
stringstream st(line);
vl in;
ll x;
while (st >> x) {
    in.pb(x);
}
```

12.4 randoms

```
// Get random numbers between [a, b]
mt19937
mt_rng(chrono::steady_clock::now().time_since_epoch().count());
// also for ll exists mt19937_64
ll randint(ll a, ll b) {
    return uniform_int_distribution<ll>(a, b)(mt_rng);
}
```

12.5 io int128

```
// Read and Print integers of 128 bits
__int128 read() {
    __int128 x = 0, f = 1;
    char ch = getchar();
    while (ch < '0' || ch > '9') {
        if (ch == '-') f = -1;
        ch = getchar();
    }
    while (ch >= '0' && ch <= '9') {
        x = x * 10 + ch - '0';
        ch = getchar();
    }
    return x * f;
}

void print(__int128 x) {
    if (x < 0) {
        putchar('-');
        x = -x;
    }
    if (x > 9) print(x / 10);
    putchar(x % 10 + '0');
}

void print(__int128 x) {
    if (x < 0) {
        cout << "-";
        x = -x;
    }
    if (x > 9) print(x / 10);
    cout << char((int)(x % 10) + '0');
}
```

12.6 decimal precision python

```
"""
For problems that needs more decimal precision
You can try this code but in C++,
it will not pass in this problem https://cses.fi/
problemset/task/1728/
"""
from decimal import *
```

```
getcontext().prec = 200 #The decimal precision
n = int(input())
nums = [int(x) for x in input().split(" ")]
ans = Decimal(0)
for i in range(0, len(nums)):
    for j in range(i+1, len(nums)):
        for k in range(1, nums[j]+1):
            ans += max(0, nums[i]-k)/
Decimal(nums[i]*nums[j])
# Also for reduce getcontext().prec = 100
# You can sum integer part, then apply the
decimal division
print("{:.6f}".format(ans)) #The rounding half even to
six decimals
```

13 A. To Order

13.1 polynomial sum lazy segtree problem

```
/* Polynomial Queries, queries
1. Increase [a,b] by 1, second by 2, third by 3, and so
on
2. Sum of [a,b]
Use:
cin >> nums[i], tree.update(i, { nums[i] })
For 1: tree.apply(l, r, {0,1});
For 2: tree.query(l, r).sum
*/
struct Node { ll sum = 0; };
struct Func { ll add, ops; };
Node e() { return {0}; };
Func id() { return {0, 0}; }
Node op(Node a, Node b) { return {a.sum + b.sum}; }
ll f(ll x) { return x * (x+1)/2; }
Node mapping(Node node, Func lazy, ll sz) {
    return { node.sum + sz*lazy.add + lazy.ops*f(sz) };
}
Func composition(Func prev, Func actual) {
    Func ans = { prev.add + actual.add, prev.ops +
actual.ops };
    return ans;
}
Func sumF(Func f, ll x) { return {f.add + x*f.ops,
f.ops}; }
struct lazytree {
    int n;
    vector<Node> nodes;
    vector<Func> lazy;
    void init(int nn) {
```

```

n = nn;
int size = 1;
while (size < n) { size *= 2; }
ll m = size * 2;
nodes.assign(m, e());
lazy.assign(m, id());
}
void push(int i, int sl, int sr) {
    nodes[i] = mapping(nodes[i], lazy[i], sr-sl+1);
    if (sl != sr) {
        ll cnt = (sr+sl)/2-sl+1; // changed
        lazy[i * 2 + 1] =
composicion(lazy[i*2+1], lazy[i]);
        lazy[i * 2 + 2] =
composicion(lazy[i*2+2], sumF(lazy[i], cnt));
    }
    lazy[i] = id();
}
void apply(int i, int sl, int sr, int l, int r,
Func f) {
    push(i, sl, sr);
    if (l <= sl && sr <= r) {
        lazy[i] = sumF(f, abs(sl-l)); //Changed
        push(i, sl, sr);
    } else if (sr < l || r < sl) {
    } else {
        int mid = (sl + sr) >> 1;
        apply(i * 2 + 1, sl, mid, l, r, f);
        apply(i * 2 + 2, mid + 1, sr, l, r, f);
        nodes[i] = op(nodes[i*2+1], nodes[i*2+2]);
    }
}
void apply(int l, int r, Func f) {
    assert(l <= r);
    assert(r < n);
    apply(0, 0, n - 1, l, r, f);
}
void update(int i, Node node) {
    assert(i < n);
    update(0, 0, n-1, i, node);
}
void update(int i, int sl, int sr, int pos, Node
node) {
    if (sl <= pos && pos <= sr) {
        push(i, sl, sr);
        if (sl == sr) {
            nodes[i] = node;
        } else {
            int mid = (sl + sr) >> 1;
            update(i * 2 + 1, sl, mid, pos, node);
            update(i * 2 + 2, mid + 1, sr, pos,

```

```

node);
        nodes[i] = op(nodes[i*2+1],
nodes[i*2+2]);
    }
}
Node query(int i, int sl, int sr, int l, int r) {
    push(i, sl, sr);
    if (l <= sl && sr <= r) {
        return nodes[i];
    } else if (sr < l || r < sl) {
        return e();
    } else {
        int mid = (sl + sr) >> 1;
        auto a = query(i * 2 + 1, sl, mid, l, r);
        auto b = query(i * 2 + 2, mid + 1, sr, l,
r);
        return op(a, b);
    }
}
Node query(int l, int r) {
    assert(l <= r);
    assert(r < n);
    return query(0, 0, n - 1, l, r);
}
};

```

13.2 mo's in tree's

DFS Euler **2N**:
 array A con cada nodo **2 veces** (ST[u] entrada, EN[u] salida).
 En Mo, **add(pos)** togglea el nodo A[pos] (activo ↔ inactivo).
Query (u,v), p=LCA(u,v), con ST[u] ≤ ST[v]:
 si p==u: rango [ST[u], ST[v]]
 si p!=u: rango [EN[u], ST[v]] y agregás p **aparte** (toggle antes/después).

13.3 poly definitions

A(x) = Sum i=0 to n (a_i * x^i) y B(x) Sum i=0 to m (b_i * x^i)
 A(x)*B(x) Sum i=0 to (n+m) Sum j=0 to (n+m) (a_j)*(b_i-j) x^i

14 Problems

14.1 shift poly

```

// ADD ntt, or karatsuba.
// A poly: c_0 + c_1*x + c_2*x^2 + ... is transformed
to
// c_0 + c_1*(x+k) + c_2*(x+k)^2 + ...
vl fact, ifact;
vl ki, iki;
void initShifts(ll n, ll k) {
    k = (k%MOD + MOD) % MOD;
    fact = ifact = vl(n+1);
    ki = iki = vl(n+1);
    fact[0] = ifact[0] = 1;
    ki[0] = iki[0] = 1;
    for (int i = 1; i <= n; i++) {
        fact[i] = (fact[i-1]*i)%MOD;
        ifact[i] = inv(fact[i]);
        ki[i] = (ki[i-1]*k) % MOD;
        iki[i] = inv(ki[i]);
    }
}
// P(x + k)
vl shift(vl &a, ll k) {
    if (k == 0) return a;
    ll n = a.size();
    initShifts(n, k);
    vl l(n), r(n);
    for (int i = 0; i < n; i++) {
        l[i] = mulmod(a[i], fact[i]);
        r[i] = mulmod(ki[n-1-i], ifact[n-1-i]);
    }
    vl c = multiply(l, r);
    vl ans(n);
    for (int i = 0; i < n; i++) {
        ans[i] = mulmod(c[n-1+i], ifact[i]);
    }
    return ans;
}

```

14.2 big primes

```

#define bint __int128
bint MOD=212345678987654321LL; // prime

```