

Team Notebook

Universidad Mayor de San Simón - Wasos del Valle

1 1. Math 3	5.3 dp mask over submasks 9	8 5. Flow 18
1.1 add josephus 3	5.4 knuths optimization 9	8.1 blossom 18
1.2 catalan convolution 3	5.5 linear recurrence cayley halmiton 10	8.2 hopcroftkarp 19
1.3 catalan 3	5.6 linear recurrence matrix exponciation 10	8.3 hungarian 19
1.4 combinatorics 3	5.7 longest increasing subsequence 11	8.4 max flow 20
1.5 count primes with pi function 3	5.8 multiple knacksack optimizacion 11	8.5 min cost max flow 20
1.6 fast fibonacci 4	5.9 optimizing pragmas for bitset 11	8.6 min cut 21
1.7 floor sums 4	5.10 separation optimization 11	9 6. Tree 21
1.8 optimized polard rho 4	5.11 sos dp reverse 11	9.1 block tree 21
1.9 subfactorial 5	5.12 sos dp 11	9.2 centroid descomposition 22
1.10 ternary search 5	6 3. Data Structures 11	9.3 heavy light 23
2 1. Math - Fft 5	6.1 custom hash 11	9.4 isomorfismo 23
2.1 fast hadamard transform 5	6.2 dynamic connectivity 12	9.5 online centroid 23
2.2 fft shifts trick 5	6.3 fast hash map 12	10 7. Strings 23
2.3 fft 5	6.4 fenwick tree 2d 12	10.1 ahocorasick 23
2.4 karatsuba 6	6.5 fenwick tree 12	10.2 fast hashing 24
2.5 ntt 6	6.6 lazy segment tree 13	10.3 function z 24
3 1. Math - Mobius 6	6.7 min sparse table 14	10.4 kmp automaton 24
3.1 linear sieve 6	6.8 mo's 14	10.5 kmp 24
3.2 mobius 7	6.9 multiorderedset 14	10.6 manacher 24
3.3 $[gcd(a, i, a, j) == k] \square \text{queries}$ 7	6.10 orderedset 15	10.7 micky hashing 25
3.4 $[gcd(i, j) == k]$ 7	6.11 persistance segtree 15	10.8 palindromic 25
3.5 $\square \sigma_{n}^{\wedge} \{i=1\} \square \frac{n}{gcd(i,n)}$ 7	6.12 persistantsegmenttree 15	10.9 suffix array 25
4 1. Math - Modular Arithmethics 8	6.13 rope 15	11 8. Geometry 26
4.1 big expontent modular exponentiation 8	6.14 segment tree 2d 16	11.1 closest pair of points sweep line 26
4.2 chinease remainder 8	6.15 segment tree 16	11.2 closest pair of points 26
4.3 diophantine ecuations 8	6.16 sqrt mod 17	11.3 heron formula 26
4.4 discrete log 8	7 4. Graphs 17	11.4 ufps circle 26
5 2. Dp 8	7.1 bellmanford find negative cycle 17	11.5 ufps halfplane 27
5.1 convex hull trick 8	7.2 strongly connected components 17	11.6 ufps line 27
5.2 divide and conquer optimization 9	7.3 two sat 18	11.7 ufps point 27

11.8 ufps polygon	28
11.9 ufps segment	29
12 9. Utils	30
12.1 bit tricks	30
12.2 decimal precision python	30
12.3 io int128	30
12.4 pragmas	30
12.5 randoms	31
12.6 string streams	31
13 A. To Order	31
13.1 mo's in tree's	31
13.2 poly definitions	31
13.3 polynomial sum lazy segtree problem	31
14 Problems	32
14.1 big primes	32
14.2 shift poly	32

1.1. Math

1.1 add josephus

1.2 catalan convolution

```
/*
Catalan Convolution.
Convolution for k=3
((( A ) B ) C ) D
Where A + B + C + D = N, for N + 1
*/
ll cnk(ll n, ll k);
// for parenthesis example
// number of n+k pairs having k open parenthesis at
beginning
// (cnk(2n+k,n)*(k+1))/(n+k+1)
ll catalanCov(ll n, ll k) {
    ll up = mul(cnk(2*n+k,n),(k+1)%MOD);
    ll down = (n+k+1)%MOD;
    return mul(up,inv(down));
}
/*
6
((
ans: 2
*/
// size, and prefix
ll countParenthesisWithPrefix(ll n, string &p) {
    if (n&1) return 0;
    ll k = 0;
    for (auto c : p) {
        if (c=='(') k++;
        else k--;
        if (k<0) return 0;
    }
    n=(n-(ll)p.size()-k)/2;
    return catalanCov(n,k);
}
```

1.3 catalan

Catalan, cuenta numero de formas
(A) B, donde $|A|+|B| = N$, para $N+1$

```
ll catalan(ll n) {
    if (n<0) return 0;
    ll up = fact[2*n]; ll down = mul(fact[n],fact[n+1]);
    return mul(up,inv(down));
}
```

1.4 combinatorics

```
// 0(min(n, n-k)) lineal
ll nck(ll n, ll k) {
    if (k < 0 || n < k) return 0;
    k = min(k, n-k);
    ll ans = 1;
    for (int i = 1; i <= k; i++)
        ans = ans * (n-i+1) / i;
    return ans;
}
```

1.5 count primes with pi function

```
// sprime.count_primes(n);
// 0(n^(2/3))
// PI(n) = Count prime numbers until n inclusive
struct count_primers_struct {
    vector<int> primes;
    vector<int> mnprimes;
    ll ans;
    ll y;
    vector<pair<pair<ll, int>, char>> queries;
    ll count_primes(ll n) {
        // this y is actually n/y
        // also no logarithms, welcome to reality, this
        y is the best for n=10^12 or n=10^13
        y = pow(n, 0.64);
        if (n < 100) y = n;
        // linear sieve
        primes.clear();
        mnprimes.assign(y + 1, -1);
        ans = 0;
        for (int i = 2; i <= y; ++i) {
            if (mnprimes[i] == -1) {
                mnprimes[i] = primes.size();
                primes.push_back(i);
            }
            for (int k = 0; k < primes.size(); ++k) {
                int j = primes[k];
                if (i * j > y) break;
                mnprimes[i * j] = k;
                if (i % j == 0) break;
            }
        }
        if (n < 100) return primes.size();
        ll s = n / y;
        for (int p : primes) {
            if (p > s) break;
            ans++;
        }
        // pi(n / y)
    }
}
```

```
int ssz = ans;
// F with two pointers
int ptr = primes.size() - 1;
for (int i = ssz; i < primes.size(); ++i) {
    while (ptr >= i && (ll)primes[i] *
primes[ptr] > n)
        --ptr;
    if (ptr < i) break;
    ans -= ptr - i + 1;
}
// phi, store all queries
phi(n, ssz - 1);
sort(queries.begin(), queries.end());
int ind = 2;
int sz = primes.size();
// the order in fenwick will be reversed,
because prefix sum in a fenwick is just one query
fenwick fw(sz);
for (auto qq : queries) {
    auto na = qq.F;
    auto sign = qq.S;
    auto n = na.F;
    auto a = na.S;
    while (ind <= n)
        fw.add(sz - 1 - mnprimes[ind++], 1);
    ans += (fw.ask(sz - a - 2) + 1) * sign;
}
queries.clear();
return ans - 1;
}
void phi(ll n, int a, int sign = 1) {
    if (n == 0) return;
    if (a == -1) {
        ans += n * sign;
        return;
    }
    if (n <= y) {
        queries.emplace_back(make_pair(n, a),
sign);
        return;
    }
    phi(n, a - 1, sign);
    phi(n / primes[a], a - 1, -sign);
}
struct fenwick {
    vector<int> tree;
    int n;
    fenwick(int n = 0) : n(n) {
        tree.assign(n, 0);
    }
    void add(int i, int k) {
```

```

        for (; i < n; i = (i | (i + 1)))
            tree[i] += k;
    }
    int ask(int r) {
        int res = 0;
        for (; r >= 0; r = (r & (r + 1)) - 1)
            res += tree[r];
        return res;
    }
};
};
count_primers_struct sprime;

```

1.6 fast fibonacci

```

0(log n), fib(n).F = Fib at n-th position
pair<ll, ll> fib (ll n) {
    if (n == 0) return {0, 1};
    auto p = fib(n >> 1);
    ll c = (p.F * (2*p.S - p.F + MOD)%MOD)%MOD;
    ll d = (p.F * p.F + p.S * p.S)%MOD;
    if (n & 1) return {d, (c + d)%MOD};
    else return {c, d};
}

```

1.7 floor sums

```

// from atcoder
// floor_sum(n,m,a,b) = sum{0 to n-1} [(a*i+b)/m]
// 0(log m), mod 2^64, n<2^32, m<2^32
constexpr long long safe_mod(long long x, long long m)
{
    x %= m;
    if (x < 0) x += m;
    return x;
}
unsigned long long floor_sum_unsigned(unsigned long
long n,
                                unsigned long
long m,
                                unsigned long
long a,
                                unsigned long
long b) {
    unsigned long long ans = 0;
    while (true) {
        if (a >= m) {
            ans += n * (n - 1) / 2 * (a / m);
            a %= m;
        }
        if (b >= m) {
            ans += n * (b / m);

```

```

        b %= m;
    }
    unsigned long long y_max = a * n + b;
    if (y_max < m) break;
    // y_max < m * (n + 1)
    // floor(y_max / m) <= n
    n = (unsigned long long)(y_max / m);
    b = (unsigned long long)(y_max % m);
    swap(m, a);
}
return ans;
}
long long floor_sum(long long n, long long m, long long
a, long long b) {
    assert(0 <= n && n < (1LL << 32));
    assert(1 <= m && m < (1LL << 32));
    unsigned long long ans = 0;
    if (a < 0) {
        unsigned long long a2 = safe_mod(a, m);
        ans -= 1ULL * n * (n - 1) / 2 * ((a2 - a) / m);
        a = a2;
    }
    if (b < 0) {
        unsigned long long b2 = safe_mod(b, m);
        ans -= 1ULL * n * ((b2 - b) / m);
        b = b2;
    }
    return ans + floor_sum_unsigned(n, m, a, b);
}

```

1.8 optimized polard rho

```

// Fast factorization with big numbers, use fact method
// Seems to be 0(log^3(n)) !!! Need revision
#define fore(i, b, e) for(int i = b; i < e; i++)
ll gcd(ll a, ll b){return a?gcd(b%a,a):b;}
ll mulmod(ll a, ll b, ll m) {
    ll r=a*b-(ll)((long double)a*b/m+.5)*m;
    return r<0?r+m:r;
}
ll expmod(ll b, ll e, ll m){
    if(!e)return 1;
    ll q=expmod(b,e/2,m);q=mulmod(q,q,m);
    return e&1?mulmod(b,q,m):q;
}
bool is_prime_prob(ll n, int a){
    if(n==a)return true;
    ll s=0,d=n-1;
    while(d%2==0)s++,d/=2;
    ll x=expmod(a,d,n);
    if((x==1)|| (x+1==n))return true;
}

```

```

fore(_,0,s-1){
    x=mulmod(x,x,n);
    if(x==1)return false;
    if(x+1==n)return true;
}
return false;
}
bool rabin(ll n){ // true iff n is prime
    if(n==1)return false;
    int ar[]={2,3,5,7,11,13,17,19,23};
    fore(i,0,9)if(!is_prime_prob(n,ar[i]))return false;
    return true;
}
// optimized version: replace rho and fact with the
following:
const int MAXP=1e6+1; // sieve size
int sv[MAXP]; // sieve
ll add(ll a, ll b, ll m){return (a+b)<m?a+b-m;}
ll rho(ll n){
    static ll s[MAXP];
    while(1){
        ll x=rand()%n,y=x,c=rand()%n;
        ll *px=s,*py=s,v=0,p=1;
        while(1){
            *py+=y=add(mulmod(y,y,n),c,n);
            *py+=y=add(mulmod(y,y,n),c,n);
            if((x=*px++)==y)break;
            ll t=p;
            p=mulmod(p,abs(y-x),n);
            if(!p)return gcd(t,n);
            if(++v==26){
                if((p=gcd(p,n))>1&&p<n)return p;
                v=0;
            }
        }
        if(v&&(p=gcd(p,n))>1&&p<n)return p;
    }
}
void init_sv(){
    fore(i,2,MAXP)if(!sv[i])for(ll
j=i;j<MAXP;j+=i)sv[j]=i;
}
void fact(ll n, map<ll,int>& f){ // call init_sv
first!!!
    for(auto&& p:f){
        while(n%p.F==0){
            p.S++; n/=p.F;
        }
    }
    if(n<MAXP)while(n>1)f[sv[n]]++,n/=sv[n];
    else if(rabin(n))f[n]++;
}

```

```

    else {ll q=rho(n);fact(q,f);fact(n/q,f);}
}

```

1.9 subfactorial

```

const int mxN = 2e6 + 10;
vector<ll> subFact(mxN);
void init() {
    subFact[0] = 1, subFact[1] = 0;
    for (int i = 2; i < mxN; i++)
        subFact[i] = mul(add(subFact[i-1], subFact[i-2]), i-1);
}

```

1.10 ternary search

```

// this is for find minimum point in a parabolic
// O(log3(n))
// TODO: Improve to generic!!!
ll left = 0;
ll right = n - 1;
while (left + 3 < right) {
    ll mid1 = left + (right - left) / 3;
    ll mid2 = right - (right - left) / 3;
    if (f(b, lines[mid1]) <= f(b, lines[mid2])) {
        right = mid2;
    } else {
        left = mid1;
    }
}
ll target = -4 * a * c;
ll ans = -1; // find the answer, in this case any
works.
for (ll mid = left; mid <= right; mid++) {
    if (f(b, lines[mid]) + target < 0) {
        ans = mid;
    }
}

```

2 1. Math - Fft

2.1 fast hadamard transform

```

// like polynomial multiplication, but XORing exponents
// instead of adding them (also ANDing, ORing)
const int MAXN=1<<18;
#define fore(i,l,r) for(int i=int(l);i<int(r);++i)
#define SZ(x) ((int)(x).size())
ll c1[MAXN+9],c2[MAXN+9]; //MAXN must be power of 2!
void fht(ll* p, int n, bool inv){
    for(int l=1;2*l<=n;l*=2)
        for(int i=0;i<n;i+=2*l)

```

```

        fore(j,0,l){
            ll u=p[i+j],v=p[i+l+j];
            // if(!inv)p[i+j]=u+v,p[i+l+j]=u-v; // XOR
            // else p[i+j]=(u+v)/2,p[i+l+j]=(u-v)/2;
            //if(!inv)p[i+j]=v,p[i+l+j]=u+v; // AND
            //else p[i+j]=-u+v,p[i+l+j]=u;
            if(!inv)p[i+j]=u+v,p[i+l+j]=u; // OR
            else p[i+j]=v,p[i+l+j]=u-v;
        }
    }
    // like polynomial multiplication, but XORing exponents
    // instead of adding them (also ANDing, ORing)
    vector<ll> multiply(vector<ll>& p1, vector<ll>& p2){
        int n=1<<(32-__builtin_clz(max(SZ(p1),SZ(p2))-1));
        fore(i,0,n)c1[i]=0,c2[i]=0;
        fore(i,0,SZ(p1))c1[i]=p1[i];
        fore(i,0,SZ(p2))c2[i]=p2[i];
        fht(c1,n,false);fht(c2,n,false);
        fore(i,0,n)c1[i]*=c2[i];
        fht(c1,n,true);
        return vector<ll>(c1,c1+n);
    }
    // maxime the OR of a pair of given nums and count
    // how many pairs can get that maximum OR
    // tested: csacademy.com/contest/archive/task/maxor
    void test_case() {
        ll n; cin >> n;
        vl a(MAXN),b(MAXN);
        for (int i = 0; i < n; i++) {
            ll x; cin >> x; a[x]++; b[x]++;
        }
        vl c = multiply(a,b);
        pair<ll,ll> best = {0, c[0]};
        for (int i = 0; i < MAXN; i++)
            if (c[i]) best = {i, (c[i]-a[i])/2};
        cout << best.F << " " << best.S << endl;
    }
}

```

2.2 fft shifts trick

```

//FFT Trick, it very useful for shifts in the
following:
// Sum j_0 to n-1 a[j]*a[j+i]
// where i is the number of shifts, and 'a' is some
array.
auto copy = actual;
reverse(all(copy));
// be careful with doubles precision, so maybe NTT
could be useful here.
// multply is the method of FTT or NTT
auto polinomy = multiply(actual, copy);

```

```

ll m = actual.size();
answer[0] = polinomy[m-1]; // 0 with m-1, 1 with m-2
=m-1
for (int i = 1; i <= m-1; i++) { // 1 step no m-1 steps
    // 0 with m-2 is 1 step, 1 with m-3 is one then
m-1-1, also the last one m-1 is with m-1
    // 0 with m-3 is 2 step, m-1 with m-1-1
    answer[i] = polinomy[m-1-i] + polinomy[2*(m-1)-
i+1];
}

```

2.3 fft

```

// FFT multiplies polinomial 'a' and 'b' in O(n log n)
// you can define double as long double, but maybe TLE
using cd = complex<double>;
void fft(vector<cd> & a, bool invert) {
    ll n = a.size();
    for (ll i = 1, j = 0; i < n; i++) {
        ll bit = n >> 1;
        for (; j & bit; bit >>= 1)
            j ^= bit;
        j ^= bit;
        if (i < j)
            swap(a[i], a[j]);
    }
    for (ll len = 2; len <= n; len <= 1) {
        double ang = 2 * PI / len * (invert ? -1 : 1);
        cd wlen(cos(ang), sin(ang));
        for (ll i = 0; i < n; i += len) {
            cd w(1);
            for (ll j = 0; j < len / 2; j++) {
                cd u = a[i+j], v = a[i+j+len/2] * w;
                a[i+j] = u + v;
                a[i+j+len/2] = u - v;
                w *= wlen;
            }
        }
    }
    if (invert) {
        for (cd & x : a)
            x /= n;
    }
}
vector<ll> multiply(vector<ll> & a, vector<ll> & b) {
    vector<cd> fa(a.begin(), a.end()),
        fb(b.begin(), b.end());
    ll n = 1;
    while (n < a.size() + b.size())
        n <= 1;
    fa.resize(n);

```

```
fb.resize(n);
fft(fa, false);
fft(fb, false);
for (ll i = 0; i < n; i++)
    fa[i] *= fb[i];
fft(fa, true);
vector<ll> result(n);
for (ll i = 0; i < n; i++)
    result[i] = round(fa[i].real());
// fa[i].real() + 0.5 is faster
return result;
}
```

2.4 karatsuba

```
// Multiplication of Polynomials in  $O(n^{1.58})$ 
// with any Module that you want
#define ll long long
const int MOD = 1e9+7;
#define poly vector<ll>
#define fore(i,a,b) for(int i=a,ThxDem=b;i<ThxDem;++i)
typedef int tp;
ll sum(ll x, ll y) {
    ll ans = (x + y) % MOD;
    if (ans < 0) ans += MOD;
    return ans;
}
ll mult(ll x, ll y) {
    ll ans = (x % MOD) * (y % MOD);
    ans %= MOD;
    if (ans < 0) ans += MOD;
    return ans;
}
#define add(n,s,d,k) \
    fore(i,0,n)(d)[i] = sum((d)[i],mult((s)[i],k))
tp* ini(int n){
    tp *r=new tp[n];fill(r,r+n,0);
    return r;
}
void karatsura(int n, tp* p, tp* q, tp* r){
    if(n<=0)return;
    if(n<35)
        fore(i,0,n)
            fore(j,0,n)
                r[i+j]=sum(r[i+j], mult(p[i],q[j]));
    else {
        int nac=n/2,nbd=n-n/2;
        tp *a=p,*b=p+nac,*c=q,*d=q+nac;
        tp *ab=ini(nbd+1),*cd=ini(nbd+1),
            *ac=ini(nac*2),*bd=ini(nbd*2);
        add(nac,a,ab,1);add(nbd,b,ab,1);
```

```
add(nac,c,cd,1);add(nbd,d,cd,1);
karatsura(nac,a,c,ac);karatsura(nbd,b,d,bd);
add(nac*2,ac,r+nac,-1);add(nbd*2,bd,r+nac,-1);
add(nac*2,ac,r,1);add(nbd*2,bd,r+nac*2,1);
karatsura(nbd+1,ab,cd,r+nac);
free(ab);free(cd);free(ac);free(bd);
}
}
vector<tp> multiply(vector<tp> p0, vector<tp> p1){
    int n=max(p0.size(),p1.size());
    tp *p=ini(n),*q=ini(n),*r=ini(2*n);
    fore(i,0,p0.size())p[i]=p0[i];
    fore(i,0,p1.size())q[i]=p1[i];
    karatsura(n,p,q,r);
    vector<tp> rr(r,r+p0.size()+p1.size()-1);
    free(p);free(q);free(r);
    return rr;
}
```

2.5 ntt

```
// Multiply Poly with special Modules
// MAXN must be power of 2 !!
// MOD-1 needs to be a multiple of MAXN !!
// #define int long long
#define fore(i,a,b) for(ll i=a,ThxDem=b;i<ThxDem;++i)
// const ll MOD=998244353,RT=3,MAXN=1<<18;
const ll MOD=2305843009255636993ll,RT=5,MAXN=1<<18;
typedef vector<ll> poly;
ll mulmod(__int128 a, __int128 b){
    return ((a%MOD)*(b%MOD)) % MOD;
}
ll addmod(ll a, ll b){
    ll r=a+b;if(r>=MOD)r-=MOD;return r;
}
ll submod(ll a, ll b){ll r=a-b;if(r<0)r+=MOD;return r;
}
ll pm(ll a, ll e){
    ll r=1;
    while(e){
        if(e&1)r=mulmod(r,a);
        e>>=1;a=mulmod(a,a);
    }
    return r;
}
struct CD {
    ll x;
    CD(ll x):x(x){}
    CD(){}
    ll get()const{return x;}
};
CD operator*(const CD& a, const CD& b){
    return CD(mulmod(a.x,b.x));
}
CD operator+(const CD& a, const CD& b){
```

```
return CD(addmod(a.x,b.x));}
CD operator-(const CD& a, const CD& b){
    return CD(submod(a.x,b.x));}
vector<ll> rts(MAXN+9,-1);
CD root(ll n, bool inv){
    ll r=rts[n]<0?rts[n]=pm(RT,(MOD-1)/n):rts[n];
    return CD(inv?pm(r,MOD-2):r);
}
CD cp1[MAXN+9],cp2[MAXN+9];
ll R[MAXN+9];
void dft(CD* a, ll n, bool inv){
    fore(i,0,n)if(R[i]<i)swap(a[R[i]],a[i]);
    for(ll m=2;m<=n;m*=2){
        CD wi=root(m,inv); // NTT
        for(ll j=0;j<n;j+=m){
            CD w(1);
            for(ll k=j,k2=j+m/2;k2<j+m;k++,k2++){
                CD u=a[k];CD v=a[k2]*w;a[k]=u+v;
                a[k2]=u-v;w=w*wi;
            }
        }
    }
    if(inv){
        CD z(pm(n,MOD-2)); // pm: modular exponentiation
        fore(i,0,n)a[i]=a[i]*z;
    }
}
poly multiply(poly& p1, poly& p2){
    ll n=p1.size()+p2.size()+1;
    ll m=1,cnt=0;
    while(m<=n)m*=m,cnt++;
    fore(i,0,m){R[i]=0;
        fore(j,0,cnt) R[i]=(R[i]<<1)|((i>>j)&1);}
    fore(i,0,m)cp1[i]=0,cp2[i]=0;
    fore(i,0,p1.size())cp1[i]=p1[i];
    fore(i,0,p2.size())cp2[i]=p2[i];
    dft(cp1,m,false);dft(cp2,m,false);
    fore(i,0,m)cp1[i]=cp1[i]*cp2[i];
    dft(cp1,m,true);
    poly res;
    n-=2;
    fore(i,0,n)res.pb(cp1[i].x); // NTT
    return res;
}
```

3 1. Math - Mobius

3.1 linear sieve

```

/* For getting the primes less than mxN in O(mxN)*/
const int mxN = 1e6 + 10;
vl sv(mxN); // if prime sv[i]==i, it stores the lowest
prime of 'i'
vl primes;
void init() { // O(n)
    for (int i = 2; i < mxN; i++) {
        if (sv[i] == 0) {
            sv[i] = i;
            primes.pb(i);
        }
        for (int j = 0; j < primes.size() &&
primes[j]*i < mxN; j++) {
            sv[primes[j]*i] = primes[j];
            if (primes[j] == sv[i]) break;
        }
    }
}
// factorization using linear sieve, O(prime_count(n))
// Very fast factorization but only for (n < mxN) !!!
void fact(map<ll, int> &f, ll num) {
    while (num > 1) {
        ll p = sv[num];
        while (num % p == 0) num /= p, f[p]++;
    }
}

```

3.2 mobius

```

/*
Mobius Function.
Multiplicative function that is useful to inclusion/
exclusion with
prime numbers (it gives the coeficient). Also you can
reduce some
sumatories using its equality with unit(n) function
(see the key below)
unit(n) = [ n == 1 ]
unit(1) = 1, unit(2) = 0, unit(0) = 0
(This is the key!!!)
unit(n) = sum_{ d divides n } mobius(d)
mobius(1) = 1
mobius(quantity of primes is odd) = -1
mobius(quantity of primes is even) = 1
mobius(n is divisible by a square prime) = 0
Check https://codeforces.com/blog/entry/53925 for more
information.
Check mobius examples
*/
// This is shorter code and O(n log n)
const int mxN = 1e5 + 10;

```

```

vl mo(mxN);
void init() { // Call init() first !!!
    mo[1] = 1;
    for (int i = 1; i < mxN; i++)
        for (int j = i; j < mxN; j += i) mo[j] -= mo[i];
}
// This is O(n), but not too much difference of speed
with the other
const int mxN = 1e6 + 10;
vl sv(mxN); // prime if sv[i]==i, it stores the lowest
prime of i
vl primes; // Primes less than mxN
vl mo(mxN); // Mobius
void init() {
    // sv[1] = 1; // Check if needed
    for (int i = 2; i < mxN; i++) { // Linear Sieve
        if (sv[i] == 0) { sv[i] = i; primes.pb(i);
            for (int j = 0; j < primes.size() &&
primes[j]*i < mxN; j++) {
                sv[primes[j]*i] = primes[j];
                if (primes[j] == sv[i]) break;
            }
        }
        mo[1] = 1; // Mobius
        for (int i = 2; i < mxN; i++) {
            if (sv[i]/sv[i]] == sv[i]) mo[i] = 0;
            else mo[i] = -1*mo[i/sv[i]];
        }
    }
}

```

3.3 [gcd(a i, a j) == k] text{ queries}

```

// Given an array and q queries of count pairs
gcd(a_i, a_j) == k
// i < j, a_i < 1e5, q < 1e5, n < 1e5
// Complexity O(n * log n + q)
// Tested: https://www.hackerrank.com/contests/ab-yeh-
kar-ke-dikhao-returns/challenges/gcd-pairs
const int mxN = 1e5 + 10;
vl mo(mxN);
void init() { // Call init() first !!!
    mo[1] = 1;
    for (int i = 1; i < mxN; i++)
        for (int j = i; j < mxN; j += i) mo[j] -= mo[i];
}
vl cnt(mxN), dcnt(mxN), ans(mxN);
void test_case() {
    ll n, q; cin >> n >> q;
    for (int i = 0; i < n; i++) {
        ll x; cin >> x;
        cnt[x]++; // cnt[x] = quantity of X's in array
    }
}

```

```

}
for (int i = 1; i < mxN; i++)
    for (int j = i; j < mxN; j += i)
        dcnt[i] += cnt[j];
// dcnt[x] = quantity of a_i divisible by x
for (int k = 1; k < mxN; k++) {
    for (int d = 1; d <= mxN/k; d++) {
        ll totalCnt = d*k < mxN ? dcnt[d*k] : 0;
        ans[k] += mo[d] * totalCnt * totalCnt;
    }
    ans[k] += cnt[k]; // subtracting j>=i
    ans[k] /= 2;
}
while (q--) {
    ll k; cin >> k;
    if (k < mxN) cout << ans[k] << "\n";
    else cout << 0 << "\n";
}
}

```

3.4 [gcd(i, j) == k]

```

// Counts pairs gcd(i, j) == k
// 1 <= i <= a, 1 <= j <= b, where (1, 2) equals to
(2, 1)
// Call Mobius First !!!
// O(min(a, b)/K)
// Tested: https://vjudge.net/problem/HDU-1695
ll solve(ll a, ll b, ll k) {
    if (k == 0) return 0;
    a /= k;
    b /= k;
    if (a > b) swap(a, b);
    if (a == 0) return 0;
    ll ans = 0;
    for (ll d = 1; d <= a; d++) {
        ans += (a/d) * (b/d) * mo[d];
    }
    ll sub = 0; // Subtracting equals, e.g. (1, 2) to
(2, 1)
    for (ll d = 1; d <= a; d++) {
        sub += (a/d) * (a/d) * mo[d];
    }
    ans -= (sub - 1) / 2;
    return ans;
}

```

3.5 $\sum_{i=1}^n \frac{n}{\gcd(i, n)}$

```
// Multiplicative Function
// Calc f(n), f(n) = sum_{1 to n} n / gcd(n,i)
// f(p) = (p-1)*p + 1
// f(p^k) = f(p^(k-1)) + p^k*p^(k-1)*(p-1)
const int mxN = 1e7 + 10;
vl lp(mxN); // least prime factor
vl pw(mxN); // power of least prime factor
vl fn(mxN); // answer of f(n)
vl primes;
void init() { // O(n), Call init first !!!!
    fn[1] = pw[1] = lp[1] = 1;
    for (ll i = 2; i < mxN; i++) {
        if (lp[i] == 0) {
            lp[i] = pw[i] = i;
            fn[i] = (i-1)*i + 1;
            primes.pb(i);
        }
        for (auto p : primes) {
            ll j = i*p;
            if (j >= mxN) break;
            if (lp[j] != p) {
                lp[j] = pw[j] = p;
                fn[j] = fn[i] * fn[p];
            } else {
                lp[j] = p;
                pw[j] = pw[i] * p;
                ll fk = fn[pw[i]] + pw[j] * pw[i] *
                (p-1);

                fn[j] = fn[i/pw[i]] * fk;
                break;
            }
        }
    }
}
```

4 1. Math - Modular Arithmethics

4.1 big expontent modular exponentiation

```
// Calc a^b^c % MOD
// MOD is prime
ll pot(ll x, ll y, ll mod);
void test_case() {
    ll a, b, c;
    cin >> a >> b >> c;
    // fermat theorem
    // a^(p-1) = 1 (mod p)
```

```
b = pou(b, c, MOD - 1);
a = pou(a, b, MOD);
cout << a << "\n";
}
```

4.2 chinease remainder

```
/*
Finds this system congruence
X = a_1 (mod m_1)
X = a_2 (mod m_2)
...
X = a_k (mod m_k)
*/
ll x, y;
ll euclid(ll a, ll b) {
    if(b == 0) { x = 1; y = 0; return a; }
    ll d = euclid(b, a%b);
    ll aux = x;
    x = y;
    y = aux - a/b*y;
    return d;
}
pair<ll, ll> crt(vector<ll> A, vector<ll> M) {
    ll n = A.size(), ans = A[0], lcm = M[0];
    for (int i = 1; i < n; i++) {
        ll d = euclid(lcm, M[i]);
        if ((A[i] - ans) % d) return {-1, -1};
        ll mod = lcm / d * M[i];
        ans = (ans+x*(A[i] - ans)/d % (M[i]/d)*lcm) % mod;
        if (ans < 0) ans += mod;
        lcm = mod;
    }
    return {ans, lcm};
}
```

4.3 diophantine ecuations

Encuentra x, y en la ecuación de la forma $ax + by = c$
 Agregar Extended Euclides.

```
ll g;
bool diophantine(ll a, ll b, ll c) {
    x = y = 0;
    if (!a && !b) return (!c); // sólo hay solución si c=0
    g = euclid(abs(a), abs(b));
    if (c % g) return false;
    a /= g; b /= g; c /= g;
    if (a < 0) x *= -1;
    x = (x % b) * (c % b) % b;
    if (x < 0) x += b;
    y = (c - a*x) / b;
```

```
return true;
}
```

4.4 discrete log

Devuelve un entero x tal que $a^x = b \pmod m$ or -1 si no existe tal x.
 // Always check if change int to ll !!!

```
int expmod(int b, int e, int m) {
    int ans = 1;
    while (e) {
        if (e&1) ans = (1ll*ans*b) % m;
        b = (1ll*b*b) % m;
        e /= 2;
    }
    return ans;
}
ll discrete_log(ll a, ll b, ll m) {
    a %= m, b %= m;
    if (b == 1) return 0;
    int cnt = 0;
    ll tmp = 1;
    for (int g = __gcd(a, m); g != 1; g = __gcd(a, m)) {
        if (b%g) return -1;
        m /= g, b /= g;
        tmp = tmp*a / g % m;
        ++cnt;
        if (b == tmp) return cnt;
    }
    map<ll, int> w;
    int s = ceil(sqrt(m));
    ll base = b;
    for (int i = 0; i < s; i++) {
        w[base] = i;
        base = base*a % m;
    }
    base = expmod(a, s, m);
    ll key = tmp;
    for (int i = 1; i <= s+1; i++) {
        key = key*base % m;
        if (w.count(key)) return i*s - w[key] + cnt;
    }
    return -1;
}
```

5 2. Dp

5.1 convex hull trick

```
/**
* Author: Simon Lindholm
```

```

Description: Container where you can add lines of the
* form  $kx+m$ , and query maximum values at points  $x$ .
Useful for dynamic programming ('convex hull trick').
* Time:  $O(\log N)$ 
* Status: stress-tested
*/
// For minimum you can multiply by -1 'k' and 'm'
// when adding, and the answer when querying.
// Tested atcoder.jp/contests/dp/submissions/55836691
#pragma once
struct Line {
    mutable ll k, m, p;
    bool operator<(const Line& o) const {return k < o.k;}
    bool operator<(ll x) const { return p < x; }
};
struct LineContainer : multiset<Line, less<>> {
    // (for doubles, use inf = 1/.0, div(a,b) = a/b)
    static const ll inf = LLONG_MAX;
    ll div(ll a, ll b) { // floored division
        return a / b - ((a ^ b) < 0 && a % b); }
    bool isect(iterator x, iterator y) {
        if (y == end()) return x->p = inf, 0;
        if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
        else x->p = div(y->m - x->m, x->k - y->k);
        return x->p >= y->p;
    }
    void add(ll k, ll m) {
        auto z = insert({k, m, 0}), y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y))
            isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            isect(x, erase(y));
    }
    ll query(ll x) {
        assert(!empty());
        auto l = *lower_bound(x);
        return l.k * x + l.m;
    }
};

```

5.2 divide and conquer optimization

```

/*
Dividir un arreglo en k segmentos contiguos minimizando
(suma del segmento)^2
dp(i,j) = min 0<=k<=j such that dp(i-1,k-1) + cost(k,j)
Only works when cost(a,c)+cost(b,d) <=
cost(a,d)+cost(b,c)
dp(i,j) = 0 when j < 0
*/

```

```

const int mxn = 3005;
int nums[mxn], pf[mxn];
vector<ll> dp_cur, dp_before;
ll cost(ll i, ll j) {
    return (pf[j+1]-pf[i])*(pf[j+1]-pf[i]);
}
void solve(ll l, ll r, ll optl, ll optr) {
    if (r < l) return;
    ll mid = (l+r)>>1;
    pair<ll,int> best = {INT64_MAX, -1};
    for (int i = optl; i <= min(optr,mid); i++) {
        // check if dp_before[-1] should be 0
        ll nxt = (i ? dp_before[i-1] : 0) + cost(i,mid);
        best = min(best,{nxt,i});
    }
    dp_cur[mid] = best.first;
    ll p = best.second;
    solve(l,mid-1,optl,p);
    solve(mid+1,r,p,optr);
}
void test_case() {
    ll n, k; cin >> n >> k;
    dp_before.assign(n,0);
    dp_cur.assign(n,0);
    for (int i = 0; i < n; i++)
        cin >> nums[i], pf[i+1] = pf[i] + nums[i];
    for (int i = 0; i < n; i++) dp_before[i] = cost(0,i);
    for (int i = 2; i <= k; i++) {
        solve(0,n-1,0,n-1);
        dp_before = dp_cur;
    }
    cout << dp_before[n-1] << "\n";
} // https://cses.fi/problemset/task/2086/

```

5.3 dp mask over submasks

```

// DP of submask over submasks
// 0(3^n)
// j&(-j); get a '1' bit of j
// for (int j=i;j;j = (j-1)&i){...} j is submask of 'i'
the mask
ll dp[1<<18]; // answer of mask
ll cst[1<<18]; // cost of use a submask
ll a[18][18]; // elements
ll pos[1<<18]; // trick to get fast the pos
void test_case() {
    ll n;
    cin >> n;
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            cin >> a[i][j];

```

```

}
}
for (int i = 0; i < n; i++) {
    pos[1<<i] = i;
}
for (int i = 0; i < (1<<n); i++) {
    ll j = i;
    vl idxs;
    while (j) {
        ll k = j&(-j);
        idxs.pb(pos[k]);
        j ^= k;
    }
    for (int j = 0; j < idxs.size(); j++) {
        for (int k = j+1; k < idxs.size(); k++) {
            cst[i] += a[idxs[j]][idxs[k]];
        }
    }
    dp[i] = cst[i];
    for (int j=i;j;j = (j-1)&i) {
        dp[i] = max(dp[i],cst[j]+dp[i^j]);
    }
}
cout << dp[(1<<n)-1] << "\n";
}

```

5.4 knuths optimization

```

/*
Knuth's Optimization
For dp[i][j] = min_{i<=k<=j} dp[i][k] + dp[k+1][j] +
cost[i][j]
Optimizing that from  $O(n^3)$  to  $O(n^2)$ , it's required to
hold the following:
opt[i][j] = optimal splitting point of dp[i][j], the
'k' the minimizes the above definition
opt[i][j-1] <= opt[i][j] <= opt[i+1][j]
You can demonstrate that by the following:
a<=b<=c<=d
cost(b,c) <= cost(a,d), // an contained interval is <=
of the interval
cost(a,c)+cost(b,d) <= cost(a,d)+cost(b,c) // partial
intersection <= total intersection
Complexity:  $O(n^2)$ 
*/
void test_case() {
    cin >> n; nums.assign(n,0); pf.assign(n+1,0); // READ
input!!!
    for (int i = 0; i < n; i++) cin >> nums[i], pf[i+1] =
pf[i] + nums[i];
    for (int i = 0; i < n; i++) { // base case

```

```

        dp[i][i] = 0; // depends of the dp!!!
        opt[i][i] = i;
    }
    for (int i = n-2; i >= 0; i--) {
        for (int j = i+1; j < n; j++) {
            dp[i][j] = inf; // set to inf, any option
            //note about dp[i][j] is that I set inf instead of
            //cost(i,j) and it got accepted, not sure why
            ll cost = sum(i,j); // depends of problem
            for (int k = opt[i][j-1]; k <=
min(j-1, opt[i+1][j]); k++) {
                ll actual = dp[i][k] + dp[k+1][j] +
cost;
                if (actual < dp[i][j]) { // if flag
'-1' used, change here!!
                    dp[i][j] = actual;
                    opt[i][j] = k;
                }
            }
        }
    }
    cout << dp[0][n-1] << "\n";
}
// https://cses.fi/problemset/task/2088
// https://www.spoj.com/problems/BRKSTRNG/

```

5.5 linear recurrence cayley halmiton

```

// O(N^2 log K)
const int mod = 1e9 + 7;
template <int32_t MOD>
struct modint {
    int32_t value;
    modint() = default;
    modint(int32_t value_) : value(value_) {}
    inline modint<MOD> operator + (modint<MOD> other)
const { int32_t c = this->value + other.value; return
modint<MOD>(c >= MOD ? c - MOD : c); }
    inline modint<MOD> operator * (modint<MOD> other)
const { int32_t c = (int64_t)this->value * other.value
% MOD; return modint<MOD>(c < 0 ? c + MOD : c); }
    inline modint<MOD> & operator += (modint<MOD> other)
{ this->value += other.value; if (this->value >= MOD)
this->value -= MOD; return *this; }
    modint<MOD> pow(uint64_t k) const {
        modint<MOD> x = *this, y = 1;
        for (; k >= 1) {
            if (k & 1) y *= x;
            x *= x;
        }
    }
}

```

```

        return y;
    }
    modint<MOD> inv() const { return pow(MOD - 2); } //
MOD must be a prime
};
using mint = modint<mod>;
vector<mint> combine (int n, vector<mint> &a,
vector<mint> &b, vector<mint> &tr) {
    vector<mint> res(n * 2 + 1, 0);
    for (int i = 0; i < n + 1; i++) {
        for (int j = 0; j < n + 1; j++) res[i + j] += a[i]
* b[j];
    }
    for (int i = 2 * n; i > n; --i) {
        for (int j = 0; j < n; j++) res[i - 1 - j] +=
res[i] * tr[j];
    }
    res.resize(n + 1);
    return res;
};
// transition -> for(i = 0; i < x; i++) f[n] += tr[i] *
f[n-i-1]
// S contains initial values, k is 0 indexed
mint LinearRecurrence(vector<mint> &S, vector<mint>
&tr, long long k) {
    int n = S.size(); assert(n == (int)tr.size());
    if (n == 0) return 0;
    if (k < n) return S[k];
    vector<mint> pol(n + 1, e(pol));
    pol[0] = e[1] = 1;
    for (++k; k; k /= 2) {
        if (k % 2) pol = combine(n, pol, e, tr);
        e = combine(n, e, e, tr);
    }
    mint res = 0;
    for (int i = 0; i < n; i++) res += pol[i + 1] * S[i];
    return res;
}
void test_case() {
    ll n;
    cin >> n; // Fibonacci
    vector<mint> initial = {0, 1}; // F0, F1
    vector<mint> tr = {1, 1};
    cout << LinearRecurrence(initial, tr, n).value <<
"\n";
}

```

5.6 linear recurrence matrix exponciation

```

// Solves F_n = C_{n-1} * F_{n-1} + ... + C_0 * F_0 + p + q * n
+ r * n^2
// O((n+3)^3 * log(k))
// Also solves (k steps)-min path of a matrix in same
complexity
// Tested and for more details see: https://codeforces.
com/blog/entry/80195
const int MOD = 1e9 + 7;
const int N = 10 + 3; // 10 is MAX N, 3 is for p,q,r
inline ll add(ll x, ll y) { return (x+y)%MOD; }
inline ll mul(ll x, ll y) { return (x*y)%MOD; }
// const ll inf = ll(1e18) + 5; // for k-min path
struct Mat {
    array<array<ll, N>, N> mt;
    Mat(bool id=false) {
        for (auto &x : mt) fill(all(x), 0);
        if (id) for (int i=0; i<N; i++) mt[i][i]=1;
        //for (auto &x : mt) fill(all(x), inf); // For k-min
path
        //if (id) for (int i=0; i<N; i++) mt[i][i]=0;
    }
    inline Mat operator * (const Mat &b) {
        Mat ans;
        for (int k=0; k<N; k++) for (int i=0; i<N; i+
+) for (int j=0; j<N; j++)
            ans.mt[i][j] = add(ans.mt[i][j], mul(mt[i]
[k], b.mt[k][j]));
        //ans.mt[i][j] = min(ans.mt[i][j], mt[i]
[k]+b.mt[k][j]); // For K-min Path
        return ans;
    }
    inline Mat pow(ll k) {
        Mat ans(true), p=*this; // Note '!!!
        while (k) {
            if (k&1) ans = ans*p;
            p=p*p;
            k>>=1;
        }
        return ans;
    }
    string db() { // Optional for debugging
        string ans;
        for (int i=0; i<mt.size(); i++) for (int
j=0; j<mt.size(); j++)
            ans += to_string(mt[i][j]), ans += "\n"
[j==N-1];
        return "\n"+ans;
    }
};
// Important!!! Remember to set N = MAX_N + 3
// Solves F_n = C_{n-1} * F_{n-1} + ... + C_0 * F_0 + p + q * n

```

```
+ r*n^2
// f = {f_0,f_1,f_2,f_3,...,f_n}
// c = {c_0,c_1,c_2,c_3,...,c_n}
ll fun(vl f, vl c, ll p, ll q, ll r, ll k) {
    ll n = c.size();
    if (k < n) return f[k];
    reverse(all(c)), reverse(all(f));
    Mat mt, st;
    for (int i = 0; i < n; i++) mt.mt[0][i] = c[i];
    for (int i = 1; i < n; i++) mt.mt[i][i-1] = 1;
    for (int i = 0; i < n; i++) st.mt[i][0] = f[i];
    vl extra = {p, q, r}; // To extend here with
    1*p, i*q, i*i*r, etc
    for (int i = 0; i < extra.size(); i++) {
        st.mt[n+i][0] = 1; // 1, i, i*i, i*i*i
        mt.mt[0][n+i] = extra[i]; // p, q, r
        mt.mt[n+i][n] = 1; // pascal
        for (int j = 1; j <= i; j++) { // pascal
            st.mt[n+i][0] *= n; // 1, i, i*i, i*i*i
            mt.mt[n+i][n+j] = mt.mt[n+i-1][
                n+j] + mt.mt[n+i-1][n+j-1];
        }
    }
    return (mt.pow(k-(n-1))*st).mt[0][0];
}
```

5.7 longest increasing subsequence

```
// Find the Longest Increasing Subsequence of an array
in O(n log n)
int lis(vl &nums) {
    vl best;
    int n = nums.size();
    for (int i = 0; i < n; i++) {
        // For non-decreasing
        // int idx = upper_bound(all(best), nums[i]) - best.begin();
        // For increasing
        int idx =
            lower_bound(all(best), nums[i]) - best.begin();
        if (idx == best.size()) best.pb(nums[i]);
        else best[idx] = min(best[idx], nums[i]);
    }
    return best.size();
}
```

5.8 multiple knacksack optimizacion

```
/*
Multiple Knacksack
Time complexity is O(W*N*sum)
W = capacity, N = number of objects,
sum is: for (int i = 0, sum = 0; i < n; i++) sum +=
```

```
log2(copies[i])
Tested in https://cses.fi/problemset/task/1159/
n <= 100, capacity <= 10^5, copies[i] <= 1000
*/
ll multipleKnacksack(vl &value, vl &weight,
                    vl &copies, ll capacity) {
    vl vs, ws;
    ll n = value.size();
    for (int i = 0; i < n; i++) {
        ll h = value[i], s = weight[i], k = copies[i];
        ll p = 1;
        while (k > p) {
            k -= p; // Binary Grouping Optimization
            vs.pb(s*p); ws.pb(h*p); p *= 2;
        }
        if (k) {
            vs.pb(s*k); ws.pb(h*k);
        }
    }
    vl dp(capacity+1);
    // 0-1 knacksack
    for (int i = 0; i < ws.size(); i++) {
        for (int j = capacity; j >= ws[i]; j--) {
            dp[j] = max(dp[j], dp[j-ws[i]] + vs[i]);
        }
    }
    return dp[capacity];
}
```

5.9 optimizing pragmas for bitset

```
#pragma GCC optimize("O3,unroll-loops")
#pragma GCC target("avx2,bmi,bmi2,lzcnt,popcnt")
// without popcnt is TLE in cses /task/2137/
```

5.10 separation optimization

No se si tiene un nombre, pero en varios problemas vi este truco:
 $dp[x] = f(x, y)$ donde se necesita un optimo 'y'.
 Truco: si puedes separarlo en $f(x, y)$ en $f(x)$ (+) $f(y)$, puedes guardar en una estructura optima $f(y)$ como un segment tree.

5.11 sos dp reverse

```
// Useful to calculate reverse sos DP.
// DP[x] = op(DP[y_1], DP[y_2], ...), where x is
// submask of y_i
vector<ll> nums(n);
for (int i = 0; i < n; i++) {
    nums[i] = rd(); // read submask, and set init
```

```
state
    dp[nums[i]] = min(dp[nums[i]], {0, i});
}
for (int mask = (1<<m)-1; mask >= 0; mask--) { //
    You can switch fors depends of the problem
    if (dp[mask].first > 0) continue; // Don't
    propagate
    for (int i = 0; i < m; i++) {
        if ((mask >> i) & 1) { // Propagate to all
            submasks
                auto nxt = dp[mask]; nxt.first--;
                dp[mask^(1<<i)] =
                    min(dp[mask^(1<<i)], nxt);
        }
    }
}
```

5.12 sos dp

```
// F(mask) = op(F(x_1), F(x_2), ...) where x is submask
// of mask
// init sos[z]
for (int i = 0; i < M; i++) {
    for (int mask = 0; mask < (1 << M); mask++) {
        if (mask & (1 << i)) {
            sos[mask] += sos[mask ^ (1 << i)];
        }
    }
}
```

6 3. Data Structures

6.1 custom hash

```
// Avoid hashing hacks and improve performance of hash
// structures
// e.g. unordered_map<ll, ll, custom_hash>
// use a fixed ll FIXED_RANDOM =
// chrono::steady_clock::now().time_since_epoch().count();
struct custom_hash {
    size_t operator()(uint64_t x) const {
        x ^= FIXED_RANDOM;
        return x ^ (x >> 16);
    }
};
// pair
struct chash {
    size_t operator()(const pair<ll, ll> &x) const {
        return ...;
    }
};
```

6.2 dynamic connectivity

```

struct union_find {
    struct uf_save { ll a, rnka, b, rnkb; };
    vector<uf_save> saves;
    vector<ll> p, rnk;
    ll n, comps;
    union_find(ll _n) : n(_n), p(_n), rnk(_n) {
        for (int i = 0; i < n; i++) p[i] = i;
        comps = n;
    };
    ll find(ll x) { return p[x] == x ? x : find(p[x]); }
    int merge(ll a, ll b) {
        a = find(a);
        b = find(b);
        if (a == b) return 0;
        if (rnk[b] > rnk[a]) swap(a, b);
        comps--;
        saves.pb({a, rnk[a], b, rnk[b]});
        p[b] = a;
        if (rnk[a] == rnk[b]) rnk[a]++;
        return 1;
    };
    void rollback() {
        if (saves.empty()) return;
        uf_save lst = saves.back();
        saves.pop_back();
        comps++;
        p[lst.a] = lst.a, rnk[lst.a] = lst.rnka;
        p[lst.b] = lst.b, rnk[lst.b] = lst.rnkb;
    }
};

struct query { ll a, b; };
struct segtree {
    int n; // size of queries!!!
    vector<vector<query>> t; // node si a vector<query>
    segtree(int queries_n) : n(queries_n), t(2*n) {}
    void addQuery(int l, int r, const query &q) {
        l += n, r += n+1;
        for (; l < r; l >>= 1, r >>= 1) {
            if (l&1) t[l++].pb(q);
            if (r&1) t[--r].pb(q);
        }
    }
};

void dfs(int id, vector<ll> &ans, union_find &uf) {
    ll cnt = 0;
    for (auto &q : t[id]) cnt += uf.merge(q.a, q.b);
    if (id < n)
        dfs(id*2, ans, uf), dfs(id*2+1, ans, uf);
    else ans[id-n] = uf.comps;
    for (int i = 0; i < cnt; i++) uf.rollback();
}
    
```

```

}
vector<ll> solve(union_find &uf) {
    vector<ll> ans(n);
    dfs(1, ans, uf);
    return ans;
}

};

void test_case() {
    ll n, m, q; cin >> n >> m >> q;
    segtree tree(q+1);
    vector<map<int,int>> lst(n); // to manage living
    time!
    auto addEdge = [&](int x, int y, int time) {
        if (y < x) swap(x, y);
        lst[x][y] = time;
    };
    auto erEdge = [&](int x, int y, int time) {
        if (y < x) swap(x, y);
        tree.addQuery(lst[x][y], time-1, {x, y});
        lst[x].erase(y);
    };
    for (int i = 0; i < m; i++) {
        ll x, y; cin >> x >> y; x--, y--;
        addEdge(x, y, 0);
    }
    for (int time = 1; time <= q; time++) {
        ll t, x, y; cin >> t >> x >> y;
        x--, y--;
        if (t == 1) addEdge(x, y, time);
        else erEdge(x, y, time);
    }
    for (int i = 0; i < n; i++)
        for (auto &[j, v] : lst[i]) // be carefull with
            it and erasing
                tree.addQuery(v, q, {i, j});
    union_find uf(n);
    auto ans = tree.solve(uf);
    for (int i = 0; i < ans.size(); i++) {
        cout << ans[i] << " \n" [i+1 == ans.size()];
    }
} // https://cses.fi/problemset/task/2133/
    
```

6.3 fast hash map

```

#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
const int RANDOM =
chrono::high_resolution_clock::now().time_since_epoch().count();
struct chash {
    long long operator()(const ll &x) const {
        return x ^ RANDOM;
    }
}
    
```

```

};
};
// There is no mp.count(x), so use mp.find(x) !=
mp.end()
gp_hash_table<ll, ll, chash> mp;
    
```

6.4 fenwick tree 2d

```

struct BIT2D { // 1-indexed
    vector<v> bit;
    ll n, m;
    BIT2D(ll n, ll m) : bit(n+1, v(m+1)), n(n), m(m) {}
    ll lsb(ll i) { return i & -i; }
    void add(int row, int col, ll x) {
        for (int i = row; i <= n; i += lsb(i))
            for (int j = col; j <= m; j += lsb(j))
                bit[i][j] += x;
    }
    ll sum(int row, int col) {
        ll res = 0;
        for (int i = row; i > 0; i -= lsb(i))
            for (int j = col; j > 0; j -= lsb(j))
                res += bit[i][j];
        return res;
    }
    ll sum(int x1, int y1, int x2, int y2) {
        return sum(x2, y2) - sum(x1-1, y2)
            - sum(x2, y1-1) + sum(x1-1, y1-1);
    }
    void set(int x, int y, ll val) {
        add(x, y, val - sum(x, y, x, y));
    }
};
    
```

6.5 fenwick tree

```

struct FenwickTree {
    vector<int> bit;
    int n;
    FenwickTree(int n) {
        this->n = n;
        bit.assign(n, 0);
    }
    FenwickTree(vector<int> a) : FenwickTree(a.size()) {}

    for (size_t i = 0; i < a.size(); i++)
        add(i, a[i]);

    int sum(int r) {
        int ret = 0;
        for (; r >= 0; r = (r & (r + 1)) - 1)
            ret += bit[r];
    }
}
    
```

```

    return ret;
}
int sum(int l, int r) {
    return sum(r) - sum(l - 1);
}
void add(int idx, int delta) {
    for (; idx < n; idx = idx | (idx + 1))
        bit[idx] += delta;
}
// TODO: Lower Bound
};

```

6.6 lazy segment tree

```

/*
Lazy Iterative Seg Tree.
This example is for cses 1735
*/
struct Node { ll x; };
const ll SET = 1;
const ll ADD = 2;
struct Func { ll type, val; }; // applied Function
Node e() { return { 0 }; }; // op(x, e()) = x
Func id() { return {ADD, 0}; } // mapping(x, id()) = x
Node op(Node &a, Node &b) { // associative property
    return {a.x + b.x};
}
Node mapping(Node node, ll sz, const Func &lazy) {
    if (lazy.type == SET) node.x = lazy.val * sz;
    else node.x += lazy.val * sz;
    return node;
}
Func comp(Func prev, const Func &actual) {
    if (actual.type == SET) return actual;
    if (prev.type == SET)
        return {SET, prev.val + actual.val};
    return {ADD, prev.val + actual.val};
}
struct lazyseg {
    ll n, h;
    vector<Node> t;
    vector<Func> lz;
    vector<int> sz; // if sz of node needed
    lazyseg(ll n) : n(n), t(2*n, e()), lz(n, id()), sz(2*n, 1) {
        h = 32 - __builtin_clz(n);
        for (int i = n-1; i > 0; i--) sz[i] = sz[i*2] + sz[i*2+1];
    }
    void all_apply(ll x, const Func & f) {
        t[x] = mapping(t[x], sz[x], f);
        if (x < n) lz[x] = comp(lz[x], f);
    }
}

```

```

void push(ll x) {
    all_apply(x*2, lz[x]);
    all_apply(x*2+1, lz[x]);
    lz[x] = id();
}
void build(ll x) {
    t[x] = op(t[x*2], t[x*2+1]);
}
bool ok(ll x, ll i) {
    return ((x >> i) << i) != x;
}
void update(ll p, Node v) {
    p += n;
    for (int i = h; i > 0; i--) push(p >> i);
    t[p] = v;
    for (int i = 1; i <= h; i++) build(p >> i);
}
Node query(ll l, ll r) {
    if (l > r) return e();
    l += n, r += n+1;
    for (int i = h; i > 0; i--) {
        if (ok(l, i)) push(l >> i);
        if (ok(r, i)) push((r-1) >> i);
    }
    Node ansL = e(), ansR = e();
    for (; l < r; l >= l, r >= r+1) {
        if (l & 1) ansL = op(ansL, t[l++]);
        if (r & 1) ansR = op(t[--r], ansR);
    }
    return op(ansL, ansR);
}
void apply(ll l, ll r, const Func &f) {
    if (l > r) return;
    l += n, r += n+1;
    for (int i = h; i > 0; i--) {
        if (ok(l, i)) push(l >> i);
        if (ok(r, i)) push((r-1) >> i);
    }
    {
        int l2 = l, r2 = r;
        for (; l < r; l >= l, r >= r+1) {
            if (l & 1) all_apply(l++, f);
            if (r & 1) all_apply(--r, f);
        }
        l = l2, r = r2;
    }
    for (int i = 1; i <= h; i++) {
        if (ok(l, i)) build(l >> i);
        if (ok(r, i)) build((r-1) >> i);
    }
}
};

```

```

// Maximum r that satisfy g(op(t[l], t[l+1], ...,
t[r-1])) = True
// if there's no g() that returns true, then r = l
template <class G> int max_right(int l, G g) {
    assert(0 <= l && l <= n);
    assert(g(e()));
    if (l == n) return n;
    l += n;
    for (int i = h; i >= 1; i--) push(l >> i);
    Node sm = e();
    do {
        while (l % 2 == 0) l >>= 1;
        if (!g(op(sm, t[l]))) {
            while (l < n) {
                push(l);
                l = (2 * l);
                if (g(op(sm, t[l]))) {
                    sm = op(sm, t[l]);
                    l++;
                }
            }
            return l - n;
        }
        sm = op(sm, t[l]);
        l++;
    } while ((l & -l) != l);
    return n;
}
// If g is monotone, this is the minimum l that
satisfies
// g(op(a[l], a[l+1], ..., a[r-1])) = true.
template <class G> int min_left(int r, G g) {
    assert(0 <= r && r <= n);
    assert(g(e()));
    if (r == 0) return 0;
    ll size = n;
    r += size;
    for (int i = h; i >= 1; i--) push((r-1) >> i);
    Node sm = e();
    do {
        r--;
        while (r > 1 && (r % 2)) r >>= 1;
        if (!g(op(t[r], sm))) {
            while (r < size) {
                push(r);
                r = (2 * r + 1);
                if (g(op(t[r], sm))) {
                    sm = op(t[r], sm);
                    r--;
                }
            }
        }
    }
}

```

```

        return r + 1 - size;
    }
    sm = op(t[r], sm);
} while ((r & -r) != r);
return 0;
}
};

```

6.7 min sparse table

```

using Type = int;
// Gets the minimum in a range [l,r] in O(1)
// Preprocessing is O(n log n)
struct min_sparse {
    int log;
    vector<vector<Type>> sparse;
    void init(vector<Type> &nums) {
        int n = nums.size();
        log = 0;
        while (n) log++, n/=2;
        n = nums.size();
        sparse.assign(n, vector<Type>(log, 0));
        for (int i = 0; i < n; i++) sparse[i][0] = nums[i];
        for (int l = 1; l < log; l++) {
            for (int j = 0; j + (1 << l) - 1 < n; j++) {
                sparse[j][l] = min(sparse[j][l-1],
                                   sparse[j+(1 << (l-1))][l-1]);
            }
        }
    }
    Type query(int x, int y) {
        int n = y - x + 1;
        int logg = -1;
        while (n) logg++, n/=2; // TODO: improve this
        with fast builtin
        return min(sparse[x][logg], sparse[y-(1 <<
        logg)+1][logg]);
    }
};

```

6.8 mo's

```

/*
Mo's algorithm O((N + Queries)*SQRT(N))
It answers queries offline using SQRT Descomposition,
sometimes get TLE when you have Set, Map, various
iteration when adding, So you need to implement
efficiently (with arrays) in O(1). You can answer
questions like in a range, the number of distincts
values.
*/
// For se 1e5=310, for 2e5=430

```

```

const int BLOCK_SIZE = 430;
struct query {
    int l, r, idx;
    bool operator <(query &other) const {
        return MP(l / BLOCK_SIZE, r) <
               MP(other.l / BLOCK_SIZE, other.r);
    }
};
void add(int idx);
void remove(int idx);
ll getAnswer();
vector<ll> mo(vector<query> queries) {
    vector<ll> answers(queries.size());
    int l = 0;
    int r = -1;
    sort(all(queries));
    each(q, queries) {
        while (q.l < l) add(--l);
        while (r < q.r) add(++r);
        while (l < q.l) remove(l--);
        while (q.r < r) remove(r--);
        answers[q.idx] = getAnswer();
    }
    return answers;
}
v1 nums; //init
ll ans = 0;
int cnt[1000001];
void add(int idx) {
    // update ans, when adding an element
}
void remove(int idx) {
    // update ans, when removing an element
}
ll getAnswer() { return ans; }

```

6.9 multiorderedset

```

#include <bits/stdc++.h>
#include <ext/pb_ds/tree_policy.hpp>
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
struct multiordered_set {
    tree<ll,
        null_type,
        less_equal<ll>, // this is the trick
        rb_tree_tag,
        tree_order_statistics_node_update> oset;
    //this function inserts one more occurrence of (x)
    into the set.
    void insert(ll x) {

```

```

        oset.insert(x);
    }
    //this function checks weather the value (x) exists
    in the set or not.
    bool exists(ll x) {
        auto it = oset.upper_bound(x);
        if (it == oset.end()) {
            return false;
        }
        return *it == x;
    }
    //this function erases one occurrence of the value
    (x).
    void erase(ll x) {
        if (exists(x)) {
            oset.erase(oset.upper_bound(x));
        }
    }
    //this function returns the value at the index
    (idx)..(0 indexing).
    ll find_by_order(ll pos) {
        return *(oset.find_by_order(pos));
    }
    //this function returns the first index of the
    value (x)..(0 indexing).
    int first_index(ll x) {
        if (!exists(x)) {
            return -1;
        }
        return (oset.order_of_key(x));
    }
    //this function returns the last index of the value
    (x)..(0 indexing).
    int last_index(ll x) {
        if (!exists(x)) {
            return -1;
        }
        if (find_by_order(size() - 1) == x) {
            return size() - 1;
        }
        return first_index(*oset.lower_bound(x)) - 1;
    }
    //this function returns the number of occurrences
    of the value (x).
    int count(ll x) {
        if (!exists(x)) {
            return -1;
        }
        return last_index(x) - first_index(x) + 1;
    }
    // Count the numbers between [l, r]

```

```

int count(ll l, ll r) {
    auto left = oset.upper_bound(l);
    if (left == oset.end() || *left > r) {
        return 0;
    }
    auto right = oset.upper_bound(r);
    if (right != oset.end()) {
        right =
    }
    oset.find_by_order(oset.order_of_key(*right));
    }
    if (right == oset.end() || *right > r) {
        if (right == oset.begin()) return 0;
        right--;
    }
    return last_index(*right) - first_index(*left) + 1;
}
//this function clears all the elements from the
set.
void clear() {
    oset.clear();
}
//this function returns the size of the set.
ll size() {
    return (ll)oset.size();
}
};
    
```

6.10 orderedset

```

// Same as set, but you can get the order of an element
or the
// element in given sorted position in O(log n)
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
#define oset tree<ll, null_type, less<ll>,
rb_tree_tag, tree_order_statistics_node_update>
//find_by_order(k) order_of_key(k)
    
```

6.11 persistence segtree

```

const int mxn = 2e5;
struct Node { int l=0, r=0; ll sum=0; }; //Elem Neutro
int T = 0; // st[0] siempre neutro
Node st[mxn*30]; //!!! Check
struct PST {
    inline int nn(ll s) {
        ++T, st[T] = {0, 0, s};
        return T;
    }
    inline int nn(int l, int r) {
        ++T, st[T] = {l, r, 0};
    }
}
    
```

```

if (l) st[T].sum += st[l].sum;
if (r) st[T].sum += st[r].sum;
return T;
}
int build(int tl, int tr, vector<ll> &a) {
    if (tl==tr) return nn(a[tr]);
    int m = (tl+tr)>>1;
    return nn(build(tl, m, a), build(m+1, tr, a));
}
ll qry(int v, int tl, int tr, int l, int r) {
    if (!v || r < tl || tr < l) return 0;
    if (l <= tl && tr <= r) return st[v].sum;
    int tm = (tl+tr)>>1;
    return qry(st[v].l, tl, tm, l, r)
        + qry(st[v].r, tm+1, tr, l, r);
}
int upd(int v, int tl, int tr, int pos, ll val) {
    if (tl==tr) return nn(val);
    int tm = (tl+tr)>>1;
    if (pos <= tm)
        return nn(upd(st[v].l, tl, tm, pos, val), st[v].r);
    return nn(st[v].l, upd(st[v].r, tm+1, tr, pos, val));
}
int build(vector<ll> &a) {
    return build(0, (int)a.size()-1, a);
}
ll query(int v, int n, int l, int r) {
    return qry(v, 0, n-1, l, r);
}
int upd(int v, int n, int pos, int val) {
    return upd(v, 0, n-1, pos, val);
}
int copy(int v) { return v; }
};
    
```

6.12 persistent segment tree

```

struct Vertex {
    Vertex *l, *r;
    ll sum;
    Vertex(int val) : l(nullptr), r(nullptr), sum(val)
}
Vertex(Vertex *l, Vertex *r) : l(l), r(r), sum(0) {
    if (l) sum += l->sum;
    if (r) sum += r->sum;
}
};
Vertex* build(vector<ll> &a, int tl, int tr) {
    if (tl == tr)
        return new Vertex(a[tl]);
    int tm = (tl + tr) / 2;
    }
    
```

```

return new Vertex(build(a, tl, tm), build(a, tm+1,
tr));
}
ll get_sum(Vertex* v, int tl, int tr, int l, int r) {
    if (l > r)
        return 0;
    if (l == tl && tr == r)
        return v->sum;
    int tm = (tl + tr) / 2;
    return get_sum(v->l, tl, tm, l, min(r, tm))
        + get_sum(v->r, tm+1, tr, max(l, tm+1), r);
}
Vertex* update(Vertex* v, int tl, int tr, int pos, int
new_val) {
    if (tl == tr)
        return new Vertex(new_val);
    int tm = (tl + tr) / 2;
    if (pos <= tm)
        return new Vertex(update(v->l, tl, tm, pos,
new_val), v->r);
    else
        return new Vertex(v->l, update(v->r, tm+1, tr,
pos, new_val));
}
Vertex* build(vector<ll> &a) {
    return build(a, 0, a.size()-1);
}
ll get_sum(Vertex *v, ll n, int l, int r) {
    return get_sum(v, 0, n-1, l, r);
}
Vertex* update(Vertex* v, ll n, int pos, int newV) {
    return update(v, 0, n-1, pos, newV);
}
Vertex* copy(Vertex* v) {
    return new Vertex(v->l, v->r);
}
}
    
```

6.13 rope

```

/**
 * Description: insert element at $i$-th position, cut
a substring and
 * re-insert somewhere else. At least 2 times slower
than handwritten treap.
 * Time: O(\log N) per operation? not well tested
 * Source: https://codeforces.com/blog/entry/10355
 * Verification: CEOI 2018 Day 2 Triangles
 * https://szkopul.edu.pl/problemset/problem/AzKAZ2RDtVTjwSBoIwoC5zl/site/?key=statement
 * vector is faster for this problem ...
 */
    
```

```
#include <ext/rope>
using namespace __gnu_cxx;
void ropeExample() {
    rope<int> v(5,0); // initialize with 5 zeroes
    FOR(i,sz(v)) v.mutable_reference_at(i) = i+1;
    FOR(i,5) v.pb(i+1); // constant time pb
    rope<int> cur = v.substr(1,2);
    v.erase(1,3); // erase 3 elements starting from 1st
    element
    for (rope<int>::iterator it = v.mutable_begin();
        it != v.mutable_end(); ++it) pr((int)*it, ' ');
    ps(); // 1 5 1 2 3 4 5
    v.insert(v.mutable_begin()+2,cur); // or just 2
    v += cur; FOR(i,sz(v)) pr(v[i], ' ');
    ps(); // 1 5 2 3 1 2 3 4 5 2 3
}
/*
Tested in cses https://cses.fi/problemset/task/1749/
https://cses.fi/problemset/result/10105636/ 2 times
slower than ordered set
It's better to create rope with an given size and value
TLE with 2*10^5
Need revision!!
push_back() - O(log N).
pop_back() - O(log N)
insert(int x, rope r1): O(log N) and Worst O(N)
substr(int x, int l): O(log N)
replace(int x, int l, rope r1): O(log N).
*/
```

6.14 segment tree 2d

```
// Tested: https://www.spoj.com/problems/MATSUM/
struct Node { ll x = 0; };
Node e() { return Node(); } // Identity element,
op(x,e()) = x
// Binary Operation, Associative. (a+b)+c = a+(b+c)
Node op(const Node &a, const Node &b) {
    Node c;
    c.x = a.x + b.x;
    return c;
}
struct segtree2d {
    int n, m;
    vector<vector<Node>> t;
    void init(int n, int m) {
        this->n = n;
        this->m = m;
        t.assign(n*2, vector<Node>(m*2, e()));
    }
    void init(int n, int m, vector<vector<Node>> &nums) {
```

```
init(n, m);
for (int i = 0; i < n; i++) { // build leaf segtrees
    for (int j = 0; j < m; j++) t[i+n][j+m] = nums[i][j];
    for (int j = m-1; j > 0; j--)
        t[i+n][j] = op(t[i+n][j*2], t[i+n][j*2+1]);
}
// build non leaf segtrees
for (int i = n-1; i > 0; i--) {
    for (int j = 0; j < 2*m; j++)
        t[i][j] = op(t[i*2][j], t[i*2+1][j]);
}
}
Node query_y(int x, int l, int r) {
    l += m, r += m+1;
    Node resl = e(), resr = e();
    for (; l < r; l >>= 1, r >>= 1) {
        if (l&1) resl = op(resl, query_y(l++, y1, y2));
        if (r&1) resr = op(query_y(--r, y1, y2), resr);
    }
    return op(resl, resr);
}
Node query(int x1, int y1, int x2, int y2) {
    ll l = x1+n, r = x2+n+1;
    Node resl = e(), resr = e();
    for (; l < r; l >>= 1, r >>= 1) {
        if (l&1) resl = op(resl, query_y(l++, y1, y2));
        if (r&1) resr = op(query_y(--r, y1, y2), resr);
    }
    return op(resl, resr);
}
void update(int x, int y, const Node &v) {
    x += n, y += m;
    t[x][y] = v; // fix leaf segtrees
    for (int j = y; j >>= 1; ) {
        t[x][j] = op(t[x][j*2], t[x][j*2+1]);
    }
    for (; x >>= 1; ) { // fix non leaf segtree
        t[x][y] = op(t[x*2][y], t[x*2+1][y]);
        for (int j = y; j >>= 1; ) {
            t[x][j] = op(t[x*2][j], t[x*2+1][j]);
        }
    }
}
Node get(int x, int y) { return t[x+n][y+m]; }
};
```

6.15 segment tree

```
const int inf = 1e9;
// >>>>>>>> Implement
struct Node { ll mn = inf, mx = -inf; };
```

```
Node e() { return Node(); } // op(a, e()) = a
Node op(const Node &a, const Node &b) { // asoc property
    Node c;
    c.mn = min(a.mn, b.mn); c.mx = max(a.mx, b.mx);
    return c;
}
// <<<<<<<
struct segtree {
    vector<Node> t;
    ll n;
    void init(int n) {
        t.assign(n * 2, e());
        this->n = n;
    }
    void init(vector<Node> &s) {
        n = s.size();
        t.assign(n * 2, e());
        for (int i = 0; i < n; i++) t[i+n] = s[i];
        build();
    }
    void build() { // build the tree
        for (int i = n - 1; i > 0; --i)
            t[i] = op(t[i*2], t[i*2+1]);
    }
    // set value at position p
    void update(int p, const Node &value) {
        for (t[p += n] = value; p >>= 1; )
            t[p] = op(t[p*2], t[p*2+1]);
    }
    // sum on interval [l, r]
    Node query(int l, int r) {
        r++; // make this inclusive
        Node resl = e(), resr = e(); // null element
        for (l += n, r += n; l < r; l >>= 1, r >>= 1) {
            if (l&1) resl = op(resl, t[l++]);
            if (r&1) resr = op(t[--r], resr);
        }
        return op(resl, resr);
    }
    Node get(int i) {
        return t[i+n];
    }
    // Maximum r that satisfy g(op(t[l], t[l+1], ...,
    t[r-1])) = True
    // if there's no g() that returns true, then r = l
    template <class F> int max_right(int l, F f) const
    {
        assert(0 <= l && l <= n);
        assert(f(e()));
        if (l == n) return n;
        ll size = n;
```

```

l += size;
Node sm = e();
do {
    while (l % 2 == 0) l >>= 1;
    if (!f(op(sm, t[l]))) {
        while (l < size) {
            l = (2 * l);
            if (f(op(sm, t[l]))) {
                sm = op(sm, t[l]);
                l++;
            }
        }
        return l - size;
    }
    sm = op(sm, t[l]);
    l++;
} while ((l & -l) != l);
return n;
}

// If g is monotone, this is the minimum l that
satisfies
// g(op(a[l], a[l + 1], ..., a[r - 1])) = true.
template <class F> int min_left(int r, F f) const {
    assert(0 <= r && r <= n);
    assert(f(e()));
    if (r == 0) return 0;
    ll size = n;
    r += size;
    Node sm = e();
    do {
        r--;
        while (r > 1 && (r % 2)) r >>= 1;
        if (!f(op(t[r], sm))) {
            while (r < size) {
                r = (2 * r + 1);
                if (f(op(t[r], sm))) {
                    sm = op(t[r], sm);
                    r--;
                }
            }
            return r + 1 - size;
        }
    }
    sm = op(t[r], sm);
} while ((r & -r) != r);
return 0;
}
};

```

6.16 sqrt mod

```

/*
Trick using Sqrt for problems using de different floor
values o a num.
A num has only around Sqrt(n) possible values when
it is floor divided, for 2e5 is around 890
e.g. floor(n/i)=j. j has around sqrt(n) values.
e.g. floor(10/i)=j. j only can be 1,2,3,5,10 for any i
The following function calculates when a n/i changes
if you iterate over i increasing.
You can solve CF GYM 105009/L using this.
*/
const int MXN = 2e5 + 10;
int nums[MXN];
vector<int> ch[MXN];
for (int i = 0; i < n; i++) {
    for (int d = 1; d <= nums[i]; d = nums[i] / (nums[i] / d) + 1) {
        ch[d].pb(i);
    }
    ch[nums[i] + 1].pb(i);
}

```

7 4. Graphs

7.1 bellmanford find negative cycle

```

// This uses Bellmanford algorithm to find a negative
cycle
// 0(n*m) m=edges, n=nodes
void test_case() {
    ll n, m;
    cin >> n >> m;
    vector<ll> dist(n+1);
    vector<ll> p(n+1);
    vector<tuple<ll, ll, ll>> edges(m);
    for (int i = 0; i < m; i++) {
        ll x, y, z;
        cin >> x >> y >> z;
        edges[i] = {x, y, z};
    }
    ll efe = -1;
    for (int i = 0; i < n; i++) {
        efe = -1;
        for (auto pp : edges) {
            ll x, y, z;
            tie(x, y, z) = pp;
            if (dist[x] + z < dist[y]) {
                dist[y] = dist[x] + z;
                p[y] = x;
                efe = y;
            }
        }
    }
}

```

```

}
}
if (efe == -1) {
    cout << "NO\n";
} else {
    cout << "YES\n";
    ll x = efe;
    for (int i = 0; i < n; i++) {
        x = p[x];
    }
    vector<ll> cycle;
    ll y = x;
    while (cycle.size() == 0 || y != x) {
        cycle.pb(y);
        y = p[y];
    }
    cycle.pb(x);
    reverse(all(cycle));
    for (int i = 0; i < cycle.size(); i++) {
        cout << cycle[i] << " \n" [i == cycle.size() - 1];
    }
}
}
}

```

7.2 strongly connected components

```

/*
Tarjan t(graph); provides you the SCC of that graph
passing the adjacency list of the graph (as vector<vl>)
This is 0-indexed, (but you can have node 0 as dummy-node)
Use t.comp[x] to get the component of node x
SCC is the total number of components
adjComp()
gives you the adjacency list of strongly components
*/
struct Tarjan {
    vl low, pre, comp;
    ll cnt, SCC, n;
    vvl g;
    const int inf = 1e9;
    Tarjan(vvl &adj) {
        n = adj.size();
        g = adj;
        low = vl(n);
        pre = vl(n, -1);
        cnt = SCC = 0;
        comp = vl(n, -1);
        for (int i = 0; i < n; i++)
            if (pre[i] == -1) tarjan(i);
    }
    stack<int> st;
}

```

```

void tarjan(int u) {
    low[u] = pre[u] = cnt++;
    st.push(u);
    for (auto &v : g[u]) {
        if (pre[v] == -1) tarjan(v);
        low[u] = min(low[u], low[v]);
    }
    if (low[u] == pre[u]) {
        while (true) {
            int v = st.top(); st.pop();
            low[v] = inf;
            comp[v] = SCC;
            if (u == v) break;
        }
        SCC++;
    }
}

vvl adjComp() {
    vvl adj(SCC);
    for (int i = 0; i < n; i++) {
        for (auto j : g[i]) {
            if (comp[i] == comp[j]) continue;
            adj[comp[i]].pb(comp[j]);
        }
    }
    for (int i = 0; i < SCC; i++) {
        sort(all(adj[i]));
        adj[i].erase(
            unique(all(adj[i])),
            adj[i].end());
    }
    return adj;
}

};
/* Another way is with with Kosaraju:
1. Find topological order of G
2. Run dfs in topological order in reverse Graph
to find o connected component
*/

```

7.3 two sat

```

/*
2-Sat (Boolean satisfiability problem with 2-clause
literals)
Complexity: O(n)
Tested: https://cses.fi/problemset/task/1684
To find a solution that makes this true with N boolean
vars as form:
(x or y) and (~x or y) and (z or ~x) and d and (x ==>
y)

```

```

Call s.satisfiable() to see if solution, and sat2.value
to see
values of variables
*/
struct sat2 {
    int n;
    vector<vector<vector<int>>> g;
    vector<int> tag;
    vector<bool> seen, value;
    stack<int> st;
    sat2(int n) : n(n), g(2, vector<vector<int>>(2*n)),
        tag(2*n), seen(2*n), value(2*n) {}

    int neg(int x) { return 2*n-x-1; }
    void add_or(int u, int v) { implication(neg(u), v); }
    void make_true(int u) { add_edge(neg(u), u); }
    void make_false(int u) { make_true(neg(u)); }
    void eq(int u, int v) {
        implication(u, v);
        implication(v, u);
    }
    void diff(int u, int v) { eq(u, neg(v)); }
    void implication(int u, int v) {
        add_edge(u, v);
        add_edge(neg(v), neg(u));
    }
    void add_edge(int u, int v) {
        g[0][u].push_back(v);
        g[1][v].push_back(u);
    }
    void dfs(int id, int u, int t = 0) {
        seen[u] = true;
        for(auto& v : g[id][u])
            if(!seen[v])
                dfs(id, v, t);
        if(id == 0) st.push(u);
        else tag[u] = t;
    }
    void kosaraju() {
        for(int u = 0; u < n; u++) {
            if(!seen[u]) dfs(0, u);
            if(!seen[neg(u)]) dfs(0, neg(u));
        }
        fill(seen.begin(), seen.end(), false);
        int t = 0;
        while(!st.empty()) {
            int u = st.top(); st.pop();
            if(!seen[u]) dfs(1, u, t++);
        }
    }
    bool satisfiable() {
        kosaraju();

```

```

        for(int i = 0; i < n; i++) {
            if(tag[i] == tag[neg(i)]) return false;
            value[i] = tag[i] > tag[neg(i)];
        }
        return true;
    }
};

```

8 5. Flow

8.1 blossom

Halla el máximo match en un grafo general $O(E * v^2)$

```

struct network {
    struct struct_edge {
        int v; struct_edge * n;
    };
    typedef struct_edge* edge;
    int n;
    struct_edge pool[MAXE]; // 2*n*n;
    edge top;
    vector<edge> adj;
    queue<int> q;
    vector<int> f, base, inq, inb, inp, match;
    vector<vector<int>> ed;
    network(int n) : n(n), match(n, -1), adj(n),
        top(pool), f(n), base(n),
        inq(n), inb(n), inp(n), ed(n, vector<int>(n))
    {}

    void add_edge(int u, int v) {
        if (ed[u][v]) return;
        ed[u][v] = 1;
        top->v = v, top->n = adj[u], adj[u] = top++;
        top->v = u, top->n = adj[v], adj[v] = top++;
    }

    int get_lca(int root, int u, int v) {
        fill(inp.begin(), inp.end(), 0);
        while (1) {
            inp[u = base[u]] = 1;
            if (u == root) break;
            u = f[match[u]];
        }
        while (1) {
            if (inp[v = base[v]]) return v;
            else v = f[match[v]];
        }
    }

    void mark(int lca, int u) {
        while (base[u] != lca) {
            int v = match[u];

```

```
int doit(int u) {
    if (u == -1) return 0;
    int v = f[u];
    doit(match[v]);
    match[v] = u; match[u] = v;
    return u != -1;
}

// (i < net.match[i]) => means match
int maximum_matching() {
    int ans = 0;
    for (int u = 0; u < n; u++)
        ans += (match[u] == -1) && doit(bfs(u));
    return ans;
}

};
```

```

/*
HopcroftKarp hk(n, m);
hk.add(x, y), solo un sentido.
hk.mm()
*/
struct HopcroftKarp { // [0,n)->[0,m) (ids independent
in each side)
    int n, m;
    vector<vector<int>> g;
    vector<int> mt, mt2, ds;
    HopcroftKarp(int nn, int mm) : n(nn), m(mm), g(n) {}
    void add(int a, int b) { g[a].pb(b); }
    bool bfs() {
        queue<int> q;
        ds = vector<int>(n, -1);
        for (int i=0; i<n; i++)
            if (mt2[i] < 0) ds[i] = 0, q.push(i);
        bool r = false;
        while (!q.empty()) {
            int x = q.front();
            q.pop();
            for (int y : g[x]) {
                if (mt[y] >= 0 && ds[mt[y]] < 0) {
                    ds[mt[y]] = ds[x] + 1, q.push(mt[y]);
                } else if (mt[y] < 0) r = true;
            }
        }
        return r;
    }
    bool dfs(int x) {
        for (int y : g[x]) {
            if (mt[y] < 0 || ds[mt[y]] == ds[x] + 1 &&
dfs(mt[y])) {

```

```
// Halla el camino match en un grafo bipartito con
// pesos (min cost)  $O(V^3)$ 
typedef ll T;
const T inf = 1e18;
struct hung {
    int n, m;
    vector<T> u, v; vector<int> p, way;
    vector<vector<T>> g;
    hung(int n, int m):
        n(n), m(m), g(n+1, vector<T>(m+1, inf-1)),
        u(n+1), v(m+1), p(m+1), way(m+1) {}
    void set(int u, int v, T w) { g[u+1][v+1] = w; }
    T assign() {
        for (int i = 1; i <= n; ++i) {
            int j0 = 0; p[0] = i;
            vector<T> minv(m+1, inf);
            vector<char> used(m+1, false);
            do {
                used[j0] = true;
                int i0 = p[j0], j1; T delta = inf;
                for (int j = 1; j <= m; ++j) if (!
                    used[j]) {
                        T cur = g[i0][j] - u[i0] - v[j];
                        if (cur < minv[j]) minv[j] = cur,
                            j1 = j;
                    }
                if (minv[j1] < delta) delta =
                    minv[j1];
                for (int j = 0; j <= m; ++j)
                    if (used[j]) u[p[j]] += delta, v[j]
                        -= delta;
            } while (j1 > 0);
        }
    }
};
```

```

        else minv[j] -= delta;
        j0 = j1;
    } while (p[j0]);
    do {
        int j1 = way[j0]; p[j0] = p[j1]; j0 =
j1;
    } while (j0);
    }
    return -v[0];
}
};

```

8.4 max flow

```

// #define int long long // take care int overflow with this
// #define vi vector<long long>
struct Dinitz{
    const int INF = 1e9 + 7;
    Dinitz(){}
    Dinitz(int n, int s, int t) {init(n, s, t);}
    void init(int n, int s, int t)
    {
        S = s, T = t;
        nodes = n;
        G.clear(), G.resize(n);
        Q.resize(n);
    }
    struct flowEdge
    {
        int to, rev, f, cap;
    };
    vector<vector<flowEdge>> G;
    // Añade arista (st -> en) con su capacidad
    void addEdge(int st, int en, int cap) {
        flowEdge A = {en, (int)G[en].size(), 0, cap};
        flowEdge B = {st, (int)G[st].size(), 0, 0};
        G[st].pb(A);
        G[en].pb(B);
    }
    int nodes, S, T; // asignar estos valores al armar
    el grafo G
    // nodes = nodos en red de flujo.
    Hacer G.clear(); G.resize(nodes);
    vi work, lvl;
    vi Q;
    bool bfs() {
        int qt = 0;
        Q[qt++] = S;
        lvl.assign(nodes, -1);
        lvl[S] = 0;
    }
}

```

```

    for (int qh = 0; qh < qt; qh++) {
        int v = Q[qh];
        for (flowEdge &e : G[v]) {
            int u = e.to;
            if (e.cap <= e.f || lvl[u] != -1)
                continue;
            lvl[u] = lvl[v] + 1;
            Q[qt++] = u;
        }
    }
    return lvl[T] != -1;
}
int dfs(int v, int f) {
    if (v == T || f == 0) return f;
    for (int &i = work[v]; i < G[v].size(); i++) {
        flowEdge &e = G[v][i];
        int u = e.to;
        if (e.cap <= e.f || lvl[u] != lvl[v] + 1)
            continue;
        int df = dfs(u, min(f, e.cap - e.f));
        if (df) {
            e.f += df;
            G[u][e.rev].f -= df;
            return df;
        }
    }
    return 0;
}
int maxFlow() {
    int flow = 0;
    while (bfs()) {
        work.assign(nodes, 0);
        while (true) {
            int df = dfs(S, INF);
            if (df == 0) break;
            flow += df;
        }
    }
    return flow;
}
}
void test_case() {
    ll n, m, s, t;
    cin >> n >> m >> s >> t;
    Dinitz flow;
    flow.init(n, s, t);
    for (int i = 0; i < m; i++) {
        ll a, b, c;
        cin >> a >> b >> c;
        flow.addEdge(a, b, c);
    }
}

```

```

ll f = flow.maxFlow(); // max flow
vector<tuple<ll, ll, ll>> edges; // edges used with
flow
for (int i = 0; i < n; i++) {
    for (auto edge : flow.G[i]) {
        if (edge.f > 0) {
            edges.pb({i, edge.to, edge.f});
        }
    }
}
}
}

```

8.5 min cost max flow

```

// 0(min(E^2*V^2, E*V*FLOW))
// Min Cost Max Flow Dinitz
struct CheapDinitz{
    const int INF = 1e9 + 7;
    CheapDinitz() {}
    CheapDinitz(int n, int s, int t) {init(n, s, t);}
    int nodes, S, T;
    vi dist;
    vi pot, curFlow, prevNode, prevEdge, Q, inQue;
    struct flowEdge{
        int to, rev, flow, cap, cost;
    };
    vector<vector<flowEdge>> G;
    void init(int n, int s, int t)
    {
        nodes = n, S = s, T = t;
        curFlow.assign(n, 0), prevNode.assign(n, 0),
        prevEdge.assign(n, 0);
        Q.assign(n, 0), inQue.assign(n, 0);
        G.clear();
        G.resize(n);
    }
    void addEdge(int s, int t, int cap, int cost)
    {
        flowEdge a = {t, (int)G[t].size(), 0, cap,
        cost};
        flowEdge b = {s, (int)G[s].size(), 0, 0, -
        cost};
        G[s].pb(a);
        G[t].pb(b);
    }
    void bellmanFord()
    {
        pot.assign(nodes, INF);
        pot[S] = 0;
        int qt = 0;
        Q[qt++] = S;
    }
}

```

```

for (int qh = 0; (qh - qt) % nodes != 0; qh++)
{
    int u = Q[qh % nodes];
    inQue[u] = 0;
    for (int i = 0; i < (int)G[u].size(); i++)
    {
        flowEdge &e = G[u][i];
        if (e.cap <= e.flow) continue;
        int v = e.to;
        int newDist = pot[u] + e.cost;
        if (pot[v] > newDist)
        {
            pot[v] = newDist;
            if (!inQue[v])
            {
                Q[qt++ % nodes] = v;
                inQue[v] = 1;
            }
        }
    }
}
}
ii MinCostFlow()
{
    bellmanFord();
    int flow = 0;
    int flowCost = 0;
    while (true) // always a good start for an
algorithm :v
    {
        set<ii> s;
        s.insert({0, S});
        dist.assign(nodes, INF);
        dist[S] = 0;
        curFlow[S] = INF;
        while (s.size() > 0)
        {
            int u = s.begin() -> s;
            int actDist = s.begin() -> f;
            s.erase(s.begin());
            if (actDist > dist[u]) continue;
            for (int i = 0; i < (int)G[u].size();
i++)
            {
                flowEdge &e = G[u][i];
                int v = e.to;
                if (e.cap <= e.flow) continue;
                int newDist = actDist + e.cost +
pot[u] - pot[v];
                if (newDist < dist[v])
                {

```

```

dist[v] = newDist;
s.insert({newDist, v});
prevNode[v] = u;
prevEdge[v] = i;
curFlow[v] = min(curFlow[u],
e.cap - e.flow);
        }
    }
}
if (dist[T] == INF)
    break;
for (int i = 0; i < nodes; i++)
    pot[i] += dist[i];
int df = curFlow[T];
flow += df;
for (int v = T; v != S; v = prevNode[v])
{
    flowEdge &e = G[prevNode[v]]
[prevEdge[v]];
    e.flow += df;
    G[v][e.rev].flow -= df;
    flowCost += df * e.cost;
}
}
return {flow, flowCost};
};

```

8.6 min cut

```

/*
Minimum Cut, need revision for general cases!!!
Tested in https://cses.fi/problemset/task/1695/
with undirected graph with capacity 1
1. Run Max Flow Algorithm
2. Get reachable vertices from source in the residual
graph!
   using BFS or DFS, call this reachable vertices = S
3. Iterate S, iterate edges of S in normal graph that
not belongs to S,
   thats the mincut edges of the answer.
*/
void test_case() {
    ll n, m; cin >> n >> m;
    vvl g(n);
    Dinitz f(n,0,n-1); // add Dinitz for maxFlow!!
    for (int i =0;i<m;i++) {
        ll x, y;cin >> x >> y;x--,y--;
        g[x].pb(y); g[y].pb(x); //this example the
graph is bidirectional
        f.addEdge(x,y,1); f.addEdge(y,x,1);

```

```

}
f.maxFlow(); // step 1
vvl residual(n); // Step 2
for (int i =0;i<n;i++) for (auto j:f.G[i])
    if ((j.f<0 && j.cap==0) || (j.f==0 && j.cap >
0))
        residual[i].pb(j.to); // residual graph
set<ll> vis;
function<void(int)> dfs = [&](int x) {
    vis.insert(x); // dfs on residual from source
    for (auto y : residual[x]) if (!vis.count(y))
dfs(y);
};
dfs(0);
vector<pair<ll,ll>> ans; // step 3
for (auto x : vis)
    for (auto y : g[x])
        if (!vis.count(y))
            ans.pb({x,y});
cout << ans.size() << "\n";
for (auto e : ans) {
    cout << e.F + 1 << " " << e.S + 1 << "\n";
}
}

```

9 6. Tree

9.1 block tree

```

/*
SQRT on Trees.
For having queries and updates online to subtrees or
sub forests.
See: https://codeforces.com/blog/entry/46843
Solution to: https://codeforces.com/gym/100589/problem/
A
Properties:
- Each node will have atmost SQRT children nodes in
Block Tree
- There will be atmost SQRT Blocks
- There will be atmost SQRT nodes belongs to a block
- Not completely sure, but for merging answers of
childs it should be fast
*/
struct Block { // Block storing info depending of
problem!!!
    // O(n) memory here is possible, but better O(sqrt
n) to BlockTree creation be O(n)
    vector<int> depthCnt;
    ll sum = 0;

```

```

void update(int lvl, ll v) { // !!! depends of
problem
    assert(lvl < depthCnt.size());
    if (lvl >= depthCnt.size()) return;
    sum += v * depthCnt[lvl];
}
ll query() { return sum; }
};

struct BlockTree {
    const int SQRT = 320; // sqrt of max N
    ll n;
    vector<Block> blocks;
    vector<vector<int>> child; // if node < n, then
normal node, otherwise block node
    vector<int> depth;
    vector<int> leader; // for the sqrt group of nodes
the first ancestor that is not in the group
    vector<int> blockId;
    // ===== depends of the problem!!!
    vector<ll> sum;
    // =====
    BlockTree(ll n, vector<vector<ll>> &adj) : n(n),
child(2*n+5), depth(2*n+5),
leader(2*n+5), blockId(2*n+5) {
    sum = vector<ll>(n);
    build(adj); // adjacency should be x -> y, and
y -> x
    }
    bool is_block(ll x) { return x >= n; }
    void build(vector<vector<ll>> &adj, ll root = 0) {
        auto dfs = [&](ll x, ll p, auto &&dfs) -> void
        {
            for (auto y : adj[x]) if (y != p) {
                depth[y] = depth[x]+1;
                dfs(y, x, dfs);
            }
        };
        dfs(root, -1, dfs); // !!! Don't forget
        ll idNewBlock = n;
        auto createBlock = [&](int parent, const
vector<ll> &nodes) {
            ll id = idNewBlock++;
            if (parent != -1) {
                child[parent].push_back(id);
                depth[id] = depth[parent]+1;
            }
            Block block; // Modify the creation of your
block here!!!
            leader[id] = parent;
            blockId[id] = id;

```

```

        block.depthCnt = vector<int>(n);
        auto dfsOverBlock = [&](ll x, auto
&&dfsOverBlock) -> void {
            leader[x] = parent;
            blockId[x] = id;
            block.depthCnt[depth[x]]++;
            for (auto y : child[x]) {
                if (!is_block(y)) dfsOverBlock(y,
dfsOverBlock);
                else child[id].push_back(y); //
depending of the problem, you can add
// relationship between block node
-> node or block node -> block node, like this
            }
        };
        for (auto & x : nodes) dfsOverBlock(x,
dfsOverBlock);
        blocks.push_back(block);
    };
    vector<vector<ll>> byDepth(n); // counting sort
    for (int i = 0; i < n; i++) byDepth[n-1-
depth[i]].pb(i);
    vector<ll> sz(n);
    for (auto & nodes : byDepth) {
        for (int x : nodes) {
            ll blockSz = 0;
            vector<ll> curBlock;
            sz[x] = 1;
            for (int y : adj[x]) if (depth[x] <
depth[y]) {
                sz[x] += sz[y];
                blockSz += sz[y];
                curBlock.pb(y);
                if (blockSz > SQRT) {
                    createBlock(x, curBlock);
                    sz[x] -= blockSz;
                    blockSz = 0;
                    curBlock.clear();
                }
            }
            child[x].insert(child[x].end(),
curBlock.begin(), curBlock.end());
        }
    }
    createBlock(-1, { root });
}

void update(int lvl, ll v) {
    sum[lvl] += v;
    for (auto & block : blocks) {
        block.update(lvl, v);
    }
}

```

```

    }
    ll query(ll x) { // dfs over node blocks and non
node blocks
        ll ans = is_block(x) ? blocks[x-n].query() :
sum[depth[x]];
        for (auto & y : child[x])
            ans += query(y);
        return ans;
    }
};

```

9.2 centroid descomposition

```

vector<vector<ll>> adj;
vector<bool> alive;
vector<int> sz;
void init(int n) {
    alive = vector<bool>(n+1, true);
    sz = vector<int>(n+1);
    adj = vector<vector<ll>>(n+1);
    // belongs =
vector<vector<pair<ll, ll>>>(n+1); // !! for online
}
int get_sz(int x, int p) {
    sz[x] = 1;
    for (auto y : adj[x]) if (y != p && alive[y])
        sz[x] += get_sz(y, x);
    return sz[x];
}
int find_centroid(int x, int p, int tree_sz) {
    for (auto y : adj[x]) if (y != p && alive[y]) {
        if (sz[y] * 2 > tree_sz) {
            return find_centroid(y, x, tree_sz);
        }
    }
    return x;
}
//!!! Implement O(sz) solution, use adj, only use alive
nodes check with alive[x]
// dont sz[x] because it is not rerooted to centroid
void process_centroid(int root, int sz);
void centroid_decomp(ll x) {
    int sz = get_sz(x, -1);
    int centroid = find_centroid(x, -1, sz);
    process_centroid(centroid, sz); // implement!!!
    alive[centroid] = false;
    for (auto y : adj[centroid]) if (alive[y]) {
        centroid_decomp(y);
    }
}
}

```

9.3 heavy light

```
vector<vector<int>> adj; // INIT this, use init()!!!
vector<int> parent, depth, heavy, head, pos;
int cur_pos;
int dfs(int v) {
    int size = 1, max_size = 0;
    for (int c : adj[v]) if (c != parent[v]) {
        parent[c] = v, depth[c] = depth[v] + 1;
        int c_size = dfs(c);
        size += c_size;
        if (c_size > max_size)
            max_size = c_size, heavy[v] = c;
    }
    return size;
}
void decompose(int v, int h) {
    head[v] = h, pos[v] = cur_pos++;
    if (heavy[v] != -1) // check when copy head and heavy
        decompose(heavy[v], h);
    for (int c : adj[v]) {
        if (c != parent[v] && c != heavy[v])
            decompose(c, c);
    }
}
segtree tree; // !!ADD SegTree
vector<ll> values;
void init() {
    int n = adj.size();
    parent = depth = head = pos = vector<int>(n);
    heavy = vector<int>(n, -1);
    cur_pos = 0;
    dfs(0);
    decompose(0, 0);
    tree.init(n);
    for (int i = 0; i < n; i++) tree.update(pos[i], values[i]);
}
int seg_query(int a, int b) {
    return tree.query(a, b).x; // !! depends of segtree
}
void update_query(int node, int val) {
    tree.update(pos[node], { val }); // depends of segtree
}
int query(int a, int b) {
    int res = 0;
    for (; head[a] != head[b]; b = parent[head[b]]) {
        if (depth[head[a]] > depth[head[b]])
            swap(a, b);
    }
}
```

```
int cur_heavy_path_max =
seg_query(pos[head[b]], pos[b]);
res = max(res, cur_heavy_path_max);
}
if (depth[a] > depth[b])
    swap(a, b);
int last_heavy_path_max = seg_query(pos[a], pos[b]); // consider pos[a]+1 when query edges
res = max(res, last_heavy_path_max); // Change to Segment Tree Operation
return res;
}
```

9.4 isomorfismo

Permite hashear árboles para comparar su estructura rápidamente.

Agregar Random Integer para ll

```
map<ll, ll> table;
ll get(ll x) {
    if (table.count(x)) return table[x];
    return table[x] = rand(0, 1e18);
}
ll hashes[N], sum[N];
void dfs(int u, int p) {
    sum[u] = 0;
    for (auto &v : g[u]) {
        if (v == p) continue;
        dfs(v, u);
        sum[u] += hashes[v];
    }
    hashes[u] = get(sum[u]);
}
```

9.5 online centroid

```
// !!! Add centroid Descomposition
// When you can get Answers for fixed root
// When you can get answer for all paths for fixed root
struct centroid_data {
    ll idx = 0, best_red = -1;
    void mark_red(int x, ll d) {
        if (best_red == -1) best_red = d;
        best_red = min(best_red, d);
    }
    int query(int x, ll d) {
        if (best_red == -1) return inf;
        return best_red + d;
    }
};
vector<vector<pair<ll, ll>>> belongs; // idx centroid, extra data, init this!!
```

```
vector<centroid_data> centroids;
int id_centroid = 0;
void process_centroid(int root, int sz) { // creates centroids
    centroids.push_back({id_centroid++, -1});
    auto &c = centroids.back();
    auto dfs = [&](int x, int p, ll dist, auto &&dfs) -> void {
        belongs[x].pb({c.idx, dist});
        for (auto &y : adj[x]) if (y != p && alive[y])
            dfs(y, x, dist+1, dfs);
    };
    dfs(root, -1, 0, dfs);
}
void mark_red(int x) { // UPDATE O(log n) centroids belongs to node
    for (auto [idx, dist] : belongs[x])
        centroids[idx].mark_red(x, dist);
}
int query(int x) { // iterates over each centroid belongs to node O(logn)
    int best = 1e9;
    for (auto [idx, dist] : belongs[x])
        best = min(best, centroids[idx].query(x, dist));
    return best;
}
```

10 7. Strings

10.1 ahocorasick

```
struct node {
    int next[alpha], end;
    // link -> back-edge, exit -> super link,
    // cnt -> saber para conteo de posibles
    // a lo mucho es: n*sqrt(n)
    int link = 0, exit = 0, cnt; // para aho corasick
    int& operator [] (int i) { return next[i]; }
};
vector<node> trie = {node()};
void add_str(string &s, int id = 1) {
    int u = 0;
    for (auto ch : s) {
        int c = ch-L;
        if (!trie[u][c]) {
            trie[u][c] = trie.size();
            trie.pb(node());
        }
        u = trie[u][c];
    }
}
```

```

    }
    trie[u].end = id; // con id > 0
    // trie[u].cnt++; // para aho corasick
}
void build_ac() {
    queue<int> q; q.push(0);
    while (q.size()) {
        int u = q.front(); q.pop();
        for (int c = 0; c < alpha; ++c) {
            int v = trie[u][c];
            if (!v) trie[u][c] = trie[trie[u].link][c];
            else q.push(v);
            if (!u || !v) continue;
            trie[v].link = trie[trie[u].link][c];
            trie[v].exit = trie[trie[v].link].exit;
            trie[v].link : trie[trie[v].link].exit;
            trie[v].cnt += trie[trie[v].link].cnt;
        }
    }
}
vector<int> cnt;
void run_ac(string &s) {
    int u = 0, sz = s.size();
    for (int i = 0; i < sz; ++i) {
        int c = s[i]-L;
        while (u && !trie[u][c]) u = trie[u].link;
        u = trie[u][c];
        int x = u;
        while (x) {
            int id = trie[x].end;
            if (id) cnt[id-1]++;
            x = trie[x].exit;
        }
    }
}

```

10.2 fast hashing

```

const int N = 1e6 + 9; // Max size
int power(long long n, long long k, const int mod) {
    int ans = 1 % mod;
    n %= mod;
    if (n < 0) n += mod;
    while (k) {
        if (k & 1) ans = (long long) ans * n % mod;
        n = (long long) n * n % mod;
        k >>= 1;
    }
    return ans;
}
const int MOD1 = 127657753, MOD2 = 987654319;

```

```

const int p1 = 137, p2 = 277;
int ip1, ip2;
pair<int, int> pw[N], ipw[N];
void init() { // Call init() first!!!
    pw[0] = {1, 1};
    for (int i = 1; i < N; i++) {
        pw[i].first = 1LL * pw[i-1].first * p1 % MOD1;
        pw[i].second = 1LL * pw[i-1].second * p2 % MOD2;
    }
    ip1 = power(p1, MOD1 - 2, MOD1);
    ip2 = power(p2, MOD2 - 2, MOD2);
    ipw[0] = {1, 1};
    for (int i = 1; i < N; i++) {
        ipw[i].first = 1LL * ipw[i-1].first * ip1 % MOD1;
        ipw[i].second = 1LL * ipw[i-1].second * ip2 % MOD2;
    }
}
struct Hashing {
    int n; string s; // 0 - indexed
    vector<pair<int, int>> hs; // 1 - indexed
    Hashing() {}
    Hashing(string _s) {
        n = _s.size(); s = _s;
        hs.emplace_back(0, 0);
        for (int i = 0; i < n; i++) {
            pair<int, int> p;
            p.first = (hs[i].first + 1LL * pw[i].first * s[i]
% MOD1) % MOD1;
            p.second = (hs[i].second + 1LL * pw[i].second *
s[i] % MOD2) % MOD2;
            hs.push_back(p);
        }
    }
    pair<int, int> get_hash(int l, int r) { // 1-indexed
        assert(1 <= l && l <= r && r <= n);
        pair<int, int> ans;
        ans.first = (hs[r].first - hs[l-1].first + MOD1)
* 1LL * ipw[l-1].first % MOD1;
        ans.second = (hs[r].second - hs[l-1].second +
MOD2) * 1LL * ipw[l-1].second % MOD2;
        return ans;
    }
    pair<int, int> get(int l, int r) { // 0-indexed
        return get_hash(l+1, r+1);
    }
    pair<int, int> get_hash() {
        return get_hash(1, n);
    }
};

```

10.3 function z

```

vector<int> funz(string &s) {
    int n = s.size(), l = 0, r = 0; vi v(n);
    for (int i = 1; i < n; i++) {
        if (i < r) v[i] = min(r-i, v[i-l]);
        while (i+v[i] < n && s[v[i]] == s[i+v[i]]) v[i]++;
        if (i+v[i] > r) l = i, r = i+v[i];
    }
    return v;
}

```

10.4 kmp automaton

```

// Very useful for some DP's with strings
// aut[i][j], you are in 'i' position, and choose
// character 'j', the next position.
const int MAXN = 1e5 + 5, alpha = 26;
const char L = 'A';
int aut[MAXN][alpha]; // aut[i][j] = a donde vuelvo si
// estoy en i y pongo una j
void build(string &s) {
    int lps = 0;
    aut[0][s[0]-L] = 1;
    int n = s.size();
    for (int i = 1; i < n+1; i++) {
        for (int j = 0; j < alpha; j++) aut[i][j] =
aut[lps][j];
        if (i < n) {
            aut[i][s[i]-L] = i + 1;
            lps = aut[lps][s[i]-L];
        }
    }
}

```

10.5 kmp

```

vector<int> prefix_function(vector<ll> &s) {
    int n = s.size();
    vector<int> pf(n);
    pf[0] = 0;
    for (int i = 1; i < n; i++) {
        while (j && s[i] != s[j]) j = pf[j-1];
        if (s[i] == s[j]) j++;
        pf[i] = j;
    }
    return pf;
}

```

10.6 manacher

```
Devuelve un vector p donde, para cada i, p[i] es igual
al largo del palindromo mas largo con centro en i.
string parse(string &s) {
    string t = "";
    for (auto &c : s) t.pb('#'), t.pb(c);
    t += "$";
    return t;
}
vector<int> manacher(string &s) {
    string t = parse(s);
    int n = t.size(), c = 0, r = 0;
    vector<int> p(n, 0);
    for (int i = 1; i < n-1; i++) {
        int j = c - (i-c);
        if (r > i) p[i] = min(r-i, p[j]);
        while (t[i+1+p[i]] == t[i-1-p[i]]) p[i]++;
        if (i+p[i] > r) {
            c = i; r = i+p[i];
        }
    }
    return p;
    // si p[i] > 0 entonces, s[l, r) es palíndromo
    // donde l = (i-1-p[i])/2 y r = l+p[i];
}
```

10.7 micky hashing

```
ll pot(ll x, ll y, ll m) {
    if (y==0) return 1;
    ll ans = pot(x,y/2,m);
    ans = (ans*ans)%m;
    if (y&1) ans = (ans*x)%m;
    return ans;
}
struct Hash {
    int p = 997, m[2], in[2];
    vl h[2], inv[2];
    Hash(string s) {
        m[0] = 998244353, m[1]=1e9+9;
        for (int i = 0; i<2; i++) {
            in[i] = pot(p,m[i]-2,m[i]);
            h[i].resize(s.size()+1);
            inv[i].resize(s.size()+1);
            ll acu = 1;
            h[i][0]=0, inv[i][0]=1;
            for (int j = 0; j<s.size(); j++) {
                h[i][j+1]=(h[i][j]+acu*s[j])%m[i];
                inv[i][j+1]=(1ll*inv[i][j]*in[i])%m[i];
                acu = (acu * p) % m[i];
            }
        }
    }
}
```

```
}
ll get(int b, int e) {
    e++;
    ll ha[2];
    for (int i =0; i<2; i++) {
        ha[i] = (((h[i][e] - h[i][b]) * (ll)inv[i][b]) %
m[i]) + m[i]) % m[i];
    }
    return ((ha[0]<<32)|ha[1]);
}
};
```

10.8 palindromic

```
struct node {
    int next[alfa], link, len;
    int cnt;
    node(int x, int l = 0, int c = 1) {
        len = x, link = l, cnt = c;
        memset(next, 0, sizeof next);
    }
    int& operator [] (int i) { return next[i]; }
};
struct palindromic_tree {
    vector<node> tree; string s;
    int n, last;
    palindromic_tree(string t = "") {
        n = last = 0;
        tree.pb(node(-1));
        tree.pb(node(0));
        for (auto &c: t) add_char(c);
    }
    int getlink(int p) {
        while (s[n - tree[p].len - 1] != s[n])
            p = tree[p].link;
        return p;
    }
    void add_char(char ch) {
        s.pb(ch); int p = getlink(last), c = ch - L;
        if (!tree[p][c]) {
            int link = getlink(tree[p].link);
            link = max(1, tree[link][c]);
            tree[p][c] = SZ(tree);
            tree.pb(node(tree[p].len + 2, link, 0));
        }
        last = tree[p][c];
        tree[last].cnt++; n++;
    }
};
```

10.9 suffix array

```
#define RB(x) (x<n?r[x]:0)
void csort(vector<int> &sa, vector<int> &r, int k){
    int n=SZ(sa);
    vector<int> f(max(255,n+1)),t(n);
    fore(i,0,n) f[RB(i+k)]++;
    int sum=0;
    fore(i,0,max(255,n+1))f[i]=(sum+=f[i])-f[i];
    fore(i,0,n)t[f[RB(sa[i]+k)]++]=sa[i];
    sa=t;
}
vector<int> constructSA(vector<int> &s){
    int n=SZ(s),rank;
    vector<int> sa(n),r(n),t(n);
    fore(i,0,n)sa[i]=i,r[i]=s[i];
    for(int k=1;k<n;k*=2){
        csort(sa,r,k);csort(sa,r,0);
        t[sa[0]]=rank=0;
        fore(i,1,n){
            if(r[sa[i]]!=r[sa[i-1]]||RB(sa[i]+k)!
=RB(sa[i-1]+k))rank++;
            t[sa[i]]=rank;
        }
        r=t;
        if(r[sa[n-1]]==n-1)break;
    }
    return sa;
}
vector<int> computeLCP(vector<int> &s,vector<int> &sa){
    int n=SZ(s),L=0;
    vector<int> lcp(n),plcp(n),phi(n);
    phi[sa[0]]=-1;
    fore(i,1,n)phi[sa[i]]=sa[i-1];
    fore(i,0,n){
        if(phi[i]<0){plcp[i]=0;continue;}
        while(s[i+L]==s[phi[i]+L])L++;
        plcp[i]=L;
        L=max(L-1,0);
    }
    fore(i,0,n)lcp[i]=plcp[sa[i]];
    // lcp[i] = lcp(sa[i-1], sa[i]);
    return lcp;
}
void test_case() { // max element <= n
    vector<int> nums;
    nums.pb(0); // min element
    auto sa = constructSA(nums);
    auto lcp = computeLCP(nums, sa);
    sa.erase(sa.begin());
    lcp.erase(lcp.begin());
    nums.pop_back();
}
```

11 8. Geometry

11.1 closest pair of points sweep line

```
#define x first
#define y second
ll dist2(pair<int,int> a, pair<int,int> b) {
    return 1LL * (a.x-b.x)*(a.x-b.x) + 1LL * (a.y-
b.y)*(a.y-b.y);
}
pair<pair<ll,ll>,pair<ll,ll>>
ClosestPair(vector<pair<int, int>> pts) {
    int n = pts.size();
    sort(pts.begin(), pts.end());
    set<pair<ll, ll>> s;
    long long best_dist = 8e18;
    int last_best = 0; // if you need the points
    int j = 0;
    for (int i = 0; i < n; ++i) {
        ll d = ceil(sqrtll(best_dist));
        while (pts[i].first - pts[j].first >= d) {
            s.erase({pts[j].second, pts[j].first});
            j += 1;
        }
        auto it1 = s.lower_bound({pts[i].second - d,
pts[i].first});
        auto it2 = s.upper_bound({pts[i].second + d,
pts[i].first});
        for (auto it = it1; it != it2; ++it) {
            ll dx = pts[i].first - it->second;
            ll dy = pts[i].second - it->first;
            ll distance = 1LL * dx * dx + 1LL * dy *
dy;
            if (distance <= best_dist) { // must be <=
otherwise got WA
                best_dist = distance;
                last_best = i; // if you need the
points
            }
            s.insert({pts[i].second, pts[i].first});
        }
        // If you need the points otherwise return
best_dist;
        for (int i = 0; i < last_best; i++) {
            if (dist2(pts[i],pts[last_best])==best_dist) {
                return {pts[i],pts[last_best]};
            }
        }
    }
    assert(false);
    return {{0,0},{0,0}};
```

```
}
void test_case() {
    ll n;
    cin >> n;
    vector<pair<int,int>> points(n);
    for (int i = 0; i < n; i++) {
        ll x, y;
        cin >> x >> y;
        points[i] = {x,y};
    }
    auto ans = ClosestPair(points);
    cout << dist2(ans.F, ans.S) << "\n";
}
// AC https://cses.fi/problemset/task/2194/
```

11.2 closest pair of points

```
// It seems O(n log n), not sure but it worked for
50000
// This algorithms is not the best, TLE in CSES
// https://cses.fi/problemset/task/2194
#define x first
#define y second
long long dist2(pair<int, int> a, pair<int, int> b) {
    return 1LL * (a.x - b.x) * (a.x - b.x) + 1LL * (a.y -
b.y) * (a.y - b.y);
}
pair<int, int> closest_pair(vector<pair<int, int>> a) {
    int n = a.size();
    assert(n >= 2);
    vector<pair<pair<int, int>, int>> p(n);
    for (int i = 0; i < n; i++) p[i] = {a[i], i};
    sort(p.begin(), p.end());
    int l = 0, r = 2;
    long long ans = dist2(p[0].x, p[1].x);
    pair<int, int> ret = {p[0].y, p[1].y};
    while (r < n) {
        while (l < r && 1LL * (p[r].x.x - p[l].x.x) *
(p[r].x.x - p[l].x.x) >= ans) l++;
        for (int i = l; i < r; i++) {
            long long nw = dist2(p[i].x, p[r].x);
            if (nw < ans) {
                ans = nw;
                ret = {p[i].y, p[r].y};
            }
        }
        r++;
    }
    return ret;
}
// Tested: https://vjudge.net/solution/52922194/
```

```
ccPUXODAMWTzpZCEvXbV
void test_case() {
    ll n;
    cin >> n;
    vector<pair<int,int>> points(n);
    for (int i = 0; i < n; i++) cin >> points[i].x >>
points[i].y;
    auto ans = closest_pair(points);
    cout << fixed << setprecision(6);
    if (ans.F > ans.S) swap(ans.F,ans.S);
    ld dist =
sqrtll(dist2(points[ans.F],points[ans.S]));
    cout << ans.F << " " << ans.S << " " << dist <<
endl;
}
```

11.3 heron formula

```
ld triangle_area(ld a, ld b, ld c) {
    ld s = (a + b + c) / 2;
    return sqrtll(s * (s - a) * (s - b) * (s - c));
}
```

11.4 ufps circle

```
struct circle {
    pt c; T r;
};
// (x-xo)^2 + (y-yo)^2 = r^2
// circle that passes through abc
circle center(pt a, pt b, pt c) {
    b = b-a, c = c-a;
    assert(cross(b, c) != 0); // no circumcircle if A,
B, C aligned
    pt cen = a + rot90ccw(b*norm(c) - c*norm(b))/
cross(b, c)/2;
    return {cen, abs(a-cen)};
}
// centers of the circles that pass through ab and have
radius r
vector<pt> centers(pt a, pt b, T r) {
    if (abs(a-b) > 2*r + eps) return {};
    pt m = (a+b)/2;
    double f = sqrt(r*r/norm(a-m) - 1);
    pt c = rot90ccw(a-m)*f;
    return {m-c, m+c};
}
int inter_cl(circle c, line l, pair<pt, pt> &out) {
    lf h2 = c.r*c.r - l.sq_dist(c.c);
    if (h2 >= 0) { // line touches circle
        pt p = l.proj(c.c);
        pt h = l.v*sqrt(h2)/abs(l.v); // vector of len
```

```

h parallel to line
    out = {p-h, p+h};
}
return 1 + sign(h2); // if 1 -> out.F == out.S
}
int inter_cc(circle c1, circle c2, pair<pt, pt> &out) {
    pt d = c2.c-c1.c;
    double d2 = norm(d);
    if (d2 == 0) { assert(c1.r != c2.r); return 0; } //
concentric circles (identical)
    double pd = (d2 + c1.r*c1.r - c2.r*c2.r)/2; // = |
0_1p| * d
    double h2 = c1.r*c1.r - pd*pd/d2; // = h^2
    if (h2 >= 0) {
        pt p = c1.c + d*pd/d2, h = rot90ccw(d)*sqrt(h2/
d2);
        out = {p-h, p+h};
    }
    return 1 + sign(h2);
}
// circle-line inter = 1
int tangents(circle c1, circle c2, bool inner,
vector<pair<pt, pt>> &out) {
    if (inner) c2.r = -c2.r; // inner tangent
    pt d = c2.c-c1.c;
    double dr = c1.r-c2.r, d2 = norm(d), h2 = d2-dr*dr;
    if (d2 == 0 || h2 < 0) { assert(h2 != 0); return
0; } // (identical)
    for (double s : {-1, 1}) {
        pt v = (d*dr + rot90ccw(d)*sqrt(h2)*s)/d2;
        out.pb({c1.c + v*c1.r, c2.c + v*c2.r});
    }
    return 1 + (h2 > 0); // if 1: circle are tangent
}
// circle tangent passing through pt p
int tangent_through_pt(pt p, circle c, pair<pt, pt>
&out) {
    double d = abs(p - c.c);
    if (d < c.r) return 0;
    pt base = c.c-p;
    double w = sqrt(norm(base) - c.r*c.r);
    pt a = {w, c.r}, b = {w, -c.r};
    pt s = p + base*a/norm(base)*w;
    pt t = p + base*b/norm(base)*w;
    out = {s, t};
    return 1 + (abs(c.c-p) == c.r);
}
}

```

11.5 ufps halfplane

```

struct halfplane {
    double angle;
    pt p, pq;
    halfplane() {}
    halfplane(pt a, pt b): p(a), pq(b - a) {
        angle = atan2(pq.y, pq.x);
    }
    bool operator < (halfplane b) const { return angle
< b.angle; }
    bool out(pt q) { return cross(pq, (q-p)) < -
eps; } // checks if p is inside the half plane
};
const lf inf = 1e100;
// intersection pt of the lines of 2 halfplanes
pt inter(halfplane& h1, halfplane& h2) {
    if (abs(cross(unit(h1.pq), unit(h2.pq))) <= eps)
        return {inf, inf};
    lf alpha = cross((h2.p - h1.p), h2.pq)/cross(h1.pq,
h2.pq);
    return h1.p + (h1.pq * alpha);
}
// intersection of halfplanes
vector<pt> intersect(vector<halfplane>& b) {
    vector<pt> box = {{inf, inf}, {-inf, inf}, {-inf, -
inf}, {inf, -inf}};
    for (int i = 0; i < 4; i++) {
        b.pb({box[i], box[(i + 1) % 4]});
    }
    sort(b.begin(), b.end());
    int n = b.size(), q = 1, h = 0;
    vector<halfplane> c(n + 10);
    for (int i = 0; i < n; i++) {
        while (q < h && b[i].out(inter(c[h], c[h-1]))) h--;
        while (q < h && b[i].out(inter(c[q], c[q+1]))) q++;
        c[++h] = b[i];
        if (q < h && abs(cross(c[h].pq, c[h-1].pq)) < eps) {
            if (dot(c[h].pq, c[h-1].pq) <= 0) return {};
            h--;
            if (b[i].out(c[h].p)) c[h] = b[i];
        }
    }
    while (q < h-1 && c[q].out(inter(c[h], c[h-1]))) h--;
    while (q < h-1 && c[h].out(inter(c[q], c[q+1]))) q++;
    if (h - q <= 1) return {};
    c[h+1] = c[q];
    vector<pt> s;
    for(int i = q; i < h+1; i++)s.pb(inter(c[i],
c[i+1]));
    return s;
}

```

11.6 ufps line

```

struct line {
    pt v; T c; // v:direction c: pos in y axis
    line(pt v, T c) : v(v), c(c) {}
    line(T a, T b, T c) : v({b, -a}), c(c) {} // ax +
by = c
    line(pt p, pt q) : v(q-p), c(cross(v, p)) {}
    T side(pt p) { return cross(v, p)-c; }
    lf dist(pt p) { return abs(side(p)) / abs(v); }
    lf sq_dist(pt p) { return side(p)*side(p) /
(lf)norm(v); }
    line perp_through(pt p) { return {p, p +
rot90ccw(v)}; } // line perp to v passing through p
    bool cmp_proj(pt p, pt q) { return dot(v, p) <
dot(v, q); } // order for points over the line
    line translate(pt t) { return {v, c + cross(v,
t)}; }
    line shift_left(double d) { return {v, c +
d*abs(v)}; }
    pt proj(pt p) { return p - rot90ccw(v)*side(p)/
norm(v); } // pt projected on the line
    pt refl(pt p) { return p - rot90ccw(v)*2*side(p)/
norm(v); } // pt reflected on the other side of the
line
};
bool inter_ll(line l1, line l2, pt &out) {
    T d = cross(l1.v, l2.v);
    if (d == 0) return false;
    out = (l2.v*l1.c - l1.v*l2.c) / d; // floating
points
    return true;
}
// bisector divides the angle in 2 equal angles
// interior line goes on the same direction as l1 and
l2
line bisector(line l1, line l2, bool interior) {
    assert(cross(l1.v, l2.v) != 0); // l1 and l2 cannot
be parallel!
    lf sign = interior ? 1 : -1;
    return {l2.v/abs(l2.v) + l1.v/abs(l1.v) * sign,
l2.c/abs(l2.v) + l1.c/abs(l1.v) * sign};
}

```

11.7 ufps point

```

// esto me pidio alex agregar
lf angle(pt a) {
    return atan2(a.y, a.x);
}
lf angle(pt a) {
    lf r = abs(a);

```

```

    return (a.y < 0 ? -1 : 1)*acos(a.x / r);
}
lf angle(pt a, pt b) {
    lf aa = angle(a);
    lf bb = angle(b);
    lf dif = abs(aa - bb);
    return min(dif, 2*PI - dif);
}
// esto pidio alex agregar
typedef double lf;
const lf eps = 1e-9;
const lf PI = acos(-1.0);
typedef double T;
struct pt {
    T x, y;
    pt operator + (pt p) { return {x+p.x, y+p.y}; }
    pt operator - (pt p) { return {x-p.x, y-p.y}; }
    pt operator * (pt p) { return {x*p.x-y*p.y,
x*p.y+y*p.x}; }
    pt operator * (T d) { return {x*d, y*d}; }
    pt operator / (lf d) { return {x/d, y/d}; } // only
for floating point
    bool operator == (pt b) { return x == b.x && y ==
b.y; }
    bool operator != (pt b) { return !(*this == b); }
    bool operator < (const pt &o) const { return y <
o.y || (y == o.y && x < o.x); }
    bool operator > (const pt &o) const { return y >
o.y || (y == o.y && x > o.x); }
};
int cmp(lf a, lf b) { return (a + eps < b ? -1 : (b +
eps < a ? 1 : 0)); } // double comparator
T norm(pt a) { return a.x*a.x + a.y*a.y; }
lf abs(pt a) { return sqrt(norm(a)); }
lf arg(pt a) { return atan2(a.y, a.x); }
pt unit(pt a) { return a/abs(a); }
T dot(pt a, pt b) { return a.x*b.x + a.y*b.y; } // x =
90 -> cos = 0
T cross(pt a, pt b) { return a.x*b.y - a.y*b.x; } // x
= 180 -> sin = 0
T orient(pt a, pt b, pt c) { return cross(b-a, c-
a); } // clockwise = -
pt rot(pt p, lf a) { return {p.x*cos(a) - p.y*sin(a),
p.x*sin(a) + p.y*cos(a)}; }
pt rotate_to_b(pt a, pt b, lf ang) { return rot(a-b,
ang)+b; } // rotate by ang center b
pt rot90ccw(pt p) { return {-p.y, p.x}; }
pt rot90cw(pt p) { return {p.y, -p.x}; }
pt translate(pt p, pt v) { return p+v; }
pt scale(pt p, double f, pt c) { return c + (p-
c)*f; } // c-center

```

```

bool are_perp(pt v, pt w) { return dot(v, w) == 0; }
int sign(T x) { return (T(0) < x) - (x < T(0)); }
bool in_angle(pt a, pt b, pt c, pt x) { // x inside
angle abc (center in a)
    assert(orient(a, b, c) != 0);
    if (orient(a, b, c) < 0) swap(b, c);
    return orient(a, b, x) >= 0 && orient(a, c, x) <=
0;
}
// angle bwn 2 vectors [0, pi] -> [0, 180] and (-pi, 0)
-> (180, 360)
lf angle(pt a, pt b) { return acos(max(-1.0, min(1.0,
dot(a, b)/abs(a)/abs(b)))); }
lf angle(pt a, pt b) { return atan2(cross(a, b), dot(a,
b)); }
lf angle360(pt a, pt b) { // [0, 360)
    lf ang = angle(a, b); return (ang < 0 ? ang+2*PI :
ang) * 360/(2*PI);
}
// returns vector to transform points
pt get_linear_transformation(pt p, pt q, pt r, pt fp,
pt fq) {
    pt pq = q-p, num{cross(pq, fq-fp), dot(pq, fq-fp)};
    return fp + pt{cross(r-p, num), dot(r-p, num)} /
norm(pq);
}
bool half(pt p) { // true if is in (0, 180] (line is x
axis)
    assert(p.x != 0 || p.y != 0); // the argument of
(0, 0) is undefined
    return p.y > 0 || (p.y == 0 && p.x < 0);
}
bool half_from(pt p, pt v = {1, 0}) { // line is v
(above v is true)
    return cross(v, p) < 0 || (cross(v, p) == 0 &&
dot(v, p) < 0);
}
bool polar_cmp(const pt &a, const pt &b) { // polar
sort
    return make_tuple(half(a), 0) < make_tuple(half(b),
cross(a, b));
    // return make_tuple(half(a), 0, sq(a)) <
make_tuple(half(b), cross(a, b), sq(b)); // further
ones appear later
}

```

11.8 ufps polygon

```

enum {IN, OUT, ON};
struct polygon {
    vector<pt> p;

```

```

polygon(int n) : p(n) {}
int top = -1, bottom = -1;
void delete_repetead() {
    vector<pt> aux;
    sort(p.begin(), p.end());
    for (pt &i : p)
        if (aux.empty() || aux.back() != i)
            aux.pb(i);
    p.swap(aux);
}
bool is_convex() {
    bool pos = 0, neg = 0;
    for (int i = 0, n = p.size(); i < n; i++) {
        int o = orient(p[i], p[(i+1)%n], p[(i+2)%n]);
        if (o > 0) pos = 1;
        if (o < 0) neg = 1;
    }
    return !(pos && neg);
}
lf area(bool s = false) { // better on ccw order
    lf ans = 0;
    for (int i = 0, n = p.size(); i < n; i++)
        ans += cross(p[i], p[(i+1)%n]);
    ans /= 2;
    return s ? ans : abs(ans);
}
lf perimeter() {
    lf per = 0;
    for (int i = 0, n = p.size(); i < n; i++)
        per += abs(p[i] - p[(i+1)%n]);
    return per;
}
bool above(pt a, pt p) { return p.y >= a.y; }
bool crosses_ray(pt a, pt p, pt q) { // pq crosses ray
from a
    return (above(a, q)-above(a, p))*orient(a, p, q)>0;
}
int in_polygon(pt a) {
    int crosses = 0;
    for (int i = 0, n = p.size(); i < n; i++) {
        if (on_segment(p[i], p[(i+1)%n], a)) return ON;
        crosses += crosses_ray(a, p[i], p[(i+1)%n]);
    }
    return (crosses&1 ? IN : OUT);
}
void normalize() { // polygon is CCW
    bottom = min_element(p.begin(), p.end())-p.begin();
    vector<pt> tmp(p.begin()+bottom, p.end());
    tmp.insert(tmp.end(), p.begin(), p.begin()+bottom);
    p.swap(tmp);
    bottom = 0;
}

```

```

    top = max_element(p.begin(), p.end()) - p.begin();
}
int in_convex(pt a) {
    // need to normalize first
    assert(bottom == 0 && top != -1);
    if (a < p[0] || a > p[top]) return OUT;
    T orientation = orient(p[0], p[top], a);
    if (orientation == 0) {
        if (a == p[0] || a == p[top]) return ON;
        return top == 1 || top + 1 == p.size() ? ON : IN;
    } else if (orientation < 0) {
        auto it = lower_bound(p.begin()+1, p.begin()+top,
a);
        T d = orient(*prev(it), a, *it);
        return d < 0 ? IN : (d > 0 ? OUT : ON);
    } else {
        auto it = upper_bound(p.rbegin(), p.rend()-top-1,
a);
        T d = orient(*it, a, it == p.rbegin() ? p[0] :
*prev(it));
        return d < 0 ? IN : (d > 0 ? OUT : ON);
    }
}
polygon cut(pt a, pt b) { // cuts polygon on line ab
    line l(a, b);
    polygon new_polygon(0);
    for (int i = 0, n = p.size(); i < n; ++i) {
        pt c = p[i], d = p[(i+1)%n];
        lf abc = cross(b-a, c-a), abd = cross(b-a, d-a);
        if (abc >= 0) new_polygon.pb(c);
        if (abc*abd < 0) {
            pt out; inter_ll(l, line(c, d), out);
            new_polygon.pb(out);
        }
    }
    return new_polygon;
}
void convex_hull() {
    sort(p.begin(), p.end());
    vector<pt> ch;
    ch.reserve(p.size()+1);
    for (int it = 0; it < 2; it++) {
        int start = ch.size();
        for (auto &a : p) {
            // if colinear are needed, use < and remove
            repeated points
            while (ch.size() >= start+2 &&
orient(ch[ch.size()-2], ch.back(), a) <= 0)
                ch.pop_back();
            ch.pb(a);
        }
    }
}

```

```

    ch.pop_back();
    reverse(p.begin(), p.end());
}
if (ch.size() == 2 && ch[0] == ch[1]) ch.pop_back();
// be careful with CH of size < 3
p.swap(ch);
}
vector<pii> antipodal() {
    vector<pii> ans;
    int n = p.size();
    if (n == 2) ans.pb({0, 1});
    if (n < 3) return ans;
    auto nxt = [&](int x) { return (x+1 == n ? 0 :
x+1); };
    auto area2 = [&](pt a, pt b, pt c) { return
cross(b-a, c-a); };
    int b0 = 0;
    while (abs(area2(p[n-1], p[0], p[nxt(b0)])) >
abs(area2(p[n-1], p[0], p[b0]))) ++b0;
    for (int b = b0, a = 0; b != 0 && a <= b0; ++a) {
        ans.pb({a, b});
        while (abs(area2(p[a], p[nxt(a)], p[nxt(b)])) >
abs(area2(p[a], p[nxt(a)], p[b]))) {
            b = nxt(b);
            if (a != b0 || b != 0) ans.pb({a, b});
            else return ans;
        }
        if (abs(area2(p[a], p[nxt(a)], p[nxt(b)])) ==
abs(area2(p[a], p[nxt(a)], p[b]))) {
            if (a != b0 || b != n-1) ans.pb({a, nxt(b)});
            else ans.pb({nxt(a), b});
        }
    }
    return ans;
}
pt centroid() {
    pt c{0, 0};
    lf scale = 6. * area(true);
    for (int i = 0, n = p.size(); i < n; ++i) {
        int j = (i+1 == n ? 0 : i+1);
        c = c + (p[i] + p[j]) * cross(p[i], p[j]);
    }
    return c / scale;
}
ll pick() {
    ll boundary = 0;
    for (int i = 0, n = p.size(); i < n; i++) {
        int j = (i+1 == n ? 0 : i+1);
        boundary += __gcd((ll)abs(p[i].x - p[j].x),
(ll)abs(p[i].y - p[j].y));
    }
}

```

```

    return area() + 1 - boundary/2;
}
pt& operator [] (int i) { return p[i]; }
};

```

11.9 ufps segment

```

bool in_disk(pt a, pt b, pt p) { // pt p inside ab disk
    return dot(a-p, b-p) <= 0;
}
bool on_segment(pt a, pt b, pt p) { // p on ab
    return orient(a, b, p) == 0 && in_disk(a, b, p);
}
// ab crossing cd
bool proper_inter(pt a, pt b, pt c, pt d, pt &out) {
    T oa = orient(c, d, a),
    ob = orient(c, d, b),
    oc = orient(a, b, c),
    od = orient(a, b, d);
    // Proper intersection exists iff opposite signs
    if (oa*ob < 0 && oc*od < 0) {
        out = (a*ob - b*oa) / (ob-oa);
        return true;
    }
    return false;
}
// intersection bwn segments
set<pt> inter_ss(pt a, pt b, pt c, pt d) {
    pt out;
    if (proper_inter(a, b, c, d, out)) return {out}; //
if cross -> 1
    set<pt> s;
    if (on_segment(c, d, a)) s.insert(a); // a in cd
    if (on_segment(c, d, b)) s.insert(b); // b in cd
    if (on_segment(a, b, c)) s.insert(c); // c in ab
    if (on_segment(a, b, d)) s.insert(d); // d in ab
    return s; // 0, 2
}
lf pt_to_seg(pt a, pt b, pt p) { // p to ab
    if (a != b) {
        line l(a, b);
        if (l.cmp_proj(a, p) && l.cmp_proj(p, b)) // if
closest to projection = (a, p, b)
            return l.dist(p); // output distance to
line
    }
    return min(abs(p-a), abs(p-b)); // otherwise
distance to A or B
}
lf seg_to_seg(pt a, pt b, pt c, pt d) {
    pt dummy;
}

```

```

    if (proper_inter(a, b, c, d, dummy)) return 0; //
ab intersects cd
    return min({pt_to_seg(a, b, c), pt_to_seg(a, b, d),
pt_to_seg(c, d, a), pt_to_seg(c, d, b)}); // try the 4
pts
}

```

12 9. Utils

12.1 bit tricks

```

y = x & (x-1) // Turn off rightmost lbit
y = x & (-x) // Isolate rightmost lbit
y = x | (x-1) // Right propagate rightmost lbit(fill
in 1s)
y = x | (x+1) // Turn on rightmost 0bit
y = ~x & (x+1) // Isolate rightmost 0bit
// If x is of long type, use __builtin_popcountl(x)
// If x is of long long type, use
__builtin_popcountll(x)
// 1. Counts the number of one's(set bits) in an
integer.
__builtin_popcount(x)
// 2. Checks the Parity of a number. Returns true(1) if
the
// number has odd number of set bits, else it returns
// false(0) for even number of set bits.
__builtin_parity(x)
// 3. Counts the leading number of zeros of the
integer.
__builtin_clz(x)
// 4. Counts the trailing number of zeros of the
integer.
__builtin_ctz(x)
// 5. Returns 1 + the index of the least significant 1-
bit.
__builtin_ffs(x) // If x == 0, returns 0.
// Iterate over non empty subsets of bitmask
for(int s=m;s=(s-1)&m) // Decreasing order
for(int s=0;s=s-m&m;) // Increasing order

```

12.2 decimal precision python

```

"""
For problems that needs more decimal precision
You can try this code but in C++,
it will not pass in this problem https://cses.fi/
problemset/task/l728/
"""
from decimal import *
getcontext().prec = 200 #The decimal precision

```

```

n = int(input())
nums = [int(x) for x in input().split(" ")]
ans = Decimal(0)
for i in range(0,len(nums)):
    for j in range(i+1,len(nums)):
        for k in range(1,nums[j]+1):
            ans += max(0,nums[i]-k)/
Decimal(nums[i]*nums[j])
# Also for reduce getcontext().prec = 100
# You can sum integer part, then apply the
decimal division
print("{:.6f}".format(ans)) #The rounding half even to
six decimals
# import ast as a
# tree = ast.parse("x + 5")
# print(ast.dump(tree, indent=2))
# eval(string expr)

```

12.3 io int128

```

// Read and Print integers of 128 bits
__int128 read() {
    __int128 x = 0, f = 1;
    char ch = getchar();
    while (ch < '0' || ch > '9') {
        if (ch == '-') f = -1;
        ch = getchar();
    }
    while (ch >= '0' && ch <= '9') {
        x = x * 10 + ch - '0';
        ch = getchar();
    }
    return x * f;
}
void print(__int128 x) {
    if (x < 0) {
        putchar('-');
        x = -x;
    }
    if (x > 9) print(x / 10);
    putchar(x % 10 + '0');
}
void print(__int128 x) {
    if (x < 0) {
        cout << "-";
        x = -x;
    }
    if (x > 9) print(x / 10);
    cout << char((int)(x % 10) + '0');
}

```

12.4 pragmas

```

//#pragma GCC target("popcnt")
//It's worth noting that after adding
__builtin_popcount() is replaced to corresponding
machine instruction (look at the difference). In my
test this maked x2 speed up. bitset::count() use
__builtin_popcount() call in implementation, so it's
also affected by this.
#pragma GCC target ("avx2")
#pragma GCC optimization ("O3")
#pragma GCC optimization ("unroll-loops")
#pragma GCC target("popcnt")
#pragma GCC
target("avx,avx2,sse3,ssse3,sse4.1,sse4.2,tune=native")
#pragma GCC optimize(3)
#pragma GCC optimize("O3")
#pragma GCC optimize("inline")
#pragma GCC optimize("-fgcse")
#pragma GCC optimize("-fgcse-lm")
#pragma GCC optimize("-fipa-sra")
#pragma GCC optimize("-ftree-pre")
#pragma GCC optimize("-ftree-vrp")
#pragma GCC optimize("-fpeephole2")
#pragma GCC optimize("-fsched-spec")
#pragma GCC optimize("-falign-jumps")
#pragma GCC optimize("-falign-loops")
#pragma GCC optimize("-falign-labels")
#pragma GCC optimize("-fdevirtualize")
#pragma GCC optimize("-fcaller-saves")
#pragma GCC optimize("-fcrossjumping")
#pragma GCC optimize("-fthread-jumps")
#pragma GCC optimize("-freorder-blocks")
#pragma GCC optimize("-fschedule-insns")
#pragma GCC optimize("inline-functions")
#pragma GCC optimize("-ftree-tail-merge")
#pragma GCC optimize("-fschedule-insns2")
#pragma GCC optimize("-fststrict-aliasing")
#pragma GCC optimize("-falign-functions")
#pragma GCC optimize("-fcse-follow-jumps")
#pragma GCC optimize("-fsched-interblock")
#pragma GCC optimize("-fpartial-inlining")
#pragma GCC optimize("no-stack-protector")
#pragma GCC optimize("-freorder-functions")
#pragma GCC optimize("-findirect-inlining")
#pragma GCC optimize("-fhoist-adjacent-loads")
#pragma GCC optimize("-frerun-cse-after-loop")
#pragma GCC optimize("inline-small-functions")
#pragma GCC optimize("-finline-small-functions")
#pragma GCC optimize("-ftree-switch-conversion")
#pragma GCC optimize("-foptimize-sibling-calls")

```

```
#pragma GCC optimize("-fexpensive-optimizations")
#pragma GCC optimize("inline-functions-called-once")
#pragma GCC optimize("-fdelete-null-pointer-checks")
```

12.5 randoms

```
// Get random numbers between [a, b]
mt19937
mt_rng(chrono::steady_clock::now().time_since_epoch().count());
// also for ll exists mt19937_64
ll randint(ll a, ll b) {
    return uniform_int_distribution<ll>(a, b)(mt_rng);
}
```

12.6 string streams

```
// For some complex reading of input
// st is the same as a cin, but you pass the string
string line;
getline(cin, line);
stringstream st(line);
vl in;
ll x;
while (st >> x) {
    in.pb(x);
}
```

13 A. To Order

13.1 mo's in tree's

DFS Euler **2N**:
array A con cada nodo **2 veces** (ST[u] entrada, EN[u] salida).
En Mo, **add**(pos) togglea el nodo A[pos] (activo ↔ inactivo).
Query (u,v), p=**LCA**(u,v), con ST[u]≤ST[v]:
si p==u: rango [ST[u], ST[v]]
si p!=u: rango [EN[u], ST[v]] y agregás p **aparte** (toggle antes/después).

13.2 poly definitions

$A(x) = \sum_{i=0}^n (a_i \cdot x^i)$ y $B(x) = \sum_{i=0}^m (b_i \cdot x^i)$
 $A(x) \cdot B(x) = \sum_{i=0}^{n+m} (a_j \cdot b_{i-j}) \cdot x^i$

13.3 polynomial sum lazy segtree problem

```
/* Polynomial Queries, queries
1. Increase [a,b] by 1, second by 2, third by 3, and so on
2. Sum of [a,b]
Use:
cin >> nums[i], tree.update(i, { nums[i] })
For 1: tree.apply(l,r,{0,1});
For 2: tree.query(l,r).sum
*/
struct Node { ll sum = 0; };
struct Func { ll add, ops; };
Node e() { return {0}; };
Func id() { return {0, 0}; };
Node op(Node a, Node b) { return {a.sum + b.sum}; };
ll f(ll x) { return x * (x+1)/2; };
Node mapping(Node node, Func lazy, ll sz) {
    return { node.sum + sz*lazy.add + lazy.ops*f(sz) };
}
Func composicion(Func prev, Func actual) {
    Func ans = { prev.add + actual.add, prev.ops + actual.ops };
    return ans;
}
Func sumF(Func f, ll x) { return {f.add + x*f.ops, f.ops}; }
struct lazytree {
    int n;
    vector<Node> nodes;
    vector<Func> lazy;
    void init(int nn) {
        n = nn;
        int size = 1;
        while (size < n) { size *= 2; }
        ll m = size * 2;
        nodes.assign(m, e());
        lazy.assign(m, id());
    }
    void push(int i, int sl, int sr) {
        nodes[i] = mapping(nodes[i], lazy[i], sr-sl+1);
        if (sl != sr) {
            ll cnt = (sr-sl)/2-sr+1; // changed
            lazy[i * 2 + 1] =
composicion(lazy[i*2+1], lazy[i]);
            lazy[i * 2 + 2] =
composicion(lazy[i*2+2], sumF(lazy[i], cnt));
        }
        lazy[i] = id();
    }
    void apply(int i, int sl, int sr, int l, int r,
Func f) {
        push(i, sl, sr);
```

```
if (l <= sl && sr <= r) {
    lazy[i] = sumF(f, abs(sl-l)); //Changed
    push(i, sl, sr);
} else if (sr < l || r < sl) {
} else {
    int mid = (sl + sr) >> 1;
    apply(i * 2 + 1, sl, mid, l, r, f);
    apply(i * 2 + 2, mid + 1, sr, l, r, f);
    nodes[i] = op(nodes[i*2+1], nodes[i*2+2]);
}
}
void apply(int l, int r, Func f) {
    assert(l <= r);
    assert(r < n);
    apply(0, 0, n - 1, l, r, f);
}
void update(int i, Node node) {
    assert(i < n);
    update(0, 0, n-1, i, node);
}
void update(int i, int sl, int sr, int pos, Node
node) {
    if (sl <= pos && pos <= sr) {
        push(i, sl, sr);
        if (sl == sr) {
            nodes[i] = node;
        } else {
            int mid = (sl + sr) >> 1;
            update(i * 2 + 1, sl, mid, pos, node);
            update(i * 2 + 2, mid + 1, sr, pos,
node);
            nodes[i] = op(nodes[i*2+1],
nodes[i*2+2]);
        }
    }
}
Node query(int i, int sl, int sr, int l, int r) {
    push(i, sl, sr);
    if (l <= sl && sr <= r) {
        return nodes[i];
    } else if (sr < l || r < sl) {
        return e();
    } else {
        int mid = (sl + sr) >> 1;
        auto a = query(i * 2 + 1, sl, mid, l, r);
        auto b = query(i * 2 + 2, mid + 1, sr, l,
r);
        return op(a, b);
    }
}
Node query(int l, int r) {
```

```

    assert(l <= r);
    assert(r < n);
    return query(0, 0, n - 1, l, r);
}
};

```

14 Problems

14.1 big primes

```

#define bint __int128
bint MOD=212345678987654321LL; // prime

```

14.2 shift poly

```

// ADD ntt, or karatsuba.
// A poly: c_0 + c_1*x + c_2*x^2 + ... is transformed
to
// c_0 + c_1*(x+k) + c_2*(x+k)^2 + ...
vl fact, ifact;
vl ki, iki;
void initShifts(ll n, ll k) {
    k = (k%MOD + MOD) % MOD;
    fact = ifact = vl(n+1);
    ki = iki = vl(n+1);
    fact[0] = ifact[0] = 1;
    ki[0] = iki[0] = 1;
    for (int i = 1; i <= n; i++) {
        fact[i] = (fact[i-1]*i)%MOD;
        ifact[i] = inv(fact[i]);
        ki[i] = (ki[i-1]*k) % MOD;
        iki[i] = inv(ki[i]);
    }
}
// P(x + k)
vl shift(vl &a, ll k) {
    if (k == 0) return a;
    ll n = a.size();
    initShifts(n, k);
    vl l(n), r(n);
    for (int i = 0; i < n; i++) {
        l[i] = mulmod(a[i], fact[i]);
        r[i] = mulmod(ki[n-1-i], ifact[n-1-i]);
    }
    vl c = multiply(l,r);
    vl ans(n);
    for (int i = 0; i < n; i++) {
        ans[i] = mulmod(c[n-1+i], ifact[i]);
    }
    return ans;
}
}

```