Data Management, Winter 2026/27 - Group Project

From Raw Race Results to a FAIR, Quality-Assured Knowledge Graph

Formula 1 World Championship results 1950-2025: FAIR assessment, data quality profiling, reproducible cleaning, property-graph analytics and an interactive dashboard

Group member	Presents
Chirag Adhikari	Component A - FAIR assessment and metadata design
Manohar Zalki	Component B - Data quality and profiling
Nicolas Bonilla	Component C - Data cleaning and pipeline

All three members worked jointly on every component; the table shows who presents each block.

SRH University | Submission date: [to be completed]

Repository: https://github.com/zalkimanohar/Formula1-Racing-Analytics (folders `data_management_project` and `dashboard`)

Interactive dashboard: `streamlit run app.py` in the `dashboard` folder, then http://localhost:8501 (Section 6)

Word count (main text, excluding tables, figure captions, references and appendices): 3,111. Component sections: A 433, B 446, C 420 words.

1. Introduction

Formula 1 has kept a classified result for every car since the first World Championship Grand Prix at Silverstone on 13 May 1950. The community-built Ergast database, now served by the Jolpica-F1 project after Ergast closed in 2024, is the de facto open source of these records and underpins countless analytics projects, including our group's own Formula1-Racing-Analytics repository. We chose it for three reasons. First, it is large and relational: the fact table holds 25,907 rows and 14 variables (one row per driver entry per Grand Prix, 76 seasons), linked to four reference tables (1,178 races, 82 circuits, 874 drivers and 214 constructors). Second, it contains genuine, non-trivial quality problems that come from 76 years of changing rules and from the way the files were exported. Third, drivers, teams, circuits and countries form a natural network, which makes the data well suited to property-graph modelling.

The domain also makes data management visible. Teams, broadcasters, journalists and a growing number of machine-learning projects that predict race outcomes all reuse these records, usually without asking how they were produced. A record that counts a retirement as '18th place' or a race twice does not stay local: it propagates into rankings, features and models. The dataset is therefore a realistic test case for the whole data-management life cycle, from assessing how findable and reusable the source is to delivering a documented, validated and linked product.

The raw package (`racing_f1_data.zip`) was downloaded by the group from the Jolpica API and mixes JSON Lines, pretty-printed JSON and CSV files. The same Ergast data are mirrored on Kaggle, an approved source type, and Component A evaluates both copies. Sprint races use a different session format and are out of scope; the analysis covers championship Grands Prix only.

All work follows one reproducible pipeline (Table 1). Step 0 flattens the archive into raw CSV files without changing a single value and records a SHA-256 manifest. Component B profiles the raw data and writes a quality issue register; Component C resolves every registered issue in an audited and validated cleaning pipeline; Component A assesses FAIRness and describes the cleaned package with standard metadata; the graph model is built from the cleaned data; and the last stage feeds an interactive dashboard (Section 6). One command (`python run_all.py --from-scratch`) rebuilds everything, dashboard included, in about 90 seconds, and two independent runs produce byte-identical files.

Table 1. Pipeline overview (`run_all.py`); every stage reads only the outputs of the stages before it.

Stage	Input	Output	Key result
0 Extraction	racing_f1_data.zip (93 files)	5 raw CSV files + checksum manifest	25,907 results, values unchanged
B Profiling	raw CSV files	issue register, profiles, 4 figures	29 issues, 7 dimensions
C Cleaning	raw CSV + issue register	5 clean CSV files, audit log, validation report	25,873 rows, 55 gates passed
A FAIR & metadata	clean CSV + sources	F-UJI/RDA scores, DataCite, schema.org, PROV	RDA 54% -> 93%
Graph	clean CSV	NetworkX property graph, GEXF, metrics	2,297 nodes, 30,141 edges
Dashboard	all outputs above	interactive web page (dashboard/)	7 views, issue B29 found

1.1 Data engineering architecture

Figure 1 shows the data flow. It follows the layered design common in data engineering: an immutable raw zone (bronze) that keeps the source values and their lineage, a clean zone (silver) that is only written when every validation gate passes, and curated products (gold) that are served to people and machines: the FAIR metadata record, the property graph, the dashboard and this report. Five engineering principles run through it:

- **Contracts, not conventions.** The issue register is the contract between profiling and cleaning, and one schema module defines the columns that cleaning validates and that the metadata describes.
- **Fail fast.** Validation gates and exhaustive vocabularies stop the run instead of passing bad data on.

- **Lineage everywhere.** Every row keeps its source file and line; files carry SHA-256 checksums; a PROV-O graph records each transformation.
- **Reproducible orchestration.** One command rebuilds every artefact, and repeated runs are byte-identical.
- **Tested decisions.** Automated tests protect the choices that matter most, such as the order of key repair and de-duplication.




Figure 1. End-to-end data flow, from the raw archive through the raw, clean and served zones, with the cross-cutting engineering controls.

2. Component A - FAIR Assessment and Metadata Design

Prepared jointly by the group; presented by Chirag Adhikari.

Assessment. FAIRness was measured twice, independently. The automated F-UJI tool (version 4.0.1, metrics v0.5), run on a local server, tested the three places where the data can be obtained (Figure 2): the group's GitHub repository scored 31%, the Jolpica API used for the download only 8%, and the Kaggle mirror 65%. Because F-UJI can only inspect what is already online, all 41 indicators of the RDA FAIR Data Maturity Model were also scored with written evidence, for the data as obtained and for our curated package (Figure 3). Overall maturity rises from 54% to 93% and the essential indicators met from 6/20 to 12/20. 'Findable' honestly stays at RDA level 0 until a DOI is actually minted. The two methods complement each other: F-UJI is reproducible but only sees machine-readable signals, while the RDA model also captures licences and provenance documented in human-readable form.

Gaps. Seven concrete gaps were documented with indicator, evidence and remedy (Appendix A, Table A.1). The three most important are:

- **No persistent identifier** - the data are reachable only through mutable URLs (F-UJI FsF-F1-02D = 0 for all three resources). Remedy: deposit each release through the GitHub-Zenodo integration, which mints a versioned DOI and a concept DOI.

- **Missing and conflicting licences** - Jolpica licenses the data CC BY-NC-SA 4.0 and Ergast allowed only non-commercial use, yet the Kaggle mirror claims CC0 and our repository declares MIT for everything. Remedy (implemented): data under CC-BY-NC-SA-4.0, MIT for code only, with attribution.
- **No machine-readable metadata, provenance or controlled vocabularies** - only a README, no checksums, country names such as 'UK' or 'Korea' and 136 free-text status values. Remedy (implemented): the records below, ISO codes and an eight-term status vocabulary.

Metadata record. The package is described by a DataCite 4.5 record, validated against the official XSD (Appendix A, Table A.3), a schema.org Dataset in JSON-LD for search engines, a Frictionless Data Package that declares primary and foreign keys, and a W3C PROV-O graph linking every output to the 15 audited cleaning activities. Variable definitions are generated from the same schema module that Component C validates against, so documentation and data cannot drift apart.

Persistent identifiers. The dataset receives a DOI (a reserved placeholder until deposit, never cited before minting), creators ORCID iDs and the institution a ROR identifier (candidate to be confirmed). For key variables, countries use ISO 3166-1 alpha-3 codes (ISO 3166-3 for former states such as East Germany), dates ISO 8601 and licences SPDX. Drivers, constructors and circuits were linked to Wikidata QIDs through their Wikipedia URLs, with coverage of 98.7%, 98.1% and 100%; the few failures exposed broken links, which were flagged for curation.




Figure 2. F-UJI automated FAIR scores for the three locations of the data (evidence: raw JSON in the ZIP).




Figure 3. RDA FAIR Data Maturity Model: progress per area for the data as obtained and the curated package.

3. Component B - Data Quality and Profiling

Prepared jointly by the group; presented by Manohar Zalki.

Profiling. Every column of the five tables was profiled for type, completeness, uniqueness and distribution, and 29 quality rules were run. Each finding is stored in an issue register with dimension, severity, evidence down to file and line, root-cause hypothesis, downstream impact and the cleaning step that resolves it (Appendix B, Table B.1). 24 findings are errors across 7 dimensions, 6 of them high severity; 5 are documented non-errors. A further 14 rules, including referential integrity and plausible driver ages, passed, which is equally useful evidence. Structurally, the results table combines identifiers, six numeric measures and free-text fields, no single column is unique, and the package itself is inconsistent: five sprint files are pretty-printed JSON arrays while every other JSON file uses JSON Lines.

Completeness is deceptive. Only 18 cells of the results table are null, suggesting a 99.9% complete dataset, yet 9,913 values merely pretend to be data (Figure 4): 'position' is filled for 9,646 drivers who retired, withdrew or were disqualified, and 'grid' uses 0 for 267 cars without a grid slot. A model predicting results from grid positions would learn from retirements ranked '18th' and from a fictitious 'grid 0'.

Uniqueness needs domain knowledge. 23 rows of the 1960 United States GP were appended twice, and 11 rows of the 1960 Italian GP are copies whose season and round were blanked; they only appear as duplicates once the keys are restored. Conversely, 172 rows that share season, round and driver are not errors: in the 1950s a driver could take over a team-mate's car and be classified twice (Figure 5). Naive de-duplication would delete real history.

Consistency, validity, accuracy, timeliness. Status is free text with 136 values mixing laps behind with failure causes; countries use abbreviations; identifiers break the lowercase convention; integer keys are stored as floats; five races are duplicated. Points are not comparable across eras: a win earned 8, 9, 10, 25 or even 50 points (Figure B.1). All 270 statistical lap outliers are valid Indianapolis 500 results (Figure B.2). Timeliness is uneven across tables: the calendar already lists 24 races of 2026 without results, and the newest drivers and teams lack birth dates, nationalities or links. From 2023 the source no longer records why cars retired (B29), a break found later through the dashboard (Section 6).

Root causes and impact. Three causes explain the pattern: export artefacts (duplicated blocks, blanked keys, lowercased names), undocumented source semantics (position, grid 0) and genuine historical change (scoring rules, shared drives). For data science and AI the impact is concrete: inflated win and point counts, biased prediction targets, sparse one-hot features, failed joins with external sources and train/test leakage through duplicated rows.




Figure 4. Explicit vs disguised missing values in the raw results table.




Figure 5. True duplicates vs legitimate shared drives among rows sharing season, round and driver.

4. Component C - Data Cleaning and Pipeline

Prepared jointly by the group; presented by Nicolas Bonilla.

Design and tools. The pipeline is written in Python (pandas) as twelve small, documented steps, each answering specific issues from the Component B register. Python was preferred to Tableau Prep because code can be version-controlled, reviewed and tested. The pipeline runs from the original archive with one command, is deterministic (two runs give byte-identical files) and 14 automated tests protect its key decisions. Every step writes an audit record: rows, changed cells and missing values before and after, and columns added (Appendix C, Table C.2). Each clean row keeps its source file and line, so any value can be traced back to the raw record.

Key decisions.

- **Types first.** A schema makes keys integers and dates real dates (C01).
- **Order matters.** Missing seasons (5) and rounds (7) are restored by deterministic lookup, from the file name and from races.csv, before de-duplication (C02); only then does exact matching find all 34 copies (C03). In the reverse order 11 duplicates survive, which a unit test documents.
- **No invented values.** No statistical imputation is used: the grid sentinel 0 becomes missing plus a flag (C05), and withdrawn entries keep a missing car number because none existed.
- **Separate meanings.** 'position' is kept as position_order, and a new classified_position is filled only for classified drivers (C06).
- **Exhaustive vocabularies.** 136 status values become 8 groups (C07) and countries receive ISO codes; any unmapped value stops the pipeline.
- **Flag, don't delete.** Indianapolis 500 rows and shared drives stay, flagged (C08, C11); points_normalised makes scoring eras comparable (C09).

Reference tables are de-duplicated (5 races, 4 circuits), one person stored under two identifiers is merged and recorded as an alias, names are title-cased and URLs use https (C10). The tables are joined with many-to-one validation, so no join can lose or multiply rows (C11).

Validation and result. 55 gates check schema, keys, foreign keys, vocabularies and ranges (C12); if one fails, nothing is published as clean. The final table has 25,873 rows (34 removed) and 35 documented columns. Of the 29 issues, 18 are fixed, 3 mitigated or flagged, 5 kept and documented, and 3 verified as non-errors (Figure 6).

Trade-offs. Rule-based title-casing cannot restore every spelling, so six names needed curated exceptions. Normalised points improve comparability but hide absolute values, so raw points are kept. The wider table (35 columns) is deliberate: flags preserve information that deletion would destroy. Strict gates make the pipeline fail on any new, unmapped status value, which costs convenience but guarantees that no unexpected category silently reaches an analysis.




Figure 6. Resolution of the 29 Component B issues per quality dimension.

5. Graph Modelling

5.1 Property graph model

The cleaned data are modelled as a labelled property graph (Figure 7) with five node labels - Driver (817), Race (1,149), Constructor (203), Circuit (78) and Country (50) - and seven relationship types. RACED_IN

connects a driver to a race and carries the result as properties (grid, classified position, points, normalised points, status group, car number), so the 25,873 results become edges rather than nodes. DROVE_FOR aggregates a driver's spell with a constructor (first and last season, races, points, wins); HELD_AT and LOCATED_IN place races on circuits and circuits in countries; HAS_NATIONALITY and REGISTERED_IN link drivers and constructors to countries through ISO codes. TEAMMATE_OF is a derived, undirected relationship between drivers who drove for the same constructor in the same race, weighted by the number of shared races. Node keys are the cleaned identifiers and Wikidata QIDs are node properties, so the graph inherits the interoperability work of Component A.

5.2 NetworkX implementation

The graph is built with NetworkX as a MultiDiGraph of 2,297 nodes and 30,141 typed edges and exported to GEXF for Gephi. Analytics run on the TEAMMATE_OF projection (714 drivers, 3,081 weighted links). Following Component B, the 11 Indianapolis 500 rounds are excluded from this projection: there the 'constructor' is a chassis builder used by dozens of independent entrants, which would create false team-mate links.

5.3 Analytics and interpretation

Connectivity and small world. The projection has 42 connected components; a giant component holds 663 drivers (92.9%) and 35 drivers never had a team-mate. Its average clustering coefficient is 0.41, against 0.014 for random graphs of the same size and density, while the average shortest path (4.8 links) stays close to the random benchmark (3.2): a small-world network (sigma = 19). Any two drivers of 75 years are on average fewer than five team-mate links apart; Juan Manuel Fangio reaches Max Verstappen in 8 steps (Juan Fangio - Jo Bonnier - Mario Andretti - Bruno Giacomelli - Andrea de Cesaris - Rubens Barrichello - Jenson Button - Sergio Pérez - Max Verstappen).

Betweenness centrality counts how often a driver lies on the shortest paths between others (Figure 8). The top drivers are not the most successful but the most connective: Jo Bonnier (0.150), Jack Brabham (0.147), Andrea de Cesaris (0.144), Mario Andretti (0.139), Riccardo Patrese (0.135). They combined long careers with many teams and therefore bridge generations; removing them would lengthen the paths between eras. Degree tells a different story, because the highest degrees belong to 1950s-60s drivers such as Stirling Moss (78 team-mates).

PageRank and assortativity. Weighted PageRank, which rewards links to well-connected drivers and long partnerships, ranks Jack Brabham, Graham Hill and Jo Bonnier highest, again early-era drivers. Degree assortativity is slightly positive (0.15): well-connected drivers tend to share teams with other well-connected drivers. The network diameter is 12 links, so even the most distant drivers of the giant component are connected through a dozen team-mate relationships.

Community detection with the Louvain method (modularity 0.70) finds 11 communities. Although the algorithm never sees a date, the large communities line up with eras (Figure 9): the 1950s around Stirling Moss, the 1960s around Jack Brabham and Graham Hill, the 1970s around Ronnie Peterson and Niki Lauda, the 1980s around Riccardo Patrese, two parallel 2000s groups (Barrichello and Schumacher; Alonso and Raikkonen) and the 2010s around Sergio Perez. Small communities capture short-lived teams such as Manor in 2015 (Figure D.1).

What the measures reveal about data quality. In the 1950s and 1960s the constructor field records the chassis make (Cooper, Maserati) shared by many private entrants, so early drivers receive inflated degree and PageRank. Network measures are only as valid as the meaning of the attributes they rest on - a direct link back to documenting semantics (A), profiling them (B) and defining 'team' explicitly (C).




Figure 7. Property graph model with instance counts.




Figure 8. Top 12 drivers by betweenness centrality, with their degree.




Figure 9. Louvain communities and the seasons their drivers were active.

6. The Interactive Dashboard

The project ends where its users begin: an interactive web dashboard (folder `dashboard`, opened with `streamlit run app.py`) that turns the validated outputs into seven views (Figure 10): constructor eras, an all-time timing tower with an era-adjusted score, a grid-to-finish heatmap, reliability over time, a 3D globe of the circuits, the team-mate network and a final view that explains how the data were checked. It is not a separate product. Its data file is generated by `build_web_data.py`, which reads only the outputs of the components, and `run_all.py` calls it as its last step, so the dashboard can never show numbers that the validation gates have not passed (Table 2). Appendix H shows every view.

The dashboard also worked as a quality instrument. Its reliability view showed mechanical failures and accidents vanishing after 2022. The cause was not engineering: from 2023 the source records almost every retirement only as 'Retired', 89% of them in 2023 and all of them in 2024 and 2025. No completeness or uniqueness rule had flagged it, because every value was present and valid. The finding became issue B29 in the quality register, cause analyses are now limited to 1950-2022, and the chart marks the break instead of hiding it. Visual exploration is therefore part of profiling, not only of reporting.

Table 2. Each dashboard view and the project output it is built from.

Dashboard view	Project output it reads	What it shows
Eras, timing tower, grid, circuits	Cleaned results and reference tables (C)	points_normalised, classified_position, ISO codes
Reliability	status_group (C07) and issue B29 (B)	Break in cause recording marked at 2023
Team-mate network	TEAMMATE_OF projection and metrics (graph)	Communities, betweenness, shortest path
How the numbers were checked	Issue register (B), validation gates (C), RDA and PIDs (A)	29 issues, 55 gates, RDA 54% -> 93%




Figure 10. The interactive dashboard: start-light opening, constructor eras, the Fangio-to-Verstappen chain in the team-mate network, and the view that explains how the data were checked.

7. How the Components Connect

The components were designed as one chain with explicit contracts: the issue register is the interface between B and C (every issue names the cleaning step that resolves it, and C measures every issue again after cleaning), the schema module is shared by C and A, and the graph and dashboard read only validated output. Table 3 traces six findings through all components. The dependencies also ran backwards: the dashboard exposed issue B29, the graph analysis revealed that 'constructor' changes meaning over time, a semantic issue that profiling alone had not flagged and that now belongs in the metadata, and Component A's identifier lookup exposed broken links that Component C records for curation. Terminology is shared through the data dictionary, so 'classified position', 'shared drive' and 'status group' mean the same thing in every section.

Table 3. Six examples of how one finding flows through all components.

Finding (B)	Cleaning (C)	FAIR / metadata (A)	Graph and dashboard
Country abbreviations 'UK', 'USA', 'Korea' (B21)	ISO 3166 codes added (C10)	Interoperability gap G4 closed	Country nodes keyed by ISO code
Indy 500 lap outliers (B16)	Kept and flagged is_indy500 (C08)	Flag documented in dictionary	Excluded from TEAMMATE_OF projection
Duplicates with blanked keys (B06, B07)	Key repair before de-duplication (C02, C03)	Checksums and PROV provenance	No double-counted RACED_IN edges
Same driver under two IDs (B20)	Alias merged (C10)	Wikidata QIDs as PIDs	One Driver node per person
'position' set for retirements (B11)	classified_position separated (C06)	Semantics in data dictionary	Correct RACED_IN result property
Causes not recorded from 2023 (B29), found in the dashboard	Mapped to 'Retired (unspecified)' (C07)	Limitation documented	Dashboard marks the break

8. Conclusion

Lessons learned. First, quality is contextual: outliers, duplicates and record-count gaps were often valid history, so every automated rule needed domain verification before anything was deleted. Second, the order of operations matters, as the 11 hidden duplicates show. Third, the largest FAIR gaps were not in the values but around them: no identifier, an inconsistent licence and no provenance. Fourth, validation gates and an audit log turned cleaning from a series of manual edits into evidence an examiner can check. Fifth, generating documentation from code (data dictionary, metadata and this report's figures) kept every artefact consistent with the data, even when the pipeline changed late in the project. Sixth, looking at the data is itself a quality check: the dashboard found an issue that no automated rule had flagged.

Limitations. The seven short races of 2014-2025 match documented absences but should be confirmed against official FIA classifications. The RDA scores are a self-assessment, F-UJI can only test what is online, and the DOI is not minted yet. Title-casing needed manual exceptions, a few Wikidata links are broken, the team concept is ambiguous before the 1970s, and sprint races were left out. Finally, the CC BY-NC-SA 4.0 licence inherited from the source restricts reuse: the curated data may support research and teaching, but not, for example, a commercial betting model.

Recommendations. We recommend publishing the package on Zenodo to obtain a DOI, publishing the status vocabulary as SKOS, modelling 'team' separately from 'chassis', reporting the source defects (duplicated blocks, identifier case) upstream to Jolpica, and running the validation gates automatically whenever new race data arrive, so that quality is checked continuously rather than once.

References

Batini, C., & Scannapieco, M. (2016). *Data and Information Quality: Dimensions, Principles and Techniques*. Springer.

Blondel, V. D., Guillaume, J.-L., Lambiotte, R., & Lefebvre, E. (2008). Fast unfolding of communities in large networks. *Journal of Statistical Mechanics*, P10008.

DataCite Metadata Working Group (2024). *DataCite Metadata Schema 4.5*. https://schema.datacite.org/meta/kernel-4.5/

Devaraju, A., & Huber, R. (2021). An automated solution for measuring the progress toward FAIR research data. *Patterns*, 2(11), 100370.

Freeman, L. C. (1977). A set of measures of centrality based on betweenness. *Sociometry*, 40(1), 35-41.

Hagberg, A., Schult, D., & Swart, P. (2008). Exploring network structure, dynamics, and function using NetworkX. *Proceedings of the 7th Python in Science Conference*, 11-15.

Jolpica-F1 (2025). Jolpica-F1 API and Terms of Use. https://github.com/jolpica/jolpica-f1

Lebo, T., Sahoo, S., & McGuinness, D. (2013). *PROV-O: The PROV Ontology*. W3C Recommendation.

Rao, R. (2025). *Formula 1 World Championship (1950-2024)* [Data set]. Kaggle.

RDA FAIR Data Maturity Model Working Group (2020). *FAIR Data Maturity Model: Specification and Guidelines*. https://doi.org/10.15497/RDA00050

Wang, R. Y., & Strong, D. M. (1996). Beyond accuracy: What data quality means to data consumers. *Journal of Management Information Systems*, 12(4), 5-33.

Watts, D. J., & Strogatz, S. H. (1998). Collective dynamics of 'small-world' networks. *Nature*, 393, 440-442.

Wilkinson, M. D., et al. (2016). The FAIR Guiding Principles for scientific data management and stewardship. *Scientific Data*, 3, 160018.

Appendix A - FAIR Assessment and Metadata (Component A)

Table A.1. FAIR compliance gaps with evidence and actionable improvements.

Gap	Title	RDA indicators	Evidence	Improvement	Status
G1	No persistent identifier for the data or metadata	RDA-F1-01D; RDA-F1-01M; RDA-F3-01M; RDA-A1-03D	F-UJI FsF-F1-02D = 0 for the GitHub archive, the Jolpica API and even the Kaggle mirror; data are only reachable by mutable URLs.	Publish each release of the curated package through the GitHub-Zenodo integration to mint a versioned DOI (prefix 10.5281) and a concept DOI; cite the DOI in README and CITATION.cff.	Prepared (DataCite record with DOI placeholder); minting requires the group's Zenodo account.
G2	Missing and conflicting licence information	RDA-R1.1-01M; RDA-R1.1-02M; RDA-R1.1-03M	Jolpica TERMS.md (27 Aug 2025): data licensed CC BY-NC-SA 4.0. The group's README declares 'MIT License' for everything; the Kaggle mirror declares CC0 although Ergast allowed non-commercial use only. F-UJI FsF-R1.1-01M = 0 for GitHub and Jolpica.	License the data CC BY-NC-SA 4.0 (ShareAlike obliges it), add LICENSE-DATA with the SPDX id CC-BY-NC-SA-4.0 and the legal-code URI, keep MIT for code only, and attribute Jolpica-F1 and Ergast.	Implemented in DataCite rightsList, schema.org license and datapackage.json.
G3	No machine-readable, standard dataset metadata	RDA-F2-01M; RDA-F4-01M; RDA-I1-01M; RDA-R1-01M; RDA-R1.3-01M; RDA-R1.3-02M	Only a pipeline README; F-UJI FsF-F2-01M = 0.5/2 (GitHub) and 0/2 (Jolpica); FsF-R1-01MD = 1/4 and 0/4.	Ship a DataCite 4.5 record (XML validated against the XSD), schema.org Dataset JSON-LD for search engines and a Frictionless Data Package with a full data dictionary.	Implemented.
G4	Non-standard vocabularies inside the data	RDA-I2-01D; RDA-I1-02D	Country values 'UK', 'USA', 'UAE', 'Korea'; nationalities as lowercase demonyms including former states ('east german', 'rhodesian'); 136 free-text status values mixing laps-behind with failure causes.	Add ISO 3166-1 alpha-3 codes (ISO 3166-3 for former states), Wikidata QIDs, and an 8-category status vocabulary; publish the status vocabulary as SKOS.	ISO codes, QIDs and status groups implemented; SKOS publication proposed.
G5	No provenance or integrity information	RDA-R1.2-01M; RDA-R1.2-02M	The repository never names Ergast or Jolpica as the source; no checksums; no record of transformations; the original Ergast terms page now returns 404.	Record derivation (DataCite IsDerivedFrom), SHA-256 checksums of every source and output file, the cleaning audit log, and a W3C PROV-O graph.	Implemented.
G6	Unqualified and partly broken links to external entities	RDA-I3-01D; RDA-I3-02D	861 of 864 driver URLs use http; 12 entities have no URL; 1 driver URL is a Wikipedia talk page (monarch); 2 constructor pages no longer exist (Hall, Turner).	Normalise to https and add Wikidata QIDs as persistent entity identifiers; flag unresolved links for manual curation.	Implemented (QID crosswalk in data/reference/).
G7	No guarantee that metadata outlives the data	RDA-A2-01M	The Ergast API was shut down and is only mirrored by a volunteer project (Jolpica) that 'does not guarantee uptime'; GitHub repositories can be deleted.	Deposit in a certified repository (Zenodo/CERN) whose policy keeps metadata and a tombstone page after withdrawal.	Proposed; requires deposit.

Table A.2a. F-UJI 4.0.1 results (metrics v0.5); raw JSON responses in outputs/component_a_fair/fuji/.

Resource	URL	FAIR %	F %	A %	I %	R %
github_repository	https://github.com/zalkimanohar/Formula1-Racing-Analytics	31.25	35.71	33.33	25.0	30.0
jolpica_ergast_api	http://api.jolpi.ca/ergast/f1/	8.33	14.29	33.33	0.0	0.0
kaggle_ergast_mirror	https://www.kaggle.com/datasets/rohanrao/formula-1-world-championship-1950-2020	64.58	50.0	100.0	75.0	60.0

Table A.2b. RDA FAIR Data Maturity Model summary (41 indicators; per-indicator scores and evidence in rda_fair_assessment.csv).

Area	Indicators	Progress obtained %	Essential obtained	Level obtained	Progress curated %	Essential curated	Level curated
Findable	7	50.0	1/7	0	82.1	2/7	0
Accessible	12	83.3	5/8	0	93.8	5/8	0
Interoperable	12	37.5	0/0	1	93.8	0/0	2
Reusable	10	40.0	0/5	0	100.0	5/5	5
Overall	41	53.7	6/20		93.3	12/20	

Table A.3. Complete DataCite 4.5 metadata record of the curated dataset (JSON form; the equivalent XML validates against the kernel-4.5 XSD). The DOI and creator names are placeholders until deposit.

DataCite property	Value
doi	10.5281/zenodo.TO-BE-MINTED
prefix	10.5281

DataCite property	Value
suffix	zenodo.TO-BE-MINTED
creators	- name: Adhikari, Chirag; nameType: Personal; givenName: Chirag; familyName: Adhikari; nameIdentifiers: nameIdentifier: TO-BE-ADDED; nameIdentifierScheme: ORCID; schemeUri: https://orcid.org; affiliation: name: SRH University [campus and ROR to be confirmed] - name: Zalki, Manohar; nameType: Personal; givenName: Manohar; familyName: Zalki; nameIdentifiers: nameIdentifier: TO-BE-ADDED; nameIdentifierScheme: ORCID; schemeUri: https://orcid.org; affiliation: name: SRH University [campus and ROR to be confirmed] - name: Bonilla, Nicolas; nameType: Personal; givenName: Nicolas; familyName: Bonilla; nameIdentifiers: nameIdentifier: TO-BE-ADDED; nameIdentifierScheme: ORCID; schemeUri: https://orcid.org; affiliation: name: SRH University [campus and ROR to be confirmed]
titles	- title: Formula 1 World Championship Race Results 1950-2025: Curated and Quality-Assessed Dataset; lang: en - title: Cleaned, FAIR-documented derivative of the Ergast/Jolpica-F1 race results; titleType: Subtitle; lang: en
publisher	name: Zenodo
publicationYear	2026
subjects	- subject: Formula One; subjectScheme: Wikidata; schemeUri: https://www.wikidata.org/wiki/; valueUri: https://www.wikidata.org/wiki/Q1968; lang: en - subject: auto racing; subjectScheme: Wikidata; schemeUri: https://www.wikidata.org/wiki/; valueUri: https://www.wikidata.org/wiki/Q5386; lang: en - subject: sport; subjectScheme: Wikidata; schemeUri: https://www.wikidata.org/wiki/; valueUri: https://www.wikidata.org/wiki/Q349; lang: en - subject: motorsport; lang: en - subject: race results; lang: en - subject: sports analytics; lang: en - subject: data quality; lang: en - subject: data cleaning; lang: en - subject: FAIR data; lang: en - subject: Ergast; lang: en
contributors	- name: Ergast Developer API; nameType: Organizational; contributorType: DataCollector - name: Jolpica-F1; nameType: Organizational; contributorType: Distributor - name: SRH University [campus and ROR to be confirmed]; nameType: Organizational; contributorType: HostingInstitution
dates	- date: 2026-11-09; dateType: Created - date: 2026-10-15; dateType: Collected; dateInformation: Modification dates of the files in the raw archive - date: 1950-05-13/2025-12-07; dateType: Other; dateInformation: Temporal coverage: first and last race day in the dataset
language	en
types	resourceTypeGeneral: Dataset; resourceType: Tabular sports results
relatedIdentifiers	- relatedIdentifier: https://api.jolpi.ca/ergast/f1/; relatedIdentifierType: URL; relationType: IsDerivedFrom; resourceTypeGeneral: Service - relatedIdentifier: http://ergast.com/mrd/; relatedIdentifierType: URL; relationType: IsDerivedFrom; resourceTypeGeneral: Service - relatedIdentifier: https://github.com/zalkimanohar/Formula1-Racing-Analytics/blob/main/racing_f1_data.zip; relatedIdentifierType: URL; relationType: IsDerivedFrom; resourceTypeGeneral: Dataset - relatedIdentifier: https://github.com/zalkimanohar/Formula1-Racing-Analytics; relatedIdentifierType: URL; relationType: IsSupplementTo; resourceTypeGeneral: Software - relatedIdentifier: https://www.kaggle.com/datasets/rohanrao/formula-1-world-championship-1950-2020; relatedIdentifierType: URL; relationType: References; resourceTypeGeneral: Dataset
sizes	- f1_race_results_clean.csv: 25873 rows, 7278022 bytes - races_clean.csv: 1173 rows, 135632 bytes - circuits_clean.csv: 78 rows, 10155 bytes - drivers_clean.csv: 873 rows, 99662 bytes - constructors_clean.csv: 214 rows, 17970 bytes
formats	- text/csv - application/ld+json - application/xml
version	1.0.0
rightsList	rights: Creative Commons Attribution Non Commercial Share Alike 4.0 International; rightsUri: https://creativecommons.org/licenses/by-nc-sa/4.0/legalcode; rightsIdentifier: CC-BY-NC-SA-4.0; rightsIdentifierScheme: SPDX; schemeUri: https://spdx.org/licenses/; lang: en
descriptions	- description: Race results of every FIA Formula One World Championship Grand Prix from 1950-05-13 to 2025-12-07 (76 seasons, 1149 Grands Prix, 25,873 driver entries, 817 drivers, 203 constructor entries, 77 circuits in 34 countries). The dataset is a cleaned, documented derivative of the Ergast database as served by the Jolpica-F1 API. Duplicates, missing keys, sentinel values, inconsistent identifiers and free-text categories were resolved; legitimate historical shared drives were kept and flagged; ISO 3166 country codes and Wikidata identifiers were added.; descriptionType: Abstract - description: Extracted from racing_f1_data.zip (SHA-256 81b027c4221901d92d30ad7b76eacf22668d299098e5c16dcb391c91fd39c748) without modifying values, profiled across completeness, uniqueness, validity, consistency, accuracy and timeliness, and cleaned with a reproducible Python/pandas pipeline that logs before/after statistics for every step. Source code, audit log and quality report are part of the package.; descriptionType: Methods - description: UTF-8 encoded CSV (RFC 4180), comma separated, header row, ISO 8601 dates. Primary key of the fact table: result_id. Column definitions in data_dictionary.csv and datapackage.json.; descriptionType: TechnicalInfo - description: Points follow the scoring rules of each season; use points_normalised for cross-era comparisons. Indianapolis 500 rounds (1950-1960) are flagged with is_indy500. Prepared for deposit in Zenodo; the DOI shown is a placeholder until minted.; descriptionType: Other
geoLocations	78 entries: 'Worldwide' plus one geoLocationPoint per circuit (77 points with latitude/longitude; listed in datacite_metadata.xml)

Table A.4. Wikidata QID coverage of entity identifiers.

entity_type	records	with_url	with_qid	qid_coverage_percent
circuit	82	82	82	100.0
constructor	214	212	210	98.1
driver	874	864	863	98.7

Appendix B - Data Quality Profiling (Component B)

Table B.1. Quality issue register (evidence, root cause and impact per issue in quality_issues.md).

ID	Dimension	Table	Issue	Affected	%	Severity	Error	Resolved by
B01	Completeness	results	Season missing	5	0.019	High	True	C02

ID	Dimension	Table	Issue	Affected	%	Severity	Error	Resolved by
B02	Completeness	results	Round missing	7	0.027	High	True	C02
B03	Completeness	results	Car number missing	6	0.023	Low	False	C01
B04	Completeness	results	Disguised missing value: grid = 0 sentinel	267	1.031	Medium	True	C05
B05	Completeness	results	Races with fewer entries than the season norm (2014+): verified, not data loss	7	2.778	Info	False	None (verified as genuine)
B06	Uniqueness	results	Exact duplicate records	23	0.089	High	True	C03
B07	Uniqueness	results	Hidden duplicates masked by missing keys	11	0.042	High	True	C02 + C03
B08	Uniqueness	results	Natural-key collisions that are NOT errors (shared drives)	172	0.664	Info	False	C11 (flag is_shared_drive)
B09	Validity	results	Identifier violates lowercase convention	2	0.008	Medium	True	C04
B10	Validity	results	Incorrect storage types (integers stored as floats, dates stored as text)	25907	100.0	Medium	True	C01
B11	Validity	results	'position' is filled for drivers who were not classified	9646	37.233	High	True	C06
B12	Consistency	results	Non-standard categorical values: free-text status	25907	100.0	Medium	True	C07
B13	Consistency	results	Contradiction: retired ('R') but status says lapped finish	26	0.1	Low	True	C06 (flag status_position_conflict)
B14	Consistency	results	Inconsistent text formatting (proper names stored in lowercase)	25907	100.0	Low	True	C10, C11
B15	Consistency	results	Points not comparable across eras (scoring rules changed)	8425	32.52	Medium	True	C09
B16	Accuracy	results	Statistical outliers that are valid (Indianapolis 500)	270	1.042	Info	False	C08
B17	Referential integrity	results	Results that cannot be linked to a race	11	0.042	High	True	C02
B18	Uniqueness	races	Duplicate race records	5	0.424	Medium	True	C10
B19	Uniqueness	circuits	Duplicate circuits (exact copies and copies without ID)	4	4.878	Medium	True	C10
B20	Uniqueness	drivers	Same person under two identifiers	2	0.229	Medium	True	C10
B21	Validity	circuits	Country names not in a standard vocabulary	19	23.171	Medium	True	C10
B22	Completeness	circuits	Missing coordinates	1	1.22	Low	True	Documented (kept missing)
B23	Completeness	drivers / constructors	Missing attributes for newest entities	12	1.103	Low	True	Documented (kept missing)
B24	Timeliness	races	Reference calendar ahead of the results snapshot	24	2.037	Low	False	C10 (flag has_results)
B25	Consistency	drivers / constructors	Mixed URL schemes (http vs https)	1073	45.933	Low	True	C10
B26	Consistency	drivers / circuits	Proper names stored in lowercase	956	100.0	Low	True	C10
B27	Accuracy	circuits	Name differs from the official spelling	2	2.439	Low	True	Documented (kept, alias noted)
B28	Consistency	source package	Mixed file formats in one package	8	8.602	Low	True	Step 0 (format detection in manifest)
B29	Consistency	results	Retirement causes no longer recorded in recent seasons	129	0.498	Medium	True	C07 (mapped to 'Retired (unspecified)'; cause analyses limited to earlier seasons)

Table B.2. Root-cause hypotheses and downstream impact for the key issues.

ID	Root-cause hypothesis	Downstream impact on data science / AI
B04	Source encodes 'pit-lane start / no grid slot' as 0 instead of null.	Grid-vs-result models treat 0 as pole-better-than-pole; mean grid is biased low; correlation with finishing position is distorted.
B06	A block of rows was appended twice (copy/paste or a re-run of an append-only load).	Double-counts points and wins, inflates sample weight of one race, leaks identical rows across train/test splits.
B07	The duplicated block of B06 was additionally damaged (keys blanked), so naive exact-match de-duplication misses it.	Same as B06; also shows that cleaning order matters (repair keys before de-duplicating).
B08	Historic rule allowed a driver to take over a team-mate's car; each car is a separate classified entry.	Naive de-duplication on (season, round, driver) would delete real history; the correct key includes the car number.
B11	Source semantics: 'position' is the order of finishing incl. retirements, not the official result.	Analyses that treat 'position' as the result (e.g. grid-vs-finish regressions, the project dashboard) count a retirement as e.g. 18th place, biasing targets for prediction models.
B12	Status is recorded verbatim from race reports over 75 years without a controlled vocabulary.	One-hot encoding creates 136 sparse features; reliability analyses (DNF causes) cannot be aggregated.
B15	Not a recording error: FIA scoring systems changed (1950, 1960, 1961, 1991, 2003, 2010, 2014 double points, 2019 fastest lap).	All-time rankings and models using raw points are dominated by the post-2010 era (25 points per win).
B16	Indy 500 (200 laps, 1950-1960) counted for the championship under different rules.	Removing them as 'outliers' would delete valid history; keeping them unflagged skews lap-based features.
B21	Abbreviations typed by hand; no ISO 3166 codes in the source.	Geo joins and choropleth maps fail (the dashboard map showed only 1 country); no interoperability.

Table B.3. Rules that were tested and passed.

Dimension	Rule	Violations	Result
Referential integrity	results.driverId exists in drivers	0	passed
Referential integrity	results.constructorId exists in constructors	0	passed
Referential integrity	races.circuitId exists in circuits	0	passed
Consistency	results.date equals races.date for the same race	0	passed
Consistency	results.raceName equals races.raceName	0	passed
Consistency	numeric positionText equals position	0	passed
Consistency	year of date equals season (where season present)	0	passed
Validity	no negative points, grid or laps	0	passed
Validity	points > 0 only for rows with a position	0	passed
Validity	all dates parse as ISO 8601	0	passed
Accuracy	driver age at race between 16 and 60 years	0	passed
Accuracy	circuit coordinates within valid lat/long ranges	0	passed
Uniqueness	driverId unique in drivers	0	passed
Uniqueness	constructorId unique in constructors	0	passed




Figure B.1. Points for a race win by season: raw points are not comparable across scoring eras.




Figure B.2. Laps completed: every value beyond the IQR fence is a valid Indianapolis 500 result.

Appendix C - Cleaning Pipeline (Component C)

Table C.1. Issue resolution: every Component B issue measured again on the cleaned data.

ID	Dimension	Issue	Before	After	Resolution
B01	Completeness	Season missing	5	0	Fixed
B02	Completeness	Round missing	7	0	Fixed
B03	Completeness	Car number missing	6	6	Kept missing (structurally not applicable)
B04	Completeness	Disguised missing value: grid = 0 sentinel	267	0	Fixed (sentinel -> missing + flag)
B05	Completeness	Races with fewer entries than the season norm (2014+): verified, not data loss	7	-	Not an error (verified)
B06	Uniqueness	Exact duplicate records	23	0	Fixed
B07	Uniqueness	Hidden duplicates masked by missing keys	11	0	Fixed (keys repaired before de-duplication)
B08	Uniqueness	Natural-key collisions that are NOT errors (shared drives)	172	337	Not an error (kept and flagged)
B09	Validity	Identifier violates lowercase convention	2	0	Fixed
B10	Validity	Incorrect storage types (integers stored as floats, dates stored as text)	25907	0	Fixed (schema enforced)
B11	Validity	'position' is filled for drivers who were not classified	9646	0	Fixed (classified_position separated from position_order)
B12	Consistency	Non-standard categorical values: free-text status	25907	0	Fixed (136 values -> 8 controlled groups; raw kept)
B13	Consistency	Contradiction: retired ('R') but status says lapped finish	26	26	Flagged (kept)
B14	Consistency	Inconsistent text formatting (proper names stored in lowercase)	25907	0	Fixed
B15	Consistency	Points not comparable across eras (scoring rules changed)	8425	-	Mitigated (points_normalised added)
B16	Accuracy	Statistical outliers that are valid (Indianapolis 500)	270	270	Not an error (kept and flagged)
B17	Referential integrity	Results that cannot be linked to a race	11	0	Fixed
B18	Uniqueness	Duplicate race records	5	0	Fixed
B19	Uniqueness	Duplicate circuits (exact copies and copies without ID)	4	0	Fixed
B20	Uniqueness	Same person under two identifiers	2	0	Fixed (1 alias recorded)
B21	Validity	Country names not in a standard vocabulary	19	0	Fixed (ISO 3166 codes added)
B22	Completeness	Missing coordinates	1	1	Kept missing (documented)
B23	Completeness	Missing attributes for newest entities	12	11	Kept missing (documented)
B24	Timeliness	Reference calendar ahead of the results snapshot	24	24	Flagged (has_results)
B25	Consistency	Mixed URL schemes (http vs https)	1073	0	Fixed
B26	Consistency	Proper names stored in lowercase	956	0	Fixed
B27	Accuracy	Name differs from the official spelling	2	1	Kept (documented alias)
B28	Consistency	Mixed file formats in one package	8	0	Handled at extraction (manifest)
B29	Consistency	Retirement causes no longer recorded in recent seasons	129	129	Kept and documented (cause unknown in source; cause analyses limited to 1950-2022)

Table C.2. Audit log with before/after statistics per step (step details in audit_log.md).

Step	Name	Issues	Table	Rows before	Rows after	Cells changed	Missing before	Missing after
C01	Enforce schema and data types	B10, B03	results	25907	25907	0	18	18
C02	Repair missing keys by deterministic lookup	B01, B02, B17	results	25907	25907	12	18	6
C03	Remove exact duplicates (after key repair)	B06, B07	results	25907	25873	0	6	6
C04	Standardise identifiers	B09	results	25873	25873	2	6	6
C05	Replace grid sentinel 0 with missing + flag	B04	results	25873	25873	267	6	273
C06	Separate classification from finishing order	B11, B13	results	25873	25873	0	273	273
C07	Standardise status into 8 groups	B12	results	25873	25873	0	9911	9911
C08	Flag statistical outliers (keep valid extremes)	B16	results	25873	25873	0	9911	9911
C09	Normalise points across scoring eras	B15	results	25873	25873	0	9911	9911
C10a	Clean races reference table	B18, B24, B25	races	1178	1173	1173	0	0
C10b	Clean circuits reference table	B19, B21, B22, B25, B26	circuits	82	78	174	4	2
C10c	Clean drivers reference table	B09, B20, B21, B23, B25, B26	drivers	874	873	3475	28	25
C10d	Clean constructors reference table	B21, B23, B25	constructors	214	214	426	2	2
C11	Integrate into analysis-ready table	B08, B14	results	25873	25873	25873	9911	9911
C12	Validation gates	all	results	25873	25873	0	9911	9911

Table C.3. All 55 validation gates (C12).

Validation gate	Result
columns match schema (names and order)	passed
no missing values in required column result_id	passed
no missing values in required column race_id	passed
no missing values in required column season	passed
no missing values in required column round	passed
no missing values in required column race_name	passed
no missing values in required column race_date	passed
no missing values in required column circuit_id	passed
no missing values in required column circuit_name	passed
no missing values in required column circuit_locality	passed
no missing values in required column circuit_country	passed
no missing values in required column circuit_country_iso3	passed
no missing values in required column driver_id	passed
no missing values in required column driver_name	passed
no missing values in required column constructor_id	passed
no missing values in required column constructor_name	passed
no missing values in required column constructor_nationality_iso3	passed
no missing values in required column grid_position_missing	passed
no missing values in required column laps_completed	passed
no missing values in required column points	passed
no missing values in required column points_normalised	passed
no missing values in required column position_order	passed
no missing values in required column position_text	passed
no missing values in required column finish_category	passed
finish_category uses controlled vocabulary	passed
no missing values in required column status_raw	passed
no missing values in required column status_group	passed
status_group uses controlled vocabulary	passed
no missing values in required column is_shared_drive	passed
no missing values in required column is_indy500	passed
no missing values in required column laps_outlier_iqr	passed
no missing values in required column status_position_conflict	passed
no missing values in required column source_file	passed
no missing values in required column source_line	passed
result_id unique	passed
natural key (season, round, driver_id, car_number) unique	passed
no exact duplicate records	passed
season within snapshot	passed
every race_id exists in races	passed
every circuit_id exists in circuits	passed
every driver_id exists in drivers	passed
every constructor_id exists in constructors	passed
identifiers are lowercase	passed
grid_position >= 1 when present	passed
classified_position missing for every non-classified result	passed
points_normalised within [0, 1]	passed
one winner share of 1.0 per race	passed
duplicate classified positions only occur in shared drives	passed
race names are not all-lowercase	passed
country codes present for every circuit	passed
races table: race_id unique	passed
circuits table: circuit_id unique and present	passed

Validation gate	Result
drivers table: driver_id unique	passed
drivers table: no person under two IDs	passed
reference URLs use https	passed




Figure C.1. Status standardisation: 136 raw values mapped to 8 groups.

Appendix D - Graph Metrics

Table D.1. Network-level metrics.

Metric (team-mate projection)	Value
drivers in projection	714
teammate links	3,081
density	0.0121
connected components	42
giant component drivers	663
giant component share	0.9286
isolated drivers	35
average degree	8.6303
average clustering giant	0.4073
average shortest path giant	4.8165
diameter giant	12
random graph clustering	0.0141
random graph shortest path	3.1626
small world sigma	18.9881
louvain communities	11
modularity	0.6967
degree assortativity	0.1538

Table D.2. Top 12 drivers by betweenness centrality.

Driver	First	Last	Degree	Betweenness	PageRank	Community
Jo Bonnier	1956	1971	65	0.1504	0.0094	3
Jack Brabham	1955	1970	77	0.1474	0.0113	3
Andrea de Cesaris	1980	1994	19	0.1443	0.005	5
Mario Andretti	1968	1982	23	0.1387	0.0046	4
Riccardo Patrese	1977	1993	14	0.1354	0.0055	5
Rolf Stommelen	1970	1978	20	0.134	0.0029	4
Rubens Barrichello	1993	2011	15	0.0936	0.0052	7
Michael Schumacher	1991	2012	11	0.0812	0.0048	7
Jacques Laffite	1974	1986	18	0.0738	0.0038	4
Jacky Ickx	1967	1979	26	0.0688	0.0046	4
Nigel Mansell	1980	1995	9	0.0658	0.0041	5
Nico Hülkenberg	2010	2025	11	0.0561	0.0037	10

Table D.3. Louvain communities.

Community	Drivers	First debut	Median debut	Last active	Most central drivers (PageRank)
1	135	1950	1952.0	1964	Stirling Moss; Maurice Trintignant; Louis Rosier
2	5	1954	1954.0	1955	Leslie Marr; Don Beauman; John Riseley-Prichard
3	173	1952	1961.0	1977	Jack Brabham; Graham Hill; Jo Bonnier
4	110	1963	1974.0	1986	Ronnie Peterson; Niki Lauda; Carlos Reutemann
5	93	1975	1986.0	2002	Riccardo Patrese; Michele Alboreto; Nelson Piquet
6	13	1985	1993.0	2009	Pierluigi Martini; Gianni Morbidelli; Luca Badoer
7	32	1989	2001.5	2025	Rubens Barrichello; Michael Schumacher; Lewis Hamilton
8	48	1988	2001.5	2025	Fernando Alonso; Kimi Räikkönen; Jarno Trulli
9	2	2003	2003.5	2004	Zsolt Baumgartner; Gianmaria Bruni
10	49	2005	2015.0	2025	Sergio Pérez; Nico Hülkenberg; Daniel Ricciardo
11	3	2014	2015.0	2015	Will Stevens; Roberto Merhi; Alexander Rossi

Table D.4. Shortest team-mate path from Juan Manuel Fangio to Max Verstappen.

From	To	Shared constructor	Races together
Juan Fangio	Jo Bonnier	maserati	5
Jo Bonnier	Mario Andretti	lotus-ford	1
Mario Andretti	Bruno Giacomelli	alfa	15
Bruno Giacomelli	Andrea de Cesaris	alfa	18
Andrea de Cesaris	Rubens Barrichello	jordan	2
Rubens Barrichello	Jenson Button	brawn, honda	70
Jenson Button	Sergio Pérez	mclaren	19
Sergio Pérez	Max Verstappen	red_bull	90




Figure D.1. Team-mate network (giant component) coloured by Louvain community; node size = betweenness.

Appendix E - Data Dictionary of the Cleaned Results Table

Table E.1. Variables of f1_race_results_clean.csv (all tables in data_dictionary.md).

Column	Type	Description	Nullable
result_id	string	Deterministic surrogate key: season_round_driverId_carNumber.	False
race_id	string	Identifier of the Grand Prix: season and round.	False
season	Int64	Championship season (year).	False
round	Int64	Round number of the race within the season.	False
race_name	string	Official Grand Prix name in title case.	False
race_date	date	Race day.	False
circuit_id	string	Circuit identifier (Ergast convention).	False
circuit_name	string	Circuit name in title case.	False
circuit_locality	string	City or locality of the circuit.	False
circuit_country	string	Country of the circuit; abbreviations expanded (UK, USA, UAE, Korea), other names kept as in source.	False
circuit_country_iso3	string	Country of the circuit.	False
driver_id	string	Driver identifier, lowercase snake case.	False
driver_name	string	Driver full name in title case.	False
driver_nationality_iso3	string	Driver nationality as a country code (ISO 3166-3 code for former states).	True
constructor_id	string	Constructor (team) identifier.	False
constructor_name	string	Constructor name.	False
constructor_nationality_iso3	string	Constructor nationality as a country code.	False
car_number	Int64	Race number of the car. Missing for some withdrawn entries.	True
grid_position	Int64	Starting grid slot. Missing when the source used the sentinel 0 (pit-lane start or no grid slot).	True
grid_position_missing	boolean	True when the source grid value was the sentinel 0.	False
laps_completed	Int64	Laps completed in the race.	False
points	float	Championship points awarded, as published for that season's rules.	False
points_normalised	float	Points divided by the highest points total awarded in the same race (0-1), comparable across scoring eras.	False
position_order	Int64	Finishing order including retirements (source field 'position'). Not a classification.	False
classified_position	Int64	Official classified finishing position. Missing when the driver was not classified.	True
position_text	string	Source classification code: a number, R, W or D.	False
finish_category	string	Classification outcome derived from position_text.	False
status_raw	string	Original free-text status (136 values).	False
status_group	string	Standardised status category.	False
is_shared_drive	boolean	True when the car or the driver appears more than once in the same race (historic shared drives).	False
is_indy500	boolean	True for Indianapolis 500 rounds (1950-1960), which counted for the title but used different rules.	False
laps_outlier_iqr	boolean	True when laps_completed lies outside the 1.5 x IQR fences.	False
status_position_conflict	boolean	True when position_text says retired (R) but the status describes a lapped finish.	False
source_file	string	Lineage: source file inside racing_f1_data.zip.	False
source_line	Int64	Lineage: line number inside the source file.	False

Appendix F - Reproducibility and Deliverables

Requirements: Python 3.11+, packages in requirements.txt. From the folder data_management_project run `python run_all.py --from-scratch` (about 70 s, no network needed), then `python -m pytest -q` and `python -m src.build_report`.

Table F.1. Map of the assignment deliverables.

Deliverable	Location in the ZIP
1 Joint written report	report/F1_Data_Management_Joint_Report.docx / .pdf
2 Python cleaning scripts	src/cleaning.py, src/vocabularies.py, src/schema.py, run_all.py, tests/
3 Tableau Prep flow	not used (pipeline fully in Python)
4 Metadata record	outputs/component_a_fair/datacite_metadata.xml/.json, schema_org_dataset.jsonld, datapackage.json, provenance_prov.jsonld
5 FAIR assessment evidence	outputs/component_a_fair/fuji/*.json, fig_a2_fuji_scores.png, rda_fair_assessment.csv, license_evidence/
6 Quality visualisations	outputs/component_b_quality/figures/*.png
7 Original + cleaned datasets	data/raw/f1_race_results_raw.csv, data/cleaned/f1_race_results_clean.csv (+ reference tables)
8 Graph files	src/graph_model.py, outputs/graph/*.gexf, outputs/graph/figures/*.png
Extra: interactive dashboard	dashboard/ (app.py, build_web_data.py, static/); screenshots in outputs/dashboard/
9 Individual reflection logs	submitted individually (drafts in report/reflection_drafts/)

Appendix G - Declaration of AI Tool Use

In line with the course rules, all use of AI tools is declared here. The group used Claude Code (Anthropic; models Claude Haiku 4.5 and Claude Opus 5.5) as an AI programming assistant, with the instructor's agreement for extensive use. It was used to: write and debug the Python code (extraction, profiling, cleaning, metadata generation, graph analytics, the interactive dashboard and this report builder); run the F-UJI tool locally and summarise its output; retrieve licence terms and Wikidata identifiers from primary sources; draft text for the report sections; and generate the figures.

Human responsibilities: choosing the dataset and the analysis direction, reviewing every cleaning decision and its domain justification, checking that numbers in the text match the outputs, and editing each component section and the reflection logs, which remain the work of the responsible student. All factual claims (licences, F-UJI scores, historical events) were checked against the cited evidence files included in the ZIP.

Appendix H - Dashboard Gallery

Screenshots of the running dashboard (`streamlit run app.py` in the `dashboard` folder). Every number shown is read from the validated project outputs.




Figure H.1. Opening: the start-light sequence, then the key figures of the dataset.



Figure H.2. Who ruled each era: share of wins by constructor per season, with the computed finding.




Figure H.3. The all-time timing tower: rank by wins, podiums, pole starts, era-adjusted score or points; replays season by season.




Figure H.4. Grid to finish: share of drivers from each starting slot finishing in each position, with pole conversion by decade and the furthest-back winners.




Figure H.5. Reliability: outcomes of every start, with the 2023 break in cause recording (issue B29) marked.




Figure H.6. Circuits: rotating globe and ranking by Grands Prix hosted.



Figure H.7. Team-mate network with the shortest chain from Juan Manuel Fangio to Max Verstappen.




Figure H.8. How the numbers were checked: the project pipeline and its key results.