

Fluctuation data analysis in Fusion Relevant Plasmas

Extracting information on relevant underlying dynamics

N. Vianello

June 15, 2011

Diagnostics provides information with different time and spatial resolution

1. Measurements coming from a single point
2. Spatially distributed arrays of measurements (resolving portion of the plasma or entire torus)
3. line integrated measurements (single Line Of Sight (LoS))
4. Arrays of LoS (examples are tomographic reconstruction)

Diagnostics provides information with different time and spatial resolution

1. Measurements coming from a single point
2. Spatially distributed arrays of measurements (resolving portion of the plasma or entire torus)
3. line integrated measurements (single Line Of Sight (LoS))
4. Arrays of LoS (examples are tomographic reconstruction)

Diagnostics provides information with different time and spatial resolution

1. Measurements coming from a single point
2. Spatially distributed arrays of measurements (resolving portion of the plasma or entire torus)
3. line integrated measurements (single Line Of Sight (LoS))
4. Arrays of LoS (examples are tomographic reconstruction)

Diagnostics provides information with different time and spatial resolution

1. Measurements coming from a single point
2. Spatially distributed arrays of measurements (resolving portion of the plasma or entire torus)
3. line integrated measurements (single Line Of Sight (LoS))
4. Arrays of LoS (examples are tomographic reconstruction)

Diagnostics provides information with different time and spatial resolution

1. Measurements coming from a single point
2. Spatially distributed arrays of measurements (resolving portion of the plasma or entire torus)
3. line integrated measurements (single Line Of Sight (LoS))
4. Arrays of LoS (examples are tomographic reconstruction)

We will focus on analysis technique suitable for single-point/multi point measurements, extracting information on spatial/temporal dynamics

- ▶ Generally theories are developed in the frequency/wavevector domains (ω, \mathbf{k}) rather than in time/space (t, r)

- ▶ Generally theories are developed in the frequency/wavevector domains (ω, \mathbf{k}) rather than in time/space (t, r)
- ▶ The reason for that resides principally on the fact that *Fourier transform* of governing equation allows an easier treatment of typical mathematical operator

$$\frac{\partial}{\partial t} \Longrightarrow i\omega; \quad \frac{\partial f}{\partial x_i} \Longrightarrow ik_i \hat{f}(\mathbf{k}, t)$$

- ▶ Generally theories are developed in the frequency/wavevector domains (ω, \mathbf{k}) rather than in time/space (t, r)
- ▶ The reason for that resides principally on the fact that *Fourier transform* of governing equation allows an easier treatment of typical mathematical operator

$$\frac{\partial}{\partial t} \Longrightarrow i\omega; \quad \frac{\partial f}{\partial x_i} \Longrightarrow ik_i \hat{f}(\mathbf{k}, t)$$

Some remarks on basic Fourier Transform and its discrete counterpart the Discrete Fourier Transform are mandatory

Continuous and Discrete Fourier transform 2



CONSORZIO RFX
Ricerca Formazione Innovazione

The **Direct** and **Inverse** fourier transform of a generic function of time $x(t)$ is defined as :

$$X(f) = \int_{-\infty}^{+\infty} x(t) e^{-2\pi i f t} dt$$

$$x(t) = \int_{-\infty}^{+\infty} X(f) e^{2\pi i f t} df$$

Various theorems may be applied to FT

The **Direct** and **Inverse** fourier transform of a generic function of time $x(t)$ is defined as :

$$X(f) = \int_{-\infty}^{+\infty} x(t)e^{-2\pi ift} dt$$

$$x(t) = \int_{-\infty}^{+\infty} X(f)e^{2\pi ift} df$$

Various theorems may be applied to FT

Theorem

Similarity Theorem: If $x(t)$ has the Fourier transform $X(f)$ then $x(at)$ has the Fourier Transform $|a|^{-1}F(f/a)$

This will be useful in the analysis of scaling properties of the fluctuations

The **Direct** and **Inverse** fourier transform of a generic function of time $x(t)$ is defined as :

$$X(f) = \int_{-\infty}^{+\infty} x(t)e^{-2\pi ift} dt$$

$$x(t) = \int_{-\infty}^{+\infty} X(f)e^{2\pi ift} df$$

Various theorems may be applied to FT

Theorem

Addition Theorem: If $x(t)$ and $g(t)$ have FT respectively $X(f)$ and $G(f)$ then $x(t) + g(t)$ has Fourier transform $X(f) + G(f)$

The linearity of Fourier transform allows an easy treatment of linear equation in the Fourier domain

The **Direct** and **Inverse** fourier transform of a generic function of time $x(t)$ is defined as :

$$X(f) = \int_{-\infty}^{+\infty} x(t) e^{-2\pi i f t} dt$$

$$x(t) = \int_{-\infty}^{+\infty} X(f) e^{2\pi i f t} df$$

Various theorems may be applied to FT

Theorem

Shift theorem: If $x(t)$ and $g(t)$ have FT respectively $X(f)$ then $x(t - a)$ has Fourier transform $e^{-2\pi i a f} X(f)$

The **Direct** and **Inverse** fourier transform of a generic function of time $x(t)$ is defined as :

$$X(f) = \int_{-\infty}^{+\infty} x(t)e^{-2\pi ift} dt$$

$$x(t) = \int_{-\infty}^{+\infty} X(f)e^{2\pi ift} df$$

Various theorems may be applied to FT

Theorem

Convolution theorem: If $x(t)$ and $g(t)$ have FT respectively equal to $X(f)$ and $G(f)$ the convolution of the two function $h(t) = \int_{-\infty}^{+\infty} x(t')g(t-t')dt'$ is equal to $X(f)G(f)$

The importance of the convolution equation resides on the fact that it allows treatment of non-linearities as the term $\mathbf{v} \cdot \nabla \mathbf{v}$ in the Navier-Stokes equations

The **Direct** and **Inverse** fourier transform of a generic function of time $x(t)$ is defined as :

$$X(f) = \int_{-\infty}^{+\infty} x(t)e^{-2\pi ift} dt$$

$$x(t) = \int_{-\infty}^{+\infty} X(f)e^{2\pi ift} df$$

Various theorems may be applied to FT

Theorem

Rayleigh's Theorem The integral of squared modulus of a function is equal to the integral of the squared modulus of its spectrum, i.e:

$$\int_{-\infty}^{+\infty} |f(t)|^2 dt = \int_{-\infty}^{+\infty} |F(f)|^2 df$$

This is equivalent to an energy conservation law for the time or frequency domain representation of the signal

- ▶ In practice, signals are acquired using analog-to-digital converters, so discrete signals have to be analyzed

- ▶ In practice, signals are acquired using analog-to-digital converters, so discrete signals have to be analyzed
- ▶ In discrete signal, a continuous function $x(t)$ results in a set of N discrete values of the form $x_n = x(n\Delta t)$ with $n = 0, \dots, N - 1$

- ▶ In practice, signals are acquired using analog-to-digital converters, so discrete signals have to be analyze
- ▶ In discrete signal, a continuous function $x(t)$ results in a set of N discrete values of the form $x_n = x(n\Delta t)$ with $n = 0, \dots, N - 1$
- ▶ The total duration of the signal is equal to $T = N\Delta t$ whereas the *frequency sampling* is $f_s = \frac{1}{\Delta t}$.

- ▶ In practice, signals are acquired using analog-to-digital converters, so discrete signals have to be analyzed
- ▶ In discrete signal, a continuous function $x(t)$ results in a set of N discrete values of the form $x_n = x(n\Delta t)$ with $n = 0, \dots, N - 1$
- ▶ The total duration of the signal is equal to $T = N\Delta t$ whereas the *frequency sampling* is $f_s = \frac{1}{\Delta t}$.
- ▶ A fundamental result of signal analysis is *Sampling Theorem* which states that a function whose Fourier transform is zero for $f > f_c$ is fully specified by values spaced at equal intervals not exceeding $\frac{1}{2}f_c^{-1}$

- ▶ In practice, signals are acquired using analog-to-digital converters, so discrete signals have to be analyzed
- ▶ In discrete signal, a continuous function $x(t)$ results in a set of N discrete values of the form $x_n = x(n\Delta t)$ with $n = 0, \dots, N - 1$
- ▶ The total duration of the signal is equal to $T = N\Delta t$ whereas the frequency sampling is $f_s = \frac{1}{\Delta t}$.
- ▶ A fundamental result of signal analysis is *Sampling Theorem* which states that **A function whose Fourier transform is zero for $f > f_c$ is fully specified by values spaced at equal intervals not exceeding $\frac{1}{2}f_c^{-1}$**
- ▶ **The Nyquist Frequency $f_N = \frac{1}{2\Delta t}$, equivalent to half of the sampling frequency, thus defines the maximum frequency which can be properly resolved, or equivalently given the frequency of the system we would like to investigate, we had to sample at least at twice the values of this frequency.**

- ▶ Given the discreteness of the sampling, also the corresponding Fourier transform will be discrete in the Fourier space.
- ▶ The basic concept of DFT resides on the fact that the algorithm applied on an N -sampled data, will produce an information on N frequencies, assuming that the information is conserved
- ▶ The Fourier transform of a digitized N -sampled data will be of the form $f_n = n\Delta f$ with (if N is even) $-\frac{N}{2} \leq n \leq \frac{N}{2}$. The frequency resolution, in order to span all the allowed frequency range will be of the form $\Delta f = \frac{1}{T} = \frac{1}{\Delta t}$
- ▶ The **Direct** and **Inverse** Discrete Fourier transform are then defined as

$$X_n = \frac{1}{N} \sum_{k=0}^{N-1} x_k e^{-2\pi kn/N}$$

$$x_k = \frac{1}{N} \sum_{n=-N/2}^{N/2} X_n e^{2\pi kn/N}$$

- ▶ Given the discreteness of the sampling, also the corresponding Fourier transform will be discrete in the Fourier space.
- ▶ The basic concept of DFT resides on the fact that the algorithm applied on an N -sampled data, will produce an information on N frequencies, assuming that the information is conserved
- ▶ The Fourier transform of a digitized N -sampled data will be of the form $f_n = n\Delta f$ with (if N is even) $-\frac{N}{2} \leq n \leq \frac{N}{2}$. The frequency resolution, in order to span all the allowed frequency range will be of the form $\Delta f = \frac{1}{T} = \frac{1}{\Delta t}$
- ▶ The **Direct** and **Inverse** Discrete Fourier transform are then defined as

$$X_n = \frac{1}{N} \sum_{k=0}^{N-1} x_k e^{-2\pi kn/N}$$

$$x_k = \frac{1}{N} \sum_{n=-N/2}^{N/2} X_n e^{2\pi kn/N}$$

- ▶ Given the discreteness of the sampling, also the corresponding Fourier transform will be discrete in the Fourier space.
- ▶ The basic concept of DFT resides on the fact that the algorithm applied on an N -sampled data, will produce an information on N frequencies, assuming that the information is conserved
- ▶ The Fourier transform of a digitized N -sampled data will be of the form $f_n = n\Delta f$ with (if N is even) $-\frac{N}{2} \leq n \leq \frac{N}{2}$. The frequency resolution, in order to span all the allowed frequency range will be of the form $\Delta f = \frac{1}{T} = \frac{1}{\Delta t}$
- ▶ The **Direct** and **Inverse** Discrete Fourier transform are then defined as

$$X_n = \frac{1}{N} \sum_{k=0}^{N-1} x_k e^{-2\pi kn/N}$$


$$x_k = \frac{1}{N} \sum_{n=-N/2}^{N/2} X_n e^{2\pi kn/N}$$

- ▶ Given the discreteness of the sampling, also the corresponding Fourier transform will be discrete in the Fourier space.
- ▶ The basic concept of DFT resides on the fact that the algorithm applied on an N -sampled data, will produce an information on N frequencies, assuming that the information is conserved
- ▶ The Fourier transform of a digitized N -sampled data will be of the form $f_n = n\Delta f$ with (if N is even) $-\frac{N}{2} \leq n \leq \frac{N}{2}$. The frequency resolution, in order to span all the allowed frequency range will be of the form $\Delta f = \frac{1}{T} = \frac{1}{\Delta t}$
- ▶ The **Direct** and **Inverse** Discrete Fourier transform are then defined as

$$X_n = \frac{1}{N} \sum_{k=0}^{N-1} x_k e^{-2\pi kn/N}$$


$$x_k = \frac{1}{N} \sum_{n=-N/2}^{N/2} X_n e^{2\pi kn/N}$$

- ▶ The presence of frequency higher than the Nyquist frequency may lead to the presence of spurious frequency




- ▶ A 9 kHz sine if sampled at 10 kHz exhibits a spurious 1 kHz oscillation

- ▶ The finite extension of the measurements, acquired for a given period T is equivalent to the convolution of the signal with a box function $G(t)$ with domain $0 \leq t \leq T$, i.e. $G(t) = 1$ if $0 \leq t \leq T$ 0 otherwise
- ▶ According the theorems for the Fourier transform (which can be applied also for discrete transform) this is equivalent in the Fourier space to the multiplication of the of the fourier transform but the Fourier representation of a box function is $\text{sinc}(x) = \sin(x)/x$ function as shown, which **leaking** some power from one frequency bin to the adjacents ones.



- Solution to the leakage problem is multiplying data by an appropriate window function which reduces the lobes as the *Hanning window* defined as $u_h(t) = \frac{1}{2}(1 - \cos(2\pi t/T))$ for $0 \leq t \leq T$ and 0 otherwise. Its behavior in real and fourire space is the following



- ▶ We know from the statistics a random process $x(t)$ is completely described by its moments, which are the average over the probability distribution function

$$E|x(t)| \quad E|x(t_1)x(t_2)| \quad E|x(t_1)x(t_2)x(t_3)| \quad \dots$$

- ▶ The **Auto-correlation function**, i.e. the second order momentum of the distribution, or the **autocovariance function**

$$R(\tau) = E|x(t)x(t - \tau)|$$

$$C(\tau) = E|(x(t) - m)(x(t - \tau) - m)|$$

being m the average of $x(t)$

- ▶ The **Auto-correlation coefficient factor** is defined as $\rho(\tau) = C(\tau)/C(0)$
- ▶ For digitized signals with N samples the estimator of $C(\tau)$ is defined as

$$C_j = \frac{1}{N} \sum_{i=j}^{N-1} (x_i - \bar{x})(x_{i-j} - \bar{x}) \quad \bar{x} = \frac{1}{N} \sum_{i=0}^{N-1} x_i$$

- ▶ Define the *Auto-correlation time* of a turbulent field such as the potential
- ▶ **Inserisci figura con autocorrelazione di un potenziale**

- ▶ The Power spectrum $S(f)$ is defined as the Fourier transform of the Autocorrelation-function.

- ▶ The Power spectrum $S(f)$ is defined as the Fourier transform of the Autocorrelation-function.
- ▶ It can be demonstrated that $E[|x(t)|^2] = \int_{-\infty}^{+\infty} S(f)df$, i.e. the Power spectrum describe the frequency distribution of the *power of the signal*.

- ▶ The **Power spectrum** $S(f)$ is defined as the Fourier transform of the Autocorrelation-function.
- ▶ It can be demonstrated that $E[|x(t)|^2] = \int_{-\infty}^{+\infty} S(f)df$, i.e. the Power spectrum describe the frequency distribution of the *power of the signal*.
- ▶ In the real case, with limited temporal acquisition of a signal $x_T(t)$ the ensemble average of its **periodogram** tends to the power spectrum

$$\frac{|FT(x_T(t))|^2}{T} \xrightarrow{T \rightarrow \infty} S(f)$$

- ▶ The **Power spectrum** $S(f)$ is defined as the Fourier transform of the Autocorrelation-function.
- ▶ It can be demonstrated that $E[|x(t)|^2] = \int_{-\infty}^{+\infty} S(f)dt$, i.e. the Power spectrum describe the frequency distribution of the *power of the signal*.
- ▶ In the real case, with limited temporal acquisition of a signal $x_T(t)$ the ensemble average of its **periodogram** tends to the power spectrum
$$\frac{|FT(x_T(t))|^2}{T} \xrightarrow{T \rightarrow \infty} S(f)$$
- ▶ From a practical point of view, we divide signals into M slices, assumed as independent realization of the same stochastic process and we compute

$$\hat{S}(f) = \frac{1}{M} \sum_{k=1}^M S^{(k)}(f); \quad S^{(k)}(f) = \frac{1}{T} |X_T^{(k)}(f)|$$



- ▶ The **Power spectrum** $S(f)$ is defined as the Fourier transform of the Autocorrelation-function.
- ▶ It can be demonstrated that $E[|x(t)|^2] = \int_{-\infty}^{+\infty} S(f)df$, i.e. the Power spectrum describe the frequency distribution of the *power of the signal*.
- ▶ In the real case, with limited temporal acquisition of a signal $x_T(t)$ the ensemble average of its **periodogram** tends to the power spectrum
$$\frac{|FT(x_T(t))|^2}{T} \xrightarrow{T \rightarrow \infty} S(f)$$
- ▶ From a practical point of view, we divide signals into M slices, assumed as independent realization of the same stochastic process and we compute

$$\hat{S}(f) = \frac{1}{M} \sum_{k=1}^M S^{(k)}(f); \quad S^{(k)}(f) = \frac{1}{T} |X_T^{(k)}(f)|^2$$

- ▶ With digitized signal, the power spectral estimator \hat{S}_n is related to the real power spectrum $S(f_n)$ as


$$\hat{S}_n = \frac{1}{M} \sum_{k=1}^M |X_n^{(k)}|^2; \quad \hat{S}_n \simeq S(f_n) \Delta f$$

- Mode identification at a given frequency (Conway et al. 2005)



- But information must be completed. In the example, precise identification require scaling of identified mode as a function of ion sound gyroradius

- ▶ The same information can be also analyzed in time applying the **spectrogram** technique which shows how the spectral density of the signal varying in time/frequency space (Spagnolo et al. [2011](#))



- ▶ Again the information must be completed, as in the case proposed where the Alfvénic nature of the observed peaks is revealed by the comparison with the plasma density

- ▶ Spatially distributed measurements allow access to spatial structure of the fluctuations

- ▶ Spatially distributed measurements allow access to spatial structure of the fluctuations
- ▶ The minimum set includes two measurements $x(t)$ and $y(t)$. We can define the **Cross-correlation function**, **The cross-covariance function** and the **cross-correlation coefficient function**

$$R_{xt}(\tau) = E[y(t)x(t - \tau)]$$

$$C_{xy}(\tau) = E[(y(t) - \bar{y})(x(t - \tau) - \bar{x})]$$

$$\rho_{yx}(\tau) = \frac{C_{yx}(\tau)}{\sqrt{C_{xx}(0)C_{yy}(0)}}$$

- ▶ Spatially distributed measurements allow access to spatial structure of the fluctuations
- ▶ The minimum set includes two measurements $x(t)$ and $y(t)$. We can define the **Cross-correlation function**, **The cross-covariance function** and the **cross-correlation coefficient function**

$$R_{xt}(\tau) = E[y(t)x(t - \tau)]$$

$$C_{xy}(\tau) = E[(y(t) - \bar{y})(x(t - \tau) - \bar{x})]$$

$$\rho_{yx}(\tau) = \frac{C_{yx}(\tau)}{\sqrt{C_{xx}(0)C_{yy}(0)}}$$

- ▶ In the discrete counterpart of the cross-covariance is defined as

$$C_{yx,j} = \frac{1}{N} \sum_{i=j}^{N-1} (y_i - \bar{y})(x_{i-j} - \bar{x})$$

- ▶ In analogy to the power spectrum we define the **Cross-power spectrum** $S_{XY}(f)$ as the Fourier transform of the cross-correlation function

- ▶ In analogy to the power spectrum we define the **Cross-power spectrum** $S_{XY}(f)$ as the Fourier transform of the cross-correlation function
- ▶ As in the case of power spectrum, if $x(t)$ and $y(t)$ are real function, the cross-power spectrum is totally defined by the positive frequency only

- ▶ In analogy to the power spectrum we define the **Cross-power spectrum** $S_{XY}(f)$ as the Fourier transform of the cross-correlation function
- ▶ As in the case of power spectrum, if $x(t)$ and $y(t)$ are real function, the cross-power spectrum is totally defined by the positive frequency only
- ▶ Differently from the power spectrum, the cross-spectrum is complex-valued $S_{YX}(f) = |S_{YX}(f)|e^{i\Theta_{YX}(f)}$ with $\Theta_{YX}(f)$ equal to the **Phase spectrum**


- ▶ In analogy to the power spectrum we define the **Cross-power spectrum** $S_{XY}(f)$ as the Fourier transform of the cross-correlation function
- ▶ As in the case of power spectrum, if $x(t)$ and $y(t)$ are real function, the cross-power spectrum is totally defined by the positive frequency only
- ▶ Differently from the power spectrum, the cross-spectrum is complex-valued $S_{YX}(f) = |S_{YX}(f)|e^{i\Theta_{YX}(f)}$ with $\Theta_{YX}(f)$ equal to the **Phase spectrum**
- ▶ We can also defined the **coherence** as $\gamma_{YX}(f) = \frac{|S_{YX}(f)|}{\sqrt{S_Y(f)S_X(f)}}$

- ▶ In analogy to the power spectrum we define the **Cross-power spectrum** $S_{XY}(f)$ as the Fourier transform of the cross-correlation function
- ▶ As in the case of power spectrum, if $x(t)$ and $y(t)$ are real function, the cross-power spectrum is totally defined by the positive frequency only
- ▶ Differently from the power spectrum, the cross-spectrum is complex-valued $S_{YX}(f) = |S_{YX}(f)|e^{i\Theta_{YX}(f)}$ with $\Theta_{YX}(f)$ equal to the **Phase spectrum**
- ▶ We can also defined the **coherence** as $\gamma_{YX}(f) = \frac{|S_{YX}(f)|}{\sqrt{S_Y(f)S_X(f)}}$
- ▶ In the case of discrete signals with finite temporal length the following definitions hold (in analogy to single point case)


$$\hat{S}_{Y,X,n} = \frac{1}{M} \sum_{k=1}^M Y_n^{(k)} X_n^{*(k)} \quad \hat{S}_{Y,X,n} \simeq S_{YX}(f_n) \Delta f$$

- ▶ The method can be applied also in the case of two quantities measured on the same location

- ▶ The method can be applied also in the case of two quantities measured on the same location
- ▶ In the case of Langmuir probes for example, electron density n_e and plasma potential ϕ_p are known in the same nominal position




- ▶ The method can be applied also in the case of two quantities measured on the same location
- ▶ In the case of Langmuir probes for example, electron density n_e and plasma potential ϕ_p are known in the same nominal position



- ▶ This allows the possibility to distinguish the frequency where turbulence is **Interchange-dominated** from that where turbulence is **Drift-dominated**

- ▶ The method can be applied also in the case of two quantities measured on the same location
- ▶ In the case of Langmuir probes for example, electron density n_e and plasma potential ϕ_p are known in the same nominal position



- ▶ This allows the possibility to distinguish the frequency where turbulence is **Interchange-dominated** from that where turbulence is **Drift-dominated**
- ▶ Other possibility is the determination of the polarization of magnetic fluctuations frequency resolved

- ▶ In the case of a reasonably deterministic dispersion relation between k and f , the phase may be used for the determination of k

- ▶ In the case of a reasonably deterministic dispersion relation between k and f , the phase may be used for the determination of k
- ▶ Indeed if $k = k(f)$ then at a generic position \vec{r} the function
$$g(t, \vec{r}) = \int_{-\infty}^{+\infty} G(f) e^{-ik(f) \cdot \vec{r}} e^{i2\pi f t} df$$

- ▶ In the case of a reasonably deterministic dispersion relation between k and f , the phase may be used for the determination of k
- ▶ Indeed if $k = k(f)$ then at a generic position \bar{r} the function
$$g(t, \bar{r}) = \int_{-\infty}^{+\infty} G(f) e^{-ik(f) \cdot \bar{r}} e^{i2\pi f t} df$$
- ▶ If measures exists at two position $g(t, \bar{r}_1)$ and $g(t, \bar{r}_2)$ separated by d at a given frequency the two signals will be phase shifted of $\Theta_{12}(f) = k(f)d$ where $\Theta_{12}(f)$ is computed trough the cross-power spectrum

- ▶ In the case of a reasonably deterministic dispersion relation between k and f , the phase may be used for the determination of k
- ▶ Indeed if $k = k(f)$ then at a generic position \bar{r} the function
$$g(t, \bar{r}) = \int_{-\infty}^{+\infty} G(f) e^{-ik(f) \cdot \bar{r}} e^{i2\pi f t} df$$
- ▶ If measures exists at two position $g(t, \bar{r}_1)$ and $g(t, \bar{r}_2)$ separated by d at a given frequency the two signals will be phase shifted of $\Theta_{12}(f) = k(f)d$ where $\Theta_{12}(f)$ is computed trough the cross-power spectrum
- ▶ If measurements are displaced in the aximuthal direction, i.e. $d = r_p \Delta\Theta$ then the azimuthal mode number is computed as $m = \Theta_{12}/\Delta\Theta$

- ▶ In the case of a reasonably deterministic dispersion relation between k and f , the phase may be used for the determination of k
- ▶ Indeed if $k = k(f)$ then at a generic position \bar{r} the function
$$g(t, \bar{r}) = \int_{-\infty}^{+\infty} G(f) e^{-ik(f) \cdot \bar{r}} e^{i2\pi f t} df$$
- ▶ If measures exists at two position $g(t, \bar{r}_1)$ and $g(t, \bar{r}_2)$ separated by d at a given frequency the two signals will be phase shifted of $\Theta_{12}(f) = k(f)d$ where $\Theta_{12}(f)$ is computed trough the cross-power spectrum
- ▶ If measurements are displaced in the aximuthal direction, i.e. $d = r_p \Delta\Theta$ then the azimuthal mode number is computed as $m = \Theta_{12}/\Delta\Theta$
- ▶ The probe distance d must be less than aa wave length, less than a correlation lenght, but far enough the detect a measurable phase difference

- ▶ Fluctuations induced particle flux is defined as
$$\Gamma = E[\tilde{n}(t)\tilde{v}(t)] = E[\tilde{n}(t)\tilde{E}(t)]/B$$
- ▶ According to previous definitions and properties

$$\Gamma = \frac{1}{B} R_{nE}(\tau = 0) = \frac{1}{B} \int_{-\infty}^{+\infty} S_{nE}(f) e^{i2\pi f\tau} df = \frac{2}{B} \int_0^{+\infty} \Re[S_{nE}(f)] df$$

- ▶ In quasi-static approximation $\tilde{E} = -\nabla\tilde{\phi}$, and considering the finiteness of the measurements we end up with the formula

$$\Gamma(f) = \frac{2}{BT} \Im\{E[k(f)N(f)\Phi^*(f)]\}$$
$$\Gamma(f) = \frac{2k(f)}{B} \Im\{S_{n\phi}(f)\} \text{ if } k(f) \text{ is deterministic}$$

- In practice, considering digitized signals we have (see for example (Antoni et al. [2000](#)))

$$\Gamma(f) = \frac{1}{M} \sum_{k=1}^M \Gamma^k(f)$$

$$\Gamma^{(k)}(f) = \frac{2}{B} \Im \{ k^{(k)}(f) N^{(k)}(f) \Phi^{*(k)}(f) \} 0 < f < N/2 - 1$$


$$\Gamma^{(k)}(f) = \frac{1}{B} \Im \{ k^{(k)}(f) N^{(k)}(f) \Phi^{*(k)}(f) \} f = 0, f = N/2$$

- In practice, considering digitized signals we have (see for example (Antoni et al. 2000))

$$\Gamma(f) = \frac{1}{M} \sum_{k=1}^M \Gamma^k(f)$$

$$\Gamma^{(k)}(f) = \frac{2}{B} \Im \{ k^{(k)}(f) N^{(k)}(f) \Phi^{*(k)}(f) \} 0 < f < N/2 - 1$$

$$\Gamma^{(k)}(f) = \frac{1}{B} \Im \{ k^{(k)}(f) N^{(k)}(f) \Phi^{*(k)}(f) \} f = 0, f = N/2$$




- In practice, considering digitized signals we have (see for example (Antoni et al. [2000](#)))

$$\Gamma(f) = \frac{1}{M} \sum_{k=1}^M \Gamma^k(f)$$

$$\Gamma^{(k)}(f) = \frac{2}{B} \Im\{k^{(k)}(f)N^{(k)}(f)\Phi^{*(k)}(f)\} 0 < f < N/2 - 1$$

$$\Gamma^{(k)}(f) = \frac{1}{B} \Im\{k^{(k)}(f)N^{(k)}(f)\Phi^{*(k)}(f)\} f = 0, f = N/2$$




- In practice, considering digitized signals we have (see for example (Antoni et al. [2000](#)))

$$\Gamma(f) = \frac{1}{M} \sum_{k=1}^M \Gamma^{(k)}(f)$$

$$\Gamma^{(k)}(f) = \frac{2}{B} \Im \{ k^{(k)}(f) N^{(k)}(f) \Phi^{*(k)}(f) \} 0 < f < N/2 - 1$$

$$\Gamma^{(k)}(f) = \frac{1}{B} \Im \{ k^{(k)}(f) N^{(k)}(f) \Phi^{*(k)}(f) \} f = 0, f = N/2$$



The wavenumber-Frequency Spectrum



CONSORZIO RFX
Ricerca Formazione Innovazione

- ▶ In general, we have a turbulent medium, with different wave numbers corresponding to the same frequency

The wavenumber-Frequency Spectrum



CONSORZIO RFX
Ricerca Formazione Innovazione

- ▶ In general, we have a turbulent medium, with different wave numbers corresponding to the same frequency
- ▶ We need to compute the Wave number-frequency power spectrum $S(k, \omega)$

- ▶ In general, we have a turbulent medium, with different wave numbers corresponding to the same frequency
- ▶ We need to compute the Wave number-frequency power spectrum $S(k, \omega)$
- ▶ This is equivalent to the Fourier transform of the space time correlation function $R(\chi, \tau)$

$$R(\chi, \tau) = E[g(x, t)g^*(x - \chi, t - \tau)]$$
$$S(k, \omega) = \iint_{-\infty}^{+\infty} R(\chi, \tau) e^{-i(\omega\tau - k\chi)} d\chi d\tau$$

- ▶ In general, we have a turbulent medium, with different wave numbers corresponding to the same frequency
- ▶ We need to compute the Wave number-frequency power spectrum $S(k, \omega)$
- ▶ This is equivalent to the Fourier transform of the space time correlation function $R(\chi, \tau)$

$$R(\chi, \tau) = E[g(x, t)g^*(x - \chi, t - \tau)]$$
$$S(k, \omega) = \iint_{-\infty}^{+\infty} R(\chi, \tau) e^{-i(\omega\tau - k\chi)} d\chi d\tau$$

- ▶ Again for finite time length T and finite space L we have an estimate

$$\hat{S}(k, \omega) = \frac{1}{LT} E[G_{LT}(k, \omega) G_{LT}^*(k, \omega)]$$
$$\lim_{L, T \rightarrow \infty} \hat{S}(k, \omega) = S(k, \omega)$$


- ▶ In general, we have a turbulent medium, with different wave numbers corresponding to the same frequency
- ▶ We need to compute the **Wave number-frequency power spectrum** $S(k, \omega)$
- ▶ This is equivalent to the Fourier transform of the space time correlation function $R(\chi, \tau)$

$$R(\chi, \tau) = E[g(x, t)g^*(x - \chi, t - \tau)]$$
$$S(k, \omega) = \iint_{-\infty}^{+\infty} R(\chi, \tau) e^{-i(\omega\tau - k\chi)} d\chi d\tau$$

- ▶ If, as usual, only 2 points are available, the spectrum is reconstructed on a statistical basis:

$$\hat{S}_L(k, \omega) = \hat{S}_L(p\delta k, 2\pi n\Delta f) = \frac{1}{M} \sum_{j=1}^M S_n^{(j)} I_p[k_n^j]$$
$$I_p[k_n^j] = \begin{cases} 1 & \text{for } (p - 1/2)\Delta k < k_n^{(j)} < (p + 1/2)\delta k \\ 0 & \text{elsewhere} \end{cases}$$

- Spectral power density from GPI LoS on NSTX (Agostini et al. [2007](#))



- ▶ We can consequently compute $S(k) = \int_{-\infty}^{+\infty} S(k, \omega) \frac{d\omega}{2\pi}$

