

Fluctuation data analysis in Fusion Relevant Plasmas

N. Vianello

Diagnostics provides information with different time and spatial resolution

1. Localized measurements

- (a) Measurements coming from a single point
- (b) Spatially distributed arrays of measurements (resolving portion of the plasma or entire torus)

2. Line integrated measurements

- (a) Single Line of Sight
- (b) Arrays of LoS

Diagnostics provides information with different time and spatial resolution

1. Localized measurements

- (a) Measurements coming from a single point
- (b) Spatially distributed arrays of measurements (resolving portion of the plasma or entire torus)

2. Line integrated measurements

- (a) Single Line of Sight
- (b) Arrays of LoS

Motivation & Outline

Diagnostics provides information with different time and spatial resolution

1. Localized measurements

- (a) Measurements coming from a single point
- (b) Spatially distributed arrays of measurements (resolving portion of the plasma or entire torus)

2. Line integrated measurements

- (a) Single Line of Sight
- (b) Arrays of LoS



- ▶ The **Direct** and **Inverse** fourier transform of a generic function of time $x(t)$ is defined as :

$$X(f) = \int_{-\infty}^{+\infty} x(t)e^{-2\pi ift} dt$$

$$x(t) = \int_{-\infty}^{+\infty} X(f)e^{2\pi ift} df$$

Continuous and Discrete Fourier transform

- ▶ The **Direct** and **Inverse** Fourier transform of a generic function of time $x(t)$ is defined as :

$$X(f) = \int_{-\infty}^{+\infty} x(t) e^{-2\pi i f t} dt$$

$$x(t) = \int_{-\infty}^{+\infty} X(f) e^{2\pi i f t} df$$

- ▶ In the case of discrete signals $x_n = x(n\Delta t)$ with $0 \leq n \leq N-1$, sampled at frequency $f_c = \frac{1}{\Delta t}$ we have the corresponding **Direct** and **Inverse** Discrete Fourier transform

$$X_n = \frac{1}{N} \sum_{k=0}^{N-1} x_k e^{-2\pi i k n / N}$$

$$x_k = \frac{1}{N} \sum_{n=-N/2}^{N/2} X_n e^{2\pi i k n / N}$$

Continuous and Discrete Fourier transform

- ▶ The **Direct** and **Inverse** fourier transform of a generic function of time $x(t)$ is defined as :

$$X(f) = \int_{-\infty}^{+\infty} x(t) e^{-2\pi i f t} dt$$

$$x(t) = \int_{-\infty}^{+\infty} X(f) e^{2\pi i f t} df$$

- ▶ In the case of discrete signals $x_n = x(n\Delta t)$ with $0 \leq n \leq N-1$, sampled at frequency $f_c = \frac{1}{\Delta t}$ we have the corresponding **Direct** and **Inverse** Discrete Fourier transform

$$X_n = \frac{1}{N} \sum_{k=0}^{N-1} x_k e^{-2\pi i k n / N}$$

$$x_k = \frac{1}{N} \sum_{n=-N/2}^{N/2} X_n e^{2\pi i k n / N}$$

- ▶ The **Sampling Theorem** (Bracewell 1999) ensure that a function whose Fourier transform is zero for $f > f_c$ is fully specified by values spaced at equal intervals not exceeding $\frac{1}{2} f_c^{-1}$

Continuous and Discrete Fourier transform

- ▶ The **Direct** and **Inverse** fourier transform of a generic function of time $x(t)$ is defined as :

$$X(f) = \int_{-\infty}^{+\infty} x(t) e^{-2\pi i f t} dt$$

$$x(t) = \int_{-\infty}^{+\infty} X(f) e^{2\pi i f t} df$$


- ▶ In the case of discrete signals $x_n = x(n\Delta t)$ with $0 \leq n \leq N-1$, sampled at frequency $f_c = \frac{1}{\Delta t}$ we have the corresponding **Direct** and **Inverse** Discrete Fourier transform

$$X_n = \frac{1}{N} \sum_{k=0}^{N-1} x_k e^{-2\pi i k n / N}$$

$$x_k = \frac{1}{N} \sum_{n=-N/2}^{N/2} X_n e^{2\pi i k n / N}$$

- ▶ The **Nyquist Frequency** $f_N = \frac{1}{2\Delta t}$, defines the maximum frequency which can be properly resolved, or, equivalently, given the frequency of the system we would like to investigate, we had to sample at least at twice the values of this frequency.

- ▶ The presence of frequency higher than the Nyquist frequency may lead to the presence of spurious frequency



- ▶ A 9 kHz cosine if sampled at 10 kHz exhibits a spurious 1 kHz oscillation

Properties of Fourier transform

- Various theorems may be applied to FT (Bracewell 1999) among which we cite:

Theorem

Convolution theorem: If $x(t)$ and $g(t)$ have FT respectively equal to $X(f)$ and $G(f)$ the convolution of the two functions $h(t) = \int_{-\infty}^{+\infty} x(t')g(t-t')dt'$ is equal to $X(f)G(f)$

Theorem

Rayleigh's Theorem The integral of squared modulus of a function is equal to the integral of the squared modulus of its spectrum, i.e:

$$\int_{-\infty}^{+\infty} |f(t)|^2 dt = \int_{-\infty}^{+\infty} |F(f)|^2 df$$

Single Point: the autocorrelation function

- ▶ A random process $x(t)$ is completely described by its moments, i.e. averages over the probability distribution function

$$E[x(t)] \quad E[x(t_1)x(t_2)] \quad E[x(t_1)x(t_2)x(t_3)] \quad \dots$$

- ▶ We define the **Auto-correlation function**, i.e. the second order momentum of the distribution, and the **auto-covariance function**

$$R(\tau) = E[x(t)x(t-\tau)]$$

$$C(\tau) = E[(x(t) - m)(x(t-\tau) - m)]$$


being m the average of $x(t)$

- ▶ The **Auto-correlation coefficient factor** is defined as $\rho(\tau) = C(\tau)/C(0)$
- ▶ For digitized signals with N samples the estimator of $C(\tau)$ is defined as

$$C_j = \frac{1}{N} \sum_{i=j}^{N-1} (x_i - \bar{x})(x_{i-j} - \bar{x}) \quad \bar{x} = \frac{1}{N} \sum_{i=0}^{N-1} x_i$$

Auto-correlation: practical use

- Define the **Auto-correlation time** of a turbulent field such as the potential: $R(\tau_c) = \frac{\max(R(\tau))}{e}$



Single point: the power spectrum

- ▶ The Power spectrum $S(f)$ is defined as the Fourier transform of the Autocorrelation-function.

Single point: the power spectrum

- ▶ The Power spectrum $S(f)$ is defined as the Fourier transform of the Autocorrelation-function.
- ▶ It describes the frequency distribution of the *power of the signal*.

Single point: the power spectrum

- ▶ The **Power spectrum** $S(f)$ is defined as the Fourier transform of the Autocorrelation-function.
- ▶ It describes the frequency distribution of the *power of the signal*.
- ▶ It corresponds to the limit of the **periodogram** of limited signals $x_T(t)$
$$\frac{E[FT(x_T(t))^2]}{T} \xrightarrow{T \rightarrow \infty} S(f)$$


Single point: the power spectrum

- ▶ The **Power spectrum** $S(f)$ is defined as the Fourier transform of the Autocorrelation-function.
- ▶ It describes the frequency distribution of the *power of the signal*.
- ▶ It corresponds to the limit of the **periodogram** of limited signals $x_T(t)$
$$\frac{E[FT(x_T(t))^2]}{T} \xrightarrow{T \rightarrow \infty} S(f)$$
- ▶ Numerically, the signal is divided into M slices, treated as independent realizations, and we compute the power spectral estimator \hat{S}_n related to the real power spectrum $S(f_n)$ according to

$$\hat{S}_n = \frac{1}{M} \sum_{k=1}^M |X_n^{(k)}|^2; \quad \hat{S}_n \simeq S(f_n) \Delta f$$



Power spectrum: practical use

- ▶ Mode identification at a given frequency (Conway et al. 2005)



Power spectrum: practical use

- Mode identification at a given frequency (Conway et al. 2005)



- Information must be completed. In the example [Geodesic Acoustic Modes](#) identified considering their scaling with c_s

Two-points techniques

- ▶ Spatially distributed measurements allow access to spatial structure of the fluctuations

Two-points techniques

- ▶ Spatially distributed measurements allow access to spatial structure of the fluctuations
- ▶ The minimum set includes two measurements $x(t)$ and $y(t)$. We can define the **Cross-correlation function**, **The cross-covariance function** and the **cross-correlation coefficient function**

$$R_{xt}(\tau) = E[y(t)x(t - \tau)]$$

$$C_{xy}(\tau) = E[(y(t) - \bar{y})(x(t - \tau) - \bar{x})]$$

$$\rho_{yx}(\tau) = \frac{C_{yx}(\tau)}{\sqrt{C_{xx}(0)C_{yy}(0)}}$$

Two-points techniques

- ▶ Spatially distributed measurements allow access to spatial structure of the fluctuations
- ▶ The minimum set includes two measurements $x(t)$ and $y(t)$. We can define the **Cross-correlation function**, **The cross-covariance function** and the **cross-correlation coefficient function**

$$R_{xt}(\tau) = E[y(t)x(t - \tau)]$$

$$C_{xy}(\tau) = E[(y(t) - \bar{y})(x(t - \tau) - \bar{x})]$$

$$\rho_{yx}(\tau) = \frac{C_{yx}(\tau)}{\sqrt{C_{xx}(0)C_{yy}(0)}}$$

- ▶ The discrete counterpart of the cross-covariance is defined as

$$C_{yx,j} = \frac{1}{N} \sum_{i=j}^{N-1} (y_i - \bar{y})(x_{i-j} - \bar{x})$$

- ▶ In analogy to the power spectrum we define the **Cross-power spectrum** $S_{XY}(f)$ as the Fourier transform of the cross-correlation function

Two-points technique

- ▶ In analogy to the power spectrum we define the **Cross-power spectrum** $S_{XY}(f)$ as the Fourier transform of the cross-correlation function
- ▶ If $x(t)$ and $y(t)$ are real function, the cross-power spectrum is totally defined by the positive frequency only

Two-points technique

- ▶ In analogy to the power spectrum we define the **Cross-power spectrum** $S_{XY}(f)$ as the Fourier transform of the cross-correlation function
- ▶ If $x(t)$ and $y(t)$ are real function, the cross-power spectrum is totally defined by the positive frequency only
- ▶ The cross-spectrum is complex-valued $S_{YX}(f) = |S_{YX}(f)|e^{i\Theta_{YX}(f)}$ with $\Theta_{YX}(f)$ equal to the **Phase spectrum**

Two-points technique

- ▶ In analogy to the power spectrum we define the **Cross-power spectrum** $S_{XY}(f)$ as the Fourier transform of the cross-correlation function
- ▶ If $x(t)$ and $y(t)$ are real function, the cross-power spectrum is totally defined by the positive frequency only
- ▶ The cross-spectrum is complex-valued $S_{YX}(f) = |S_{YX}(f)|e^{i\Theta_{YX}(f)}$ with $\Theta_{YX}(f)$ equal to the **Phase spectrum**
- ▶ We define the **coherence** as $\gamma_{YX}(f) = \frac{|S_{YX}(f)|}{\sqrt{S_Y(f)S_X(f)}}$


Two-points technique

- ▶ In analogy to the power spectrum we define the **Cross-power spectrum** $S_{XY}(f)$ as the Fourier transform of the cross-correlation function
- ▶ If $x(t)$ and $y(t)$ are real function, the cross-power spectrum is totally defined by the positive frequency only
- ▶ The cross-spectrum is complex-valued $S_{YX}(f) = |S_{YX}(f)|e^{i\Theta_{YX}(f)}$ with $\Theta_{YX}(f)$ equal to the **Phase spectrum**
- ▶ We define the **coherence** as $\gamma_{YX}(f) = \frac{|S_{YX}(f)|}{\sqrt{S_Y(f)S_X(f)}}$
- ▶ In the case of discrete signals with finite temporal length the following definitions hold (in analogy to single point case)


$$\hat{S}_{Y,X,n} = \frac{1}{M} \sum_{k=1}^M Y_n^{(k)} X_n^{*(k)} \quad \hat{S}_{Y,X,n} \simeq S_{YX}(f_n) \Delta f$$

- ▶ The method can be applied also in the case of two quantities measured on the same location

- ▶ The method can be applied also in the case of two quantities measured on the same location
- ▶ In the case of Langmuir probes for example, electron density n_e and plasma potential ϕ_p are known in the same nominal position



- ▶ The method can be applied also in the case of two quantities measured on the same location
- ▶ In the case of Langmuir probes for example, electron density n_e and plasma potential ϕ_p are known in the same nominal position




- ▶ This allows the possibility to distinguish the frequency where turbulence is **Interchange-dominated** from that where turbulence is **Drift-dominated**

- ▶ In the case of a reasonably deterministic dispersion relation between k and f , the phase may be used for the determination of k


Wave-vector estimate

- ▶ In the case of a reasonably deterministic dispersion relation between k and f , the phase may be used for the determination of k
- ▶ Wave vector is estimated from Phase spectrum



Wave-vector estimate

- ▶ In the case of a reasonably deterministic dispersion relation between k and f , the phase may be used for the determination of k
- ▶ Wave vector is estimated from Phase spectrum



- ▶ Distance d must be less than a wave length, less than a correlation length, but far enough to detect a measurable phase difference

Fluctuation-induced particle transport

- ▶ Fluctuations induced particle flux is defined as
$$\Gamma = E[\tilde{n}(t)\tilde{v}(t)] = E[\tilde{n}(t)\tilde{E}(t)]/B$$
- ▶ According to previous definitions and properties

$$\Gamma = \frac{1}{B} R_{nE}(\tau = 0) = \frac{2}{B} \int_0^{+\infty} \text{Re}[S_{nE}(f)] df$$

- ▶ In quasi-static approximation $\tilde{E} = -\nabla\tilde{\phi}$, with finite record length T , and assuming a deterministic dispersion relation

$$\Gamma(f) = \frac{2k(f)}{B} \text{Im}\{S_{n\phi}(f)\}$$

Fluctuation-induced particle transport 2


- ▶ In practice, considering digitized signals we have (see for example (Antoni et al. [2000](#)))

$$\Gamma(f) = \frac{1}{M} \sum_{k=1}^M \Gamma^k(f) = \frac{2}{BM} \sum_{k=1}^{M-1} k^{(k)}(f) \operatorname{Im}\{N^{(k)}(f)\Phi^{*(k)}(f)\}$$

Fluctuation-induced particle transport 2

- In practice, considering digitized signals we have (see for example (Antoni et al. [2000](#)))


$$\Gamma(f) = \frac{1}{M} \sum_{k=1}^M \Gamma^k(f) = \frac{2}{BM} \sum_{k=1}^{M-1} k^{(k)}(f) \operatorname{Im}\{N^{(k)}(f)\Phi^{*(k)}(f)\}$$



Fluctuation-induced particle transport 2

- In practice, considering digitized signals we have (see for example (Antoni et al. [2000](#)))


$$\Gamma(f) = \frac{1}{M} \sum_{k=1}^M \Gamma^k(f) = \frac{2}{BM} \sum_{k=1}^{M-1} k^{(k)}(f) \operatorname{Im}\{N^{(k)}(f)\Phi^{*(k)}(f)\}$$



Fluctuation-induced particle transport 2


- In practice, considering digitized signals we have (see for example (Antoni et al. [2000](#)))

$$\Gamma(f) = \frac{1}{M} \sum_{k=1}^M \Gamma^k(f) = \frac{2}{BM} \sum_{k=1}^{M-1} k^{(k)}(f) \operatorname{Im}\{N^{(k)}(f)\Phi^{*(k)}(f)\}$$



More than transport of particles

- Similar method may be used for the determination of the *Reynolds stress* $\langle \tilde{v}_r \tilde{v}_\perp \rangle$ which play a role in the momentum generation for both Tokamak and RFPs as $\partial_t(V_\phi) \propto -\partial_r \langle \tilde{v}_r \tilde{v}_\phi \rangle + \dots$ (see e.g. (Vianello et al. [2005a,b](#), [2006](#)))



The wavenumber-frequency Spectrum

- ▶ For turbulent medium, with different wave numbers corresponding to the same frequency we need to compute the Wave number-frequency power spectrum $S(k, \omega)$

The wavenumber-frequency Spectrum

- ▶ For turbulent medium, with different wave numbers corresponding to the same frequency we need to compute the **Wave number-frequency power spectrum** $S(k, \omega)$
- ▶ This is equivalent to the Fourier transform of the space time correlation function $R(\chi, \tau)$

$$S(k, \omega) = \iint_{-\infty}^{+\infty} R(\chi, \tau) e^{-i(\omega\tau - k\chi)} d\chi d\tau$$

The wavenumber-frequency Spectrum

- ▶ For turbulent medium, with different wave numbers corresponding to the same frequency we need to compute the **Wave number-frequency power spectrum** $S(k, \omega)$
- ▶ This is equivalent to the Fourier transform of the space time correlation function $R(\chi, \tau)$


$$S(k, \omega) = \iint_{-\infty}^{+\infty} R(\chi, \tau) e^{-i(\omega\tau - k\chi)} d\chi d\tau$$

- ▶ In the two 2 points cases are available, the spectrum is reconstructed on a statistical basis considering the M different realizations:


$$\hat{S}_L(k, \omega) = \hat{S}_L(p\Delta k, 2\pi n\Delta f) = \frac{1}{M} \sum_{j=1}^M S_n^{(j)} I_p[k_n^j]$$

$$I_p[k_n^j] = \begin{cases} 1 & \text{for } (p - 1/2)\Delta k < k_n^{(j)} < (p + 1/2)\Delta k \\ 0 & \text{elsewhere} \end{cases}$$

- Spectral power density from GPI LoS on NSTX (Agostini et al. 2007)



- ▶ We can consequently compute $S(k) = \int_{-\infty}^{+\infty} S(k, \omega) \frac{d\omega}{2\pi}$




- ▶ The Fourier decomposition uses trigonometric functions as orthogonal basis

Beyond Fourier: Wavelet transform

- ▶ The Fourier decomposition uses trigonometric functions as orthogonal basis
- ▶ These functions oscillates forever, i.e. the information is spread


Beyond Fourier: Wavelet transform

- ▶ The Fourier decomposition uses trigonometric functions as orthogonal basis
- ▶ These functions oscillates forever, i.e. the information is spread
- ▶ We need functions localized in time and scales \Rightarrow Wavelet Transform (Farge 1992; Mallat 1999).



Beyond Fourier: Wavelet transform


- ▶ The Fourier decomposition uses trigonometric functions as orthogonal basis
- ▶ These functions oscillates forever, i.e. the information is spread
- ▶ We need functions localized in time and scales \Rightarrow **Wavelet Transform** (Farge 1992; Mallat 1999).



- ▶ Defining time-frequency atoms as $\psi_{s,\tau} = \frac{1}{\sqrt{\tau}} \psi\left(\frac{t-s}{\tau}\right)$ the **Continuous Wavelet Transform** is defined as

$$w(s, \tau) = \frac{1}{\sqrt{\tau}} \int_{-\infty}^{+\infty} f(t) \psi^* \left(\frac{t-s}{\tau} \right) dt$$

- ▶ In analogy to Fourier we can define Wavelet Cross power spectrum and Corresponding phase spectrum (well localized in time/frequency)



- ▶ Phase spectrum between density and potential varies because of variation of the shear → responsible for transport reduction (Antoni et al. [2000](#))

Summary

- ▶ High temporal and spatial resolution are needed for better characterization of the plasma. But two points still gives a bunch of information
- ▶ Fourier transform allows estimate of quantities directly comparable with theories
- ▶ Often localized events (in space or time) require more sophisticated tools which maintain the locality of the information
- ▶ As much as possible correlation between different diagnostics are generally needed for an appropriate comprehension

Bibliography I

- [1] M Agostini et al. "Study of statistical properties of edge turbulence in the National Spherical Torus Experiment with the gas puff imaging diagnostic". In: *Physics of Plasmas* 14.10 (Jan. 2007), p. 102305.
- [2] V Antoni et al. "Electrostatic transport reduction induced by flow shear modification in a reversed field pinch plasma". In: *Plasma Physics and Controlled Fusion* 42.2 (2000), pp. 83–90.
- [3] Ronald Bracewell. *The Fourier Transform & Its Applications*. 3rd ed. McGraw-Hill Science/Engineering/Math, June 1999.
- [4] G D Conway et al. "Direct measurement of zonal flows and geodesic acoustic mode oscillations in ASDEX Upgrade using Doppler reflectometry". In: *Plasma Physics and Controlled Fusion* 47.8 (July 2005), pp. 1165–1185.
- [5] M Farge. "Wavelet Transforms and Their Applications to Turbulence". In: *Annual Review Of Fluid Mechanics* 24 (1992), pp. 395–457.
- [6] Stephane Mallat. *A Wavelet Tour of Signal Processing, Second Edition (Wavelet Analysis & Its Applications)*. 2nd ed. Academic Press, Sept. 1999.
- [7] Nicola Vianello et al. "Reynolds and Maxwell stress measurements in the reversed field pinch experiment Extrap-T2R". In: *Nuclear Fusion* 45.8 (July 2005), pp. 761–766.
- [8] Nicola Vianello et al. "Self-Regulation of $E \times B$ Flow Shear via Plasma Turbulence". In: *Physical Review Letters* 94.13 (Apr. 2005), p. 135001.

Bibliography II

- [9] Nicola Vianello et al. “Turbulence, flow and transport: hints from reversed field pinch”.
In: *Plasma Physics and Controlled Fusion* 48.4 (Mar. 2006), S193–S203.