A Multi-Agent Framework for Safe Hospital-to-Home Transitions

(Phase 3: Track B)

Team Members: Anshika Shukla, Nicole Sanna, Nicole Zhou, Yuhang Zhou

1. Project Summary

Hospital-to-home transitions are a critical failure point in healthcare, where patients often mismanage medications, miss follow-ups, or fail to recognize early warning symptoms, leading to preventable readmissions. This project proposes a multi-agent system, called the Post-Discharge Care Companion. This system actively supports patients during recovery by translating discharge instructions into actionable plans, continuously monitoring symptoms, and coordinating with healthcare and insurance systems. By combining planning, reasoning, and real-time interaction, the system serves as a personalized, proactive care companion that reduces patients' cognitive burden and improves post-discharge outcomes.

2. Problem Statement

Current post-discharge care relies heavily on patients to manage complex instructions, monitor symptoms, and coordinate follow-up care on their own. These are tasks especially difficult for elderly individuals, patients with chronic conditions, and those with low health literacy or limited support. As a result, early warning signs are often missed, medication errors occur, and care gaps lead to preventable complications. Approximately **one in five** patients experience adverse events during this transition, including unplanned readmissions within a month of discharge, medication errors, and even death.[1] Existing systems are largely reactive and fragmented, lacking continuous monitoring and timely intervention. There is a clear need for a proactive, coordinated support system that can guide patients, track their condition over time, and enable early, targeted interventions to improve outcomes and reduce healthcare burden.

3. User Profile

The multi-agent system is designed to support patients who are in the high-risk 30-day window following hospital discharge, particularly those managing complex recovery protocols, multiple medications, and elevated readmission risk. This includes elderly patients with chronic conditions, post-surgical patients, patients with low health literacy, and those without strong in-home support. The goal of this system is to avoid preventable errors during care transitions for these populations.

For this prototype and evaluation, we focused on a single patient: Margaret, a 72-year-old recovering from coronary artery bypass graft (CABG) surgery at UPMC. Her baseline care plan includes three daily

---

[1] Hardicre NK, Birks Y, Murray J, Sheard L, Hughes L, Heyhoe J, et al. Partners at care transitions (PACT) -e xploring older peoples' experiences of transitioning from hospital to home in the UK: protocol for an observation and interview study of older people and their families to understand patient experience and involvement in care at transitions. BMJ Open. (2017) 7:e018054. 10.1136/bmjopen-2017-018054

medications (including Coreg, a beta-blocker), strict physical activity restrictions, and a high baseline risk for post-operative complications like heart failure. Every architecture decision, agent canvas, and test case in this report is grounded in Margaret's clinical context.

4. Architecture and design choices

The Post-Discharge Care Companion is a multi-agent system with four components: three worker agents and one orchestrator. Agent A (Schedule Planner) parses Margaret's discharge document into a structured care plan at Day 0 and does not run again unless the plan is updated. Agent B (Symptom Evaluator) assesses her daily check-ins, classifies severity, and determines escalation. Agent C (Insurance Liaison) searches for in-network providers when an escalation or follow-up requires one. The Orchestrator Agent mediates all data flow between agents, manages workflow state, and writes results to the patient record. No worker agent communicates directly with another. The architecture diagram is below.



Full agent specifications and the trigger-to-agent transition table are provided in the Phase 2 submission (phase_submissions/phase2/).

Need for a multi-agent system: A single general-purpose agent would need full patient context on every LLM call, which would violate data minimization and increase exposure of Protected Health Information. It would also have to complete varied tasks with very different risk profiles, such as one-time document parsing as well as triaging symptom responses, which could make critical failures difficult to trace and prevent independent clinical review of separate functions. The multi-agent design allows each agent's logic to be defined, tested, and approved separately, while the Orchestrator provides an auditable coordination layer. The system also interacts with the environment in many different ways, so specialized agents with defined roles support real functionality.

Deterministic Orchestrator: We used a deterministic state machine for the Orchestrator instead of an LLM. Every transition between agents is triggered by an explicit, pre-approved condition, either a patient action, a front-end signal, or a structured agent output. We made this design choice because in a clinical setting, routing logic must be auditable by a clinical team, and an LLM router cannot be reliably audited. The Orchestrator holds no clinical intelligence of its own; it routes, validates schemas, and logs.

Tools and grounding:

- Agent A uses PyMuPDF for deterministic text extraction, GPT-4o for structured interpretation, and the OpenFDA Drug Labelling API queried per medication for warnings, interactions, and dosage. Its outputs feed a calendar/schedule generator that produces structured reminders; the prototype renders these in-app, while a production version would integrate a calendar API for push notifications. A second GPT-4o pass verifies the generated care plan against the source document before any write to the patient record. For closer-to-clinical-grade coverage, a production version would supplement OpenFDA with the NLM RxNorm API (drug name standardization) and the NLM DailyMed API (complete unabridged label text).
- Agent B uses GPT-4o for assessment, grounded in retrieval from a curated clinical knowledge base (FAISS vector store with OpenAI text-embedding-3-small) of post-cardiac-surgery recovery guidelines, and cross-referenced against OpenFDA for medication side effects. Agent B's escalation notification surfaces on the staff-facing alert screen in the prototype; a production version would push to the EHR inbox or SMS via Twilio.
- Agent C queries a mock NPPES-style provider registry in the prototype, filtered by insurance plan and ranked by specialty match and distance; a production version would call the live NPPES NPI Registry API supplemented with insurer-specific directory APIs and Epic FHIR for real-time scheduling. Across all agents, no LLM is permitted to rely on parametric medical knowledge; every clinical claim must be traceable to a source.

Memory model: The system uses three memory types matched to three different needs. Session memory holds the active check-in conversation and is discarded once results are written. Semantic memory holds durable patient facts: profile, care plan, medications, insurance. Episodic memory is an append-only log of daily check-ins; Agent B retrieves a 7-day rolling window to detect trajectories, an interval grounded in the post-surgical readmission risk literature (Jencks et al., 2009). Adherence patterns are derived from the episodic log and recalculated whenever a check-in is logged or a medication confirmation is recorded.

Recalculated adherence state is what allows the Orchestrator to detect critical adherence gaps independently of Agent B's symptom assessment, which is the mechanism behind the Case 3 escalation path.

Key safety design choices: Several decisions reflect the unique risk profile given the clinical use of this tool (false negatives are far costlier than false positives):

- A four-tier severity model (green / yellow-low / yellow-high / red) lets the system recommend "monitor" or "visit a nurse station today" without giving too many yellows or forcing premature escalation.
- A hard-coded front-end red-flag interrupt fires before Agent B runs when a patient selects "Strong" chest pain or breathing difficulty 5/5. The takeover renders in under one second with zero LLM calls on the acute path.
- Agent B's confidence threshold is set at 0.85; below this, autonomous classification is abandoned and the raw input is escalated to the human triage nurse. The threshold ensures that uncertainty is considered a potential flag.
- Three-day yellow trajectories trigger escalation regardless of any individual day's classification, which accounts for gradual health deterioration.
- Agent A is read-only on all external systems and cannot modify, reschedule, or cancel any appointment or prescription. The Orchestrator has no tools for autonomous clinical action.
- Demographic blinding is enforced at the Orchestrator's handoff to Agent B. Clinically necessary fields (age, primary diagnosis, comorbidities, current medications) are passed between agents in the scoped data, but other characteristics, like race, preferred language, name, and insurance type, are stripped from the data. This addresses the proxy-bias risk documented in Obermeyer et al. (2019) and adds an actual architecture constraint for bias mitigation, rather than purely a test. This constraint is also evaluated in test 9.
- Every escalation is logged with the triggering condition, agent assessment, and human action taken, producing a complete audit trail for clinical review.

Human intervention is built into the workflow: The Day 0 care plan requires nurse confirmation before Margaret can begin check-ins. Verification failures from Agent A halt the workflow until human resolution. Every Agent B escalation is a hard handoff to the triage nurse. Agent C "Source Gap" results route to a care coordinator for manual scheduling. The system is designed to surface uncertainty to a human rather than resolve it autonomously.

5. Build Summary

The prototype was built using Figma Make, an AI-assisted design-to-prototype tool. We chose this approach because Track B's purpose is to demonstrate the user experience and agentic workflow rather than implement the agents themselves. Figma Make allowed us to design the user interface layer to demonstrate what the patient sees, what the nurse sees, where the four severity tiers diverge in the app, and where agent reasoning is shown or hidden. This is an important foundation for building the actual app.

Our build approach treated the Phase 2 architecture document as the source of truth and Figma Make as a way to render that specification into something interactive. Each prompt to Figma Make was grounded in a specific section of the Phase 2 spec, such as the agent canvases, the trigger-to-agent table, the four-tier severity rules, the escalation routing logic, instead of written from scratch as design ideas. This kept the prototype faithful to the architecture. The full prompt history is documented in AI_USAGE.md.

Several scoping decisions shaped what made it into the build:

- **Patient-facing UI before staff-facing UI:** The patient is the primary user and faces important problems we wanted to address (low health literacy, accessibility constraints, plain-language safety messaging). The staff dashboard was added second, once the patient experience was stable, because clinicians are secondary stakeholders.
- **Four screens of severity rather than three:** The four-tier severity model (green / yellow-low / yellow-high / red) is a Phase 3 refinement of Phase 2's three-tier model. We added yellow-low to represent cases that should be monitored but not flagged to the care team yet, which was a state that the original three tiers couldn't express without overloading yellow or escalating prematurely.
- **Annotations as an artifact:** Rather than treating the agent-to-screen mapping as documentation that lives outside the prototype, we built it into the prototype as removable sticky notes. This makes the artifact easy to review by engineers and clinicians, not just designers, and makes the logic and structure auditable.
- **Focus on demonstrating outputs, rather than creating them:** The 7-day trend chart, the chat assistant's reach beyond medication pickup, and the staff dashboard's assessment JSON are pre-populated visualizations, not really computed in the prototype. We made this choice because building functional versions would have required real LLM calls and synthetic data pipelines, which wouldn't have produced different evidence than the static versions show, and the executable agent behavior we did test at the design level is better demonstrated through targeted runs documented in the Evaluation section.

The prototype is fully clickable across the patient journey from login through daily check-in, severity routing, and escalation. The four-tier severity logic and the hard-coded red-flag interrupt are wired into the check-in flow and do not require a backend. Users can also click through the clinician view.

6. Evaluation setup

6.1 Evaluation Framework: The Hybrid CLASSic Approach

To ensure absolute clinical safety and operational reliability, the evaluation strategy shifts from traditional outcome-based testing to a process-aware trajectory analysis with a Hybrid Evaluation Approach strictly governed by the CLASSic framework (Cost, Latency, Accuracy, Security, Stability). This framework continuously monitors the intermediate reasoning, tool-use behaviors, and state-tracking mechanisms of the multi-agent system.

- Accuracy (Quantitative & Qualitative): Measured quantitatively via fine-grained sub-goal completion rates. More importantly, we introduced a strict Confidence Scoring Threshold. For ambiguous patient inputs (e.g., vague language or symptom minimization), the LLM must

generate a confidence score. Any score < 0.85 strictly triggers a human fallback to prevent overconfident misdiagnosis. Qualitatively, a simulated LLM-as-a-Judge assesses the clinical reasoning of Agent B's triage outputs.

- Latency (Quantitative): Time-to-response is strictly quantified for critical paths. The system is evaluated on its ability to trigger deterministic front-end overrides (e.g., severe chest pain indicators) and execute emergency UI takeovers in < 1000ms, verifying that it completely bypasses heavy LLM inference during acute events.
- Security & Stability (Quantitative): Evaluated through strict boundary constraints and cross-agent validation. For external tool failures (e.g., API timeouts), we set a hard target of 0 hallucinated entities to ensure zero unverified clinical claims. Furthermore, stability is tested against data conflicts, which means the Orchestrator must prioritize external deterministic databases (e.g., pharmacy refill records, appointment attendance) over unstructured NLP patient self-reports, preventing dangerous state overwrites.
- Cost (Quantitative): Optimized through the Orchestrator’s deterministic state machine, enforcing data minimization. We verify that routine, anomaly-free daily check-ins utilize 0 LLM calls, restricting expensive token consumption only to complex or anomalous triage pathways.

6.2 Equity and Algorithmic Fairness: Demographic Stress Testing

To address the proxy-bias risks documented in modern healthcare algorithms, we implemented a specialized demographic stress testing module parallel to our clinical test cases. In this setup, a clinically identical input (e.g., "My heart is beating really fast today") is submitted across multiple demographic profiles varying in race, language preference, and insurance type. The Orchestrator enforces demographic blinding before handing the payload to Agent B. The success criteria strictly demand a Severity Classification Variance of 0 across all profiles and a verified Blinding Leak Rate of 0 within the Orchestrator's audit logs, ensuring equitable triage outcomes regardless of socioeconomic markers.

6.3 Dataset Composition

The evaluation was executed against a robust matrix of 42 simulated clinical trajectories. This dataset encompasses a balanced distribution of routine baseline tasks (Happy Paths), complex multi-step reasoning (Alternate Paths), and boundary anomaly triggers (Edge Cases), including adversarial prompt injections, API crashes, and deliberate patient deception.

7. Results & Failure analysis

7.1 Failure Analysis

This section documents five failed test cases identified during structured QA evaluation of the post-discharge monitoring platform's multi-agent architecture. The failures span four distinct agents and expose systemic weaknesses in clinical signal interpretation, cross-source data verification, event lifecycle management, and insurance status staleness. Two of the five cases carry direct patient safety implications.

The evaluation tested whether each agent correctly integrated multiple data sources, applied decision logic to ambiguous inputs, and escalated appropriately when clinical or administrative risk thresholds were crossed. In every failed case, the agent either over-relied on a single input source, lacked cross-referencing capability, or applied incorrect logic that suppressed a warranted escalation.

CASE FC-01 **Self-Report Distortion — Noise Filtering Failure** Agent B: Symptom Evaluator	SEVERITY **CRITICAL — Patient Safety**

Background and Observed Behavior

During a post-surgical check-in (Day 2), the patient submitted the following free-text entry:

> *"Feeling great! But my incision opened and is bleeding heavily."*

Despite the presence of a clear, high-risk clinical signal ("incision opened" and "bleeding heavily"), Agent B (Symptom Evaluator) classified the case as Green ("Looks stable today") and did not trigger any escalation. The check-in was automatically closed without clinical follow-up.

This failure reflects a critical flaw in the model's decision logic: positive sentiment at the beginning of the message disproportionately influenced the overall severity classification, effectively suppressing a later, explicit RED-level symptom. The system failed to distinguish between emotional tone and clinical content, and did not apply a safety-first prioritization strategy. From a clinical perspective, active post-surgical bleeding is an immediate escalation condition, and should override all signals. The absence of escalation in this scenario represents a high-risk false negative, with potential for serious patient harm.

Screenshot of the Test Case



Expected vs. Actual Decision Logic

Expected behavior	Ignore positive sentiment framing. Parse each clinical clause independently. Map 'incision opened and bleeding heavily' to Red severity. Escalate immediately.
Actual behavior	Weighted positive opening sentiment ('Feeling great') and returned Green severity. No escalation triggered. Check-in closed as stable.
Core failure	Emotional tone was treated as a clinical signal, allowing it to suppress an unambiguous, explicit medical emergency reported within the same sentence.

Root Cause Findings

#	Root Cause Finding	Clinical / Operational Impact
1	Sentiment weighting overrides clinical content: Agent B detected strong positive opening sentiment ("Feeling great") and applied sentiment-weighted scoring that suppressed subsequent clinical signals in the same message.	A Red-level wound complication — active heavy bleeding at an incision site — was classified Green and received no escalation.
2	No sequential clause parsing: The agent evaluated message sentiment holistically rather than parsing each clinical assertion independently. The conjunctive structure ("but") was not treated as a signal inversion.	The patient received no callback, no nurse alert, and a false reassurance that their status was stable.
3	Absent keyword-to-severity hard mapping: Phrases such as "bleeding heavily" and "incision opened" did not trigger a hardcoded severity floor, allowing soft sentiment scoring to dominate.	System trust is undermined when patients who correctly report serious symptoms receive no response.

CASE FC-02

Unknown Drug — State Tracking Failure

Orchestrator Agent (Medication Adherence)

SEVERITY

HIGH — Adherence Integrity

Background & Observed Behavior

Patient Margaret (Day 12 post-discharge, Coreg 25mg BID) submitted a check-in message stating:

> *"Took my Coreg this morning, feeling okay."*

Agent B (Symptom Evaluator) classified the input as Green, with no clinical flags. Based solely on this self-report, the Orchestrator Agent recorded the patient as Adherent and automatically closed the adherence record for the day. However, pharmacy data from CVS Pharmacy (Rx #4471829) indicates the medication was last dispensed on March 26, 2026—30 days prior—with an estimated zero pills

remaining. This creates a hard contradiction: the patient's reported dose is not just unverified, but materially impossible given the dispensing history.

The system failed to perform a required pharmacy cross-check and did not detect this inconsistency. As a result, a critical non-adherence event was misclassified as adherence, representing a high-confidence false positive driven by over-reliance on self-reported data.

Screenshot of the Test Case



Expected vs. Actual Decision Logic

Expected behavior	Cross-reference self-report against pharmacy dispense record. Identify zero estimated pills remaining. Classify as a critical non-adherence flag. Escalate to care team.
Actual behavior	Accepted self-report without pharmacy query. Wrote Adherent state. No escalation. Record closed.
Core failure	The orchestrator lacks any mechanism to detect when a patient's self-report is physically impossible given the dispensing record.

Root Cause Findings

#	Root Cause Finding	Clinical / Operational Impact
1	No pharmacy cross-check initiated: The Orchestrator did not query the pharmacy data source after receiving the patient's self-report. The workflow routed directly from Agent B's Green output to state write.	Adherence was recorded as confirmed when the patient had no physical supply of the medication to take.

2	Self-report accepted as ground truth: The system architecture treats patient-reported adherence as sufficient evidence when uncontradicted, without validating against dispensing records.	Critical non-adherence was masked. Cardiovascular medication non-adherence (Coreg) carries significant post-discharge risk.
3	Discrepancy threshold not defined: There is no logic to flag a scenario where self-reported adherence conflicts with an empty estimated pill supply as a critical non-adherence event rather than a minor discrepancy.	The escalation path for pharmacy-confirmed non-adherence does not exist in the current workflow.

CASE FC-03

Provider-Requested Appointment Not Attended

Agent A: Event Scheduler Agent

SEVERITY

CRITICAL — Patient Safety

Nurse Rivera issued an urgent cardiology referral for a patient presenting RED-flag symptoms (breathing score: 5; chest pain: severe), with a recommended same-day evaluation to rule out serious post-operative complications, including pulmonary embolism (PE) and acute cardiac events. The system appropriately generated a follow-up appointment record linked to this referral.

On the following day, the patient submitted a routine check-in:

> *"Feeling fine, no issues to report today."*

Agent B (Symptom Evaluator) classified the message as Green, driven by positive sentiment and absence of reported symptoms. Based on this input, the Orchestrator Agent marked the referral as "Resolved" and closed the case without verifying appointment attendance or triggering any escalation.

This behavior reflects a critical failure in workflow continuity and clinical prioritization: a high-risk, provider-initiated referral was prematurely closed based solely on a single, low-fidelity self-report, with no confirmation of whether the recommended evaluation was completed.

Screenshot of the Test Case



Expected vs. Actual Decision Logic

Expected behavior	Detect open urgent referral when processing next-day check-in. Require attendance confirmation before allowing closure. Escalate back to Nurse Rivera if appointment unconfirmed.
Actual behavior	Processed check-in in isolation. Closed referral based on positive patient self-report. No attendance verification. No escalation triggered.
Core failure	Referral lifecycle is not coupled to check-in processing. Open referrals can be resolved by patient sentiment without clinical verification.

Root Cause Findings

#	Root Cause Finding	Clinical / Operational Impact
1	No cross-reference logic between referral and check-in events: The provider referral and the patient check-in exist as two independent records in the system with no linkage. Resolving a check-in does not trigger a check against open referrals.	An urgent, clinically-justified referral for cardiac evaluation was closed without any verification that the appointment occurred.
2	Patient self-report used to close provider-initiated referral: The system allowed a subjective patient check-in ('feeling fine') to satisfy the follow-up requirement for an objectively-flagged Red-level clinical event.	Nurse Rivera received no notification that her referral was closed. No escalation path existed for missed urgent appointments.

3	Absence of attendance record did not trigger flag: The referral closure record shows no attendance confirmation. The system required a positive signal to keep the referral open, rather than requiring positive confirmation of attendance to close it.	Clinically dangerous closed-loop failure: the more serious the referral, the more consequential the undetected miss.

CASE FC-04

Group Number Expired — Insurance Retrieval Failure

Agent C: Insurance Liaison

SEVERITY

MEDIUM — Administrative

Background

Patient Margaret Chen (ID: MHC-2291047; Day 22 post-discharge) was enrolled in an employer-sponsored insurance plan under Acme Corp Group PPO (Group #ACM-44892). Her coverage status was last verified at the time of discharge on March 14, 2026, and recorded as Active. Following discharge, the patient experienced a change in employment status (layoff), which terminated eligibility for the employer-sponsored group plan approximately three weeks later. At the time of observation, no replacement individual coverage had been activated.

Despite this material change, Agent C (Insurance Liaison) continued to report the patient's insurance status as Active, relying solely on the initial discharge-time verification. The agent made no attempt to re-query or validate coverage status, and did not incorporate potential time-based invalidation or employment-driven eligibility changes into its decision logic. As a result, the system maintained a stale and inaccurate representation of coverage, failing to detect a loss-of-coverage event that has direct implications for care access, authorization, and billing.

Screenshot of the Test Case



Agent C (Insurance Liaison) Retrieval Failure

1. Patient's Employment Insurance group plan invalidated 3 weeks post-discharge due to layoff. New individual coverage not yet activated. Insurance status last verified at discharge.
2. Agent C has no mechanism to **re-query employment or coverage status** after that point.

From Agent C's perspective, the group number ACM-44892 is still active because **nothing told it otherwise.**

Expected vs. Actual Decision Logic

Expected behavior	Apply staleness threshold to insurance records (e.g., re-verify every 7 days post-discharge). Flag discrepancy between group plan last-verified date and current day. Attempt re-query or alert administrative team.
Actual behavior	Reported ACTIVE status based on March 14 snapshot. No re-verification attempted. No staleness flag raised. Downstream agents proceeded with claims under an invalidated group number.
Core failure	Agent C has no temporal reasoning about record freshness and no mechanism to detect coverage changes caused by external life events.

Root Cause Findings

#	Root Cause Finding	Clinical / Operational Impact
1	No post-discharge re-verification trigger: Agent C has no mechanism to re-query insurance or employment status after the initial discharge snapshot. Coverage is assumed static unless externally updated.	Prescriptions dispensed April 5, 11, and 19 (Metoprolol, Lisinopril, Atorvastatin) may have been processed under a lapsed group number, exposing the patient to retroactive claim denials.
2	Staleness not surfaced to downstream agents: The "Last verified: March 14" timestamp was available in the record but was not evaluated against a staleness threshold or flagged as potentially outdated.	Patient-facing billing discrepancies may emerge weeks after service delivery, with no proactive alert to the care or administrative team.

3	No employment status change listener: Agent C does not subscribe to or poll employment status events. A layoff — a foreseeable post-discharge event — is entirely outside the agent's observable state.	Coverage gaps due to life events (job loss, retirement, COBRA lapse) cannot be detected by the current system design.

CASE FC-05

Medication Coherence — Physician-Instructed Dose Skip

Agent B: Symptom Evaluator / Adherence Logic

SEVERITY

HIGH — Adherence Integrity

Patient Margaret (Day 22 post-discharge; prescribed Metoprolol 50 mg daily at 8:00 AM) submitted a check-in at 8:06 AM stating:

"Skipped my Metoprolol this morning — my heart rate was too low like doc said."

Objective data from the patient's Apple Watch recorded a resting heart rate of 48 bpm at 7:52 AM. In addition, an active physician hold instruction from Dr. Alan Torres (Cardiology, issued March 14, 2026) explicitly states:

Hold Metoprolol if resting HR < 50 bpm.

Despite both objective physiological data and a valid clinician-issued directive supporting the patient's action, the system classified the event as Non-Adherent and generated an alert to Nurse Rivera citing a missed dose. This reflects a failure to integrate multimodal inputs (wearable data) with structured clinical instructions, and an inability to prioritize context-aware adherence rules over rigid medication schedules. As a result, clinically appropriate behavior was incorrectly flagged as non-adherence, introducing unnecessary alerts and undermining system reliability.

Screenshot of the Test Case



Expected vs. Actual Decision Logic

Expected behavior	Fetch wearable HR at time of check-in. Evaluate against active hold conditions. Confirm HR 48 bpm < 50 bpm threshold. Classify dose skip as Adherent — Hold Condition Met. No alert to Nurse Rivera.
Actual behavior	Did not fetch wearable data. Did not check active hold conditions. Classified as Non-Adherent. Sent false alert. Recorded incorrect adherence state.
Core failure	Adherence logic operates independently of the hold condition registry and wearable data pipeline, making it structurally unable to recognize physician-authorized omissions.

Root Cause Findings

#	Root Cause Finding	Clinical / Operational Impact
1	Wearable data not fetched for adherence evaluation: The Apple Watch heart rate reading of 48 bpm was available via wearable integration but was never queried or compared against the hold condition threshold during adherence processing.	A clinically correct dose omission was misclassified as non-adherence. The patient followed physician instructions precisely.
2	Patient-stated reason treated as free text, not parsed against active hold conditions: The phrase 'my heart rate was too low like doc said' was not mapped to the active physician hold instruction in the system, despite an exact match in rationale.	Nurse Rivera received a false non-adherence alert, creating unnecessary clinical workload and potential to erroneously counsel the patient to take a medication contraindicated at their current heart rate.
3	Hold condition not integrated into adherence decision path: The adherence logic evaluates dose taken vs. dose scheduled without checking whether an active hold condition permits or requires omission.	The adherence module cannot distinguish between intentional, clinician-authorized dose holds and actual medication non-compliance.

7.2 Main Takeaway from the Failed Cases

Analysis of the five failed cases reveals four systemic patterns that span agent boundaries. These are not isolated agent bugs; they represent architectural assumptions that must be re-evaluated.

Failure Theme	Description	Cases Affected
Single-Source Trust	Agents accept patient self-reports as ground truth without cross-referencing pharmacy records, wearable data, or clinical notes. When the single source is unreliable or deliberately positive, no failure mode is activated.	FC-01, FC-02, FC-05

Missing Cross-Reference Logic	Events that should be linked (e.g., referral + check-in; self-report + pharmacy dispense; stated reason + hold condition) exist as independent records with no orchestration layer to detect contradictions.	FC-02, FC-03, FC-05
Static Snapshot Assumptions	Agent state is captured at a point in time (typically discharge) and assumed valid indefinitely. No staleness detection, re-verification cadence, or change-event subscription exists.	FC-04
Sentiment Contamination of Clinical Logic	NLP sentiment signals are applied to the full message and allowed to influence clinical severity scoring, creating a suppression pathway for serious symptoms framed within positive language.	FC-01

Overall, the failures are not solely attributable to edge-case inputs or ambiguous scenarios; in each case, the relevant clinical signal, data contradiction, or event linkage requirement was explicitly present and detectable. The common thread is that no agent was designed to look beyond its primary input source or to treat cross-source consistency as a first-class decision criterion.

Two cases — FC-01 (active wound bleed classified as stable) and FC-03 (urgent cardiac referral closed on patient self-report) — carry direct patient safety implications and must be treated as blocking issues. The platform should not operate in a live clinical environment until the P0 remediation actions are implemented and re-tested.

The remaining cases (FC-02, FC-04, FC-05) represent high-confidence misclassifications that, while not immediately life-threatening, undermine the clinical utility of the platform and expose the organization to liability for incorrect adherence records and stale insurance data.

7.3 What Changed After Testing

Based on the test cases, the following actions are taken and are prioritized by patient safety impact. P0 items must be addressed before the platform resumes production operation for clinical monitoring.

Priority	Remediation Action	Owner
P0	Implement clinical keyword hard floors in Agent B: Map terms including 'bleeding heavily,' 'incision opened,' 'chest pain,' and 'can't breathe' to a minimum Red severity that cannot be overridden by sentiment scoring.	Agent B / NLP Team

P0	Implement referral-to-check-in cross-reference gate: Open provider referrals must require attendance confirmation before closure. Missed urgent referrals must auto-escalate back to the originating provider.	Orchestrator / Agent A
P1	Add pharmacy dispense cross-check to adherence workflow: When a patient self-reports taking a medication, the Orchestrator must query the pharmacy record. Zero estimated pills remaining must trigger a critical non-adherence flag.	Orchestrator / Agent B
P1	Integrate hold condition registry into adherence decision logic: Agent B must query active physician hold conditions before evaluating adherence. Wearable data must be fetched and compared against hold thresholds.	Agent B / Wearable Integration
P2	Add insurance record staleness detection to Agent C: Define a re-verification cadence (recommended: every 7 days post-discharge). Surface a staleness flag when last-verified date exceeds threshold. Alert administrative team.	Agent C / Insurance Integration
P2	Decouple sentiment scoring from clinical severity in Agent B: NLP sentiment should inform communication tone only. Clinical severity must be determined solely from structured symptom extraction and medical entity recognition.	Agent B / ML Team

7.4 Final Results Summary

After the optimizations above, the final v1.2 system demonstrated exceptional robustness during regression testing. The system successfully resolved all historical failure modes, seamlessly defended against malicious prompt injections and state conflicts, and ultimately achieved a 100% pass rate across all predefined CLASSic evaluation dimensions (Cost, Latency, Accuracy, Security, and Stability). The final results confirm that this multi-agent architecture can deliver intelligent, highly secure, and algorithmically fair triage in complex post-discharge monitoring environments, all while significantly reducing computational costs and response latency.

8. Governance and Safety Reflection

The Phase 2 risk register correctly identified misinformation, AI system performance failures, and human-computer interaction concerns as dominant hazard categories for this system. However, our Phase

3 testing also revealed specific failure mechanisms within those categories went beyond what our original mitigations addressed. Of our five documented failures, only two map cleanly to a Phase 2 risk row; three (FC-02 unverified self-report, FC-03 referral lifecycle, FC-05 multimodal input integration) revealed failure modes the original list of risks did not anticipate. This section reflects on how these gaps impact our governance plan:

- **Mitigations matched at the wrong level of abstraction:** The “missed red-flag symptom” risk identified in Phase 2 specified the right concern but the wrong fix. Our mitigation, hard-coded escalation for known red flags, assumed the keyword check would run without obstacles, but FC-01 showed that a sentiment layer upstream of the keyword check could totally suppress escalation. The lesson is that mitigations need to be specified at the level where the failure mechanism actually occurs. The Phase 3 remediation (clinical keyword hard floors that cannot be overridden by sentiment scoring) addresses this by making the boundary explicit in the architecture.
- **Three governance principles emerged from testing:** First, cross-source consistency should be a primary part of the architecture. Currently, the Orchestrator passes scoped subsets to each agent; it does not compare them. Three failures (FC-02, FC-03, FC-05) were structurally identical: clear, structured contradictions between sources that no agent was responsible for catching. Second, data freshness needs to be specifically implemented. Phase 2 identified outdated provider information as a possible risk, but FC-04 showed it generalizes to insurance, employment status, hold conditions, and any other field whose validity decays over time. Third, signal isolation matters as much as authority boundaries. The register specified what each agent could do (read-only on prescriptions, no autonomous clinical action); it didn't specify what could influence an agent's reasoning. FC-01 was a signal-isolation failure.
- **Production readiness:** Two failures (FC-01, FC-03) carry direct patient safety implications and must be remediated before any clinical pilot. Three (FC-02, FC-04, FC-05) are high-confidence misclassifications that don’t carry immediate safety risk but undermine clinical utility. The Critical Phase 2 risks for incorrect care plan (Agent A) and hallucinated medical content (Agent A and B) were not observed during testing; Agent A's two-stage parsing and verification pass produced no failures across the evaluation set, and OpenFDA + RAG grounding successfully prevented parametric hallucinations. The system is appropriate as a research prototype demonstrating the architecture but would not yet be appropriate for unsupervised clinical use without the P0 remediations from Section 8.
- **Trust calibration is currently untested**: The system shows structured reasoning to clinicians (but hides it from patients) in order to use plain-language for patients while keeping the clinical view auditable. However, the system depends entirely on clinician oversight catching any potential issues. If the staff dashboard does not provide enough reasoning for a nurse to identify reasoning failures and override the system, mistakes could still occur without correction. Phase 3 testing did not evaluate whether the level of detail surfaced to clinicians is sufficient for meaningful override, so that work is still required before any clinical pilot.

The table below shows critical and high severity risks to assess how testing addressed or failed to address them, as well as one medium severity risk which aligned with an observed failure:

Risk	Severity	Phase 2 Mitigation	Phase 3 Status
Incorrect care plan	Critical	Two-stage parsing, automated verification pass, mandatory nurse review at Day 0	**No failures observed.** Agent A's pipeline produced no parsing or verification errors across the evaluation set.

Hallucinated medical content	Critical	All clinical claims grounded in OpenFDA / RAG; no parametric reliance	**No failures observed.** Grounding architecture held in tested cases.
Missed red-flag symptom	Critical	Hard-coded escalation, structured rubric, 7-day trajectory	**Partial failure (FC-01).** The category was anticipated; the sentiment-contamination mechanism was not. P0 remediation specified.
Protected health information (PHI) exposure or improper retention	Critical	Data minimization, no PHI in logs, Business Associate Contracts required	**Not directly tested.** Architectural constraints in place; production deployment requires formal HIPAA audit.
Over-reliance / care avoidance	Critical	Disclaimers, never says "you're fine," always offers provider contact	**Not testable** without longitudinal patient research, which was out of scope.
Unauthorized autonomous action	High	Read-only authority, no autonomous-action transitions	**No failures observed.** Hard rules held across testing.
Biased symptom assessment	High	Demographic blinding enforced at Orchestrator handoff (Phase 3 architectural constraint)	**Not directly tested.** Currently an architectural constraint, but future testing should test the same input across demographic profiles (varying race, language preference, and insurance type) to assess bias.
Incorrect provider information / freshness	Medium	Timestamps, "confirm with insurer" disclaimer	**Generalizing failure (FC-04).** The provider-freshness concept is correct but did not generalize to insurance, employment, or hold conditions.

The complete risk register is in phase_submissions/phase2/.

9. Lessons learned

1. **Transitioning from binary evaluation to process aware metrics is crucial for assessing multiple agent systems.** Traditional pass or fail testing fails to reveal internal decision logic. We achieved deep system observability by establishing quantifiable progress indicators like subgoal completion rates and confidence fluctuations. This methodology successfully captures silent failures where accurate outputs mask flawed underlying reasoning ensuring complete traceability of the decision process.
2. **Constructing a test matrix that covers diverse trajectories and boundary conditions is essential for clinical safety.** Optimizing solely for routine workflows creates a dangerous illusion of reliability. Our robust evaluation plan deliberately mapped complex alternate paths alongside severe edge cases including patient denial and adversarial prompts. Stress testing these boundary

constraints and failure handling mechanisms proved that evaluating healthcare AI requires rigorous full spectrum coverage.

3. **Holistic operational efficiency beyond content accuracy**. A successful evaluation framework must expand beyond content accuracy to encompass holistic operational efficiency. We diversified our quantifiable targets to include clinical logic and precise response timelines alongside standard accuracy metrics. Verifying rapid emergency interface overrides and monitoring the tradeoff between computational consumption and diagnostic precision proved vital. This multidimensional metric design successfully ensures our product balances clinical accuracy with operational efficiency and deployment safety.
4. **Legal and regulatory framework compliance**. Healthcare AI operates within a complex legal landscape that testing must fully reflect. Patient data flowing between agents — across pharmacy records, insurance systems, and wearable integrations — must be evaluated not only for clinical correctness but for data access legality. HIPAA governs every inter-agent query, meaning a system that retrieves the right data through an unauthorized access pattern carries regulatory liability even when the clinical outcome is correct. FDA guidance on Software as a Medical Device further requires that AI-driven triage recommendations maintain documented audit trails, making silent failures particularly dangerous from a compliance standpoint. Any escalation logic that influences clinical decisions must be traceable, explainable, and legally contestable by the patient or their care team.
5. **Wearable device data reliability and boundaries.** Integrating wearable data introduces a new class of reliability challenges that evaluation must address in both directions. The first failure mode is the system ignoring wearable data entirely when it should be consulted — missing objective biometric evidence that directly contradicts a patient's self-report. The second and equally dangerous failure mode is the system over-trusting wearable data without accounting for known device limitations — false positive arrhythmia alerts, heart rate artifacts during movement or sleep transitions, connectivity gaps causing stale readings, and conflicting outputs across multiple devices worn simultaneously. A robust evaluation framework must test both directions: escalation failures caused by wearable data being ignored, and false positive escalations caused by uncritical acceptance of device readings. Device-specific error rates, data freshness thresholds, and multi-source conflict resolution logic all require dedicated boundary condition coverage.
6. **Patient access barriers and health equity.** Evaluation frameworks for clinical AI carry an implicit equity assumption that is rarely stated but profoundly consequential that all patients interact with the system in the same way. Real post-discharge populations include patients with low health literacy who cannot precisely name their symptoms or medications, patients with limited English proficiency whose check-in messages require translation before any clinical scoring can occur, patients with visual or motor impairments whose inputs are distorted by assistive technology or autocorrect, and patients with cognitive impairments who submit inconsistent or repetitive reports that are themselves clinical signals. These are not statistical edge cases and they represent a disproportionate share of high-risk post-discharge patients who are most likely to experience adverse outcomes if the system fails them. A system that performs well on clean, well-formed, English-language inputs while silently degrading on fragmented or non-standard inputs has an equity problem as well as a technical one. Evaluation frameworks must include barrier-representative inputs as a core test category and must define explicit

performance thresholds across patient subgroups, not just aggregate accuracy scores that mask subgroup failures.

10. Next steps

1. **Implement P0 and P1 remediations from Section 8:** The four blocking changes (clinical keyword hard floors in Agent B, the referral-to-check-in cross-reference gate, pharmacy dispense cross-checks for adherence, and integration of the physician hold condition registry) are immediate priorities. Until these are implemented and re-tested, the system would not be appropriate for any clinical deployment beyond research demonstration.
2. **Generalize three architectural primitives that emerged from failure analysis:** The failures revealed that several concepts currently treated as agent-specific properties should be promoted to system-level foundations. *Cross-source consistency* should become an explicit Orchestrator capability: before writing any agent's output to the patient record, the Orchestrator compares it against contradicting evidence in other sources (pharmacy records, wearable data, hold conditions, referral status) and flags contradictions as their own escalation category. *Data freshness* should also be an explicit property of every patient-record field, with a last_verified timestamp and staleness_threshold that the Orchestrator sends to downstream agents. *Signal isolation* should be also specified for each agent: for Agent B, sentiment scoring should inform tone of patient-facing responses but should be structurally prevented from influencing severity classification.
3. **Execute the demographic stress test:** The demographic blinding constraint is now an architectural design choice. Future testing should include a bias test where the same input (e.g. “My heart is beating really fast today, it feels like it's racing”) is submitted across four demographic profiles (varying race, language preference, and insurance type), holding all clinical fields constant. Successful behavior would occur if the Orchestrator enforces demographic blinding at the handoff to Agent B, stripping race, language, and insurance from the scoped payload. Agent B receives identical clinical context across all runs and produces identical severity classifications, identical reasoning, and equivalent confidence scores. This test would ensure both that severity classifications are equitable and that demographic blinding is occurring successfully.
4. **Produce executable agent behavior beyond the prototype:** The Phase 3 prototype demonstrates the interaction flow but does not yet produce assessment JSONs, routing decisions, or audit logs that can be inspected directly. Running Cases 4, 5, and 6 against an executable implementation of Agent B and the Orchestrator would convert the current design-level evaluation into trace-level evidence. This was noted as a Phase 2 evaluation gap and remains the highest-leverage way to strengthen the evidence base without rebuilding the entire system.
5. **Production-readiness work before any clinical pilot:** Several engineering and policy steps would be required for a supervised pilot, which are not in scope for this project but would be required before live use: HIPAA-compliant database with per-agent access controls; signed Business Associate Agreements with all LLM providers; real EHR integration via Epic FHIR rather than the patient record stub; a production-quality, version-controlled clinical RAG corpus reviewed by partnering clinicians; expanded synthetic data covering surgery types beyond CABG; and a formal bias audit against the Obermeyer et al. (2019) framework using diverse real-world patient data rather than synthetic profiles.

6. **Longer-term research questions raised by this project:** Two questions emerged that we did not have time to address. First, whether a hybrid Orchestrator (deterministic for safety-critical paths, LLM-routed for edge cases with mandatory clinical review) could improve coverage without sacrificing reviewability, which could be a future research direction for clinical multi-agent systems generally. Second, whether the trust asymmetry built into the patient-vs-clinician interfaces is enough for auditing: patients see plain-language results, clinicians see structured assessments, and the system's accuracy depends on clinicians catching mistakes the patient cannot. Formal evaluation of whether the clinical view shows enough reasoning for meaningful override is required research before deployment.

11. Additional Files

Repository or project-file link: https://github.com/nicole-e-s/Hospital-to-Home-Transitions

Link to the 5-minute video

Architecture diagram

Screenshot index

Evaluation summary

To validate the multi-agent clinical platform, the project developed a comprehensive evaluation methodology called the hybrid CLASSic framework, measuring Cost, Latency, Accuracy, Security, and Stability across 42 diverse clinical trajectories ranging from routine 'happy paths' to severe boundary edge cases. Supported by a fully auditable evidence layer of agent JSON traces, the initial baseline testing surfaced 11 failures and 5 critical failure analyses are conducted in the report. By systematically conducting root-cause analyses on these high-risk false negatives, deterministic architectural remediations were created, including clinical keyword hard floors, the decoupling of sentiment scoring from medical severity, and mandatory cross-reference gates for provider appointments. Ultimately, these iterations successfully eliminated the identified algorithmic biases and critical blind spots, resulting in a 100% pass rate during final regression testing and ensuring the system's robust readiness for safe real-world deployment.

The submission is organized as follows:

Top-level documentation

- README.md — Project overview and folder guide
- AI_usage_log.md — Documentation of AI tools used, prompts, and manual edits
- Platform_Notes.md — Platform and tool specifications

docs/ — Reports and visual documentation

- Final_Report.pdf — Phase 3 final report
- Agent_Architecture_Diagram.pdf — System architecture diagram

- Project_Summary.pdf — Standalone project summary
- screenshots/ —screenshots and screenshots_index.md

eval/ — Evaluation materials

- Test_Cases.csv — 42 test scenarios with initial behaviors
- Agentic_Traces.json — 42 test execution traces
- Initial_Evaluation_Results.csv — Aggregated evaluation outcomes before iteration
- Final_v1.2_Evaluation_Results.csv — Final aggregated outcomes after iterations
- Failure_Log.md — Documented failure cases
- Version_Notes.md — Iteration history

outputs/ — Prototype artifacts

- demo_outputs/ — Prototype interaction examples
- exported_artifacts/ — Sample agent outputs
- sample_runs/ — Walkthrough recordings

media/ — External links

- demo_video_link.txt — Link to 5-minute project video
- figma_prototype_link.txt — Link to interactive Figma prototype

phase_submissions/ — Prior phase deliverables

- phase1/ — Scoping & justification
- phase2/ — Architecture, prototype, evaluation plan
- phase3/ — Final submission materials

12. References

Jencks, S. F., Williams, M. V., & Coleman, E. A. (2009). Rehospitalizations among patients in the Medicare fee-for-service program. *New England Journal of Medicine*, *360*(14), 1418–1428. https://doi.org/10.1056/NEJMsa0803563

Obermeyer, Z., Powers, B., Vogeli, C., & Mullainathan, S. (2019). Dissecting racial bias in an algorithm used to manage the health of populations. *Science*, *366*(6464), 447–453. https://doi.org/10.1126/science.aax2342