Lab: Unit Testing and Modules

Error Handling

1. Sub Sum

Write a function to sum a **range** of **numeric elements** from an array.

The function takes **three parameters** - the first is an **array**, the second is the **start index** and the third is the **end index**. Both indexes are **inclusive**. Have in mind that the array elements **may not be** of **type Number** and **cast everything**. Implement the following **error handling**:

- If the **first element** is not an array, **return NaN**
- If the **start index** is less than zero, consider its value to be a **zero**
- If the **end index** is outside the bounds of the array, assume it points to the **last index of the array**

Input / Output

Your function must take **three parameters**. As output, **return the sum**.

Examples

Input	Output
`[10, 20, 30, 40, 50, 60], 3, 300`	`150`
`[1.1, 2.2, 3.3, 4.4, 5.5], -3, 1`	`3.3`
`[10, 'twenty', 30, 40], 0, 2`	`NaN`
`[], 1, 2`	`0`
`'text', 0, 2`	`NaN`

What to submit?

Export your function in **subNum.js** and import it in your test file to test it. Submit a **zip** file containing the **subNum.js** and **tests folder** containing the **subNum.test.js**. **Do not** include the **node_modules** folder.

File Name: SUB-SUM.zip

2. Playing Cards

Create a JS **factory function** that returns a **Card object** to hold a card's **face** and **suit**, both set through the **constructor**. **Throw an error** if the card is **initialized** with **invalid face** or **suit** or if an attempt is made to change the **face** or **suit** of an **existing instance to an invalid** value.

- Valid card faces are: 2, 3, 4, 5, 6, 7, 8, 9, 10, J, Q, K, A
- Valid card suits are: S (♠), H (♥), D (♦), C (♣)

Both face and suit are expected as an **uppercase string**. The class also needs to have a **`toString()`** method that **prints** the card's face and suit **as a string**. Use the following UTF code literals to represent the suits:

- \u2660 – Spades (♠)
- \u2665 – Hearts (♥)
- \u2666 – Diamonds (♦)
- \u2663 – Clubs (♣)

Input / Output

The factory function takes **two string parameters**. The **`toString()`** method of the returned object must **return a string**.

Examples

Input	Output
`'A', 'S'`	A♠
`'10', 'H'`	10♥
`'1', 'C'`	Error

What to submit?

Export your function in **playingCards.js** and import it in your test file to test it. Submit a **zip** file containing the **playingCards.js** and **tests folder** containing the **playingCards.test.js**. **Do not** include the **node_modules** folder.

File Name: PLAYING-CARDS.zip

3. Deck of Cards

Write a function that takes **a deck of cards** as an **`array of strings`** and **prints** them as a **sequence** of cards (**space separated**). Use the solution from the **previous task** to generate the cards.

Print "**`Invalid card: [card]`**" when an **invalid card** definition is passed as input.

Input / Output

The function takes an **array of strings** as parameter. **Print** the list of cards as **string**, **separated by space**.

deckOfCards.js

```
function printDeckOfCards(cards) {

  function createCard {

     // Use the solution from the previous task

  }

    // TODO

}
```

Examples

Sample Input	Sample Output
['AS', '10D', 'KH', '2C']	A♠ 10♦ K♥ 2♣
['5S', '3D', 'QD', '1C']	Invalid card: 1C

What to submit?

Export your function in **deckOfCards.js** and import it in your test file to test it. Submit a **zip** file containing the **deckOfCards.js** and **tests folder** containing the **deckOfCards.test.js**. **Do not** include the **node_modules** folder.

File Name: DECK-OF-CARDS.zip

4. Sum of Numbers

Write tests to check the functionality of the following code:

sumNumbers.js

```
function sum(arr) {
    let sum = 0;
    for (num of arr)
        sum += Number(num);
    return sum;
}
```

Your tests will be supplied with a function named **'sum()'**. It should meet the following requirements:

- Take an **array of numbers** as argument
- **Return** the **sum** of the values of **all elements** inside the array

What to submit?

Export your function in **sumNumbers.js** and import it in your test file to test it. Submit a **zip** file containing the **sumNumbers.js** and **tests folder** containing the **sumNumbers.test.js**. **Do not** include the **node_modules** folder.

File Name: SUM-OF-NUMBERS.zip

5. Check for Symmetry

Write tests to check the functionality of the following code:

checkForSymmetry.js

```
function isSymmetric(arr) {
    if (!Array.isArray(arr))
        return false; // Non-arrays are non-symmetric
    let reversed = arr.slice(0).reverse(); // Clone and reverse
    let equal = (JSON.stringify(arr) == JSON.stringify(reversed));
    return equal;
}
```

Your tests will be supplied with a function named **'isSymmetric()'**. It should meet the following requirements:

- Take an **array** as argument
- **Return false** for any input that isn't of the **correct type**

- **Return true** if the input array is **symmetric**
- Otherwise, **return false**

What to submit?

Export your function in **checkForSymmetry.js** and import it in your test file to test it. Submit a **zip** file containing the **checkForSymmetry.js** and **tests folder** containing the **checkForSymmetry.test.js**. **Do not** include the **node_modules** folder.

File Name: CHECK-FOR-SYMMETRY.zip

6. RGB to Hex

Write tests to check the functionality of the following code:

rgbToHex.js

```
function rgbToHexColor(red, green, blue) {
    if (!Number.isInteger(red) || (red < 0) || (red > 255))
        return undefined; // Red value is invalid
    if (!Number.isInteger(green) || (green < 0) || (green > 255))
        return undefined; // Green value is invalid
    if (!Number.isInteger(blue) || (blue < 0) || (blue > 255))
        return undefined; // Blue value is invalid
    return "#" +
        ("0" + red.toString(16).toUpperCase()).slice(-2) +
        ("0" + green.toString(16).toUpperCase()).slice(-2) +
        ("0" + blue.toString(16).toUpperCase()).slice(-2);
}
```

Your tests will be supplied with a function named **'rgbToHexColor()'**, which takes **three arguments**. It should meet the following requirements:

- Take three **integer numbers**, representing the red, green and blue values of an RGB color, each **within range [0...255]**
- **Return** the same color in hexadecimal format as a **string** (e.g. '#FF9EAA')
- **Return undefined** if **any** of the input parameters are of **invalid type** or **not** in the **expected range**

What to submit?

Export your function in **rgbToHex.js** and import it in your test file to test it. Submit a **zip** file containing the **rgbToHex.js** and **tests folder** containing the **rgbToHex.test.js**. **Do not** include the **node_modules** folder.

File Name: RGB-TO-HEX.zip

7. Add / Subtract

Write tests to check the functionality of the following code:

addSubtract.js

```
function createCalculator() {
    let value = 0;
    return {
        add: function(num) { value += Number(num); },
        subtract: function(num) { value -= Number(num); },
        get: function() { return value; }
    }
}
```

Your tests will be supplied with a function named '**`createCalculator()`**'. It should meet the following requirements:

- **Return a module** (**object**), containing the functions **`add()`**, **`subtract()`** and **`get()`** as **`properties`**
- Keep an **internal sum** which **can't be modified** from the outside
- The functions **`add()`** and **`subtract()`** take a parameter that can be **parsed as a number** (either a number or a string containing a number) that is added or subtracted from the **internal sum**
- The function **`get()`** **returns** the value of the **internal sum**

What to submit?

Export your function in **addSubtract.js** and import it in your test file to test it. Submit a **zip** file containing the **addSubtract.js** and **tests folder** containing the **addSubtract.test.js**. **Do not** include the **node_modules** folder.

File Name: ADD-SUBRACT.zip