Exercise: Strings and Regular Expressions

1. Binary Decoding

You will receive a **string** from **zeros** and **ones**. Write a function that converts it into text.

To do that, you need to:


- Calculate the weight of the string (sum of all the ones).

 The result of that sum should be a single digit (e.g. '10011101111100111111' here the sum is 21, but since we need only one digit, we sum 2 and 1 and get 3).
- Remove from the start and the end the calculated sum and split the remaining string into groups of 8 characters.
- Convert each segment of binary code into **decimals** to get the **ASCII code** of each element.
- Print the result in the "**result**" span (only the letters and spaces).
- Be careful about unwanted characters!
- The input should consist only alphabetical symbols.

Input	Output	Comment
0100011011010111100100100000 011011100110000101101	iny france 13	The sum here is 40; 4 + 0 = 4; we take 4 characters from the beginning and end, then we split it into segments of 8 characters and we get '01101101', '01111001', '00100000', '01101101', '01100001', '01100101', '0110011'. When we convert each one of these segments into ascii we get 109 121 32 110 97 109 101 32 150 115. When we convert that into text we get 'my name is'
1000010010110110100101101110 0110011101110011011	Kingsland	



Example



What to submit?

Zip file containing the following:

- solution.js
- template.css
- template.html

File Name: BINARY-DECODING.zip

2. Expedition Problems

The expedition is over, and everyone has returned successfully to the rest house. However, it turns out that one person from the group has fallen behind. He sent a message to the leader, but his device was broken, and the message contains unwanted symbols, which prevent it from being read. Since the leader has no knowledge of programming, he has assigned the task of decrypting to you.

You will receive a text (string), which can contain all the ASCII symbols, including new lines and tabs. The location of the lost person and his message must be retrieved from this string. The text contains a keyword that indicates the beginning and the end of the message. The geographical coordinates come as a pair of longitude ("east") and latitude ("north") and each coordinate should meet the following conditions:

- 1. It should start with "north"/"east", case-insensitive;
- 2. The next symbols should be 2 digits, which form the whole part of the degrees;
- 3. The whole part of the degrees is separated from the decimal part by "," and there may be any characters between them, except ","
- 4. The decimal part consists of 6 digits



In case there is **more than one** longitude or latitude in the text, take **the latter**. The message is surrounded by the **keyword**, which will be the **first argument** from the input. The second argument from the input will be the **text**, containing **both the location** and **the message** of the lost person. See the examples below to understand how it works.

Input

The first argument contains the keyword and the second argument contains the text. There will always be **at least one pair of coordinates**.

Output

Print the latitude in a **paragraph** in the span with id **"result"** in the following format:

<degrees>.<decimal part> N

Print the second in a **paragraph** in the span with id **"result"** in the following format:

<degrees>.<decimal part> E

On the last line, print the message in the following format:

Message: <message>

Example

Input

4ds

<mark>eaSt</mark> 19,<mark>432567</mark>noRt north east 53,123456north 43,321345<mark>4dsNot all those who wander are</mark> lost.4dsnorth 47,874532

Output

47.874532 N 19.432567 E

Message: Not all those who wander are lost.

Input

<>

o u%&lu43t&^ftgv><<mark>nortH42</mark>76hrv756dcc<mark>,</mark> jytbu<mark>645746</mark>55k <mark><>ThE sanDwich is iN the</mark> <mark>refrIGErator<></mark>yl i75ev<mark>EAsT</mark>er<mark>23,</mark>lfwe <mark>987324</mark>tlblu6b


Output

42.645746 N 23.987324 E

Message: ThE sanDwich is iN the refrigerator

Hints





What to submit?

Zip file containing the following:

- solution.js
- template.css
- template.html

File Name: EXPEDITION-PROBLEMS.zip

3. James Bond

You are the spy master of a guild of spies. Since you are constantly being stalked, your spies communicate with you by sending **encoded messages**.

You will receive a special key and some lines of text which you must combine in order to encode the messages.

The special key:

- Will only consist of one or more English letters
- Must be preceded by either a space or the start of the string
- May appear in any casing (both lower and uppercase letters)

Valid encoded messages should:

- Immediately follow the special key and should be separated from it only by one or more spaces
- Be at least 8 symbols long and can only consist of the following symbols:
 - !, %, \$, # or Capital English letters
- Be followed by a space, a dot (.), a comma (,) or the end of the string.



After finding the correct **encoded messages**, you must **decode** and **replace them in the original text**.

The **decoding** should meet the following requirements:

- The symbol ! is converted to 1
- The symbol % is converted to 2
- The symbol # is converted to 3
- The symbol \$ is converted to 4
- Capital English letters are converted to lowercase

Constraints

- A pair of a special key and encoded message will never be split between multiple lines
- The preceding space before a special key will never overlap with a trailing space after an encoded message
- There will never be an **encoded message** equal to the **special key**

Input

The input comes as an array of strings - the first element is the special key, each element after it is a line of text

Output

The **output** should be displayed in the DOM - consisting of the entire text with the **correct encoded messages**, replaced with their **decoded** versions. Each **line of text** should be in a new paragraph in the "**result**" span.

Examples

Input

["specialKey",

"In this text the specialKey HELLOWORLD! is correct, but the following specialKey \$HelloWorl#d and spEcIaLKEy HOLLOWORLD1 are not, while SpeCIaLKey SOM%%ETH\$IN and SPECIALKEY ##\$\$##\$\$ are!"]

Output

In this text the specialKey helloworld1 is correct, but the following specialKey \$HelloWorl#d and spEcIaLKEy HOLLOWORLD1 are not, while SpeCIaLKeY some and SPECIALKEY 33443344 are!

Input

["enCode",

"Some messages are just not encoded what can you do?

RE - ENCODE THEMNOW! - he said.

Damn encode, ITSALLHETHINKSABOUT, eNcoDe BULL\$#!%."]

Output

Some messages are just not encoded what can you do?

RE - ENCODE themnow1 - he said.

Damn encode, ITSALLHETHINKSABOUT, eNcoDe bull4312.



Hints

Array

["enCode", "Some messages are jus

Calculate

Result: Some messages are just not encoded what can you do? RE - ENCODE themnow1 - he said. Damn encode, ITSALLHETHINKSABOUT, eNcoDe bull4312.

What to submit?

Zip file containing the following:

- solution.js
- template.css
- template.html

File Name: JAMES-BOND.zip

4. Airport Check

Your next task is to extract information about a flight.

You will be given a single string, separated by a comma. The **first** part of the string will be the text you need to extract information from. The **second** part will be the **information you need to print**.

The information to extract is as follows:

Passenger name:

- Starts with a space (' ')
- Consists of either 2 or 3 names (upper and lower-case letters)
- The names should be separated by a single dash ('-')
 - Each name should start with an upper-case letter
 - If there are 3 names, the second one should end with a dot ('.')
 - If there are 2 names, the second one should NOT contain any dots



Ends with a space (' ')
 Valid examples with 2 names: 'George-Adams', 'G-A'
 Valid examples with 3 names: 'G-A.-Adams', 'Valid-V.-Name'

Airport:

- Starts with a space (' ')
- Should consist of **3 upper-case letters**, the symbol '/' and **3 more upper-case letters**
- Ends with a space (' ')

Valid examples of airports are: 'SOF/VAR', 'VIE/AIR'

Flight number:

- Starts with a space (' ')
- Followed by 1 to 3 upper-case letters
- Followed by 1 to 5 digits
- Ends with a space (' ')

Valid examples of flight numbers are: ' DWF24 ', ' S43159 ', ' OE314 '

Company:

- Starts with dash and space '- '
- Followed by one or more letters (starting with an upper-case letter)
- Followed by '*'
- Followed by one or more letters again (starting with an upper-case letter)
- Ends with a space (' ')

Valid examples of companies are: '- Wizz*Air ', '- X*Y '

Input

A single string, separated by a comma

Output

There are four different types of output, depending on the **second** parameter:

```
'name'-print'Mr/Ms, {name}, have a nice flight!'
'flight'-print'Your flight number {flightNumber} is from {fromAirport} to
{toAirport}.'
'company'-print'Have a nice flight with {companyName}.'
```

'all'-print'Mr/Ms, {name}, your flight number {flightNumber} is from {fromAirport} to {toAirport}. Have a nice flight with {company}.'

The name should be printed without the '-' (if any) and with spaces instead:

```
' STEPH-T.-Smith ' -> 'STEPH T. Smith'.
```

The **company** should be printed **without the '- '** and the **'*'**:

```
' - Wizz*Air ' -> 'Wizz Air'.
```

The **flight number** should be printed **without the spaces in the front and back**:

```
' 0S806 ' -> '0S806'
```

Display the output in the "result" span



Examples

Input	Output
ahah George-Adams)*))&&ba MIA/ATL ela** FB973 - American*Airlines -opFB900 pa-MIA/ATl// T12G12 STD08:45 STA09:35 , all	Mr/Ms, George Adams, your flight number FB973 is from MIA to ATL. Have a nice flight with American Airlines.



What to submit?

Zip file containing the following:

- solution.js
- template.css
- Template.html
- flight.png

File Name: AIRPORT-CHECK.zip