



KINGSLAND
UNIVERSITY

REST Services and AJAX



HTTP, RESTful Web Services, AJAX Concepts, XMLHttpRequest



Table of Contents


1. The HTTP Overview
2. HTTP Developer Tools
3. REST and RESTful Services
4. Accessing the GitHub API
5. AJAX
 - Fetch API





Have a Question?

#js-advanced



HTTP Protocol

HTTP Overview



HTTP Basics

- HTTP (**H**yper **T**ext **T**ransfer **P**rotocol)
 - Text-based client-server protocol for the Internet
 - For transferring Web resources (HTML files, images, styles, etc.)
 - Request-response based



Web Client

**HTTP
request**

**HTTP
response**









Web Server



HTTP Request Methods

- **HTTP** defines **methods** to indicate the desired action to be performed on the identified resource

Method	Description
GET 	Retrieve / load a resource
POST 	Create / store a resource
PUT 	Update a resource
DELETE 	Delete (remove) a resource
PATCH 	Update resource partially
HEAD 	Retrieve the resource's headers
OPTIONS	Returns the HTTP methods that the server supports for the specified URL



HTTP GET Request - Example

GET /users/testnakov/repos HTTP/1.1

HTTP request line

Host: api.github.com

Accept: */*

Accept-Language: en

HTTP headers

Accept-Encoding: gzip, deflate

User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64)

AppleWebKit/537.36 (KHTML, like Gecko) Chrome/54.0.2840.71

Safari/537.36

Connection: Keep-Alive

Cache-Control: no-cache

The request body is empty

<CRLF>



HTTP POST Request – Example

```
POST /repos/testnakov/test-nakov-repo/issues HTTP/1.1
Host: api.github.com
Accept: */*
Accept-Language: en
Accept-Encoding: gzip, deflate
User-Agent: Mozilla/4.0 (compatible;MSIE 6.0; Windows NT 5.0)
Connection: Keep-Alive
Cache-Control: no-cache
<CRLF>
{"title":"Found a bug",
 "body":"I'm having a problem with this.",
 "labels":["bug","minor"]}
<CRLF>
```

HTTP request line

HTTP headers

The request body holds the submitted data



HTTP Response – Example



HTTP/1.1 200 OK

HTTP response status line

Date: Fri, 11 Nov 2016 16:09:18 GMT+2

Server: Apache/2.2.14 (Linux)

Accept-Ranges: bytes

Content-Length: 84

Content-Type: text/html

<CRLF>

<html>

<head><title>Test</title></head>

<body>Test HTML page.</body>

</html>

HTTP response headers

HTTP response body



HTTP Response Status Codes

Status Code	Action	Description
200	OK	Successfully retrieved resource
201	Created	A new resource was created
204	No Content	Request has nothing to return
301 / 302	Moved	Moved to another location (redirect)
400	Bad Request	Invalid request / syntax error
401 / 403	Unauthorized	Authentication failed / Access denied
404	Not Found	Invalid resource
409	Conflict	Conflict was detected, e.g. duplicated email
500 / 503	Server Error	Internal server error / Service unavailable



Content-Type and Disposition

- The **Content-Type** / **Content-Disposition** headers specify how the HTTP request / response body should be processed

JSON-encoded data

Content-Type: application/json

UTF-8 encoded HTML page. Will be shown in the browser

Content-Type: text/html; charset=utf-8

Content-Type: application/pdf

Content-Disposition: attachment;
filename="Financial-Report-April-2016.pdf"

This will download a PDF file named
Financial-Report-April-2016.pdf




Chrome Dev Tools, Fiddler, Postman

HTTP Developer Tools




Chrome Developer Tools



Read more about Chrome Developer Tools



Postman




Read more about Postman REST Client

{REST}

REST and RESTful Services

REST and RESTful Services

- **Representational State Transfer** ([REST](#))
 - Architecture for **client-server communication** over HTTP
 - Resources have **URI** (address)
 - Can be **created/retrieved/modified/deleted**/etc.
- RESTful API/RESTful Service
 - Provides access to **server-side resources** via **HTTP** and **REST**



REST Architectural Constraints

- REST defines **6 architectural constraints** which make any web service - a true RESTful API
 - Client-server architecture
 - Statelessness
 - Cacheable
 - Layered system
 - Code on demand (optional)
 - Uniform interface

[Read more about REST Architectural Constraints](#)





REST and RESTful Services – Example

- Create a new post

POST	http://some-service.org/api/posts
------	---

- Get all posts / specific post

GET	http://some-service.org/api/posts
-----	---

GET	http://some-service.org/api/posts/17
-----	---

- Delete existing post

DELETE	http://some-service.org/api/posts/17
--------	---

- Replace / modify existing post

PUT/PATCH	http://some-service.org/api/posts/17
-----------	---



Accessing GitHub Through HTTP

GitHub REST API



GitHub API

- List user's all public repositories:

GET	<u>https://api.github.com/users/testnakov/repos</u>
-----	--

- Get all commits from a public repository:

GET	<u>https://api.github.com/repos/testnakov/softuniada-2016/commits</u>
-----	--

- Get all issues/issue #1 from a public repository

GET	<u>/repos/testnakov/test-nakov-repo/issues</u>
-----	--

GET	<u>/repos/testnakov/test-nakov-repo/issues/1</u>
-----	--



Github: Labels Issue

- Get the first issue from the "**test-nakov-repo**" repository
- Send a **GET** request to:
 - <https://api.github.com/repos/testnakov/test-nakov-repo/issues/:id>
 - Where **:id** is the current issue



GitHub API (2)

- Get all labels for certain issue from a public repository:

GET	https://api.github.com/repos/testnakov/test-nakov-repo/issues/1/labels
-----	---

- Create a new issue to certain repository (with authentication)

POST	https://api.github.com/repos/testnakov/test-nakov-repo/issues
------	---


Headers	Authorization: Basic base64(user:pass)
---------	--

Body	<pre>{"title": "Found a bug", "body": "I'm having a problem with this."}</pre>
------	--



Github: Create Issue

- Create an issue when you send a "**POST**" request
- Use your Github account **credentials** to submit the issue





Asynchronous JavaScript and XML


AJAX




What is AJAX?

- **Asynchronous JavaScript And XML**
 - Background loading of **dynamic content/data**
 - Load data from the Web server and **render** it
- Two types of AJAX
 - **Partial page rendering**
 - Load HTML fragment + show it in a **<div>**
 - **JSON service**
 - Loads JSON object and displays it

AJAX: Workflow





Using the XMLHttpRequest Object



XMLHttpRequest – Standard API for AJAX

```
<button id = "load">Load Repos</button>  
<div id="res"></div>
```

```
let button = document.querySelector("#load");  
button.addEventListener('click', function loadRepos() {  
    let url = 'https://api.github.com/users/testnakov/repos';  
    const httpRequest = new XMLHttpRequest();  
    httpRequest.addEventListener('readystatechange', function () {  
        if (httpRequest.readyState == 4 && httpRequest.status == 200) {  
            document.getElementById("res").textContent = httpRequest.responseText;  
        }  
    });  
    httpRequest.open("GET", url);  
    httpRequest.send();  
});
```



What is Fetch?

- The **fetch()** method allows making network requests
- It is similar to **XMLHttpRequest** (XHR). The main **difference** is that the **Fetch API**:
 - Uses **Promises**
 - Enables a **simpler** and **cleaner** API
 - Makes code more readable and maintainable

```
fetch('./api/some.json')  
  .then(function(response) {...})  
  .catch(function(err) {...})
```



Basic Fetch Request

- The response of a **fetch()** request is a **Stream** object
- The **reading** of the stream happens **asynchronously**
- When the **json()** method is called, a **Promise** is returned
 - The **response status** is checked (should be **200**) **before parsing** the response as **JSON**

```
if (response.status !== 200) {  
    // handle error  
}  
response.json()  
    .then(function(data) { console.log(data)})
```



Chaining Promises

- When working with a JSON API, you can:
 - Define the **status** and **JSON parsing** in **separate functions**
 - The functions **return promises** which can be **chained**

```
fetch('users.json')  
  .then(status)  
  .then(json)  
  .then(function(data) {...})  
  .catch(function(error) {...});
```




GET Request

- **Fetch API** uses the **GET** method so that a direct call would be like this

```
fetch('https://swapi.co/api/people/4')  
  .then((response) => response.json())  
  .then((data) => console.log(JSON.stringify(data)))  
  .catch((error) => console.error(error))
```



POST Request

- To make a **POST** request, we can set the **method** and **body** parameters in the **fetch()** options

```
fetch('/url', {  
  method: 'post',  
  headers: { 'Content-type': 'application/json' },  
  body: JSON.stringify(data),  
})
```



Body Methods

- **clone()** - create a clone of the response
- **json()** - resolves the promise with JSON
- **redirect()** - create new promise but with different URL
- **text()** - resolves the promise with string



Response Types

- **basic** - normal, same origin response
- **cors** - response was received from a valid cross-origin request
- **error** - error network
- **opaque** - Response for "no-cors" request to cross-origin resource





Body Methods (2)

- **opaqueredirect** - the fetch request was made with **redirect: "manual"**
- **arrayBuffer()** - return a promise that resolve with an ArrayBuffer
- **blob()** - determinates with a Blob
- **formData()** - return promise that determinate with FormData object

The background of the slide is a dark blue overlay on a blurred photograph of a classroom. In the background, several students are visible, some looking towards the front of the room. A whiteboard is also visible in the upper right portion of the background image.

Live Exercises



Summary

- **HTTP** is text-based request-response protocol
- **REST** uses **GET, POST, PUT, PATCH, DELETE**
- **RESTful** services address resources by URL
 - Provide **CRUD** operations over HTTP
- **AJAX** background loading of dynamic content
 - **XMLHttpRequest**
 - **Fetch**





Questions?



License

- This course (slides, examples, demos, exercises, homework, documents, videos and other assets) is **copyrighted content**
- Unauthorized copy, reproduction or use is illegal
- © Kingsland University – <https://kingslanduniversity.com>





THANK YOU

