

alleggheny EDA

2025-07-02

```
library("readr")
library("dplyr")
library("ggplot2")
library("readr")
library("stringr")
library("glue")

g <- params$category
sn <- params$year
singular_game <- readr::read_csv(glue("Desktop/SURA project code/extended_cmu_data/extended_cmu_data_",

## New names:
## Rows: 22 Columns: 16
## -- Column specification
## ----- Delimit
## (2): LINEUP (NAMES), NUMBERS dbl (13): ...1, NUMBER OF GUARDS, OPPONENT POSSESSIONS, CMU POSSESSIONS
## CMU PTS, SCORE DIFFERENT... time (1): LINEUP MINUTES
## i Use `spec()` to retrieve the full column specification for this data. i Specify the column types o
## `show_col_types = FALSE` to quiet this message.
## * `` -> `...1`

file <- glue("Desktop/SURA project code/dictionaries/", sn , "_game_order.txt")
game_order <- scan(file, what = "", sep = ",", strip.white = TRUE)

# if negatives in any columns (specifically had problem in possession column)
for (colName in colnames(c("CMU POSSESSIONS", "OPPONENT POSSESSIONS"))){
  singular_game[[colName]][singular_game[[colName]] < 0] <- 0
}

#individual_games <- readr::read_csv("Desktop/SURA project code/data frames/shortened.csv")

singular_game$`LINEUP MINUTES` <- sapply(singular_game$`LINEUP MINUTES`, function(t){
  parts <- as.integer(strsplit(as.character(t), ":")[[1]])
  parts[1]*60 + parts[2]
})

singular_game <- singular_game %>% rename('LINEUP SECONDS' = `LINEUP MINUTES`) %>% mutate(LINEUP_SORTED =
  if (is.na(l)) return(NA)
  paste(sort(strsplit(l, ", ")[[1]]), collapse = " "))
}))

singular_game <- subset(singular_game, !((`SCORE DIFFERENTIAL WHEN ENTER` <= -11 | `SCORE DIFFERENTIAL W

game <- singular_game %>% group_by(`LINEUP_SORTED`) %>% summarise(
  `NUMBER OF GUARDS` = mean(`NUMBER OF GUARDS`),
  `OPPONENT POSSESSIONS` = sum(`OPPONENT POSSESSIONS`, na.rm = TRUE),
  `CMU POSSESSIONS` = sum(`CMU POSSESSIONS`, na.rm = TRUE),
```

```

`LINEUP SECONDS` = sum(`LINEUP SECONDS`, na.rm = TRUE),
`OPPONENT PTS` = sum(`OPPONENT PTS`, na.rm = TRUE),
`CMU PTS` = sum(`CMU PTS`, na.rm = TRUE),
`CMU 3PA` = sum(`CMU 3PA`, na.rm = TRUE),
`CMU FGA` = sum(`CMU FGA`, na.rm = TRUE),
`CMU FTA` = sum(`CMU FTA`, na.rm = TRUE),
`CMU REBOUNDS` = sum(`CMU REBOUNDS`, na.rm = TRUE),
`TOTAL REBOUNDS` = sum(`TOTAL REBOUNDS`, na.rm = TRUE),
`SCORE DIFFERENTIAL WHEN ENTER` = paste(`SCORE DIFFERENTIAL WHEN ENTER`, collapse = ", "),
`QUARTER` = paste(`QUARTER`, collapse = ", ")
) %>% mutate(`PACE` = 40 * ((`CMU POSSESSIONS` + `OPPONENT POSSESSIONS`) / (2 * `LINEUP SECONDS`/60)),
`OFFENSIVE RATING` = 100 * (`CMU PTS` / `CMU POSSESSIONS`),
`DEFENSIVE RATING` = 100 * (`OPPONENT PTS` / `OPPONENT POSSESSIONS`),
`NET RATING` = `OFFENSIVE RATING` - `DEFENSIVE RATING`,
`3PA/FGA` = `CMU 3PA` / `CMU FGA`,
`TRUE SHOOTING %` = 100 * (`CMU PTS` / (2 * (`CMU FGA` + (0.44* `CMU FTA`)))),
`TRB%` = 100 * (`CMU REBOUNDS` / `TOTAL REBOUNDS`)


```

```
game <- subset(game, `LINEUP SECONDS` >= 60)
```

```

# see where to score differential cut off time -> SHOULD DO THIS AFTER OR BEFORE CUT SCRAP MINUTES?
l <- quantile(singular_game$`SCORE DIFFERENTIAL WHEN ENTER`, probs=c(0.1))
u <- quantile(singular_game$`SCORE DIFFERENTIAL WHEN ENTER`, probs=c(0.9))
ggplot(singular_game, aes(x = `SCORE DIFFERENTIAL WHEN ENTER`)) + stat_ecdf() + geom_vline(xintercept =


```



```

# see where to cut time -> SHOULD DO THIS AFTER OR BEFORE CUT SCRAP MINUTES?
p <- quantile(game$`LINEUP SECONDS`, probs=c(0.1))
ggplot(game, aes(x = `LINEUP SECONDS`)) + stat_ecdf() + geom_vline(xintercept = p) + labs(title = "Total

```




p

```
## 10%
## 86.4
```

```
#pdf(file = glue("Desktop/SURA project code/sing_game_EDA/{g}_plot.pdf"), width = 6, height = 5)
```

```
t_f <- c("3", "4")
```

```
ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `NET RATING`, fill = factor(`
```



```
n3 <- sum(game$`NUMBER OF GUARDS` == 3)
n4 <- sum(game$`NUMBER OF GUARDS` == 4)

tapply(game$`NET RATING`[game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS`[game$`NUMBER OF GUARDS` %in% t_f],
  FUN = function(x) {
    ## $`3`
    ##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
    ## -175.000 -60.417  -37.500   -2.778   66.667  200.000
    ##
    ## $`4`
    ##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
    ##  -66.667 -40.972   1.984  15.939   85.714  100.000


    nr3m <- median(game$`NET RATING`[game$`NUMBER OF GUARDS` %in% c(3)], na.rm = TRUE)
    nr4m <- median(game$`NET RATING`[game$`NUMBER OF GUARDS` %in% c(4)], na.rm = TRUE)
    nr3m

    ## [1] -37.5
    nr4m

    ## [1] 1.984127
    nr_p

    ## [1] 0.7133032
    nr_p <- wilcox.test(`NET RATING` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f))

    ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `TRB%`, fill = factor(`NUMBER OF GUARDS`)))
```



```
tapply(game$`TRB%`, [game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS` [game$`NUMBER OF GUARDS` %
```

```
## $`3`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##  50.00  50.00   58.33   61.51  66.67   85.71
##
```

```
## $`4`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##  25.00  29.86   47.22   45.60  59.38   66.67
```

```
r3m <- median(game$`TRB%` [game$`NUMBER OF GUARDS` %in% c(3)], na.rm = TRUE)
```

```
r4m <- median(game$`TRB%` [game$`NUMBER OF GUARDS` %in% c(4)], na.rm = TRUE)
```

```
r_p <- wilcox.test(`TRB%` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f), exact
```

```
r3m
```

```
## [1] 58.33333
```


```
r4m
```

```
## [1] 47.22222
```

```
r_p
```

```
## [1] 0.1387397
```

```
ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `3PA/FGA`, fill = factor(`NUM
```




```
tapply(game$`3PA/FGA`[game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS`[game$`NUMBER OF GUARDS` %in% t_f],
```

```
## $`3`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
## 0.00000 0.00000 0.07143 0.24603 0.28571 1.00000
```

```
##
## $`4`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
## 0.00000 0.02083 0.10417 0.27083 0.53125 0.75000
```

```
three3m <- median(game$`3PA/FGA`[game$`NUMBER OF GUARDS` %in% c(3)], na.rm = TRUE)
three4m <- median(game$`3PA/FGA`[game$`NUMBER OF GUARDS` %in% c(4)], na.rm = TRUE)
three_p <- wilcox.test(`3PA/FGA` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f))
```

```
ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `TRUE SHOOTING %`, fill = fac
```




```
tapply(game$`TRUE SHOOTING %`[game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS`[game$`NUMBER OF GUARDS` %in% t_f], FUN = function(x) {
  summary(x)
})
```

```
## $`3`
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##  0.000   6.443   27.172   39.613   69.643  100.000
##
```

```
## $`4`
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##   0.00   25.40   32.71   35.05   47.20   69.88
```

```
ts3m <- median(game$`TRUE SHOOTING %`[game$`NUMBER OF GUARDS` %in% c(3)], na.rm = TRUE)
ts4m <- median(game$`TRUE SHOOTING %`[game$`NUMBER OF GUARDS` %in% c(4)], na.rm = TRUE)
ts_p <- wilcox.test(`TRUE SHOOTING %` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% c(3, 4)))
```

```
ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `PACE`, fill = factor(`NUMBER OF GUARDS` %in% t_f))) +
  facet_wrap(~ `NUMBER OF GUARDS` %in% t_f, scales = 'free')
```



```
tapply(game$`PACE`[game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS`[game$`NUMBER OF GUARDS` %
```

```
## $`3`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##  48.28  60.48   66.06   65.33  69.61   82.19
##
```


```
## $`4`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##  66.89  75.29   81.93   81.50  89.91   92.63
```

```
p3m <- median(game$`PACE`[game$`NUMBER OF GUARDS` %in% c(3)], na.rm = TRUE)
```

```
p4m <- median(game$`PACE`[game$`NUMBER OF GUARDS` %in% c(4)], na.rm = TRUE)
```

```
p_p <- wilcox.test(`PACE` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f), exact
```

```
ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `DEFENSIVE RATING`, fill = fa
```


```
tapply(game$`DEFENSIVE RATING`[game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS`[game$`NUMBER OF GUARDS` %in% t_f], FUN = function(x) {
  summary(x)
})
```

```
## $`3`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##   0.00  16.67   83.33   84.72 150.00  175.00
##
```

```
## $`4`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##   0.00  33.93   58.33   50.13  66.67   88.89
```

```
dr3m <- median(game$`DEFENSIVE RATING`[game$`NUMBER OF GUARDS` %in% c(3)], na.rm = TRUE)
dr4m <- median(game$`DEFENSIVE RATING`[game$`NUMBER OF GUARDS` %in% c(4)], na.rm = TRUE)
dr_p <- wilcox.test(`DEFENSIVE RATING` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f))
```

```
ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `OFFENSIVE RATING`, fill = factor(`NUMBER OF GUARDS`)))
```



```
tapply(game$`OFFENSIVE RATING`[game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS`[game$`NUMBER OF GUARDS` %in% t_f], FUN = function(x) {
  summary(x)
})
```

```
## $`3`
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      0.00  16.67   83.33   81.94 118.75   200.00
##
## $`4`
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      0.00  31.25   60.71   66.07  92.86   150.00
```

```
or3m
```

```
## [1] 83.33333
```

```
or4m
```

```
## [1] 120
```

```
or3m <- median(game$`OFFENSIVE RATING`[game$`NUMBER OF GUARDS` %in% c(3)], na.rm = TRUE)
or4m <- median(game$`OFFENSIVE RATING`[game$`NUMBER OF GUARDS` %in% c(4)], na.rm = TRUE)
or_p <- wilcox.test(`OFFENSIVE RATING` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% c(3, 4)))
```

```
individual_games <- individual_games %>% add_row(
  `GAME` = g,
  `SCORE` = " ",
  `3G` = n3,
  `4G` = n4,
  `3G MEDIAN NET RATING` = round(nr3m, 2),
  `4G MEDIAN NET RATING` = round(nr4m, 2),
  `NET RATING DIFFERENCE` = round(abs(nr3m - nr4m), 2),
)
```

```

`NET RATING MANN-WHITNEY P-VALUE` = round(nr_p,2),
`3G MEDIAN TRB%` = round(r3m,2),
`4G MEDIAN TRB%` = round(r4m,2),
`TRB% DIFFERENCE` = round(abs(r3m - r4m),2),
`TRB% MANN-WHITNEY P-VALUE` = round(r_p,2),
`3G MEDIAN 3PA/FGA` = round(three3m,2),
`4G MEDIAN 3PA/FGA` = round(three4m,2),
`3PA/FGA DIFFERENCE` = round(abs(three3m - three4m),2),
`3PA/FGA MANN-WHITNEY P-VALUE` = round(three_p,2),
`3G MEDIAN TRUE SHOOTING %` = round(ts3m,2),
`4G MEDIAN TRUE SHOOTING %` = round(ts4m,2),
`TRUE SHOOTING % DIFFERENCE` = round(abs(ts3m - ts4m),2),
`TRUE SHOOTING % MANN-WHITNEY P-VALUE` = round(ts_p,2),
`3G MEDIAN PACE` = round(p3m,2),
`4G MEDIAN PACE` = round(p4m,2),
`PACE DIFFERENCE` = round(abs(p3m - p4m),2),
`PACE MANN-WHITNEY P-VALUE` = round(p_p,2),
`3G MEDIAN DEFENSIVE RATING` = round(dr3m,2),
`4G MEDIAN DEFENSIVE RATING` = round(dr4m,2),
`DEFENSIVE RATING DIFFERENCE` = round(abs(dr3m - dr4m),2),
`DEFENSIVE RATING MANN-WHITNEY P-VALUE` = round(dr_p,2),
`3G MEDIAN OFFENSIVE RATING` = round(or3m,2),
`4G MEDIAN OFFENSIVE RATING` = round(or4m,2),
`OFFENSIVE RATING DIFFERENCE` = round(abs(or3m - or4m),2),
`OFFENSIVE RATING MANN-WHITNEY P-VALUE` = round(or_p,2)
)

```

hard coded -> FIX LATER

#game_order <- c("alleggheny", "penn state-behrend", "muskingum", "oberlin", "denison", "carlow", "woost

```
individual_games <- individual_games %>% arrange(factor(`GAME`, levels = game_order))
```