

nyu2 EDA

2025-07-02

```
library("readr")
library("dplyr")
library("ggplot2")
library("readr")
library("stringr")
library("glue")
```

```
g <- params$category
singular_game <- readr::read_csv(glue("Desktop/SURA project code/extended_cmu_data/extended_cmu_data_",
```

```
## New names:
## Rows: 21 Columns: 22
## -- Column specification
## -----
## (1): LINEUP (NAMES) dbl (20): ...1, NUMBER OF GUARDS, OPPONENT POSSESSIONS, CMU POSSESSIONS, OPPONENT
## DIFFERENTIAL WHEN ENTE... time (1): LINEUP MINUTES
## i Use `spec()` to retrieve the full column specification for this data. i Specify the column types o
## FALSE` to quiet this message.
## * `` -> `...1`
```

```
# if negatives in any columns (specifically had problem in possession column)
for (colName in colnames(singular_game)){
  singular_game[[colName]][singular_game[[colName]] < 0] <- 0
}
```

```
singular_game$`LINEUP MINUTES` <- sapply(singular_game$`LINEUP MINUTES`, function(t){
  parts <- as.integer(strsplit(as.character(t), ":")[[1]])
  parts[1]*60 + parts[2]
})
```

```
singular_game <- singular_game %>% rename('LINEUP SECONDS' = `LINEUP MINUTES`) %>% mutate(LINEUP_SORTED =
  if (is.na(1)) return(NA)
  paste(sort(strsplit(1, ", ")[1]), collapse = " ")
}))
```

```
game <- singular_game %>% group_by(`LINEUP_SORTED`) %>% summarise(
  `NUMBER OF GUARDS` = mean(`NUMBER OF GUARDS`),
  `OPPONENT POSSESSIONS` = sum(`OPPONENT POSSESSIONS`, na.rm = TRUE),
  `CMU POSSESSIONS` = sum(`CMU POSSESSIONS`, na.rm = TRUE),
  `LINEUP SECONDS` = sum(`LINEUP SECONDS`, na.rm = TRUE),
  `OPPONENT PTS` = sum(`OPPONENT PTS`, na.rm = TRUE),
  `CMU PTS` = sum(`CMU PTS`, na.rm = TRUE),
  `CMU 3PA` = sum(`CMU 3PA`, na.rm = TRUE),
  `CMU FGA` = sum(`CMU FGA`, na.rm = TRUE),
  `CMU FTA` = sum(`CMU FTA`, na.rm = TRUE),
  `CMU REBOUNDS` = sum(`CMU REBOUNDS`, na.rm = TRUE),
  `TOTAL REBOUNDS` = sum(`TOTAL REBOUNDS`, na.rm = TRUE),
```

```

`SCORE DIFFERENTIAL WHEN ENTER` = paste(`SCORE DIFFERENTIAL WHEN ENTER`, collapse = ", "),
`QUARTER` = paste(`QUARTER`, collapse = ", ")
) %>%mutate(`PACE` = 40 * ((`CMU POSSESSIONS` + `OPPONENT POSSESSIONS`) / (2 * `LINEUP SECONDS`/60)),
`OFFENSIVE RATING` = 100 * (`CMU PTS` / `CMU POSSESSIONS`),
`DEFENSIVE RATING` = 100 * (`OPPONENT PTS` / `OPPONENT POSSESSIONS`),
`NET RATING` = `OFFENSIVE RATING` - `DEFENSIVE RATING`,
`3PA/FGA` = `CMU 3PA` / `CMU FGA`,
`TRUE SHOOTING %` = 100 * (`CMU PTS` / ( 2 * (`CMU FGA` + (0.44* `CMU FTA`)))),
`TRB%` = 100 * (`CMU REBOUNDS` / `TOTAL REBOUNDS`))

# see where to score differential cut off time -> SHOULD DO THIS AFTER OR BEFORE CUT SCRAP MINUTES?
l <- quantile(singular_game$`SCORE DIFFERENTIAL WHEN ENTER`,probs=c(0.1))
u <- quantile(singular_game$`SCORE DIFFERENTIAL WHEN ENTER`,probs=c(0.9))


l

## 10%
## 0
u

## 90%
## 0

ggplot(singular_game, aes(x = `SCORE DIFFERENTIAL WHEN ENTER`)) + stat_ecdf() + geom_vline(xintercept =

```




```

game <- subset(game, !((`SCORE DIFFERENTIAL WHEN ENTER` <= l | `SCORE DIFFERENTIAL WHEN ENTER` >= u) &
# see where to cut time -> SHOULD DO THIS AFTER OR BEFORE CUT SCRAP MINUTES?

```

```
p <- quantile(game$`LINEUP SECONDS`, probs=c(0.9))
ggplot(game, aes(x = `LINEUP SECONDS`)) + stat_ecdf() + geom_vline(xintercept = p) + labs(title = "Total
```



```
#game <- subset(game, `LINEUP SECONDS` >= p)


p

## 90%
## 206

#pdf(file = glue("Desktop/SURA project code/sing_game_EDA/{g}_plot.pdf"), width = 6, height = 5)

t_f <- c("3", "4")

ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `NET RATING`, fill = factor(`
```




```
tapply(game$`NET RATING`[game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS`[game$`NUMBER OF GUARDS` %in% t_f],
  FUN = function(x) {
    ## $`3`
    ##      Min. 1st Qu.  Median      Mean 3rd Qu.      Max.
    ## -250.00 -120.83    0.00   -40.71   20.00   166.67
    ##
    ## $`4`
    ##      Min. 1st Qu.  Median      Mean 3rd Qu.      Max.
    ## -150.00 -100.00  -58.33   -38.33    0.00   140.00
  },
  exact = FALSE)

wilcox.test(`NET RATING` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f), exact = FALSE)

##
## Wilcoxon rank sum test with continuity correction
##
## data:  NET RATING by NUMBER OF GUARDS
## W = 27, p-value = 0.7961
## alternative hypothesis: true location shift is not equal to 0

ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `TRB%`, fill = factor(`NUMBER OF GUARDS`)))

## Warning: Removed 1 row containing non-finite outside the scale range (`stat_bin()`).
```



```
tapply(game$`TRB%`, [game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS` [game$`NUMBER OF GUARDS` %in% t_f])
```

```
## $`3`
##      Min. 1st Qu.  Median      Mean 3rd Qu.     Max.    NA's
##  33.33   50.29   63.33   67.84   91.67  100.00      1
##
```


```
## $`4`
##      Min. 1st Qu.  Median      Mean 3rd Qu.     Max.
##    0.00   12.50   33.33   42.62   70.00  100.00
```

```
wilcox.test(`TRB%` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f), exact = FALSE)
```

```
##
## Wilcoxon rank sum test with continuity correction
##
## data:  TRB% by NUMBER OF GUARDS
## W = 30.5, p-value = 0.1911
## alternative hypothesis: true location shift is not equal to 0
```

```
ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `3PA/FGA`, fill = factor(`NUMBER OF GUARDS`)))
```

```
## Warning: Removed 2 rows containing non-finite outside the scale range (`stat_bin()`).
```



```
tapply(game$`3PA/FGA`[game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS`[game$`NUMBER OF GUARDS`
```

```
## $`3`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.   NA's
## 0.00000 0.00000 0.00000 0.06349 0.12500 0.21429     1
```


```
## $`4`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.   NA's
## 0.00000 0.33333 0.41667 0.44444 0.50000 1.00000     1
```

```
wilcox.test(`3PA/FGA` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f), exact = F
```

```
##
## Wilcoxon rank sum test with continuity correction
##
## data: 3PA/FGA by NUMBER OF GUARDS
## W = 4, p-value = 0.02445
## alternative hypothesis: true location shift is not equal to 0
```

```
ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `TRUE SHOOTING %`, fill = fac
```

```
## Warning: Removed 2 rows containing non-finite outside the scale range (`stat_bin()`).
```



```
tapply(game$TRUE SHOOTING % [game$NUMBER OF GUARDS %in% t_f], game$NUMBER OF GUARDS [game$NUMBER OF GUARDS %in% t_f], FUN = function(x) {
  summary(x)
})
```


```
## $`3`
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.      NA's
##      0.000   9.084  41.963   39.682  49.397 104.167         1
##
```

```
## $`4`
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.      NA's
##      0.00   33.33   51.39   68.18 109.57 150.00         1
```

```
wilcox.test(TRUE SHOOTING % ~ NUMBER OF GUARDS, data = subset(game, NUMBER OF GUARDS %in% t_f), exact = FALSE)
```

```
##
## Wilcoxon rank sum test with continuity correction
##
## data: TRUE SHOOTING % by NUMBER OF GUARDS
## W = 14, p-value = 0.5718
## alternative hypothesis: true location shift is not equal to 0
```

```
ggplot(data = subset(game, subset = NUMBER OF GUARDS %in% t_f), aes(x = PACE, fill = factor(NUMBER OF GUARDS)))
```



```
tapply(game$`PACE`[game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS`[game$`NUMBER OF GUARDS` %in% t_f], FUN = function(x) {
  summary(x)
})
```


```
## $`3`
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##  60.00   64.44   68.88   68.23   71.94   75.95
##
```

```
## $`4`
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##  48.00   56.90   59.15   63.35   61.25  100.00
```

```
wilcox.test(`PACE` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f), exact = FALSE)
```

```
##
## Wilcoxon rank sum test with continuity correction
##
## data:  PACE by NUMBER OF GUARDS
## W = 39.5, p-value = 0.06363
## alternative hypothesis: true location shift is not equal to 0
```

```
ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `DEFENSIVE RATING`, fill = factor(`NUMBER OF GUARDS`)))
```

```


tapply(game$`DEFENSIVE RATING`[game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS`[game$`NUMBER OF GUARDS` %in% t_f],
  FUN = function(x) {
    ## $`3`
    ##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
    ##   0.00  46.67  100.00  108.57  158.33  250.00
    ##
    ## $`4`
    ##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
    ##   0.00  83.33  100.00  127.38  162.50  300.00
  },
  simplify = FALSE)

wilcox.test(`DEFENSIVE RATING` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f),
  plot.pvalue = FALSE)

##
## Wilcoxon rank sum test with continuity correction
##
## data:  DEFENSIVE RATING by NUMBER OF GUARDS
## W = 21, p-value = 0.6996
## alternative hypothesis: true location shift is not equal to 0

ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `OFFENSIVE RATING`, fill = factor(`NUMBER OF GUARDS`)))

```



```

tapply(game$`OFFENSIVE RATING`[game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS`[game$`NUMBER OF GUARDS` %in% t_f], FUN = function(x) {

```

```

## $`3`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##   0.00   0.00   75.00   67.86  100.00   200.00
##

```

```

## $`4`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##   0.00  33.33   66.67   89.05  125.00   240.00

```

```

wilcox.test(`OFFENSIVE RATING` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f), c

```

```

##
## Wilcoxon rank sum test with continuity correction
##
## data:  OFFENSIVE RATING by NUMBER OF GUARDS
## W = 22, p-value = 0.7926
## alternative hypothesis: true location shift is not equal to 0

```

```

#dev.off()

```