

brandeis1 EDA

2025-07-02

```
library("readr")
library("dplyr")
library("ggplot2")
library("readr")
library("stringr")
library("glue")
```

```
g <- params$category
singular_game <- readr::read_csv(glue("Desktop/SURA project code/extended_cmu_data/extended_cmu_data_",
```

```
## New names:
## Rows: 27 Columns: 22
## -- Column specification
## -----
## (1): LINEUP (NAMES) dbl (20): ...1, NUMBER OF GUARDS, OPPONENT POSSESSIONS, CMU POSSESSIONS, OPPONENT
## DIFFERENTIAL WHEN ENTE... time (1): LINEUP MINUTES
## i Use `spec()` to retrieve the full column specification for this data. i Specify the column types o
## FALSE` to quiet this message.
## * `` -> `...1`
```

```
# if negatives in any columns (specifically had problem in possession column)
for (colName in colnames(singular_game)){
  singular_game[[colName]][singular_game[[colName]] < 0] <- 0
}
```

```
singular_game$`LINEUP MINUTES` <- sapply(singular_game$`LINEUP MINUTES`, function(t){
  parts <- as.integer(strsplit(as.character(t), ":")[[1]])
  parts[1]*60 + parts[2]
})
```

```
singular_game <- singular_game %>% rename(`LINEUP SECONDS` = `LINEUP MINUTES`) %>% mutate(LINEUP_SORTED =
  if (is.na(1)) return(NA)
  paste(sort(strsplit(1, ", ")[1]), collapse = " "))
}))
```

```
game <- singular_game %>% group_by(`LINEUP_SORTED`) %>% summarise(
  `NUMBER OF GUARDS` = mean(`NUMBER OF GUARDS`),
  `OPPONENT POSSESSIONS` = sum(`OPPONENT POSSESSIONS`, na.rm = TRUE),
  `CMU POSSESSIONS` = sum(`CMU POSSESSIONS`, na.rm = TRUE),
  `LINEUP SECONDS` = sum(`LINEUP SECONDS`, na.rm = TRUE),
  `OPPONENT PTS` = sum(`OPPONENT PTS`, na.rm = TRUE),
  `CMU PTS` = sum(`CMU PTS`, na.rm = TRUE),
  `CMU 3PA` = sum(`CMU 3PA`, na.rm = TRUE),
  `CMU FGA` = sum(`CMU FGA`, na.rm = TRUE),
  `CMU FTA` = sum(`CMU FTA`, na.rm = TRUE),
  `CMU REBOUNDS` = sum(`CMU REBOUNDS`, na.rm = TRUE),
  `TOTAL REBOUNDS` = sum(`TOTAL REBOUNDS`, na.rm = TRUE),
```

```

`SCORE DIFFERENTIAL WHEN ENTER` = paste(`SCORE DIFFERENTIAL WHEN ENTER`, collapse = ", "),
`QUARTER` = paste(`QUARTER`, collapse = ", ")
) %>%mutate(`PACE` = 40 * ((`CMU POSSESSIONS` + `OPPONENT POSSESSIONS`) / (2 * `LINEUP SECONDS`/60)),
`OFFENSIVE RATING` = 100 * (`CMU PTS` / `CMU POSSESSIONS`),
`DEFENSIVE RATING` = 100 * (`OPPONENT PTS` / `OPPONENT POSSESSIONS`),
`NET RATING` = `OFFENSIVE RATING` - `DEFENSIVE RATING`,
`3PA/FGA` = `CMU 3PA` / `CMU FGA`,
`TRUE SHOOTING %` = 100 * (`CMU PTS` / (2 * (`CMU FGA` + (0.44* `CMU FTA`)))),
`TRB%` = 100 * (`CMU REBOUNDS` / `TOTAL REBOUNDS`)

```

```

# see where to score differential cut off time -> SHOULD DO THIS AFTER OR BEFORE CUT SCRAP MINUTES?
l <- quantile(singular_game$`SCORE DIFFERENTIAL WHEN ENTER`, probs=c(0.1))
u <- quantile(singular_game$`SCORE DIFFERENTIAL WHEN ENTER`, probs=c(0.9))

```

```
l
```

```
## 10%
```


```
## 3
```

```
u
```

```
## 90%
```

```
## 22
```


```
ggplot(singular_game, aes(x = `SCORE DIFFERENTIAL WHEN ENTER`)) + stat_ecdf() + geom_vline(xintercept =
```



```
game <- subset(game, !((`SCORE DIFFERENTIAL WHEN ENTER` <= l | `SCORE DIFFERENTIAL WHEN ENTER` >= u) &
```

```
# see where to cut time -> SHOULD DO THIS AFTER OR BEFORE CUT SCRAP MINUTES?
```

```
p <- quantile(game$`LINEUP SECONDS`, probs=c(0.9))
ggplot(game, aes(x = `LINEUP SECONDS`)) + stat_ecdf() + geom_vline(xintercept = p) + labs(title = "Total
```



```
#game <- subset(game, `LINEUP SECONDS` >= p)

p


## 90%
## 154.2

#pdf(file = glue("Desktop/SURA project code/sing_game_EDA/{g}_plot.pdf"), width = 6, height = 5)

t_f <- c("3", "4")

ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `NET RATING`, fill = factor(`

## Warning: Removed 1 row containing non-finite outside the scale range (`stat_bin()`).
```



```
tapply(game$`NET RATING`[game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS`[game$`NUMBER OF GUARDS` %in% t_f],
```

```
## $`3`
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
## -100.000 -35.000   10.662    3.466  66.667   75.000
```

```
##
```

```
## $`4`
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.   NA's
## -100.00    0.00   66.67   49.07  100.00   133.33      1
```

```
wilcox.test(`NET RATING` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f), exact = FALSE)
```

```
##
```

```
## Wilcoxon rank sum test with continuity correction
```


```
##
```

```
## data: NET RATING by NUMBER OF GUARDS
```

```
## W = 14.5, p-value = 0.3162
```

```
## alternative hypothesis: true location shift is not equal to 0
```

```
ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `TRB%`, fill = factor(`NUMBER OF GUARDS` %in% t_f)))
```



```
tapply(game$`TRB%`, [game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS` [game$`NUMBER OF GUARDS` %in% t_f])
```


```
## $`3`
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##  50.00  50.00   50.00   64.12  70.59   100.00
```

```
## $`4`
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##   0.00   0.00   33.33   31.67  50.00   100.00
```

```
wilcox.test(`TRB%` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f), exact = FALSE)
```

```
##
## Wilcoxon rank sum test with continuity correction
##
## data:  TRB% by NUMBER OF GUARDS
## W = 41, p-value = 0.04732
## alternative hypothesis: true location shift is not equal to 0
```

```
ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `3PA/FGA`, fill = factor(`NUMBER OF GUARDS`)))
```



```
tapply(game$`3PA/FGA`[game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS`[game$`NUMBER OF GUARDS`
```


```
## $`3`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
## 0.0000 0.2500 0.2500 0.2524 0.3333 0.4286
##
```

```
## $`4`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
## 0.0000 0.0000 0.2500 0.2667 0.3333 1.0000
```

```
wilcox.test(`3PA/FGA` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f), exact = F
```

```
##
## Wilcoxon rank sum test with continuity correction
##
## data: 3PA/FGA by NUMBER OF GUARDS
## W = 27, p-value = 0.8497
## alternative hypothesis: true location shift is not equal to 0
```

```
ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `TRUE SHOOTING %`, fill = fac
```



```
tapply(game$TRUE SHOOTING % [game$NUMBER OF GUARDS %in% t_f], game$NUMBER OF GUARDS [game$NUMBER OF GUARDS %in% t_f], FUN = function(x) {
  summary(x)
})
```


```
## $`3`
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      0.00  46.43   62.50   52.62  66.67   87.50
##
```

```
## $`4`
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      0.00  50.00   51.26   59.68  86.46  100.00
```

```
wilcox.test(TRUE SHOOTING % ~ NUMBER OF GUARDS, data = subset(game, NUMBER OF GUARDS %in% t_f), exact = FALSE)
```

```
##
## Wilcoxon rank sum test with continuity correction
##
## data: TRUE SHOOTING % by NUMBER OF GUARDS
## W = 22, p-value = 0.7582
## alternative hypothesis: true location shift is not equal to 0
```

```
ggplot(data = subset(game, subset = NUMBER OF GUARDS %in% t_f), aes(x = PACE, fill = factor(NUMBER OF GUARDS)))
```




```

tapply(game$`PACE` [game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS` [game$`NUMBER OF GUARDS` %in% t_f],
  FUN = function(x) {
    ## $`3`
    ##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
    ##  68.09  68.97   70.59   71.62  73.85   76.60
    ##
    ## $`4`
    ##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
    ##  52.63  63.93   69.86   72.21  83.04   89.72
  },
  exact = FALSE)

##
## Wilcoxon rank sum test with continuity correction
##
## data:  PACE by NUMBER OF GUARDS
## W = 28, p-value = 0.7595
## alternative hypothesis: true location shift is not equal to 0

ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `DEFENSIVE RATING`, fill = factor(`NUMBER OF GUARDS`)))
## Warning: Removed 1 row containing non-finite outside the scale range (`stat_bin()`).

```

```
tapply(game$`DEFENSIVE RATING`[game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS`[game$`NUMBER OF GUARDS` %in% t_f],
```


```
## $`3`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##  50.00  70.59  100.00  105.78  133.33  175.00
##
```

```
## $`4`
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.   NA's
##   0.00   0.00   50.00   68.52   66.67  200.00     1
```

```
wilcox.test(`DEFENSIVE RATING` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f),
```

```
##
## Wilcoxon rank sum test with continuity correction
##
## data: DEFENSIVE RATING by NUMBER OF GUARDS
## W = 32.5, p-value = 0.2018
## alternative hypothesis: true location shift is not equal to 0
```

```
ggplot(data = subset(game, subset = `NUMBER OF GUARDS` %in% t_f), aes(x = `OFFENSIVE RATING`, fill = fa
```



```
tapply(game$`OFFENSIVE RATING`[game$`NUMBER OF GUARDS` %in% t_f], game$`NUMBER OF GUARDS`[game$`NUMBER OF GUARDS` %in% t_f], FUN = function(x) {
  summary(x)
})
```

```
## $`3`
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      0.00  81.25  125.00  109.25  140.00  200.00
##
```

```
## $`4`
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      0.0   75.0   100.0   105.8   150.0   200.0
```

```
wilcox.test(`OFFENSIVE RATING` ~ `NUMBER OF GUARDS`, data = subset(game, `NUMBER OF GUARDS` %in% t_f), c("n", "p"))
```

```
##
## Wilcoxon rank sum test with continuity correction
##
## data:  OFFENSIVE RATING by NUMBER OF GUARDS
## W = 27, p-value = 0.8527
## alternative hypothesis: true location shift is not equal to 0
```

```
#dev.off()
```