Easy to anticipate, hard to compute: boundary dependence finds the computed outputs that entropy patching misses

Nicolás Vera Zúñiga
Independent Researcher, Chile
nicovera@quetru.cl

Abstract

Byte-level language models such as the Byte Latent Transformer (BLT) group bytes into patches and run their large global model once per patch. BLT starts a patch where a small model's next-byte entropy is high. We show that under tight patch budgets this rule has a blind spot: positions whose *type* the preceding text fixes but whose *value* must be computed, such as the number after `=` in a worked math solution. A nearly certain digit keeps the next byte's entropy near or below $\log_2 10 = 3.32$ bits, about BLT-1B's threshold for a 10% budget. In Meta's BLT-1B with patch starts on 10% of bytes, the entropy rule puts a patch start at 16% of the computed results in GSM8K solutions and gets 19.0% of them exactly right given the true preceding text; a boundary after each `=` at the same patch count gets 51.8%, and entropy combined with a label-free *boundary-dependence* signal gets 67.1% (default layout at 26% of bytes: 76.8%). The gap survives adapting BLT-1B to the budget with low-rank adapters (32.9% vs 72.7%, three runs per rule). In byte models trained from scratch at a 10% budget on a 1.9 GB math corpus, it is not detectable at 1M parameters, appears on final answers at 12M and on both targets at 50M, as training data grow too: at 50M boundary dependence gets 35.9% of computed results against 13.9% for entropy and 78.9% of final answers against 59.0% (3 seeds each), although final answers mostly copy the solution's last number and entropy starts a patch at every one. In BLT-1B the blind spot narrows at larger budgets (entropy covers about 90% of the values right after `=` at 20% of bytes) and in the same solutions rewritten as prose, where a patch start at each value still pays. Boundary dependence, the change in the model's own loss when a patch start is removed or added, measured per two-byte context on text in the same format, finds these positions without labels.

1. Introduction

Byte-level models avoid a fixed tokenizer by working on raw bytes, and recover efficiency by grouping bytes into variable-length patches [Pagnoni et al., 2025, Slagle, 2024, Hwang et al., 2026]. In BLT, a small byte-level language model estimates the entropy of each next byte; a patch starts where that entropy crosses a threshold, and the large global transformer runs once per patch. The intuition is that compute should go where prediction is hard.

Entropy measures uncertainty about the next byte. What a patch start actually provides is different: a fresh global state for the bytes that follow. These coincide in prose, where a surprising byte often begins a new word. They come apart at a computed result. After `16 - 3 - 4 =`, the next byte is almost certainly a digit, so its entropy stays near or below $\log_2 10 = 3.32$ bits however unsure the model is about which digit (BLT-1B's patcher is unsure there, at a median of 2.8–3.0 bits). At a 10% budget BLT-1B's entropy threshold sits about that high, so it spends patches on hard-to-predict

prose and skips most of these positions (§5).

We make four contributions:

1. **A blind spot in a trained 1B model.** At a 10% patch budget, BLT-1B's own entropy rule skips most computed results in GSM8K solutions, and about half at 15%; forcing a boundary after each `=` at the same patch count raises their exact match, given the true preceding text, by 19–33 points (§4). The cue before a result caps its entropy near BLT-1B's threshold at a 10% budget; larger budgets and prose without `=` narrow the blind spot (§5).
2. **The gap survives training and adaptation.** BLT-style models trained from scratch at 10–20% budgets show the same ordering across 3 seeds. Trained at 1M, 12M and 50M parameters on a 1.9 GB math corpus, with training data growing alongside, the label-free trigger's advantage over entropy is not detectable at 1M and appears at 12M (+10 points on final answers) and 50M (+20 on final answers, which mostly copy the solution's last number, and +22 on computed results; §6). BLT-1B adapted to a 10% budget with low-rank adapters keeps a 40-point gap (§8).
3. **A label-free trigger.** *Boundary dependence*, the change in the model's own loss when a patch start is removed or added, averaged per preceding two-byte context, finds computed results without labels or hand-written rules, given text in the same format to fit it; it learns the contexts that precede values (§7).
4. **Scope.** The effect needs a computed value and a model able to compute it; it is largest after a cue that fixes the value's type and, in BLT-1B, at tight budgets, while in our small models it persists at 15–25% (§5, §6). Copied names and values and logic lookups gain 1–3 points from a patch start at 10%, and values the model cannot compute show no detectable gain (−0.3 points, −1.1 to +0.5; §9). Scratchpad Patching's entropy trigger shows no detectable difference from random scratchpads on final answers (−0.3 points, −2.2 to +1.6; §10).

2. Background and related work

Patching rules. BLT [Pagnoni et al., 2025] describes two entropy rules: a global threshold, $H(x_t) > \theta_g$, and an approximate monotonic rule that starts a patch where entropy rises, $H(x_t) - H(x_{t-1}) > \theta_r$. Its final version compares both at 8B scale and defaults to the global threshold when not specified, as do the released BLT-1B checkpoint and the official code (`monotonicity: false`, threshold 1.335); we call that rule *entropy* and the monotonic rule *jump*. BLT also notes that an entropy model with a small receptive field can be stored as a lookup table, and its Figure 3 illustrates patching with a small entropy model that sees two bytes; our dependence rule (§7) is such a table with a different target. Entropy spikes as boundaries go back to dynamic pooling [Nawrot et al., 2023]. SpaceByte [Slagle, 2024] starts patches at word boundaries; H-Net [Hwang et al., 2026], AU-Net [Videau et al., 2025], MrT5 [Kallini et al., 2024] and ByteSpan [Goriely et al., 2025] learn or derive boundaries in other ways. AU-Net reports GSM8K accuracy as a benchmark, rising with the number of hierarchy stages; none of these papers examines where boundaries fall on computed outputs or measures answer accuracy as a function of where boundaries are placed.

Compute between patches. Scratchpad Patching [Zheng et al., 2026] decouples compute from patch size by inserting transient global steps ("scratchpads") inside patches, triggered by an absolute next-byte entropy threshold, and names the stale-context problem *patch lag*. Its trigger ablation compares strategies on validation bits per byte (code, natural-language and math splits) and finds the entropy trigger best; its downstream evaluation (code pass@1, multiple-choice understanding) includes no math answer accuracy. Fast BLT [Kallini et al., 2026] speeds up decoding without

changing where boundaries go. EntropyMoE [Liu et al., 2026] uses patch entropy to route each patch of a BLT-style model to feed-forward experts; it is evaluated on bits per byte and downstream accuracy, not on math.

Tokenization and arithmetic. For static tokenizers, how numbers are segmented affects arithmetic [Singh and Strouse, 2024, Meister, 2026]. Our setting differs: boundaries are decided online by a model, and the question is which positions receive a fresh global step.

Selection signals. Rho-1 [Lin et al., 2024] selects training tokens by excess loss against a reference model; we test a patch rule built on the same signal as a baseline (§12). Mixture-of-Depths [Raposo et al., 2024] routes compute per token by a learned router.

3. Setup

BLT-1B. We use the released BLT-1B through its Hugging Face conversion (`itazap/blt-1b-hf`), which accepts explicit patch lengths, so layouts can be changed at inference without retraining. The conversion drops BLT's 512-byte sliding window in the entropy patcher and in the local encoder and decoder (transformers issue 49185; it and the fix proposed in pull request 49188 were still open on 1 November 2026). We restore the window with that fix (applied to transformers 5.18; the patch is in our repository) and use the corrected model throughout, except where §13 reports the released conversion. Positions before byte 512 are unchanged by the fix, since the window covers every earlier byte; past it the released conversion over-segments, and 121 of our 294 test problems are longer than 512 bytes. With the window, the default layout starts a patch on 25.5% of bytes on GSM8K, against 28.4% without it. We build tight-budget layouts at R = 10% and 15% of bytes. Thresholds are fitted once on the first 300 GSM8K training problems (297 fit the context) so that the mean patch rate there is R, then applied position by position at test time; whether a byte starts a patch never depends on later bytes. (Choosing the top R% within each test problem instead gives the same conclusions; §13.)

Layouts. *entropy*: BLT-1B's next-byte entropy. *results* (hand-written): a boundary right after every `=`, the rest filled by entropy. *dep*: boundary dependence (§7). *entdep*: the sum of standardized entropy and dependence.

Evaluation. 294 GSM8K test problems (question, worked solution with calculator annotations removed, and "The final answer is N"), containing 796 in-line computed results: the number right after `=`, with its `$` if any (181 are written `= $N`). A target counts as exactly right when every byte is the model's top prediction given the true preceding text (teacher forcing), and as covered when a patch starts at its first byte. We report final answers as well. In GSM8K the final answer repeats the solution's last number in 94.6% of the 1,319 test problems (95.6% of our 294; thousands separators ignored), and that number ends a median of 8 bytes before the final-answer line, so under teacher forcing a final answer is mostly a copy. We test paired differences with exact McNemar tests and 95% intervals that resample whole problems.

Small models trained from scratch. A BLT-style model in MLX: a local encoder (byte embedding plus in-patch offset embedding), cross-attention pooling with the patch mean as query, a global transformer (D = 128, 4 layers unless noted; 1.1M parameters in all, 0.8M of them global), and a local decoder layer that attends to the previous 32 bytes across patch boundaries. Patch starts come from a fixed rule applied to the bytes and to a small entropy model (one layer, 32 dimensions) trained on the same corpus. Training: GSM8K and MATH training solutions [Cobbe et al., 2021, Hendrycks et al., 2021] (9.7 MB, GSM8K's calculator annotations kept), 32,000 steps

of 32 windows of 128 bytes, AdamW with warmup and cosine decay. Evaluation: 660 GSM8K and 700 MATH test problems held out from training, with greedy exact match given the true prefix on 1,000 computed results (the number after `=` inside an annotation such as `<<16-3-4=9>>9`, copied after `>>`), 660 final answers (after `####`) and 700 MATH `\boxed{}` answers; patch boundaries during decoding are decided online by the same rule. Three seeds per configuration; rules are compared by the difference of seed means with a Welch 95% interval over seeds (degrees of freedom rounded down, which widens it).

4. The blind spot in BLT-1B

At BLT-1B's default budget its patcher covers computed results well (79% of them start a patch), and removing the patch start at the final answer costs 19 points of exact match (97.0% → 78.3%), confirming that the boundary matters to BLT-1B, whose own layout starts a patch there. (That test scores the final answer as the solution last wrote it, with any `$` and thousands separators, on 300 problems; Table 1 scores the plain number after "The final answer is" on the 294 problems that fit the context, which gives 73.5% for the default layout.) Under a tight budget, entropy drops computed results faster than other positions: at 15% it covers 48% of them, at 10% only 16%.

Table 1. BLT-1B, patch layouts changed at inference (train-fitted thresholds). Exact match on 796 in-line computed results and 294 final answers.

Layout	Patch rate	Results covered	Computed results	Final answers
default (BLT-1B's own)	0.255	79%	76.8%	73.5%
entropy@15	0.157	48%	47.0%	65.0%
results@15 (hand-written)	0.157	100%	66.1%	67.0%
dep@15	0.153	100%	77.3%	40.8%
entdep@15	0.157	100%	76.5%	67.3%
entropy@10	0.106	16%	19.0%	51.4%
results@10 (hand-written)	0.106	100%	51.8%	60.5%
dep@10	0.100	100%	67.8%	4.8%
entdep@10	0.105	100%	67.1%	62.9%

At equal patch counts, a boundary after each `=` beats entropy on computed results by +19.1 points at 15% (95% interval +15.8 to +22.4; 172 results right only under *results* vs 20 only under *entropy*; McNemar $p = 2 \times 10^{-31}$) and +32.8 at 10% ($p = 7 \times 10^{-69}$). All layouts run at or slightly above budget on the test problems (patch rates 0.157 and 0.106 for entropy and the hand-written layout at 15% and 10%, 0.100 to 0.157 for the others). Figure 1 shows a single solution (425 bytes) with the top 10% of its positions by each score: entropy places its patch starts at word beginnings and misses all six computed results; entropy plus dependence starts a patch right before each of them.

5. What the blind spot depends on

Besides Table 1's 294 problems, this section uses 915 further GSM8K test problems (those among problems 300–1,318 that fit the context and had a valid prose rewrite, made for a measurement not reported here; 2,448 computed values) and a prose rewrite of 221 of the first 300 (711 values). On both, thresholds are fitted on the same 1,382 GSM8K training problems in the writing tested, and a value counts as covered when a patch starts at its first digit, after any `$`. (Table 1 counts the `$`:




Figure 1: BLT-1B patch starts in one GSM8K solution at a 10% budget, with equal patch counts for the two layouts. Bars mark patch starts and shading marks in-line computed results. Entropy starts no patch at any of the six results; entropy plus dependence starts one before each.

there the default layout starts a patch at only 20% of the 181 results written `= $N`, yet gets 71% of them right, against 78% of the others.)

The cue caps entropy. If a digit is certain to come next, the next byte's entropy cannot exceed $\log_2 10 = 3.32$ bits, however unsure the model is about which digit. BLT-1B's threshold for a 10% budget lies at about this level (3.36 bits), so after a cue that makes a digit nearly certain, entropy rarely starts a patch. In Table 1's results, entropy at 10% starts a patch at none of the 181 written `= $N` and at 21% of the 615 written `= N`. On the 915 problems the patcher gives a digit a median probability of 0.996 at the first digit after `= $` (median entropy 2.76 bits), where entropy at 10% starts no patch; after `=` the median is 0.966 (3.00 bits) and entropy covers 18.9% of the values. Of all values it misses at 10%, 90.1% (88.4 to 91.8) have a digit probability of at least 0.9. Writing `is` instead of `=` before the 1,862 values written `= N` lowers that median from 0.966 to 0.736 and raises entropy's coverage of them from 18.9% to 65.7% at the same budget (+46.9 points, +44.5 to +49.3). We found the split by cue after the fact, in the prose experiment below, and measured these problems afterwards to test it.

Budget. In BLT-1B, as the budget grows the threshold falls below the ceiling and the blind spot closes: on the 915 problems entropy starts a patch at 14% of computed values at 10% of bytes, 56%

at 15%, 89% at 20% and 97% at 25% (thresholds 3.36, 2.86, 2.38 and 1.90 bits), and after `= $` at 0%, 33%, 85% and 97%. It starts one at 94% of final answers already at 10%. BLT's own scaling experiments use average patches of 6 and 8 bytes [Pagnoni et al., 2025], about 17% and 12.5% of bytes; at 12.5% entropy covers 28% of computed values. In our models trained from scratch, whose entropy model has one layer of 32 dimensions, the gap persists at 15–25% budgets (§6).

Format. We also had an LLM rewrite the solutions as prose without `=` or arithmetic symbols between numbers, keeping every computed value in order with the same digits (checked automatically). At 10%, entropy starts a patch at 57.2% of the values in prose against 13.6% in the original (+43.6 points, +38.8 to +48.2). Adding a start at every value to entropy's layout, slightly beyond the budget, raises exact match by 37.0 points in the original (+33.1 to +41.1) but only by 12.9 in prose (+10.3 to +15.7): the blind spot narrows but does not disappear. Most of those 12.9 points come from the 163 values after `$`, a type-fixing cue the rewrite kept: entropy starts a patch at none of them (nor at any of the original's 167), and a start adds 36 points there, against 6 after a plain space, where entropy already covers 74%. A start at every value still pays in prose: against the same layout without those starts it adds 28.4 points (+24.7 to +32.2; 44.3 in the original). Values are harder in prose (default layout 56.8% against 77.9%; BLT-1B may have seen the original solutions in training), and prose has 1.43 times as many bytes per value, so the same budget gives it more patch starts per value; the `is` swap above, which changes only the cue, is the cleaner test.

6. Training at tight budgets

Changing layouts at inference puts BLT-1B out of distribution. To test whether the blind spot survives a model that learned with the tight layout, we train small byte models from scratch with each rule.

Table 2. Trained at a fixed budget (D = 128, 4 global layers, 1.1M parameters, 3 seeds). Computed results / final answers / bits per byte. Every entropy seed is below every seed of the dependence and hand-written rules on both accuracies; the hand-written and dependence seeds overlap on computed results at 20%.

Budget	Entropy	Entropy jump (BLT's monotonic rule)	Dependence (label-free)	Hand-written results rule
10%	7.1% / 10.4% / 1.654	7.0% / 64.1% / 1.639	17.1% / 67.4% / 1.678	24.7% / 72.5% / 1.640
15%	8.3% / 32.5% / 1.552	not run	14.8% / 68.2% / 1.638	22.7% / 74.8% / 1.528
20%	8.4% / 44.0% / 1.475	not run	17.4% / 68.2% / 1.577	23.9% / 75.1% / 1.451

The ordering hand-written > dependence > entropy holds at every budget in the seed means. BLT's own monotonic rule (*jump*) separates the two targets: at 10% it recovers final answers (64.1% against 10.4% for entropy) but not computed results (7.0% against 7.1%; −0.1 points, −1.1 to +0.9); we did not establish why. A patch start at the answer itself does not decide final answers here: on held-out text at 10%, neither entropy nor dependence starts a patch at a final answer (they follow `####`), yet dependence, which starts one at 37% of computed results (entropy: none) and at every copy of a result after `>>`, gets 67.4% of final answers. (Jump's recovery disappears on the larger corpus below, where entropy itself starts a patch at every final answer, so that comparison does not isolate model size.) Placement matters more than budget: dependence at 10% beats entropy at 20% on final answers by 23.4 points (95% interval over seeds +17.2 to +29.5) with half the patches. From 10% to 20%, entropy's final-answer accuracy rises (10% → 33% → 44%; +33.6 points, +21.2

to +46.1), while the result-aware rules show no detectable change (dependence +0.8, −4.3 to +5.9; hand-written +2.5, −3.5 to +8.6), nor does any rule's computed-result accuracy (entropy +1.3, −2.4 to +5.0; dependence +0.3, −8.5 to +9.2; hand-written −0.7, −13.2 to +11.8). MATH answers stay near 3% for every rule; we read this as arithmetic capacity capping each rule's level at this size, while placement sets the gaps between rules. The hand-written rule's bits per byte are lower than dependence's at every budget and than entropy's at 15% and 20%, and tied with entropy's and jump's at 10% (−0.013, −0.046 to +0.019; +0.002, −0.033 to +0.037), so its gain shows no detectable cost in bits per byte; dependence costs 1.5–7% in bits per byte against entropy.

The same pattern holds at entropy's usual 25% budget (Figure 4). At D = 128, word starts plus math syntax (18.5% of bytes) gets 30.4% of computed results against 11.0% for entropy (+19.4 points, +11.0 to +27.8, 3 seeds); word starts alone get 15.5% and a 6-byte stride plus math syntax 16.6%, so word alignment and the result boundary each reach only about half the combined accuracy. At D = 64 (0.2M parameters), BLT's entropy rule gets 9.8% of final answers, its jump variant 67.5%, and word starts plus math syntax 77.1% (3 seeds each).

Scaling to 50M parameters. The models above are small (1.1M parameters) and trained only on GSM8K and MATH solutions. To test whether the gap shrinks as models grow, we trained the same architecture from scratch at 1.1M, 11.7M and 53.7M parameters on a larger corpus: the first four shards of OpenWebMath [Paster et al., 2024] (221,264 documents, 1.71 GB, after dropping 324 that share a 13-word sequence with a test problem), plus the GSM8K and MATH training solutions repeated to 10% of the bytes (1.90 GB in total). Each rule is applied at 10% of bytes with thresholds fitted on this corpus; the dependence rule uses the trained-model table of §7 (fitted on the GSM8K and MATH corpus), because a table refitted on this corpus is dominated by web-text contexts and covers none of the computed-result starts. The models see 0.13, 0.5 and 1.5 billion bytes. The code is a PyTorch port of our MLX harness, checked against it (logits agree to 3e-6; masks are identical), and the 28 runs of Table 3 ran on one rented A40 GPU for about $19.

Table 3. Models trained from scratch at a 10% patch budget on the scaling corpus (one A40 GPU, no gradient clipping). Exact match on 660 final answers and 1,000 computed results; patch rates are measured on the evaluation text (thresholds are fitted on the training corpus, so entropy spends slightly more than 10% there).

Parameters	Rule	Seeds	Final answers (by seed)	Computed results (by seed)	Bits per byte	Eval patch rate
1.1M	entropy	3	7.0% (8.8, 4.8, 7.4)	4.4% (3.6, 4.9, 4.8)	2.093	11.2%
1.1M	dependence	2	5.4% (6.2, 4.5)	4.2% (4.3, 4.1)	2.196	10.9%
1.1M	hand-written	3	45.5% (54.8, 25.3, 56.2)	4.6% (3.9, 4.1, 5.9)	2.109	12.1%
11.7M	entropy	3	46.6% (42.0, 49.1, 48.8)	5.8% (4.8, 6.4, 6.3)	1.657	11.2%
11.7M	dependence	3	56.7% (58.5, 53.9, 57.6)	7.7% (7.2, 5.6, 10.3)	1.673	10.9%
11.7M	hand-written	3	76.3% (76.4, 73.9, 78.5)	12.9% (14.9, 10.3, 13.5)	1.645	12.1%
53.7M	entropy	3	59.0% (58.8, 57.9, 60.5)	13.9% (16.4, 10.4, 14.9)	1.439	11.2%
53.7M	dependence	3	78.9% (78.5, 80.2, 78.0)	35.9% (32.7, 35.7, 39.4)	1.420	10.9%
53.7M	hand-written	2	85.5% (85.8, 85.3)	43.4% (36.8, 49.9)	1.431	12.1%
53.7M	jump (BLT monotonic)	1	53.8% (53.8)	6.3% (6.3)	1.410	9.7%
53.7M	entropy at 20%	1	80.2% (80.2)	23.1% (23.1)	1.146	22.8%

Dependence is ahead of entropy on final answers at 11.7M and 53.7M and on computed results at 53.7M (Figure 2), but parameters, training bytes and passes over the solutions grow together. On




Figure 2: Exact match against parameter count for models trained from scratch at a 10% budget (small markers: seeds; large markers: means). The label-free dependence rule's advantage over BLT's entropy rule is not detectable at 1.1M, appears on final answers at 11.7M and on both targets at 53.7M, where parameters and training data grow together. BLT's jump rule and entropy at twice the budget were run at 50M only.

final answers the difference is −1.6 points at 1.1M (95% interval over seeds −7.8 to +4.5), +10.1 at 11.7M (+1.4 to +18.7) and +19.8 at 53.7M (+16.7 to +23.0; 78.9% against 59.0%), with every dependence seed above every entropy seed at the two larger sizes. These gaps do not come from patch starts at the final answer: on the evaluation text, entropy at 10% starts a patch at every final answer and dependence at none. Final answers mostly repeat the solution's last number (§3; 94.2% of the 660 evaluation problems), and at 11.7M and 53.7M their accuracy is ordered like the share of computed results that get a patch start (entropy 0.7%, dependence 36.7%, hand-written 100%); we did not test whether one causes the other.

On computed results, dependence and entropy separate only at 53.7M: at 1.1M and 11.7M they show no detectable difference (−0.2 points, −2.1 to +1.6; +1.9, −4.5 to +8.2), and at 53.7M dependence gets 35.9% against 13.9% for entropy (+22.0 points, +13.6 to +30.4), again with every seed above every entropy seed, and the hand-written rule 43.4% (two seeds). Dependence also has lower bits per byte than entropy (1.420 against 1.439; −0.019, −0.034 to −0.003). With a second recipe, gradient clipping at norm 1.0 on the same GPU type (3 seeds per rule), dependence again leads entropy at 53.7M on final answers, 78.2% against 59.9% (+18.3 points, +15.5 to +21.1). On computed results every dependence seed is again above every entropy seed, but the interval includes 0: 35.1% against 20.7% (+14.3, −5.7 to +34.4; entropy's seeds spread from 12.1% to 27.5%). Bits per byte show no detectable difference (+0.005, −0.016 to +0.025).

BLT's jump rule does not help on this corpus: one seed gets 53.8% of final answers and 6.3% of computed results, below every entropy seed, although it has the lowest bits per byte of the rules in Table 3 at a 10% budget (1.410). Given twice the budget (20%, which is 22.8% of the evaluation text), entropy gets 80.2% of final answers (one seed), within the range of the dependence seeds at 10% (78.0–80.2%), and 23.1% of computed results against 35.9%: its extra patches cannot reach the answer, which it already covers at 10%, and its final answers rise together with its computed results (13.9% to 23.1%). At 1.1M on this corpus only the hand-written rule rises above the floor on final answers; these models see the GSM8K and MATH solutions about 1.4 times, against about 14 times for the models of Table 2, and their entropy model covers every final answer, against none

there, so either difference could separate the two 1.1M results. One of the 28 runs of Table 3 (1.1M, dependence, seed 0) never learned (bits per byte 4.72 against 2.08–2.26 for the other 1.1M runs) and is excluded.

7. A label-free trigger: boundary dependence

The hand-written rule uses domain knowledge (`=`). We look for a signal that finds the same positions from the model alone.

Definition. For BLT-1B: on 400 GSM8K training problems, compute the per-byte loss under the default layout and under a 10% entropy layout. For each position t, take the mean rise in loss over bytes t…t+3, and average it per preceding two-byte context (b_{t-2}, b_{t-1}). At inference the score is a causal table lookup. The top contexts are arithmetic (`=$`, `0*`, `5=`, `3=`); after `=` the mean rise is 0.88 nats against 0.13 on average.

For the small trained models the same recipe fails: a reference model trained with entropy patches rarely had a boundary at a result, so it never learned to use one, and removing one costs little. Training the reference model with random patch starts (25%) and measuring the drop in loss from *adding* one patch start at t to a random 10% layout fixes this; the top contexts then include `<<`, `=6`, `x=` and `>>`.

Results. On BLT-1B (Table 1), entropy plus dependence beats entropy on computed results by +29.5 points at 15% (+25.6 to +33.4) and +48.1 at 10%, and beats even the hand-written rule by +10.4 (+7.7 to +13.2): the table also places boundaries at operands and operators, not only after `=`. On final answers it beats entropy by +11.6 points at 10% (+6.5 to +16.7; $p = 3 \times 10^{-5}$) but not at 15% (+2.4, −1.0 to +5.8), and it is tied with the hand-written rule (+2.4, −2.4 to +6.8 at 10%). Entropy starts a patch at nearly every final answer at both budgets (93.5% and 98.3%); what differs is how many computed results it covers (16% and 48%). Dependence alone fails on final answers on BLT-1B (40.8% and 4.8%), because "The final answer is" is not an arithmetic context; in the trained models dependence alone scores higher on every seed (Table 2; entropy plus dependence: 9.7% / 22.5%, 2 seeds), though with two seeds the intervals include 0 (+7.4 points, −7.4 to +22.1; +44.9, −74.6 to +164.4).

8. Adapting BLT-1B to the budget

To test whether BLT-1B can learn its way around the blind spot, we train low-rank adapters (rank 16, 16.9M parameters, on the global transformer and the decoder's cross-attention) for 1,500 steps on GSM8K training solutions under each 10% layout, three runs per rule. Each model is tested on the same 796 results under its own training layout.

Table 4. BLT-1B adapted to a 10% budget, computed results exact.

Trained and tested under	Untrained	Runs	Mean
entropy	19.0%	32.8, 32.9, 33.0	32.9%
results (hand-written)	51.8%	62.4, 62.9, 62.7	62.7%
entdep (label-free)	67.1%	72.9, 70.9, 74.4	72.7%

Adaptation helps every layout but closes none of the gap: entdep − entropy is +39.8 points (pooled over runs, +36.3 to +43.2; $p = 6 \times 10^{-217}$), hand-written − entropy +29.8, and entdep − hand-

written +10.0. The models trained under entropy do better under entdep (66.2% on average), a layout they never trained on, than under their own (32.9%). Final answers saturate near 97% after fine-tuning, because the final answer mostly repeats the solution's last number (§3) and fine-tuning teaches the copy; they no longer separate the layouts.

9. Which positions are affected

If the blind spot is about computed values, copies and lookups should gain little from a patch start. We repeat the BLT-1B test on four other target types at 10% (train-fitted thresholds).

Table 5. BLT-1B at 10%, exact match. *Forced*: a patch start at every target, the rest by entropy.

Target	Default	Entropy	Entdep	Forced	Kind
GSM8K computed results	76.8%	19.0%	67.1%	51.8%	computed, skill present
Python identifiers repeating a nearby name	83.3%	81.7%	81.3%	83.1%	copy
Proof-step conclusions, generated logic	69.1%	46.3%	41.5%	49.4%	rule lookup
Copied values, generated program traces	82.5%	58.3%	62.3%	61.0%	copy
Computed values, program traces	20.5%	10.0%	9.0%	9.7%	computed, skill absent

These copies and lookups gain 1–3 points from a patch start (code: +1.4, $p = 4 \times 10^{-5}$), against 32.8 for computed results. This does not hold for copying in general: BLT-1B's final answers, mostly copies of the solution's last number, need a start at the answer (§4). Where BLT-1B cannot compute the value (program-trace arithmetic, 20.5% even with default patches) or answer at all (logic Yes/No answers at chance under every layout), placement has nothing to act on. Small models trained on the logic and trace tasks give the same picture: logic is not learned (answers at chance), and on traces, where each value's operands sit inside the local decoder's 32-byte window, entropy skips most values (83% at 10%), yet the hand-written rule is tied with it (21.8% vs 20.6%, 2 seeds; +1.2 points, 95% interval over seeds −23.1 to +25.5). With the window cut to 8 bytes the hand-written rule is 4.1 points higher (24.2% vs 20.1%, 3 seeds), with no detectable difference (−8.4 to +16.5). Our reading is that a start pays when a model able to compute the value computes it, possibly only when the operands lie beyond the local model's reach (the window test is inconclusive); type and task are also confounded in Table 5.

10. Scratchpad Patching

We reimplemented Scratchpad Patching in the small-model harness (16-byte fixed patches, scratchpads on 6% of bytes, pooled by cross-attention over the partial patch with the mean as query) and compared triggers at equal scratchpad counts (D = 64, 2 global layers, 0.2M parameters).

Table 6. Final-answer exact match on GSM8K by scratchpad trigger, with the accuracy of each seed.

Trigger	Seeds	Final answers	By seed
answer starts (math syntax)	5	38.1%	49.2, 31.4, 8.3, 49.2, 52.4
entropy (the paper's trigger)	5	5.6%	7.3, 4.8, 4.2, 5.6, 6.1
random positions	5	5.9%	6.1, 5.6, 4.5, 5.2, 8.0
none	3	6.1%	6.2, 6.8, 5.2
denser fixed patches, same compute (8-byte)	5	7.8%	6.7, 12.3, 7.6, 5.2, 7.1

There is no detectable difference between the entropy trigger and random scratchpads (5.6% vs 5.9%, 5 seeds; −0.3 points, Welch 95% interval −2.2 to +1.6), while answer-start scratchpads give 38.1%, more than six times as much; one of their seeds stays at 8.3%, with the highest bits per byte of the five (1.922, against 1.900–1.909), in the range of the entropy and random triggers (1.911–1.930). Computed results stay near the floor under every trigger (4.7–6.3%), so this test bears on final answers, not on computed values. It does not contradict the paper's ablation, which found entropy best on bits per byte: averaged bits per byte can hide a failure at a few positions that decide answer accuracy.

11. Compute

Fewer patches save global compute, but local layers run on every byte. For BLT-1B, counting matrix-multiply FLOPs, the local layers cost 299 MFLOPs per byte, the global model 2,653 MFLOPs per patch, and the entropy model 199 MFLOPs per byte. A 10% budget then costs 65% of the default's forward compute and 15% costs 76%. A dependence-table rule is a lookup and needs no entropy model: 48% at 10% and 59% at 15% (an entropy model stored as a lookup table, as BLT suggests, would also avoid that cost). On computed results, dependence alone at 15% is tied with the default layout (77.3% against 76.8%; +0.5 points, −1.7 to +2.7) at about 60% of its compute (Figure 3), but it loses 32.7 points on final answers (−38.1 to −27.2; §7). In our small models the local layers dominate, so a 10% budget saves only 24% of compute (Figure 4).




Figure 3: BLT-1B exact match on in-line computed results (left) and final answers (right) against forward compute per byte, relative to the default layout, for layouts at 10% and 15% of bytes. Dependence alone is a lookup and pays no entropy-model cost.

12. Negative results

Spending patches on hard or learnable bytes does not help. A Rho-1-style rule (patches where a small model's loss exceeds a reference model's) and simplified learned chunking lost to hand-placed boundaries in every setting tried.

Finer arithmetic boundaries do not help. Per-digit patches after `=` and operand-aligned patches looked promising at two seeds (on computed results and final answers); at five seeds neither differs detectably from a matched random control (+0.7 points, −1.2 to +2.6; +1.9, −2.9 to +6.7).




Figure 4: Models trained at 10-25% patch budgets (D = 128): exact match against forward compute per byte, relative to entropy at 25%. Points are seed means; bars span the seeds.

A learned patcher does not beat the table. A small network that predicts the dependence gain from the last 8 bytes, trained on math and on logic/trace data together, has held-out correlations close to each domain's own table (math 0.140 against 0.140; logic and traces 0.147 against 0.158) and covers 83% of computed-result starts (table: 37%), but trained into a model at 10% it gets 14.3% / 57.4% against the table's 17.1% / 67.4% (−2.7 points, −15.9 to +10.4; −10.0, −18.2 to −1.8).

Token models are partly protected. With a Qwen2.5-0.5B draft and a 1.5B target on generated program traces, the draft agrees with the target on only 53% of computed-value tokens (86% on text), so speculative decoding loses speed there; but the draft is rarely confident on them (6.5%), so a confidence-based early exit would let few errors through. On GSM8K, computed results are the easiest tokens for these models; we did not test why (overlap with their training data is one possibility). In token models a computed value's uncertainty shows in the model's own confidence; in byte patching, the decision to start a patch before a result is made from bytes whose type is predictable.

The original synthetic result was mostly architectural. In an earlier synthetic benchmark with sum pooling and a patch-local decoder, splitting a computation across patches cost up to a full bit; with cross-attention pooling and a decoder that sees across patch boundaries, most of that penalty disappeared. All results above use the cross-attention model.

13. Limitations

Scale. Models trained from scratch reach 53.7M parameters, on 1.5 billion bytes (the models of Table 2 have 1.1M; D = 64 is 0.2M). Parameters, training bytes and passes over the GSM8K and MATH solutions (about 1.4 at 1.1M, about 15 at 53.7M) grow together, three sizes on one corpus show a trend, not a law, and at 53.7M the gap on computed results is smaller with gradient clipping, and its interval then includes 0 (+14.3, −5.7 to +34.4, against +22.0, +13.6 to +30.4 without). The models are small in every part: a 128-byte context, one local decoder layer over 32 bytes and a one-layer, 32-dimensional entropy model. BLT-1B results come from inference-time layout changes and low-rank adaptation, not from full training at a tight budget. At 50M the hand-written rule has two seeds and the jump and double-budget results one each.

Teacher forcing. All accuracies score each target given the true preceding text, so a final answer is mostly a copy of the solution's last number (§3). End to end, BLT-1B cannot solve GSM8K by itself: even after adaptation it gets about 2% of final answers under every layout (measured with the released conversion), so the gaps above could not be measured end to end. The models trained from scratch also solve essentially no GSM8K problems end to end at any size (at most 1 of 100 for any run).

Domain. The effect is established for arithmetic in worked math solutions written with cues that fix the next byte's type (`=`, `$`), in BLT-1B at budgets of 10–15% of bytes (§5) and in models trained from scratch at 10–25% (§6); the models trained from scratch saw only GSM8K's annotated format. Code shows a small, significant effect; logic and program traces were inconclusive: the models lacked the skill, or the local model may already have seen the operands (§9).

Label-free trigger. The dependence table is fitted on the domain it is tested on and does not transfer across formats (the GSM8K table covers 0% of program-trace values; a table refitted on the scaling corpus covers no computed-result start, §6). It learns the contexts that precede values, so it inherits their format. On BLT-1B, the best variant (entropy plus dependence) differs from the one that scores higher on every seed in trained models (dependence alone; §7), which does not reach the hand-written rule. A follow-up [Vera Zúñiga, 2026] used another two-byte table, fitted without labels to predict repeats of recent text, which on GSM8K works as a learned detector of the cue before values; its version 2 corrects the main claims of its first version.

Checkpoint conversion. The public BLT-1B conversion lacks the 512-byte sliding window; our BLT-1B results use it with the window restored by the fix proposed upstream (§3). With the released conversion the conclusions are the same, with different magnitudes (results − entropy at 15% and 10%: +25.0 and +26.6 points).

Thresholds. Our original BLT-1B layouts chose the top R% of positions within each test problem, so a position's selection could depend on later bytes. Train-fitted, position-by-position thresholds reproduce every conclusion, with similar or larger gaps (released conversion, results − entropy: +25.0 against +21.5 points at 15%, +26.6 against +27.1 at 10%).

14. Conclusion

Entropy tells a byte-level model where the next byte is surprising, not where its decoder needs the global model. The two diverge at computed outputs whose type the preceding text fixes: once only a digit can follow, the next byte's entropy stays near or below $\log_2 10$ bits, about BLT-1B's threshold at a 10% budget. Under tight budgets, entropy-triggered patching skips these positions and teacher-forced accuracy on them collapses: in a trained 1B model, after adaptation, and in models trained at the budget (1.1M parameters on the solutions alone, 53.7M on the larger corpus). In BLT-1B, larger budgets and cues that do not fix the type narrow the blind spot. Boundary dependence, a two-byte table fitted without labels on text in the same format, finds many of these positions by learning the contexts that precede them. Where such cues precede values and budgets are tight, patch starts should follow what the decoder needs from the global model rather than how surprising the next byte is.

Changes in version 2

Version 1's experiments and the data in its tables and figures are unchanged; version 2 adds later measurements that bound or correct its claims (§5, §6), and version 1's §5–§13 are now §6–§14. The blind spot is stated for type-fixing cues and, in BLT-1B, tight budgets (§5). Final answers are described as mostly copies under teacher forcing (§3), and explanations that assumed a patch start at the answer are corrected (§6–§8). Version 1's statements that the gap grows with model size (size and training data grew together) and that Scratchpad Patching's entropy trigger shows the same blind spot are no longer made (§6, §10); the reading of §9 and the thresholds comparison (§13) are restated. The scaling study adds intervals over seeds and a second training recipe (§6). New and corrected comparisons carry intervals; a p-value (§4), a bits-per-byte ranking (§6) and Appendix A's seed counts are corrected. §13 cites a follow-up, arXiv:2610.22100 [Vera Zúñiga, 2026], whose version 2 corrects the main claims of its first version. New scripts, results and data, with the LLM-written rewrites of §5, are in `paper/v2/`.

Declarations

Data and code. Code, raw logs and the results registry are at https://github.com/nicoveraz/segresearch (release v2.1.0 for this version), archived at https://doi.org/10.5281/zenodo.23238215. Scripts: `realblt_budget.py`, `realblt_code.py`, `realblt_reason.py` and `realblt_finetune.py` run the BLT-1B experiments (PyTorch); `mathexp.py`, `deptrigger.py` and `reasonexp.py` the trained models (MLX); `scale/` the scaling study (PyTorch, with checks against the MLX code and the scripts that ran it on a rented GPU); `flops.py` the compute estimates; `stats.py`, `make_tables.py` and `make_figures.py` rebuild the statistics and the other tables and figures from `results/`, and `paper/v2/scripts/scaling_unclipped.py` rebuilds Table 3 and Figure 2 from the runs in `results/scale/` without gradient clipping. `paper/v2/` holds the scripts, results and data new in version 2 (for §5's 915 problems, the measured rows but not the measuring script). GSM8K, MATH and the BLT-1B weights are available from their authors. **Funding:** none. **Competing interests:** none. **Use of AI:** the experiments were designed, run and analysed with an AI coding agent (Claude Code) working in a research loop under the author's direction; the standards in Appendix A came out of that process. The prose rewrites of §5 were written by an LLM (Claude Opus 5.5) from one prompt and checked automatically; the rewrites and the prompt are in `paper/v2/`. **Ethics:** public datasets and generated text only; no human subjects.

References

Karl Cobbe et al. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

Zébulon Goriely, Suchir Salhan, Pietro Lesci, Julius Cheng, and Paula Buttery. ByteSpan: Information-driven subword tokenisation. In *TokShop 2025 (non-archival)*, 2025. arXiv:2506.18639.

Dan Hendrycks et al. Measuring mathematical problem solving with the MATH dataset. *arXiv preprint arXiv:2103.03874*, 2021.

Sukjun Hwang, Brandon Wang, and Albert Gu. Dynamic chunking for end-to-end hierarchical sequence modeling. In *International Conference on Learning Representations*, 2026. arXiv:2507.07955. Code and checkpoints: https://github.com/goombalab/hnet.

Julie Kallini, Shikhar Murty, Christopher D. Manning, Christopher Potts, and Róbert Csordás. MrT5: Dynamic token merging for efficient byte-level language models. *arXiv preprint arXiv:2410.20771*, 2024.

Julie Kallini, Artidoro Pagnoni, Tomasz Limisiewicz, Gargi Ghosh, Luke Zettlemoyer, Christopher Potts, Xiaochuang Han, and Srinivasan Iyer. Fast Byte Latent Transformer. *arXiv preprint arXiv:2605.08044*, 2026.

Zhenghao Lin, Zhibin Gou, Yeyun Gong, Xiao Liu, Yelong Shen, Ruochen Xu, Chen Lin, Yujiu Yang, Jian Jiao, Nan Duan, and Weizhu Chen. Not all tokens are what you need for pretraining. In *Advances in Neural Information Processing Systems*, 2024. doi: 10.52202/079017-0914. arXiv:2404.07965 (as Rho-1: Not All Tokens Are What You Need).

Bo Liu, Muxuan Yu, Yu Zhang, Pengfei Gao, and Yongping Zhang. EntropyMoE: Entropy-aware sparse expert routing for tokenizer-free LLMs. *arXiv preprint arXiv:2608.06398*, 2026.

Clara Meister. TokEval: A tokenizer evaluation suite. In *Conference on Language Modeling (COLM)*, 2026. arXiv:2608.18062.

Piotr Nawrot, Jan Chorowski, Adrian Łańcucki, and Edoardo M. Ponti. Efficient transformers with dynamic token pooling. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics*, 2023. arXiv:2211.09761.

Artidoro Pagnoni et al. Byte Latent Transformer: Patches scale better than tokens. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Long Papers)*, 2025. arXiv:2412.09871. Code: https://github.com/facebookresearch/blt.

Keiran Paster, Marco Dos Santos, Zhangir Azerbayev, and Jimmy Ba. OpenWebMath: An open dataset of high-quality mathematical web text. In *International Conference on Learning Representations (ICLR)*, 2024. arXiv:2310.06786.

David Raposo et al. Mixture-of-Depths: Dynamically allocating compute in transformer-based language models. *arXiv preprint arXiv:2404.02258*, 2024.

Aaditya K. Singh and DJ Strouse. Tokenization counts: the impact of tokenization on arithmetic in frontier LLMs. *arXiv preprint arXiv:2402.14903*, 2024.

Kevin Slagle. SpaceByte: Towards deleting tokenization from large language modeling. In *Advances in Neural Information Processing Systems*, 2024. arXiv:2404.14408.

Nicolás Vera Zúñiga. When the next byte's type is fixed: why entropy patching skips computed values under tight budgets. *arXiv preprint arXiv:2610.22100*, 2026. Version 2; version 1 was titled "Patch where the text is new: a compression view of where byte-level models should spend compute". Version 2 corrects the main claims of version 1.

Mathurin Videau, Badr Youbi Idrissi, Alessandro Leite, Marc Schoenauer, Olivier Teytaud, and David Lopez-Paz. From bytes to ideas: Language modeling with autoregressive U-Nets. In *Advances in Neural Information Processing Systems*, 2025. arXiv:2506.14761.

Lin Zheng, Vasilisa Bashlovkina, Timothy Dozat, Dan Garrette, Laura Rimell, and Joshua Maynez. Scratchpad Patching: Decoupling compute from patch size in byte-level language models. *arXiv preprint arXiv:2605.09630*, 2026.

Appendix A. Experimental standards

The project ran as a partly autonomous research loop, and several early conclusions were wrong. The standards in `program.md` exist because breaking each produced a wrong result: a word-start rule that read the byte it was predicting (caught by an automatic causality test, `test_causal.py`); effects at two seeds that were not detectable at five (§12); a synthetic generator that placed dependencies outside the model's context; an effect that was mostly architectural; undertrained models hiding the effect; and a rule that exploited the generator's fixed number of variable names. Trained-model comparisons use three or more seeds except where a table or the text says otherwise: in Table 3, 1.1M dependence and 53.7M hand-written have two seeds, and jump and entropy at 20% one; in the text, entropy plus dependence (§7) and the window-32 trace models (§9) have two. BLT-1B comparisons use paired tests, and every rule is checked for causality.