

Estimates of long-run energy savings and realization rates from a large household energy efficiency retrofit program

Erica Myers ^{*} Maya Papineau [†] Nicholas Rivers [‡] Kareman Yassin [§]

June 22, 2022

Abstract

Goes here.

1 Introduction

2 Data

We obtain program data for the EcoEnergy Homes program and EnergyGuide for Homes as well as energy consumption data.

The program data is provided by Natural Resources Canada. The data includes all households in Medicine Hat that obtained an energy efficiency audit through the EnerGuide for Homes program. The EnerGuide for homes program is designed to provide a detailed assessment of a home's current energy consumption and to model impacts of energy upgrades on potential energy consumption. Homes go through an in-person audit by an energy efficiency auditor, which includes a physical assessment of the home as well as a blower-door test. Our data includes home measurements and modeled energy consumption.

The program data also includes a record of energy efficiency upgrades that were performed by the household in response to the energy efficiency assessment. In addition, the program data includes a prospective assessment of ex ante expectations of energy savings associated with the suite of upgrades that were undertaken by the homeowner.

The energy consumption data was provided by the City of Medicine Hat, and includes monthly billing data for natural gas and electricity for all homes in the municipality from 2007 to 2019. The energy consumption data was merged with the program participation data based on address matching.

Summary statistics for the data are provided in Table 1. The table shows that the data contain observations of 1525 households that participated in the retrofit program, along with 20204 houses that did not participate. Participant households undertook a number of energy efficiency retrofits, the

^{*}University of Calgary

[†]Carleton University

[‡]University of Ottawa

[§]University of Ottawa

most popular of which were air sealing, natural gas furnace upgrades, and attic insulation upgrades. Gas, electricity, and total energy consumption are presented in this table as an annual average over the 13 year period we have data, and include both pre- and post-retrofit observations. The table shows that over this period, there is little difference in energy consumption between participating and non-participating households. As described, the EnerGuide for houses program undertakes detailed engineering calculations to estimate energy consumption both before and following retrofits. Table 1 shows that both pre- and post-retrofit projections of energy consumption are higher than actual energy consumption, indicating a potential bias in the engineering models used to predict energy consumption. Comparing pre- and post-retrofit predictions of energy consumption, we can see that the typical participating household was projected to reduce natural gas consumption by about 28% and reduce electricity consumption by about 1.3%. Our analysis is focused on using post-retrofit billing data to determine whether these savings materialized.

Table 1: Summary statistics

participant Variable	N	No Mean	SD	N	Yes Mean	SD
air_sealing	20404	0	0	1525	0.824	0.381
ceiling_insulation	20404	0	0	1525	0.643	0.479
walls_insulation	20404	0	0	1525	0.045	0.206
bsmt_insulation	20404	0	0	1525	0.122	0.327
fnd_header	20404	0	0	1525	0.085	0.278
windowsand_doors	20404	0	0	1525	0.18	0.385
central_ac	20404	0	0	1525	0.132	0.339
natural_gas_furnace	20404	0	0	1525	0.674	0.469
actual_gas_gj_per_yr	20404	113.039	42.625	1525	113.934	37.517
actual_elec_gj_per_yr	20404	30.428	13.07	1525	30.885	12.149
actual_energy_gj_per_yr	20404	143.444	50.002	1525	144.919	44.713
predicted_preretrofit_gas_gj_per_yr	0	NaN		1525	161.003	60.61
predicted_preretrofit_elec_gj_per_yr	0	NaN		1525	33.614	1.143
predicted_preretrofit_energy_gj_per_yr	0	NaN		1525	194.617	61.223
predicted_postretrofit_gas_gj_per_yr	0	NaN		1525	116.048	40.281
predicted_postretrofit_elec_gj_per_yr	0	NaN		1525	33.158	1.429
predicted_postretrofit_energy_gj_per_yr	0	NaN		1525	149.206	40.537

3 Empirical approach and results

3.1 Graphical analysis

Figure 1 illustrates long run trends in electricity and natural gas consumption for treated and non-treated households from before and after participation in the energy-efficiency retrofit program. Prior to the beginning of the retrofit program, electricity and gas exhibited similar (annual) trends. The figure suggests that electricity consumption was relatively unchanged by the retrofits, but that natural gas consumption in treated households fell considerably relative to control households. While the

households that chose to participate in retrofits were initially consuming about 5% more natural gas than non-participant households, after the retrofits they consumed about 3-4% less natural gas than non-participating households. The change occurred during the retrofit program roll-out (shown in the lower panel of Figure 1) and appears to be stable following completion of the roll-out.

Not clear to me why the aggregate trends graph suggests a gas savings of about 10%, but we are estimating more like 20%.

3.2 Regression analysis of overall energy savings

To estimate the overall impact of participation in the energy efficiency retrofit program, we regress monthly energy consumption on an $\text{post} \times \text{treatment}$ indicator, and include household and month-of-sample fixed effects. We consider different estimating samples:

- An ever-treated sample. In this sample, we only include households that participated in the retrofit program, since these households may be more comparable to one another than non-participants. The roll-out of the program was between 2009 and 2012. We thus drop years 2012 and following. This leaves households that participated in the program in 2012 as our never-treated comparison group of participants.
- All households, before 2012. In this sample, we include both participating and non-participating households. We restrict the sample to exclude years 2012 and after to obtain an estimate over a similar timeframe as the never-treated sample.
- All households. In this sample, we include both participating and non-participating households, and include data up to 2019, which allows us to observe households for up to 11 years following initial treatment.

In all cases, we cluster standard errors on both household as well as month-of-sample. The table below shows estimates of total energy (gas plus electricity) savings under each of the different samples. Column 1 is the ever-treated sample, column 2 is all households before 2012, and column 3 is all households up to 2019. Using the ever-treated sample, we find that participation in retrofits results in roughly a 10% reduction in household energy use. When we include the non-treated households, our estimate increases in size, to around 14%. The long-run and short-run results with the full set of households are roughly the same, suggesting that energy savings from retrofits persist for 10 years following implementation.




Figure 1: Long-run trends in electricity and natural gas consumption in treated and untreated households

Dependent Variable:	log(energy)		
Model:	(1)	(2)	(3)
<i>Variables</i>			
treated_postTRUE	-0.1038*** (0.0089)	-0.1451*** (0.0074)	-0.1376*** (0.0065)
<i>Fixed-effects</i>			
id	Yes	Yes	Yes
cons_date	Yes	Yes	Yes
<i>Fit statistics</i>			
Observations	89,118	1,178,183	3,172,442
R ²	0.81032	0.80096	0.78444
Within R ²	0.00717	0.00217	0.00208

Clustered (id & cons_date) standard-errors in parentheses

Signif. Codes: ***: 0.01, **: 0.05, *: 0.1

3.3 Staggered adoption and event studies

One potential reason for the difference in results with the ever-treated and never-treated samples is because adoption of the energy efficiency measures is staggered over time. Because of the small control group in the ever-treated sample (only a few households retrofit in 2012, and these form the control group in that sample), a large weight is placed on comparisons between newly-treated and previously-treated households. Many papers suggest that these comparisons are potentially problematic, and can result in bias. We thus conduct our estimation with alternative estimators from Callaway and Sant’Anna and from Sun and Abraham. We show results in the form of an event study plot, Figure 2.

The results suggest that the TWFE estimates including the never treated households match well with the Callaway and Sant’Anna and Sun and Abraham results. In contrast, the ever-treated sub-sample appears to result in significantly biased coefficients.

3.4 Measure specific results

3.4.1 Which energy efficiency measures are adopted?

To estimate projected savings associated with different energy efficiency retrofits, we regress projected energy savings on a vector of dummy variables that indicate whether a measure was implemented:

$$\log y_i^1 - \log y_i^0 = \sum_j \beta_j x_{ij}. \quad (1)$$

In the equation, y_i^1 is the projected energy consumption of house i after a retrofit is undertaken and y_i^0 is projected energy consumption before the retrofit is undertaken. x_{ij} is a dummy variable indicating whether house i implemented retrofit j .




Figure 2: Event study plot with different estimation samples and methods

Before presenting the results, Figure 3 shows a correlation plot of energy efficiency measures. If adoption of measures is highly correlated, it may be difficult to precisely estimate energy savings. Figure 3 shows that for the most part, there is limited correlation between measures. Only basement insulation and foundation headers are highly correlated. It may make sense to aggregate these two measures (I haven't done this).

Figure 4 shows projections of energy savings by measure. Large savings are projected for natural gas furnace upgrades as well as wall insulation.

3.4.2 Estimated savings

Figure 5 shows estimated energy savings from different adopted measures (left panel) and the number of measures adopted (right panel). The largest estimated changes in gas consumption are largest for natural gas furnace upgrades and wall insulation. Air sealing and attic (ceiling) insulation also deliver gas savings that are precisely estimated. In contrast, no measure is shown to save electricity, and walls insulation may actually increase electricity consumption (although few houses adopt walls insulation).

3.4.3 Realization rates

We estimate an aggregate realization rate by regressing energy consumption on a post \times treatment dummy interacted with projected energy savings. As shown in the table below, we find a realization rate for natural gas of 50%. Our realization rate for electricity is negative (we find an increase in electricity consumption, rather than a saving). For all energy, we find a realization rate of 47%.




Figure 3: Correlation plot of retrofit measures




Figure 4: Measure-specific energy saving projections

Dependent Variables:	log(gas)	log(elec)	log(energy)
Model:	(1)	(2)	(3)
<i>Variables</i>			
as.numeric(treated_post) × delta_gas	0.5252*** (0.0211)		
as.numeric(treated_post) × delta_elec		-0.2448 (0.5091)	
as.numeric(treated_post) × delta_energy			0.4718*** (0.0275)
<i>Fixed-effects</i>			
id	Yes	Yes	Yes
cons_date	Yes	Yes	Yes
<i>Fit statistics</i>			
Observations	3,213,009	3,768,273	3,169,870
R ²	0.84839	0.54893	0.78449
Within R ²	0.00358	1.67 × 10 ⁻⁶	0.00225

Clustered (id & cons_date) standard-errors in parentheses

Signif. Codes: ***: 0.01, **: 0.05, *: 0.1




Figure 5: Estimated energy savings

We also conduct our analysis in levels rather than logs. Results are shown in the table below, and are similar to the main results in logs.

Dependent Variables:	gas	elec	energy
Model:	(1)	(2)	(3)
<i>Variables</i>			
as.numeric(treated_post) \times delta_gas_lev	0.5361*** (0.0586)		
as.numeric(treated_post) \times delta_elec_lev		-0.0119 (0.4519)	
as.numeric(treated_post) \times delta_energy_lev			0.4265*** (0.0491)
<i>Fixed-effects</i>			
id	Yes	Yes	Yes
cons_date	Yes	Yes	Yes
<i>Fit statistics</i>			
Observations	3,241,057	3,773,810	3,170,599
R ²	0.74743	0.58321	0.74833
Within R ²	0.00298	9.34×10^{-9}	0.00286

Clustered (id & cons_date) standard-errors in parentheses

*Signif. Codes: ***: 0.01, **: 0.05, *: 0.1*

Finally, we estimate measure specific realization rates by dividing realized by projected energy savings by measure. Results are presented in Figure 6. We indicate measure-specific realization rates in percentage form above each measure. For natural gas, we find realization rates of 59% for furnace upgrades and 51% for walls insulation. We find a realization rate of above 100% for air sealing measures. For electricity, we find realization rates that are mostly negative, since most measures appear to be associated with an increase in electricity consumption.

4 Conclusion




Figure 6: Measure specific realization rates