


TigerCS ↔ Genesys Integration Quick Guide

What the Genesys technical team needs to start integration and UAT.

Version	1.0 · 24 September 2026
Audience	Genesys technical team · Tiger IT
Reference	For full field lists and error codes, see the detailed "TigerCS-Genesys Integration Guide".
Security	This guide contains no credentials. Values in angle brackets are placeholders.

Three rules to remember
One conversation = one ticket. The same <code>conversationId</code> always returns the same ticket.
No ticket while a call is ringing. Phone tickets are created at agent pickup.
Ending a conversation never closes the ticket. TigerCS workflow continues.

1. Integration Overview



Genesys owns	TigerCS owns
Channels: phone, website chat, chatbot, WhatsApp, social	Tickets and the ticket lifecycle
Routing, queues and agent availability	Customer context: CRM, units, previous tickets
Conversations, transfers and message delivery	Transcripts and interaction history
Deciding when a human is needed	Agent mapping, workflow, SLA and closure

Genesys sends **conversation facts**. TigerCS decides everything about the **ticket**. Genesys never calls CRM, PACT or Tasleeh directly; TigerCS does the customer lookup.

2. Authentication

Item	What Genesys does
Header on every call	Authorization: Bearer <ACCESS_TOKEN> and Content-Type: application/json
Token	Issued for a dedicated TigerCS integration service account . Valid for 60 minutes: renew before expiry, or once after a 401.
Credentials	Shared by Tiger IT separately, through a secure channel . Never put them in flows, scripts, logs or documents.

NOTE — Final method confirmed at UAT start

Tiger IT will confirm the UAT endpoint and the final authentication setup with Genesys before testing begins (UAT step 2).

3. APIs

API	Method and path	Purpose	When to call
Customer Lookup	GET /api/genesys/customers/lookup	Customer, units, open tickets	Phone: at agent pickup
Create Ticket	POST /api/genesys/tickets	Create or reuse the ticket	Phone: after lookup · Digital: at start
Update Ticket	PATCH /api/genesys/tickets/{ticketId}	Agent, end, transcript, handoff	Handoff · conversation end

GET /api/genesys/customers/lookup?phoneNumber=+9627XXXXXXX

Required	phoneNumber
Success	200 OK with found, customer, units, tickets and openTicketCount. Also 200 when the caller is unknown (found: false). If lookup fails, still create the ticket.

POST /api/genesys/tickets

Required	conversationId, channel (Phone · WebsiteChat · WhatsApp · SocialMedia), and queueId (or the department the customer chose: departmentId / departmentCode)
Recommended	customerPhone, agentId, agentName, startedAtUtc
Success	201 TicketCreated. Sending the same conversationId again returns 200 AlreadyIngested with the same ticket. Keep ticketId.

```
Request: { "conversationId": "<ID>", "channel": "Phone", "customerPhone": "+9627XXXXXXX",
           "queueId": "<QUEUE_ID>", "agentId": "<GENESYS_USER_ID>", "agentName": "<name>" }
Response: { "outcome": "TicketCreated", "conversationId": "<ID>",
            "ticketId": 1234, "ticketNumber": "<ticketNumber>" }
```

PATCH /api/genesys/tickets/{ticketId}

Required	conversationId (must belong to ticketId)
Optional parts	agentId / agentName · ended { endedAtUtc, endReason, transcript } · handoff { required, agentAvailable, reason }. Send only what changed; resending is safe.
Success	200 Applied with ticketStatus (e.g. Open: the ticket was not closed), conversationEnded, transcriptMessageCount and handoffStatus.

Common errors: 400 invalid payload · 401 token missing/expired · 404 unknown conversation · 409 conversation belongs to another ticket · 422 queue not mapped to a department · 503 integration switched off.

4. Phone Flow




IMPORTANT — Do not create a ticket while the call is only ringing

Abandoned, missed and IVR-only calls must not reach TigerCS. The phone flow starts when an agent picks up. That is when a real inquiry exists and the agent is known.

Step	Genesys sends
Agent picks up	GET .../customers/lookup?phoneNumber=
Straight after	POST .../tickets with channel: "Phone", conversationId, customerPhone, queueId, agentId, agentName
Call ends	PATCH .../tickets/{ticketId} with ended: { endedAtUtc, endReason }

5. Digital Flow

Website Chat · Chatbot · WhatsApp · Social media



Channel	channel value
Website chat and website chatbot	WebsiteChat
WhatsApp	WhatsApp
Social media	SocialMedia

Transcript on conversation end

```

"ended": { "endedAtUtc": "2026-09-24T09:31:12Z", "endReason": "CustomerDisconnect",
  "transcript": [
    { "externalMessageId": "<MSG_ID>", "sender": "VirtualAgent",
      "sentAtUtc": "2026-09-24T09:15:05Z", "body": "How can I help?" } ] }
  
```


sender is one of **Customer**, **VirtualAgent** (bot), **HumanAgent**, **System**. Always send the **complete** transcript; messages already stored are skipped by **externalMessageId**.

RULE — The ticket remains open in TigerCS

Ending or disconnecting a conversation stores the transcript and nothing more. The ticket continues under TigerCS workflow.

6. Agent Mapping & Human Handoff

Agent mapping



- Genesys sends the **stable Genesys User ID** as `agentId`, never a name or email.
- When the ID is mapped, TigerCS records that employee as **Handled By** on the interaction. An unmapped ID never blocks the ticket.
- **Handled By is not necessarily the Ticket Owner:**

Example	Handled By	Ticket Owner
Noor (Genesys agent) answers the call	Noor	Per TigerCS assignment
Ticket later transferred to Collections and assigned to Ahmed	Noor (unchanged)	Ahmed

Human handoff

When a bot or routing decides a human is needed, send `PATCH` with a `handoff` part. The work stays on the **same ticket**.

Situation	Send	TigerCS status
Agent available	<code>handoff: { required: true, agentAvailable: true } plus that agent's agentId</code>	Assigned
No agent available	<code>handoff: { required: true, agentAvailable: false, reason: "..." }</code>	WaitingForAgent , shown to TigerCS agents in Pending Interactions

If the bot conversation ends with no human and no handoff was sent, TigerCS raises **WaitingForAgent** automatically, so the customer is never forgotten.

7. What Genesys Must Provide

Item	Field	Why
Conversation ID	<code>conversationId</code>	One ticket per conversation; same ID on every call (max 64 chars)
Queue ID	<code>queueId</code>	Routes the ticket to the right TigerCS department
Agent / User ID	<code>agentId</code>	Maps the Genesys agent to the TigerCS employee
Channel	<code>channel</code>	<code>Phone</code> , <code>WebsiteChat</code> , <code>WhatsApp</code> or <code>SocialMedia</code>
Customer phone	<code>customerPhone</code>	Customer lookup (send when available)
Transcript + message IDs	<code>transcript[].externalMessageId</code>	Digital channels: full transcript without duplicates (max 64 chars)
Handoff information	<code>handoff</code>	When human assistance is required; include agent availability

8. UAT Next Steps

#	Step	Owner	Done
1	Confirm UAT endpoint	Tiger IT	☐
2	Confirm authentication and share credentials securely	Tiger IT	☐
3	Confirm Queue IDs → TigerCS departments	Genesys + Tiger IT	☐
4	Confirm Agent IDs → TigerCS employees	Genesys + Tiger IT	☐
5	Run phone test: pickup, lookup, create, end	Both	☐
6	Run Website Chat / Chatbot test	Both	☐
7	Test transcript (including a resend)	Both	☐
8	Test human handoff: agent available and no agent	Both	☐