

Product Requirements Document

Implementation-ready specification for a Pomodoro productivity application inspired by the functional model of pomodorotimer.online. Revised scope: anonymous, local-first, no login/signup, no user authentication.

1. Product Vision

Build a fast, calming, privacy-friendly Pomodoro productivity web application that works immediately without registration. The product combines a reliable Pomodoro timer, task tracking, focus statistics, streaks, daily challenges, ambient audio, backgrounds, stopwatch utilities, offline support, and installable PWA behavior.

2. Product Principles

- No login or signup is required.
- Core personal data remains on the user's device.
- The timer remains accurate when the tab is backgrounded, refreshed, or temporarily closed.
- The product remains useful offline after required assets are cached.
- Mobile and desktop experiences are first-class.
- Functional inspiration may be replicated, but branding, copyrighted copy, artwork, audio, logos, and proprietary assets must be original or properly licensed.

3. Target Users

Students, exam aspirants, developers, remote workers, freelancers, creators, researchers, and anyone who uses timed focus sessions.

4. Core Pomodoro Experience

- Default Focus: 25 minutes.
- Default Short Break: 5 minutes.
- Default Long Break: 15 minutes.
- Default long-break interval: after four completed focus sessions.
- Start, pause, resume, reset, skip, and manual mode selection.
- Optional auto-start of breaks and focus sessions.
- Session completion alarm and optional browser notification.

5. Timer Reliability Requirements

The countdown must be deadline-based rather than decrement-counter-based. On start, persist the start timestamp, target deadline, mode, configured duration, running state, and pause information. The displayed remaining time is recalculated from wall-clock time. A Web Worker should provide update ticks while the page is active.

6. Tasks

- Create, edit, delete, complete, reorder, and select tasks.
- Support optional nested/subtasks.
- Associate completed focus sessions with the selected task.
- Break time must not count as task focus time.
- Roll child task focus totals into parent totals without double-counting.
- Persist task state locally.

7. Statistics and Engagement

- Track completed focus sessions, short breaks, long breaks, and focus duration.
- Daily statistics and historical local summaries.
- Current and longest streak.
- Configurable productive-day threshold.
- Optional weekly streak-freeze rule.
- Daily challenge progress and completion rewards.
- Rewards may include original motivational copy, productivity facts, badges, or unlocked visual/audio assets.

8. Personalization

- Focus, short-break, and long-break durations.
- Auto-start settings.
- Alarm sound and volume.
- Ambient music and independent volume.
- Background selection.
- Custom user background images stored locally.
- Show/hide seconds and animation preferences where supported.

9. Platform Features

- PWA installability.
- Offline core operation.
- Cross-tab synchronization using BroadcastChannel.
- Browser notifications with explicit permission.
- Picture-in-Picture mini timer where supported.
- Dedicated stopwatch.
- Preset timer/SEO landing pages such as 5, 15, 20, and 25 minute timers.

10. Data and Privacy

No account identity is required. Preferences and small timer state are stored in `localStorage`; structured records and binary/custom-background data are stored in `IndexedDB`. Clearing browser/site data can remove local data. The UI must explain this limitation without forcing cloud storage.

11. Non-Goals for Initial Release

- Authentication and user profiles.
- Cloud synchronization across devices.
- Social/community features.
- Team workspaces.
- Payments/subscriptions.
- Server-side storage of personal tasks or focus history.

12. Success Criteria

- Timer accuracy survives background tabs and refreshes.
- Core timer and task workflows work offline after installation/cache.
- No login gate exists.
- No personal task/session data is sent to a server by default.
- Responsive usability across common mobile and desktop sizes.
- Automated acceptance suite passes before release.