


NIDHI M N


1BM21CS266

Create a topology consisting of 2 or more devices connected with the help of a router.

TOPOLOGY-1



CONFIGURATION COMMANDS



The screenshot shows a window titled "Router1" with three tabs: "Physical", "Config", and "CLI". The "CLI" tab is active, displaying the "IOS Command Line Interface". The interface shows the following text:

```
Bridging software.  
X.25 software, Version 3.0.0.  
4 FastEthernet/IEEE 802.3 interface(s)  
2 Low-speed serial(sync/async) network interface(s)  
32K bytes of non-volatile configuration memory.  
63488K bytes of ATA CompactFlash (Read/Write)  
  
--- System Configuration Dialog ---  
  
Continue with configuration dialog? [yes/no]: no  
  
Press RETURN to get started!  
  
Router>enable  
Router#configure terminal  
Enter configuration commands, one per line. End with CNTL/Z.  
Router(config)#interface Fa0/0  
Router(config-if)#ip address 10.0.0.2 255.0.0.0  
Router(config-if)#no shutdown  
  
Router(config-if)#  
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up  
  
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to  
up
```

At the bottom right of the CLI window, there are two buttons: "Copy" and "Paste".

PING COMMANDS

```
Command Prompt
PC>ping 20.0.0.2

Pinging 20.0.0.2 with 32 bytes of data:

Request timed out.
Reply from 20.0.0.2: bytes=32 time=0ms TTL=127
Reply from 20.0.0.2: bytes=32 time=0ms TTL=127
Reply from 20.0.0.2: bytes=32 time=0ms TTL=127

Ping statistics for 20.0.0.2:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

PC>ping 20.0.0.2


Pinging 20.0.0.2 with 32 bytes of data:

Reply from 20.0.0.2: bytes=32 time=0ms TTL=127
Reply from 20.0.0.2: bytes=32 time=0ms TTL=127
Reply from 20.0.0.2: bytes=32 time=0ms TTL=127
Reply from 20.0.0.2: bytes=32 time=0ms TTL=127

Ping statistics for 20.0.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

PC>
```

TOPOLOGY-2



COMMAND LINE COMMANDS

ROUTER-0

```
--- System Configuration Dialog ---

Continue with configuration dialog? [yes/no]: no

Press RETURN to get started!

Router>enable
Router#configure terminal
Enter configuration commands, one per line. End with CNIL/Z.
Router(config)#interface Se2/0
Router(config-if)#
Router(config-if)#ip address 30.0.0.2 255.0.0.0
Router(config-if)#no shutdown

Router(config-if)#
%LINK-5-CHANGED: Interface Serial2/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial2/0, changed state to up

Router(config-if)#exit
Router(config)#interface Se3/0
Router(config-if)#ip address 40.0.0.2 255.0.0.0
Router(config-if)#no shutdown

Router(config-if)#
%LINK-5-CHANGED: Interface Serial3/0, changed state to up
exit
Router(config)#
%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial3/0, changed state to up

Router con0 is now available

Press RETURN to get started.
```

ROUTER-1

Continue with configuration dialog? [yes/no]: no

Press RETURN to get started!

```
Router>enable
```

```
Router#configure terminal
```

```
Enter configuration commands, one per line. End with CNTL/Z.
```

```
Router(config)#interface Fa0/0
```

```
Router(config-if)#10.0.0.1 255.0.0.0
```

```
% Invalid input detected at '^' marker.
```

```
Router(config-if)#ip address 10.0.0.1 255.0.0.0
```

```
Router(config-if)#no shutdown
```

```
Router(config-if)#
```

```
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up
```

```
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up
```

```
Router(config-if)#exit
```

```
Router(config)#interface Se2/0
```

```
Router(config-if)#ip address 30.0.0.1 255.0.0.0
```

```
Router(config-if)#no shutdown
```

```
%LINK-5-CHANGED: Interface Serial2/0, changed state to down
```

```
Router(config-if)#exit
```

```
Router(config)#
```

```
%LINK-5-CHANGED: Interface Serial2/0, changed state to up
```

```
%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial2/0, changed state to up
```

Router con0 is now available

Press RETURN to get started.

ROUTER-2

Continue with configuration dialog? [yes/no]: no

Press RETURN to get started!

```
Router>enable
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#interface Fa0/0
Router(config-if)#ip address 20.0.0.1 255.0.0.0
Router(config-if)#no shutdown

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

Router(config-if)#exit
Router(config)#interface 40.0.0.1 255.0.0.0
      ^
% Invalid input detected at '^' marker.

Router(config)#interface Se3/0
Router(config-if)#ip address 40.0.0.1 255.0.0.0
Router(config-if)#no shutdown

%LINK-5-CHANGED: Interface Serial3/0, changed state to down
Router(config-if)#exit
Router(config)#
%LINK-5-CHANGED: Interface Serial3/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial3/0, changed state to up
```

Router con0 is now available

Press RETURN to get started.

PING COMMANDS

Command Prompt

```
Packet Tracer PC Command Line 1.0
PC>ping 20.0.0.10

Pinging 20.0.0.10 with 32 bytes of data:

Reply from 10.0.0.1: Destination host unreachable.
Reply from 10.0.0.1: Destination host unreachable.
Request timed out.
Reply from 10.0.0.1: Destination host unreachable.

Ping statistics for 20.0.0.10:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

PC>ping 40.0.0.1

Pinging 40.0.0.1 with 32 bytes of data:

Reply from 10.0.0.1: Destination host unreachable.
Reply from 10.0.0.1: Destination host unreachable.
Reply from 10.0.0.1: Destination host unreachable.
Reply from 10.0.0.1: Destination host unreachable.

Ping statistics for 40.0.0.1:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

PC>30.0.0.1
Invalid Command.

PC>ping 30.0.0.1

Pinging 30.0.0.1 with 32 bytes of data:

Reply from 30.0.0.1: bytes=32 time=0ms TTL=255
Reply from 30.0.0.1: bytes=32 time=0ms TTL=255
Reply from 30.0.0.1: bytes=32 time=0ms TTL=255
Reply from 30.0.0.1: bytes=32 time=0ms TTL=255

Ping statistics for 30.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms

PC>ping 30.0.0.2

Pinging 30.0.0.2 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
```