```
(3 rows)
cqlsh:employee> CREATE KEYSPACE Library WITH REPLICATION={'class':'SimpleStrategy', 'replication_factor':1};
cqlsh:employee> DESCRIBE KEYSPACES;

employee  system       system_distributed  system_traces  system_virtual_schema
library   system_auth  system_schema       system_views

cqlsh:employee> USE Library;
```

```
cqlsh:library> create table library_info( stud_id INT, counter_values counter, stud_name text, book_name text, book_id int, date
_of_issue date, PRIMARY KEY(stud_id, stud_name, book_name, book_
id, date_of_issue));
cqlsh:library> describe library_info;

CREATE TABLE library.library_info (
    stud_id int,
    stud_name text,
    book_name text,
    book_id int,
    date_of_issue date,
    counter_values counter,
    PRIMARY KEY (stud_id, stud_name, book_name, book_id, date_of_issue)
) WITH CLUSTERING ORDER BY (stud_name ASC, book_name ASC, book_id ASC, date_of_issue ASC)
    AND additional_write_policy = '99p'
    AND bloom_filter_fp_chance = 0.01
    AND caching = {'keys': 'ALL', 'rows_per_partition': 'NONE'}
    AND cdc = false
    AND comment = ''
    AND compaction = {'class': 'org.apache.cassandra.db.compaction.SizeTieredCompactionStrategy', 'max_threshold': '32', 'min_thresho
ld': '4'}
    AND compression = {'chunk_length_in_kb': '16', 'class': 'org.apache.cassandra.io.compress.LZ4Compressor'}
    AND memtable = 'default'
    AND crc_check_chance = 1.0
    AND default_time_to_live = 0
    AND extensions = {}
    AND gc_grace_seconds = 864000
    AND max_index_interval = 2048
    AND memtable_flush_period_in_ms = 0
    AND min_index_interval = 128
    AND read_repair = 'BLOCKING'
```

Activate Windows
Go to Settings to activate Windows.

```
cqlsh:library> BEGIN counter BATCH UPDATE Library_info set count
er_values=counter_values+1 where stud_id=112 and stud_name='john
' and book_name='bda' and book_id=101 and date_of_issue='2026-05
-01'; apply batch;
cqlsh:library> select * from library_info;

 stud_id | stud_name | book_name | book_id | date_of_issue | counter_values
---------+-----------+-----------+---------+---------------+----------------
     112 |      john |       bda |     101 |    2026-05-01 |              1

(1 rows)
cqlsh:library> describe library_info;

CREATE TABLE library.library_info (
    stud_id int,
    stud_name text,
    book_name text,
    book_id int,
    date_of_issue date,
    counter_values counter,
    PRIMARY KEY (stud_id, stud_name, book_name, book_id, date_of_issue)
) WITH CLUSTERING ORDER BY (stud_name ASC, book_name ASC, book_id ASC, date_of_issue ASC)
    AND additional_write_policy = '99p'
    AND bloom_filter_fp_chance = 0.01
    AND caching = {'keys': 'ALL', 'rows_per_partition': 'NONE'}
    AND cdc = false
```

```
cqlsh:library> select * from library_info where stud_id=112 and book_name='bda' allow filtering;

 stud_id | stud_name | book_name | book_id | date_of_issue | counter_values
---------+-----------+-----------+---------+---------------+----------------
     112 |      john |       bda |     101 |    2026-05-01 |              2

(1 rows)
cqlsh:library> copy library_info to library_export.csv with header=TRUE;
Improper copy command.
cqlsh:library> copy library_info to 'library_export.csv' with he
ader=TRUE;
Using 7 child processes

Starting copy of library.library_info with columns [stud_id, stud_name, book_name, book_id, date_of_issue, counter_values].
Processed: 1 rows; Rate:       3 rows/s; Avg. rate:       3 rowsProcessed: 1 rows; Rate:       1 rows/s; Avg. rate:       2 rows/s
1 rows exported to 1 files in 0.677 seconds.
cqlsh:library> exit
nidhi@DESKTOP-ES2V6QC:~$ pwd
/home/nidhi
nidhi@DESKTOP-ES2V6QC:~$ nano library_import.csv
nidhi@DESKTOP-ES2V6QC:~$ cat library_import.cav
cat: library_import.cav: No such file or directory
nidhi@DESKTOP-ES2V6QC:~$ cat library_import.csv
stud_id,stud_name,book_name,book_id,date_of_issue,counter_value
112,john,bda,101,2026-05-01,1
113,jane,algorithms,102,2026-05-02,0
114,doe,datastructures,103,2026-05-03,0
nidhi@DESKTOP-ES2V6QC:~$ cqlsh

ATTENTION: All commands will be saved to history file: /home/nidhi/.cassandra/cqlsh_history
This may include sensitive information such as passwords.
```

Activate Windows
Go to Settings to activate Windows.

```
cqlsh:library> copy library_info(stud_id, stud_name, book_name, book_id, date_of_issue, counter_values) from 'library_import.csv
' with header=TRUE;
Using 7 child processes

Starting copy of library.library_info with columns [stud_id, stud_name, book_name, book_id, date_of_issue, counter_values].
Processed: 3 rows; Rate:       9 rows/s; Avg. rate:       9 rowsProcessed: 3 rows; Rate:       4 rows/s; Avg. rate:       7 rows/s
3 rows imported from 1 files in 0.456 seconds (0 skipped).
cqlsh:library> select * from library_info;

 stud_id | stud_name | book_name      | book_id | date_of_issue | counter_values
---------+-----------+----------------+---------+---------------+----------------
     114 |       doe | datastructures |     103 |    2026-05-03 |              0
     113 |      jane |     algorithms |     102 |    2026-05-02 |              0
     112 |      john |            bda |     101 |    2026-05-01 |              3

(3 rows)
cqlsh:library>
```