LABSHEET 5

App.jsx

```
import LoginForm from "./LoginForm";
import OnboardingWizard from "./OnboardingWizard";
import "./App.css";
function App() {
  return (
    <div className="app">
      <h1>React Form Module</h1>
      <LoginForm />
      <hr />
      <OnboardingWizard />
    </div>);}
export default App;
```

LoginForm.jsx

```
import { useState } from "react";
import PasswordStrength from "./PasswordStrength";
function LoginForm() {
  const [formData, setFormData] = useState({
    email: "",
    password: ""});
   const [errors, setErrors] = useState({});
  const [submitted, setSubmitted] = useState(false);
 const emailRegex = /^[^\s@]+@[^\s@]+\.[^\s@]+$/;
  const passwordRegex =
    /^(?=.*[a-z])(?=.*[A-Z])(?=.*\d)(?=.*[@$!%*?&]).{8,}$/;
  const handleChange = (e) => {
    const { name, value } = e.target;
    setFormData({
      ...formData,
      [name]: value });
    validateField(name, value);};
  const validateField = (name, value) => {
    let message = "";
    if (name === "email" && value && !emailRegex.test(value)) {
      message = "Invalid email format";}
    if (name === "password" && value && !passwordRegex.test(value)) {
      message =
```

```
        "Password must contain 8+ characters, uppercase, lowercase, number
and special character";}
    setErrors((prev) => ({
      ...prev,
      [name]: message }));};
  const handleSubmit = (e) => {
    e.preventDefault();
    const newErrors = {};
    if (!emailRegex.test(formData.email)) {
      newErrors.email = "Enter a valid email";}
    if (!passwordRegex.test(formData.password)) {
      newErrors.password = "Password does not meet security
requirements";}
    setErrors(newErrors);
    if (Object.keys(newErrors).length === 0) {
      setSubmitted(true);
    } else {
      setSubmitted(false);} };
  return (
    <div className="form-container">
      <h2>Login Form</h2>
      <form onSubmit={handleSubmit}>
        <input
          type="email"
          name="email"
          placeholder="Enter Email"
          value={formData.email}
          onChange={handleChange}/>
        {errors.email && (
          <span className="error">{errors.email}</span> )}
        <input
          type="password"
          name="password"
          placeholder="Enter Password"
          value={formData.password}
          onChange={handleChange}/>
        <PasswordStrength password={formData.password} />
        {errors.password && (
          <span className="error">{errors.password}</span>)}
        <button type="submit">Login</button>
```

```
      </form>
      {submitted && (
        <p className="success">Login validation successful!</p>)}
    </div>);}
export default LoginForm;
```

OnboardingWizard.jsx

```
import { useState } from "react";
function OnboardingWizard() {
  const [step, setStep] = useState(1);
  const [data, setData] = useState({
    name: "",
    email: "",
    age: "",
    city: "" });
  const handleChange = (e) => {
    setData({
      ...data,
      [e.target.name]: e.target.value}); };
  const nextStep = () => {
    if (step < 3) {
      setStep(step + 1); }};
  const previousStep = () => {
    if (step > 1) {
      setStep(step - 1);}};
  const handleSubmit = (e) => {
    e.preventDefault();
    alert(
      `Registration Successful!\nName: ${data.name}\nEmail:
${data.email}\nCity: ${data.city}`);};
  return (
    <div className="form-container">
      <h2>User Onboarding</h2>
      <div className="steps">
        Step {step} of 3
      </div>
      <form onSubmit={handleSubmit}>
        {step === 1 && (
          <div>
            <h3>Personal Information</h3>
            <input
```

```
            type="text"
            name="name"
            placeholder="Full Name"
            value={data.name}
            onChange={handleChange} />
          <input
            type="number"
            name="age"
            placeholder="Age"
            value={data.age}
            onChange={handleChange}
          /></div>)}
        {step === 2 && (
          <div>
            <h3>Contact Information</h3>

            <input
              type="email"
              name="email"
              placeholder="Email"
              value={data.email}
              onChange={handleChange}
            /></div>)}
        {step === 3 && (
          <div>
            <h3>Location</h3>
            <input
              type="text"
              name="city"
              placeholder="City"
              value={data.city}
              onChange={handleChange}/>
            <p>
              <b>Name:</b> {data.name}
            </p>
            <p>
              <b>Email:</b> {data.email}
            </p>
            <p>
              <b>City:</b> {data.city}
```

```
            </p></div> )}
        <div className="buttons">
          {step > 1 && (
            <button
              type="button"
              onClick={previousStep} >
              Previous
            </button>)}
          {step < 3 ? (
            <button
              type="button"
              onClick={nextStep} >
              Next
            </button>) : (
            <button type="submit">
              Submit
            </button>)}</div></form></div>);}
export default OnboardingWizard;
```

PasswordStrength.jsx

```
function PasswordStrength({ password }) {
  let strength = 0;
  if (password.length >= 8) strength++;
  if (/[A-Z]/.test(password)) strength++;
  if (/[a-z]/.test(password)) strength++;
  if (/\d/.test(password)) strength++;
  if (/[@$!%*?&]/.test(password)) strength++;
  const percentage = (strength / 5) * 100;
  let text = "Very Weak";
  if (strength === 2) text = "Weak";
  if (strength === 3) text = "Medium";
  if (strength === 4) text = "Strong";
  if (strength === 5) text = "Very Strong";
  return (
    <div className="strength-container">
      <div className="progress">
        <divclassName="progress-bar"
          style={{ width: `${percentage}%` }}
        ></div></div>
      <p>Password Strength: {text}</p></div>);}
export default PasswordStrength;
```