MeetingAI
MEETING INTELLIGENCE

MEETINGAI · HYBRID NLP + LLM

Project Report

AI-powered meeting intelligence: transcripts, decisions, action items, calendar, chat and minutes - with names on every voice.



LIVE APPLICATION
gd4n8x8sjkkxmdhfptkc9m.streamlit.app

SOURCE CODE
github.com/nidhitiwari23/Meeting-AI-

EDITION
October 2026

Contents

1. Executive summary 2
2. The problem, the objectives and the scope 3
3. A tour of the application 4
4. System architecture 24
5. Start-up, set-up and "training" 26
6. End-to-end processing flow 28
7. Speech and "who said what" 29
8. Classical NLP: how sentences are understood 32
9. The confidence gateway 34
10. The LLM layer and the validation layer 36
11. Search and the chatbot 38
12. Minutes, calendar, follow-ups and e-mail 40
13. Data model and storage 41
14. User-interface design 43
15. Technology stack and why each piece was chosen 43
16. Assumptions and design decisions - consolidated 45
17. Security, privacy and honesty by design 46
18. Deployment 47
19. Source-code map 48
20. Glossary 49

1 Executive summary

A meeting assistant that listens, remembers, organises and answers - and says so honestly when it does not know.

Meetings produce decisions, promises and deadlines, and most of them are forgotten within days. **MeetingAI** turns a meeting recording or a written transcript into organised, searchable knowledge. It runs as a web application built entirely in Python and can be deployed for free.

12	14	610	16	0
application pages	processing steps per meeting	seed sentences used to train the classifier	free services & libraries combined	paid components required




Figure 1 · *The MeetingAI dashboard*

What a user gets from one upload

- A **transcript** with timestamps and **speaker names** ("Priya: ...", not "Speaker 2") using pyannote speaker recognition.
- A structured **summary**: overview, key discussion points, decisions and conclusions.
- **Action items** with owner, deadline, priority and status. When the meeting did not say who or when, the application shows **Unassigned** or **Not specified** instead of guessing.
- **Decisions** with the exact quote that proves them, and **dated events** that are placed on a **calendar** automatically.

- A **chatbot** and a **cross-meeting search** whose answers come only from the meetings and always show their sources.
- Editable **Minutes of Meeting** (Word, PDF, Markdown) that can be **e-mailed** after you confirm.
- **Follow-up suggestions** (recaps, reminders) that stay drafts until you approve them.

KEY IDEA · WHAT MAKES THE PROJECT DIFFERENT

- **Hybrid NLP.** Fast, explainable classical NLP runs first. A *confidence gateway* sends only doubtful sentences to a free LLM.
- **Validation.** Everything an LLM returns is checked against the real transcript (verbatim quotes, real owners, dates computed by code).
- **Honesty.** Unknown owner = *Unassigned*, unknown date = *Not specified*, unanswerable question = *not found*.
- **Runs free.** Free-tier LLMs, a local embedding model, SQLite and ChromaDB - deployable on Streamlit Community Cloud.

2 The problem, the objectives and the scope

Why the project exists, what it had to achieve, and where its boundaries are.

The problem. Important information is buried in long conversations. Manual minutes take time, ordinary transcription gives a wall of text without understanding, and general-purpose chatbots may invent facts that were never said.

2.1 Objectives and where each one is met

#	Objective	Where it lives
1	Upload audio, video or text transcripts	New Meeting page, `parsing.py`, `stt.py`
2	Speech-to-text with speakers and timestamps	`stt.py`, `diarize.py`, `speakers.py`
3	Structured AI summary	`llm_tasks.py`, with an offline fallback in `nlp.py`
4	Action items with owner / deadline / status, editable	`nlp.py`, `gateway.py`, Action Tracker page
5	Grounded meeting chatbot	`rag.py`, Ask MeetingAI page
6	Cross-meeting search with sources	`rag.py`, `db.py` (FTS5), Search page
7	Meeting library and history (including chat history)	`db.py`, Library page
8	Minutes of Meeting: edit, accept, export, e-mail	`mom.py`, `mailer.py`
9	Events and deadlines scheduled on a calendar	`dates.py`, Calendar page, `ics.py`
10	Central action tracker with statuses	Action Tracker page
11	Follow-up suggestions that ask before sending	`followups.py`
12	Dashboard statistics	Dashboard page
13	Honest handling of missing or uncertain information	`gateway.py`, validation in `pipeline.py`
14	Professional dark SaaS-style interface	`ui/theme.py`, `ui/components.py`

2.2 Scope

In scope	Deliberately out of scope
Recorded or transcribed meetings, English-language focus	Live (real-time) meeting capture
One shared workspace (optionally password-protected)	Per-user accounts and permissions
Free-tier AI services with automatic fallback	Paid or self-hosted large models
E-mail via SMTP; calendar via links and `.ics` files	Direct calendar creation through OAuth sign-in

ASSUMPTION · SINGLE SHARED WORKSPACE

Assumption: one deployment serves one team, so all meetings live in one shared database. **Why:** per-user accounts would need authentication, authorisation and a hosted database - none of which fit a free, single-process deployment. **Effect:** anyone with the link sees the same data, which is why an optional `APP_PASSWORD` gate exists.

3 A tour of the application

Every page shares one design language - navy background, violet-blue gradients, glass cards, status chips and icons.




Figure 2 · *Navigation map: sidebar groups and pages*

3.1 Dashboard

KPIs (meetings, action items, completed, pending, overdue, decisions), recent meetings, upcoming deadlines and events, a task-status donut, open work by owner, and **NLP-engine health** - how many items classical NLP handled alone versus how many went to the LLM.




Figure 3 · *Dashboard - charts and NLP engine health*

3.2 New Meeting

Drag in audio, video or a transcript (txt, vtt, srt, docx, pdf), or paste one. A status panel shows which engines are connected. Progress is shown as a live stepper.




Figure 4 · *Upload page*

3.3 Meeting Library

Every analysed meeting as a card: date, summary snippet, status, task counts, tags. Search, sort, open, ask AI, or delete.




Figure 5 · *Meeting library*

3.4 Meeting details

Overview - summary, key discussion points, conclusions, topics, participants and an "at a glance" panel.




Figure 6 · *Meeting overview*

Transcript - one coloured avatar per speaker, timestamps, search, a speaker filter, and chips marking where tasks, decisions and events were said. If the original recording exists you can jump the audio player to any line.




Figure 7 · *Transcript with speaker names and insight chips*

Action items - an editable table (task, owner, deadline, status, priority) with the exact deadline wording, source meeting, confidence and "needs review" flags.




Figure 8 · *Editable action items*

Decisions and events - each decision shows the quote that proves it; each event can be added to Google Calendar or downloaded as `.ics`.




Figure 9 · *Decisions and events*

How it was analysed - the transparency tab. For every candidate sentence it shows the confidence, margin, outcome (accepted / sent to the LLM / review), reason code and a plain-English explanation.




Figure 10 · *Gateway decisions per meeting*

3.5 Who is who? (speaker names)

pyannote separates voices; this panel puts names on them. Suggestions come from what people said ("I'm Priya", "Rahul, can you..."), each with its evidence and confidence. Play a sample, correct the name, press **Apply names**, and optionally **Remember this voice** so that future meetings label it automatically.




Figure 11 · *Who is who panel*

3.6 Ask MeetingAI

A chatbot restricted to your meetings. Answers cite sources, show *how I searched*, and say "not found" when the meetings do not contain the answer. Chats are saved and can be continued later.




Figure 12 · *Chat*

3.7 Search

Smart (hybrid), keyword, semantic or exact-phrase search across all meetings. Results show the meeting, timestamp, speakers, the supporting text with highlights, and whether a hit came from keywords, meaning or both.




Figure 13 · *Cross-meeting search*

3.8 Action Tracker

All tasks from all meetings in one table with filters (status, owner, meeting, deadline, text, needs-review). Edit inline and press *Save changes*.




Figure 14 · *Action tracker*

3.9 Calendar

A month grid. Events and task deadlines found in meetings appear on their dates (violet = event, blue = deadline, red = overdue, green = done), followed by an agenda list with *Add to Google* buttons and a downloadable `.ics` file.




Figure 15 · *Calendar month view*




Figure 16 · *Calendar agenda*

3.10 Minutes of Meeting

Generate a professional draft, edit it, preview it, **accept** it, then download Word / PDF / Markdown or e-mail it to the addresses you enter - after a confirmation tick.




Figure 17 · *Minutes preview*




Figure 18 · *Minutes export and e-mail*

3.11 Follow-ups

Suggested recaps, reminders per person, requests for owners of unassigned tasks and event reminders. Edit, polish with AI (facts unchanged), then send or open in your mail app.




Figure 19 · *Follow-ups*

3.12 NLP Lab

A "look under the hood" page: try the NLP live on any text, see held-out accuracy and the confusion matrix, tune the thresholds with a simulator, and see gateway statistics.




Figure 20 · *NLP Lab - live analysis*




Figure 21 · *NLP Lab - classifier evaluation*




Figure 22 · *NLP Lab - gateway statistics*

3.13 Settings

Connect free AI services, choose speech and speaker engines, save team voices, tune the confidence gateway, configure e-mail, back up or restore data.




Figure 23 · *Settings - AI and speech*




Figure 24 · *Settings - voice profiles*




Figure 25 · *Settings - confidence gateway*

3.14 Phone layout

Columns stack, the sidebar collapses after navigation, and tables scroll.




Figure 26 · *Phone layout*

4 System architecture

Four layers with one strict rule - pages never contain business logic.



Figure 27 · *System architecture*

Layer	Folder	Responsibility
Presentation	`app.py`, `views/`, `ui/`	Pages, theme, reusable HTML components, charts, navigation
Application logic	`core/`	Parsing, speech, speakers, NLP, gateway, LLM, search, minutes, e-mail
Storage	`data/` (created at run time)	SQLite database, FTS5 index, ChromaDB vectors, uploaded recordings
External services	HTTPS	Groq, Gemini, OpenRouter, pyannoteAI, AssemblyAI, SMTP

> **NOTE · EVERY EXTERNAL SERVICE IS OPTIONAL**
> With no keys at all, text transcripts still produce tasks, decisions, events, summaries, search and minutes using classical NLP only. Each service is checked at run time and has a fallback, so a missing key never breaks a page.

How a Streamlit application runs. Streamlit re-runs the whole script after every click. `app.py` therefore does the same four things each time: apply the theme, check the optional password, draw the sidebar, and import and render the selected page. Per-user state (current page, selected meeting, chat session) lives in `st.session_state`; durable data lives in SQLite; expensive objects (the trained classifier) are cached.




Figure 28 · *Which module uses which*

5 Start-up, set-up and "training"

What is prepared before the first upload - and why nothing large is pre-trained or stored.



Figure 29 · *Start-up sequence*

5.1 At server start

- `init_db()` creates 13 tables and the FTS5 keyword index in `data/meetingai.db`.
- The classical NLP model is **trained from scratch in about one second** and cached in memory for the lifetime of the server process. Nothing is saved to disk.
- The theme CSS is injected and the optional password gate is checked.

5.2 What "training" means in this project

There is **no large pre-trained model of our own** and no GPU work. The only model trained is a small text classifier:

Item	Detail
Training data	`core/seed_data.py` builds **610 sentences** from hand-written templates (190 action, 110 decision, 100 question, 210 discussion), using fixed random seed 42 so results are repeatable
Example template	`"{P} will {V} {O} {D}."` becomes "Priya will send the budget sheet by Monday." Names, verbs, objects and dates are swapped in

Item	Detail
Test data	42 hand-written sentences in a different style, never used for training; used only by the NLP Lab
Features	TF-IDF over unigrams and bigrams (`sublinear_tf=True`)
Models	`MultinomialNB(alpha=0.3)` is used in the app; a logistic regression is trained alongside only for comparison in the NLP Lab

ASSUMPTION · TEMPLATE-GENERATED SEED DATA

Assumption: a small synthetic seed corpus is enough to give the classifier a useful baseline. **Why:** no public meeting corpus has the labels this project needs (action items, owners, deadlines), and annotating real meetings was outside the project's scope. **Effect:** the classifier is a *baseline*, not a production model. The confidence gateway exists precisely to compensate: when the model is unsure, the sentence goes to the LLM.

DESIGN DECISION · TRAIN AT START-UP INSTEAD OF SHIPPING A MODEL FILE

Training takes about a second, so there is no model file to version, no pickle to load from an untrusted source, and the training data stays visible and editable. Changing the seed sentences immediately changes the model.

5.3 On the first analysed meeting

- The **all-MiniLM-L6-v2** embedding model (ONNX build, about 80 MB, 384 numbers per text) is downloaded once and cached.
- A ChromaDB `PersistentClient` collection with cosine distance is opened.
- The meeting's transcript chunks, decisions and tasks are embedded and indexed.

ASSUMPTION · A SMALL ONNX EMBEDDING MODEL INSTEAD OF PYTORCH

Assumption: a compact general-purpose English model gives good-enough semantic search for meeting text. **Why:** PyTorch needs about 2 GB; the free cloud tier offers about 1 GB. The ONNX MiniLM model is small, fast and CPU-friendly. **Effect:** semantic quality is good for English but not state-of-the-art; the backend can be switched to BGE-small (`EMBEDDING_BACKEND=sbert`) where memory allows.

6 End-to-end processing flow

The fourteen steps executed by pipeline.py for every meeting.



Figure 30 · *A meeting from upload to answers*

1. **Upload.** `views/upload.py` creates a meeting row and chooses a path by file type.
2. **Read the file.** Text goes through `parsing.py` (speaker lines, subtitle files, header lines such as `Meeting:` and `Attendees:`). Audio and video are converted by FFmpeg into mono 16 kHz MP3 chunks of ten minutes.
3. **Speech-to-text.** Whisper (via Groq) transcribes each chunk with word timestamps.
4. **Who spoke when.** pyannote separates the voices; saved voices add names.
5. **Save transcript** to SQLite and the FTS5 keyword index.
6. **Sentences.** The text is cleaned of fillers ("um", "you know"), split into sentences, and each sentence remembers its speaker, timestamp and neighbours.
7. **Classical NLP** scores every sentence and extracts owner, deadline and events.

8 **Confidence gateway** decides which results are trusted.

9 **LLM (optional)** writes the summary, double-checks uncertain sentences and looks for items the rules missed.

10 **Validation** checks every LLM item against the transcript (quotes, owners, dates).

11 **Merge and de-duplicate** - agreement between classical NLP and the LLM raises confidence to 0.95.

12 **Save results** (tasks, decisions, events, summary, gateway log).

13 **Index for search** in ChromaDB.

14 **Ready** - dashboard, tracker, calendar, chat, search, minutes and follow-ups all use the new data.

ASSUMPTION · SYNCHRONOUS PROCESSING

Assumption: meetings are processed in the foreground, with a progress stepper. **Why:** the free host runs a single Streamlit process; a background worker would add infrastructure (queues, extra processes) that free hosting does not provide. **Effect:** very long recordings keep the upload page busy until they finish; ten-minute chunking keeps each external call small and resumable.

7

Speech and "who said what"

pyannote finds the voices; names come from saved voiceprints, clues in the conversation, or you.




Figure 31 · *Speaker pipeline*

7.1 Speech-to-text

`stt.py` converts media with FFmpeg and sends each chunk to **Groq Whisper (large-v3-turbo)**, asking for **word-level timestamps**. Chunks are time-shifted so the transcript has one continuous timeline. Whisper's two-to-five-second fragments are merged into readable paragraphs (same speaker, small gap, at most 60 words), and segments Whisper probably invented over silence are discarded. A local Whisper model (faster-whisper or openai-whisper) is used if installed and no cloud engine is configured.

ASSUMPTION · TEN-MINUTE CHUNKS, 32 KBPS MONO AUDIO

Why: the free Groq tier limits uploads to roughly 25 MB. Ten minutes of 32 kbps mono MP3 is about 2.4 MB, leaving a very large safety margin, and speech recognition does not need more than 16 kHz mono.

7.2 Diarization with pyannote

`diarize.py` supports two ways to run pyannote:

	pyannoteAI hosted API	pyannote.audio locally
Needs	`PYANNOTEAI_API_KEY`	PyTorch (~2 GB), `HF_TOKEN`, accepted model terms
Works on free cloud hosting	**Yes**	No (memory)
Recognises saved voices by name	**Yes**	No (anonymous labels)

The hosted flow uploads the audio to temporary storage (`media://...`), submits a **diarize** job (or an **identify** job when voice profiles exist), polls the job until it succeeds, and reads the speaker **turns** (`Speaker 1: 0.0 - 3.2 s`, ...). Errors are translated into plain language (invalid key, no credits, rate limit).

DESIGN DECISION · HOSTED PYANNOTE FOR THE DEPLOYED APP

The brief asked for pyannote. Running it locally is possible, but it cannot fit on the free cloud tier. The hosted pyannoteAI API (from the pyannote authors) gives the same family of models without PyTorch, and additionally supports **voiceprints** for automatic naming. Local pyannote remains available for use on a personal computer.

7.3 Aligning words with speakers

`assign_speakers` gives every Whisper word to the speaker whose turn contains the word's midpoint, so a sentence is split exactly where the voice changes. One-word interjections ("yeah") do not fragment a turn. If a recording has no word timestamps, the speaker with the largest time overlap wins the segment. Raw labels (`SPEAKER_00`) become `Speaker 1`, `Speaker 2` in order of first appearance.

7.4 Putting names on voices

1. **Voice profiles (automatic).** Settings → Voices: give a name and a 5-30 second clip of one person. pyannoteAI returns a **voiceprint**, a compact fingerprint stored in the local database. On later recordings the *identify* job matches voices to voiceprints; a voice that matches well enough gets the name, the rest stay "Speaker N".
2. **Clues in the conversation** (`speakers.py`): self-introductions ("I'm Priya", weight 3), being addressed ("Rahul, can you..." means the *next* voice, 1.2), being thanked ("Thanks Rahul" means the *previous* voice, 0.9), elimination (one unnamed voice and one unused attendee), and an optional LLM that must quote its evidence. Names must be attendees or appear in the transcript.
3. **Manual.** The *Who is who?* panel with audio samples. Suggestions are never applied silently.

ASSUMPTION · MATCH STRICTNESS 60 / 100

Assumption: a pyannoteAI match score of 60 or more is trustworthy. **Why:** pyannoteAI documents 50-70 as the sensible range - lower produces wrong names, higher leaves real colleagues as "Speaker N". 60 sits in the middle. **Effect:** adjustable in Settings → Voices. Unknown people are never forced onto a name.

ASSUMPTION · EVIDENCE WEIGHTS FOR NAME SUGGESTIONS

Assumption: a self-introduction is stronger evidence (3.0) than being addressed (1.2) or thanked (0.9). **Why:** people name themselves reliably, whereas "Thanks Rahul" could refer to someone who spoke earlier. Confidence is `0.45 + 0.12 x votes`, capped at 0.95, and the user always confirms.

Applying names renames the transcript, task owners and decisions, updates the attendee list and refreshes the search index. If the speaker service fails or has no credits, the transcript is still saved (as one speaker) with a visible warning.

8 Classical NLP: how sentences are understood

Two independent experts vote on every sentence; three extractors then find the owner, the deadline and any event.




Figure 32 · *Classical NLP scoring*

8.1 The rule expert

Weighted cue patterns, combined as `1 - (1-w1)(1-w2)...`:

Cue	Weight
"action item", "next steps are"	0.95
"X will / 'll <action verb>"	0.92
"can you / could you <verb>"	0.88
"going to <verb>", "responsible for", "assigned to"	0.85 - 0.88
"needs to <verb>"	0.80
"we decided / agreed / resolved"	0.96

Cue	Weight
"the decision is", "Decision:"	0.96 - 1.0
"let's go with", "it's settled"	0.85 - 0.92

Hedging words (*maybe, might, perhaps, we could, consider*...) mark a suggestion instead of a commitment. A question mark does not turn a request into a question: "Priya, can you send the report?" stays a task.

8.2 The statistics expert

TF-IDF features and Multinomial Naive Bayes (section 5.2) give a probability for each label: action, decision, question, discussion.

8.3 Fusion

`score = 0.5 x NaiveBayes + 0.5 x rules`, multiplied by 0.8 when the sentence is hedged. The **margin** is the gap to the best competing label. Sentences scoring below 0.33 are treated as ordinary conversation and never reach the gateway.

ASSUMPTION · EQUAL WEIGHT FOR RULES AND STATISTICS; HEDGE FACTOR 0.8; FLOOR 0.33

Assumption: the two experts deserve equal say. **Why:** the statistics expert was trained on template data and the rules were written by hand; neither is clearly better, and averaging lets each correct the other. **Effect:** values were chosen by inspecting behaviour on the sample meetings and the held-out sentences, not by large-scale tuning. They are constants in `nlp.py` and can be changed.

8.4 The extractors

- **Owner** (`extract_owner`): "I" becomes the speaker; "Priya will..." matches a known speaker's full name ("Priya Nair"); "Priya, can you..." addresses Priya; "we / someone" means *Unassigned*; "he / she / they" cannot be resolved. Each result carries a confidence (0.95 for a known person down to 0.4 for a pronoun).
- **Deadline** (`dates.py`): finds expressions such as "by Monday", "next Friday at 3 PM", "end of the month", "in two weeks", "25th October" and converts them **relative to the meeting date**.
- **Event** (`extract_event`): a meeting-type word (call, demo, review, sync, workshop...) plus an exact date becomes a calendar event with an optional time.

KEY IDEA · DATES ARE COMPUTED BY CODE, NEVER BY AN LLM

The date resolver is deterministic and unit-tested. Vague phrases ("next week", "soon") keep their text but receive **no calendar date**; the deadline shows *Not specified*. Ambiguous numeric dates such as `03/04` are never guessed.

ASSUMPTION · DATE CONVENTIONS

Assumption: relative dates are measured from the **meeting date**, "Monday" means the next Monday strictly after it, and "next Monday" means the Monday of the following calendar week; "end of the week" means Friday. **Why:** a meeting held on Wednesday that says "by Monday" means the coming Monday. Calendar weeks start on Monday in most workplaces. **Effect:** if a team uses different conventions, the rules live in one file (`core/dates.py`).

9 The confidence gateway

The checkpoint between classical NLP and the LLM. Four questions, asked in order.




Figure 33 · *Confidence gateway*

Question	Compared	Default
Q1 Is the score high enough?	fused score (after hedge penalty)	at least 0.80
Q2 Is it clearly ahead of the other labels?	margin	at least 0.15
Q3 Is the owner reliable? (tasks)	owner confidence	at least 0.85

Question	Compared	Default
Q4 Is the deadline trustworthy? (tasks)	not from the neighbouring sentence; exact-date confidence	at least 0.85

Failing is not rejecting. It means "not sure". Then:

- **LLM configured:** the sentence and its context go to **one batched call**. If the LLM says task or decision it is kept (method *LLM fallback*, confidence at least 0.85) and validated; if it says "neither" the sentence is dropped.
- **No LLM:** an item with score of at least 0.55 is kept and marked **Needs review**; below that it is not added to the tracker. Either way the decision is logged.

Every decision is stored with a **reason code** (`CLASSICAL_ACCEPTED`, `LOW_CLASSIFICATION_CONFIDENCE`, `LOW_CLASS_MARGIN`, `OWNER_UNCERTAIN`, `DEADLINE_FROM_NEIGHBOUR`, `HEDGED_LANGUAGE`, `LLM_CONFIRMED`, `LLM_REJECTED`, `MISSING_EVIDENCE`, ...) and a readable message. Thresholds are editable in Settings and explored with the NLP Lab's *Threshold simulator*.

Worked examples

Sentence	Score	Owner	Date	Result
"Priya will send the project report by Monday."	0.98	0.95	0.95	accepted, no LLM
"Please book the conference room."	0.87	0.50	-	`OWNER_UNCERTAIN` -> LLM; else *Unassigned*
"Maybe we should consider hiring another developer."	low (hedged)	-	-	not a task
"We need to fix the login bug soon."	0.85	0.90 ("we" = nobody)	0.60 (vague)	accepted; owner *Unassigned*, deadline *Not specified*

ASSUMPTION · THRESHOLD VALUES 0.80 / 0.15 / 0.85 / 0.85

Assumption: these are sensible *starting* values, not measured optima. **Why:** a wrong owner or date does more harm than a wrong label, so owner and deadline are held to a higher bar (0.85) than classification (0.80). The 0.15 margin is a common convention for "clearly ahead". Raw Naive Bayes probabilities are often over-confident, so the rules half of the fusion keeps scores honest. **Effect:** all four are sliders in Settings. A vague deadline deliberately does **not** fail the gateway, because an LLM cannot invent a date that was never said.

10 The LLM layer and the validation layer

Free models do the language work; code checks everything they say.




Figure 34 · *The free-LLM router*

10.1 A router over free LLMs

`llm.py` speaks the OpenAI-compatible API of **Groq**, **Gemini** and **OpenRouter** using plain HTTPS. Providers are tried in order; a rate limit puts a provider on a 45-second cool-down and the next one is tried; for very long transcripts Gemini (large context window) goes first; if a free model has been retired, the router asks the provider for its current model list and picks a replacement. Malformed JSON gets one automatic repair attempt.

ASSUMPTION · FREE-TIER MODEL NAMES WILL CHANGE

Why: free model catalogues are renamed or retired frequently. Instead of hard-coding one name the router carries defaults, allows overrides through secrets (`GROQ_MODEL`, `GEMINI_MODEL`, …) and can discover a working model on its own.

10.2 What the LLM is asked to do

Call	Purpose
Analysis (per chunk of transcript)	Summary, key points, topics, conclusions, plus independent task / decision / event suggestions
Merge (long meetings)	Combine chunk summaries into one
Adjudication (one batch)	"Is each uncertain sentence a task, a decision or neither?"
Answer	Grounded chat and search answers
Naming, polishing (optional)	Speaker-name evidence, friendlier follow-up wording

The prompts demand **verbatim quotes** and **copied date phrases** instead of computed dates, and ask for JSON so that results can be validated mechanically.

10.3 Validation: never trust an LLM blindly




Figure 35 · *Validation layer*

- **Quote check.** Each task, decision and event must include an exact quote; fuzzy matching finds it in the transcript or the item is dropped (`MISSING_EVIDENCE`).
- **Owner check.** The owner must be a participant or appear in the transcript; otherwise *Unassigned* and a review flag.
- **Date check.** Our own resolver converts the copied phrase, and the phrase must occur near the quote.
- **Agreement.** An item found by both classical NLP and the LLM is marked *NLP + LLM agree* (confidence 0.95). Different owners produce `CONFLICTING_EXTRACTIONS` and a review flag.

ASSUMPTION · FUZZY-MATCH TOLERANCE FOR QUOTES

Assumption: a quote matching at 82 % (or 92 % for an immediate accept) of its characters counts as "found". **Why:** models sometimes drop punctuation or a filler word from an otherwise exact quote; demanding 100 % would reject genuine items, while accepting much less would allow paraphrases.

11

Search and the chatbot

Find the evidence first, answer only from it, then verify the answer.




Figure 36 · *Retrieval-augmented answers*

Indexing. The transcript is cut into chunks of about 110 words, each embedded by MiniLM and stored in a **ChromaDB** collection (cosine distance). Decisions and tasks are indexed too. SQLite is the source of truth - ChromaDB can always be rebuilt from it.

The query router (`route_query`) reads the question and chooses which sources matter:



Figure 37 · *How a question is routed*

Hybrid search. Semantic search (meaning) and SQLite FTS5 keyword search (words, with stemming) each return a ranked list; **Reciprocal Rank Fusion** (`1 / (60 + rank)`) merges them so that passages ranking well in both rise to the top.

Relevance gate. If nothing is relevant (similarity of at least 0.28, or at least half of the question's content words appear in the text) the answer is "not found" and **no LLM is called**.

Answering. The best evidence is labelled `[E1]`, `[T2]`, `[D1]` … and given to the LLM with strict rules: answer only from this, cite it, say what is missing. Afterwards the code verifies that cited ids exist, measures how much of the answer is supported by the cited text, and warns about numbers that are not in the evidence. Without an LLM the same evidence is shown directly (a "direct retrieval" answer). Questions, answers, sources and routing details are saved in the chat history.

ASSUMPTION · CHUNK SIZE ~110 WORDS, SIMILARITY FLOOR 0.28, RRF CONSTANT 60

Why: meeting speech is short-turn; about 110 words keeps a chunk on one topic. 0.28 was calibrated by comparing cosine scores of relevant and unrelated queries on the sample meetings (relevant: roughly 0.28 - 0.65; unrelated: below about 0.2). 60 is the standard constant in the original RRF paper. **Effect:** the floor is a slider in Settings. Near-miss wording ("stock market crash" vs "checkout crash") can still pass the floor; the LLM then answers "not found" because the evidence does not support the question.

12 Minutes, calendar, follow-ups and e-mail

Everything that leaves the application waits for your confirmation.



Figure 38 · *From insights to action*

- **Minutes** (`mom.py`) are generated *on demand* from saved data: details, attendees, agenda, summary, highlights, decisions, action items, events and conclusions. Uncertain rows carry a warning mark. The editor accepts Markdown; **Accept** unlocks e-mailing; exports are Word, PDF and Markdown, produced by our own renderer (python-docx and ReportLab).
- **E-mail** (`mailer.py`) uses SMTP (Gmail app password, Outlook, Yahoo, Brevo ...). Addresses are validated, a preview is shown, a confirmation tick is required, and attachments (Word and/or PDF) are chosen by the user. A "Connect your e-mail" panel appears wherever sending is needed and SMTP is not configured; if sending is impossible a `mailto:` link is offered.
- **Calendar** (`views/calendar.py`, `ics.py`) merges events and task deadlines. Items can be exported as `.ics` or added through a Google Calendar link - the user confirms by clicking.
- **Follow-ups** (`followups.py`) are drafted from decisions, pending tasks per person, unowned tasks and upcoming events. They are never sent automatically.

DESIGN DECISION · CALENDAR THROUGH LINKS AND .ICS FILES, NOT OAUTH

Creating events directly in Google Calendar needs an OAuth sign-in flow, a verified app and stored tokens - heavy for a free single-process deployment, and a security burden. A pre-filled "Add to Google Calendar" link and a standards-compliant `.ics` file achieve the same result with no permissions, work with Outlook and Apple Calendar too, and keep the user in control.

ASSUMPTION · MINUTES ARE GENERATED ONLY ON REQUEST

Why: the brief asked for minutes the user can review before sharing. Generating them automatically for every meeting would create drafts nobody asked for. The draft is built from stored, already-validated data, so it needs no extra LLM call.

13

Data model and storage

SQLite is the source of truth; ChromaDB holds only vectors and can be rebuilt at any time.




Figure 39 · *Data model*

SQLite (`data/meetingai.db`) holds every durable fact: meetings, transcript segments (plus the `segments_fts` keyword index), summaries, decisions, tasks, events, minutes, chat sessions and messages, follow-ups, the gateway log (`analysis_log`), the e-mail log, settings and **voiceprints**. ChromaDB (`data/chroma/`) holds only vectors, and uploaded recordings live in `data/uploads/`.

DESIGN DECISION · SQLITE PLUS CHROMADB INSTEAD OF A HOSTED DATABASE

The project deliberately avoids a database server (no PostgreSQL, no Supabase): SQLite is a file, ships with Python and supports full-text search through FTS5; ChromaDB runs inside the app for semantic search. The two are complementary - exact lookups and keywords in SQLite, meaning in ChromaDB.

ASSUMPTION · TEMPORARY STORAGE ON FREE HOSTING

Assumption: users accept that free hosting may reset the disk. **Why:** a persistent database would require a paid or externally managed service. **Effect: Settings → Data & backup** creates a zip (database, vectors, recordings) that can be restored later. Locally, data simply persists.

14 User-interface design

A dedicated AI-product look instead of a default dashboard.

- **Palette:** deep navy (`#060A19`) background with violet (`#8B5CF6`) to blue (`#3B82F6`) gradients, glass-style cards, and green / amber / red reserved for status.
- **Typography:** Sora for headings, Inter for text, JetBrains Mono for timestamps; Material Symbols icons.
- **Components** (`ui/components.py`): metric cards, status chips, speaker avatars, the transcript viewer, a month grid, steppers, empty states.
- **Behaviour:** smooth fade-ins, an animated hero, loading steppers and spinners, toast messages, helpful empty states, responsive columns, and a sidebar that collapses after navigation on phones.
- **Consistency:** every page uses the same header, section titles, cards and buttons, so the product feels like one application.

DESIGN DECISION · CUSTOM CSS INSIDE STREAMLIT

Streamlit's default look is plain, so about 240 lines of CSS restyle the sidebar, buttons, inputs, tabs, chat bubbles and tables. Cards and chips are small HTML builders (`H()` strips indentation so that Markdown never turns HTML into a code block, and every piece of user text is escaped with `esc()`).

15 Technology stack and why each piece was chose

Everything is free to use; each choice solves a specific constraint.




Figure 40 · *Technology stack*

Job	Technology	Why
Interface	**Streamlit** + custom CSS	One language (Python), fast to build, free hosting
Charts	Plotly	Interactive and themeable
Structured data	**SQLite**	A full database in one file; nothing to install or pay for
Keyword search	**SQLite FTS5** (porter stemming)	Built in and fast
Semantic search	**ChromaDB** + **ONNX MiniLM**	Local vector database; a small model without PyTorch fits free hosting
Classical NLP	**scikit-learn**, regular expressions, **rapidfuzz**	Fast, offline, explainable, produces confidence
Dates	Custom resolver (`dates.py`)	Deterministic and testable; never hallucinates
Speech-to-text	**Whisper** via Groq (or local)	Best open ASR; Groq's free tier is fast
Speakers	**pyannote** (pyannoteAI hosted or local); AssemblyAI as alternative	Leading diarization toolkit; the hosted API fits free hosting and recognises voices
LLMs	**Groq (Llama)**, **Gemini**, **OpenRouter free models**	All free tiers; automatic fallback when one is limited
Audio	**FFmpeg**	The standard tool
Documents	**python-docx**, **ReportLab**	Pure Python, no Office installation needed
E-mail	**SMTP**	Works with any provider
Deployment	**Streamlit Community Cloud** + GitHub	Free, redeploys on every push

16 Assumptions and design decisions - consolidate

Every place where the project chose a value or a rule instead of measuring it, with the reason.

The callout boxes in earlier sections explain assumptions in context. This table gathers them in one place so that a reader can see at a glance **what was assumed, why, and how to change it**.

#	Assumption / decision	Why it was made	How to change it
1	One shared workspace, no user accounts	Accounts need auth and a hosted database; not possible on free single-process hosting	Optional `APP_PASSWORD`; accounts are future work
2	Classifier trained on 610 template-generated sentences	No public dataset has action / owner / deadline labels	Edit `core/seed_data.py` or add real annotated sentences
3	Train at start-up, store no model file	Takes about 1 s; avoids stale or untrusted pickle files	n/a
4	Rules and Naive Bayes fused 50 / 50; hedge factor 0.8; floor 0.33	Neither expert is clearly better; values chosen by inspection	Constants in `core/nlp.py`
5	Gateway thresholds 0.80 / 0.15 / 0.85 / 0.85	Starting values; owner and date errors are costlier than label errors	Settings sliders + NLP Lab simulator
6	Vague deadlines do not trigger the LLM	An LLM cannot invent a date that was never spoken	n/a (by design)
7	Dates relative to the **meeting date**; weekday and week rules as in section 8	Matches how people speak in a meeting	`core/dates.py`
8	Dates are never produced by an LLM	Prevents hallucinated calendar entries	n/a (by design)
9	Unknown owner = *Unassigned*, unknown date = *Not specified*	Honesty requirement of the brief	n/a (by design)
10	Audio converted to 32 kbps mono, 10-minute chunks	Free API upload limits (about 25 MB)	`CHUNK_SECONDS` in `core/stt.py`
11	Hosted pyannote for deployment	PyTorch does not fit the free tier; the hosted API also offers voiceprints	`HF_TOKEN` + `requirements-local.txt` for local pyannote
12	Voice-match strictness 60 / 100	pyannoteAI recommends 50-70	Settings → Voices
13	Name-suggestion evidence weights (3.0 / 1.2 / 0.9)	Self-introduction is stronger than being addressed or thanked	`core/speakers.py`
14	Word midpoint decides the speaker of a word	Simple and robust against small timing offsets	`assign_speakers` in `core/diarize.py`
15	MiniLM ONNX embeddings, ~110-word chunks, similarity floor 0.28, RRF constant 60	Small, CPU-friendly, calibrated on sample queries	`EMBEDDING_BACKEND`, Settings slider
16	LLM quotes must match the transcript at 82 % or better	Tolerates punctuation / filler differences, rejects paraphrase	`verify_quote` in `core/pipeline.py`

#	Assumption / decision	Why it was made	How to change it
17	Free-model names will change	Free catalogues are renamed often	Secrets overrides + automatic model discovery
18	Processing is synchronous	Free hosting has one process, no worker queue	n/a
19	Calendar through links and `.ics`, not OAuth	No stored tokens, works with any calendar	n/a
20	Minutes generated only on request	The user reviews before anything is shared	n/a
21	Temporary disk on free hosting	A persistent database would be a paid service	Backup / restore in Settings
22	English-language focus	Models, cue patterns and seed sentences are English	New cue patterns and seed data per language
23	Sample meetings use dates relative to *today*	The calendar and tracker always show upcoming and overdue items	`core/demo.py`

NOTE · READING THE TABLE HONESTLY

None of these values claims to be an optimum. They are documented so that they can be challenged, measured and replaced - and the NLP Lab, the gateway log and the Settings sliders exist to make that easy.

17 Security, privacy and honesty by design

Keys stay out of the code, users stay in control, and the system never pretends to know.

- **Keys** are never written to the database or the repository: Streamlit secrets, environment variables, or typed into Settings (kept for the browser session only).
- **Password gate:** set `APP_PASSWORD` to protect a public deployment; the comparison is constant-time.
- **Confirmation before side effects:** e-mails and follow-ups are sent only after an explicit tick or click; calendar additions are links the user clicks.
- **Untrusted content:** transcripts and LLM output are treated as data - they cannot trigger actions, and LLM output must pass validation.
- **What leaves the machine** (only when configured): audio to Groq and pyannoteAI (or AssemblyAI); transcript text to Groq / Gemini / OpenRouter. A switch on the upload page turns LLM use off per meeting.
- **Voiceprints** stay in your own database; create them only for people who agreed, and delete them at any time.
- **Honesty:** unknown owners show *Unassigned*, unknown dates *Not specified*, unanswerable questions *not found*, uncertain items *Needs review*.
- **Safe file handling:** restore archives are checked against path traversal; uploaded files get generated names.

18 Deployment

Free hosting on Streamlit Community Cloud, straight from GitHub.




Figure 41 · *Deployment architecture*

Live application	https://gd4n8x8sjkkxmdhfptkc9m.streamlit.app/
Source repository	https://github.com/nidhitiwari23/Meeting-AI-
Hosting	Streamlit Community Cloud (free)

Deployment steps

1. Push the code to GitHub (`git push origin main`).
2. In Streamlit Cloud choose the repository, branch `main` and file `app.py`; pick Python 3.11 or 3.12.
3. Streamlit installs `requirements.txt` (Python packages) and `packages.txt` (FFmpeg).

4 Paste the API keys into the app's **Secrets** box (`GROQ_API_KEY`, `GEMINI_API_KEY`, `PYANNOTEAI_API_KEY`, `SMTP_*`, `APP_PASSWORD`).

5 Every later `git push` redeploys automatically.

Facts about the free tier that shaped the design: about 1 GB of memory (hence ONNX instead of PyTorch), the app sleeps when idle, and the disk is temporary (hence backup and restore). Alternatives: Hugging Face Spaces (more memory), Render, Google Cloud Run, or running locally.

19 Source-code map

One line per file. The Code Walkthrough document explains every file in depth.

Entry point and configuration

File	What it does
`app.py`	Page setup, optional password gate, sidebar, loads the selected page
`requirements.txt` / `packages.txt`	Python packages / system packages (FFmpeg) for deployment
`requirements-local.txt`	Optional: local pyannote.audio (PyTorch)
`.streamlit/config.toml`, `secrets.toml.example`	Dark theme and upload limit / template for API keys

`core/` - application logic

File	What it does
`config.py`	Paths, defaults, secret lookup (session, secrets, environment)
`db.py`	All SQLite tables and every read / write function, FTS5 search
`parsing.py`	Reads txt / vtt / srt / docx / pdf into speaker segments
`stt.py`	FFmpeg conversion, Whisper (Groq / local), AssemblyAI, merging, orchestration
`diarize.py`	pyannote (hosted / local), voiceprints, word-to-speaker alignment
`speakers.py`	Name suggestions for anonymous voices, applying names
`dates.py`	Finds and converts date and time expressions
`seed_data.py`	Training and test sentences for the classifier
`nlp.py`	Sentences, rules, Naive Bayes, owner / deadline / event extraction, offline summary
`gateway.py`	The confidence gateway and reason codes
`llm.py`	Free-LLM router with fallback and model discovery
`llm_tasks.py`	Prompts and parsers for everything the LLM does
`pipeline.py`	Orchestrates analysis, validation, merging and saving
`rag.py`	ChromaDB index, hybrid search, query router, grounded answers
`mom.py`	Minutes generation and Markdown / HTML / Word / PDF rendering
`mailer.py`	SMTP sending, address validation, `mailto:` links

File	What it does
ics.py	Calendar files and Google Calendar links
followups.py	Drafts follow-up messages and reminders
demo.py	Three sample meetings

ui/ and views/ - the interface

File	What it does
ui/theme.py	All CSS (colours, cards, animations, responsive rules)
ui/components.py	Reusable HTML: cards, chips, transcript viewer, calendar grid
ui/charts.py, ui/nav.py	Themed Plotly charts; navigation helpers
views/dashboard.py … views/settings.py	One file per page: dashboard, upload, library, meeting, chat, search, tracker, calendar, mom, followups, nlplab, settings
views/_tasks.py, _speakers.py, _email.py	Shared panels: editable task table, *Who is who?*, *Connect e-mail*

20 Glossary

Plain-language definitions of the terms used in this report.

Term	Meaning
Action item	A task someone agreed to do
ASR	Automatic speech recognition - turning audio into text
Chunk	A short piece of transcript stored for searching
Confidence	A number from 0 to 1 showing how sure a model is
Diarization	Working out who spoke when
Embedding	A list of numbers representing the meaning of a text
FTS5	SQLite's built-in full-text search
Gateway	The checkpoint deciding whether classical NLP is trusted or the LLM must double-check
Hallucination	Confident but false AI output
LLM	Large language model (Llama, Gemini)
Margin	The gap between the best and second-best guess
MoM	Minutes of Meeting
Naive Bayes	A simple probability-based classifier
NLP	Natural language processing
RAG	Retrieval-augmented generation: find relevant text first, then answer only from it
RRF	Reciprocal rank fusion, a way of merging two ranked lists

Term	Meaning
TF-IDF	A score of how important a word is in a text compared with all others
Voiceprint	A compact numeric fingerprint of a voice
Whisper	OpenAI's open speech-recognition model