Ex.No.7	Write a code using RAW sockets to implement packet sniffing.
DATE:	

AIM:

To develop a Python program using raw sockets that captures Ethernet frames and extracts the source and destination MAC addresses and protocol details for network analysis and troubleshooting.

Definition:

Packet sniffing is the technique of capturing and examining network packets transmitted over a network to monitor communication, troubleshoot network issues, and analyze network traffic.

Algorithm:

1. Start.
2. Import the required modules.
3. Get the local host IP address.
4. Create and bind a raw socket.
5. Enable IP header inclusion and promiscuous mode.
6. Set the packet count to **5**.
7. Receive one packet at a time.
8. Extract and display:

Destination MAC address

Source MAC address

Protocol type

Packet length

9. Repeat until **5 packets** are captured.
10. Disable promiscuous mode.
11. Display the completion message.
12. Stop.

PROGRAM:

```
import socket
import struct


def get_mac_addr(bytes_addr):
    """Convert MAC address from bytes to readable format."""
    return ':'.join('{:02X}'.format(b) for b in bytes_addr)


def get_protocol(bytes_proto):
    """Convert protocol bytes to hexadecimal."""
    return hex(struct.unpack('!H', bytes_proto)[0])


def ethernet_frame(data):
    """Extract Ethernet frame information."""
    dest_mac, src_mac, proto = struct.unpack('!6s6s2s', data[:14])
    return (
        get_mac_addr(dest_mac),
        get_mac_addr(src_mac),
        get_protocol(proto),
        data[14:]
    )
def main():
    host = socket.gethostbyname(socket.gethostname())
    print("Listening on:", host)
    try:
        # Create raw socket
        conn = socket.socket(socket.AF_INET,
                             socket.SOCK_RAW,
```

```
            socket.IPPROTO_IP)

# Bind socket
conn.bind((host, 0))

# Include IP header
conn.setsockopt(socket.IPPROTO_IP,
            socket.IP_HDRINCL,
            1)

# Enable promiscuous mode
conn.ioctl(socket.SIO_RCVALL, socket.RCVALL_ON)

print("\nPacket Sniffer Started...\n")

# Capture only 5 packets
packet_count = 5

for i in range(packet_count):

   raw_data, addr = conn.recvfrom(65536)

   print(f"\nPacket {i+1}")
   print("-" * 40)

   if len(raw_data) >= 14:
      dest_mac, src_mac, eth_proto, data = ethernet_frame(raw_data)
```

```
            print("Destination MAC :", dest_mac)
            print("Source MAC      :", src_mac)
            print("Protocol        :", eth_proto)
            print("Packet Length   :", len(raw_data), "bytes")

        # Disable promiscuous mode
        conn.ioctl(socket.SIO_RCVALL, socket.RCVALL_OFF)

        print("\nPacket Sniffer Stopped Successfully.")

    except PermissionError:
        print("Run this program as Administrator.")

    except KeyboardInterrupt:
        conn.ioctl(socket.SIO_RCVALL, socket.RCVALL_OFF)
        print("\nPacket Sniffer Stopped by User.")

if __name__ == "__main__":
    main()
```

SAMPLE OUTPUT:

```
Listening on: 192.168.1.10

Packet Sniffer Started...

Packet 1
----------------------------------------
```

Destination MAC : 45:00:00:3C:1C:46

Source MAC : 40:06:B1:E6:C0:A8

Protocol : 0x101

Packet Length : 60 bytes

Packet 2

Destination MAC : 45:00:00:34:2F:9A

Source MAC : 40:11:C3:D8:C0:A8

Protocol : 0x101

Packet Length : 52 bytes

Packet 3

Destination MAC : 45:00:00:54:3B:8F

Source MAC : 40:06:91:AB:C0:A8

Protocol : 0x101

Packet Length : 84 bytes

Packet 4

Destination MAC : 45:00:00:28:5D:71

Source MAC : 40:01:6F:12:C0:A8

Protocol : 0x101

Packet Length : 40 bytes

Packet 5

Destination MAC : 45:00:00:3C:7A:15

Source MAC : 40:06:5A:9F:C0:A8

Protocol : 0x101

Packet Length : 60 bytes

Packet Sniffer Stopped Successfully.

OUTPUT:

```
Listening on: 192.168.56.1

Packet Sniffer Started...


Packet 1
----------------------------------------
Destination MAC : 45:00:00:A5:68:82
Source MAC      : 00:00:04:11:65:22
Protocol        : 0xc0a8
Packet Length   : 165 bytes

Packet 2
----------------------------------------
Destination MAC : 45:00:00:A5:68:82
Source MAC      : 00:00:04:11:65:22
Protocol        : 0xc0a8
Packet Length   : 165 bytes

Packet 3
----------------------------------------
Destination MAC : 45:00:00:A5:68:83
Source MAC      : 00:00:04:11:65:21
Protocol        : 0xc0a8
Packet Length   : 165 bytes

Packet 4
----------------------------------------
Destination MAC : 45:00:00:A5:68:83
Source MAC      : 00:00:04:11:65:21
Protocol        : 0xc0a8
Packet Length   : 165 bytes

Packet 5
----------------------------------------
Destination MAC : 45:00:00:A5:68:84
Source MAC      : 00:00:04:11:65:20
Protocol        : 0xc0a8
Packet Length   : 165 bytes

Packet Sniffer Stopped Successfully.
>>>
```

RESULT:

To write a code using Raw Socket to implement Packet Sniffing is verified.