Temasek Polytechnic School of Informatics & IT

Introduction to Security Incident Response & Management

(Security Incident Investigation in a SOC Environment with IBM Security QRadar SIEM)

IBM Security QRadar SIEM
Hands-on Lab Exercises

IBM Security QRadar SIEM Hands-on Lab Exercises

	Hands-on Lab Exercises		
Investigating an offense that is triggered by events exercise	1. Investigating the Local DNS scanner offense	5	
Investigating the events of an offense exercises	 Looking for events that contribute to an offense Saving search criteria and search results Investigating event details 	10 13 15	
Investigating an offense that is triggered by flows exercise	5. Investigating an offense that is triggered by flows	19	




Investigating an offense that is triggered by events exercises

Exercise 1 Investigating the local DNS scanner offense

To investigate an offense triggered by events, this exercise looks at the offense named **Local DNS Scanner containing Invalid DNS**. Perform the following steps:

- In the QRadar SIEM console, double-click the **Offenses** tab.
 The All Offenses page opens.
- Select the offense with the description Local DNS Scanner containing Invalid DNS.
 - a. If you do not see the **Local DNS Scanner containing Invalid DNS** offense, search for the offense. From the **Search** list, select **New Search**.



b. On the Search Parameters pane, define the search criteria. In the **Description** field, type Local DNS Scanner.






Note: The description search criteria is case sensitive.

c. Click Search.

The All Offenses page shows the offense that meets the search criteria, **Local DNS** Scanner containing Invalid DNS.




- 3. Answer the following questions for the **Local DNS Scanner containing Invalid DNS** offense.
 - a. What is the offense type and offense source and magnitude?



b. What network does the offense source IP belong to?



4. Double-click the **Local DNS Scanner containing Invalid DNS** offense to view the Offense Summary page. The Offense Summary page provides detailed information about the offense.




5.	Answer the	following	questions	for this	offense.

- a. How many events or flows are associated with this offense?
- b. What time did this offense begin?
- c. Is the source IP involved in any other offenses?
- d. How many destinations IPs are targets of the offense? Are the destinations IPs local or remote devices?

© Copyright IBM Corp. 2014 Student Exercises

7


e. List the event categories that contributed to this offense. From the **Display** list on the toolbar, select **Categories** to view the event categories.



f.	What do you learn about this offense based on the annotations? From the Display list or the toolbar, select Annotations .
-	

g. What is the event name, event category, and destination port for the events listed in the Last 10 Events list? Click Summary on the toolbar and scroll down to the Last 10 Events list.

- h. The destination port is well known for what type of server communications?
- 6. Perform the following actions on this offense.
 - a. Add a note:
 - i. From the **Actions** toolbar, select **Add Note**.



- ii. Type This offense was investigated in the QRadar SIEM Foundations course.
- iii. Click Add Note.



Note: The note is displayed in the Last 5 Notes pane on the Offense Summary page. A **Notes** icon is displayed in the **Status** field on the Offense Summary page and in the flag column for the offense on the All Offenses page. Hold the mouse over the **Notes** icon to view the note.

b. Protect the offense. From the **Actions** toolbar on the Offense Summary page, select **Protect Offense**. The **Protected** icon is displayed in the **Status** field on the Offense Summary page and in the flag column for the offense on the All Offenses page.



Why do you protect an offense?




Investigating the events of an offense exercises

Exercise 1 Looking for events that contribute to an offense

In <u>Unit 4, "Investigating an offense that is triggered by events exercises," on page 5,</u> you investigated the offense by analyzing the offense summary information. In this exercise, you use the log events that are viewed in the **Log Activity** tab to further analyze the offense.

- In the QRadar SIEM console, double-click the Offenses tab.
 The All Offenses page opens.
- 2. Find and double-click the Local DNS Scanner containing invalid DNS offense.
- Show the low-level categories of the offense's events by selecting Display > Categories on the toolbar.



To investigate the events that are associated with this offense in the low-level category DNS
Protocol Anomaly, right-click the table row that shows DNS Protocol Anomaly and click
Events.




Note: Alternatively, you can select **DNS Protocol Anomaly** and click **Events** in the title bar above the table.



The List of Events page opens.

Create a filter to exclude the source IP that contributed to the Local DNS Scanner offense.
 Select an event. Right-click 10.152.247.69 and select Filter on Source IP is not 10.152.247.69.



6. What results are returned?

7. What do the results of this search indicate?

© Copyright IBM Corp. 2014 Student Exercises


11

8. To look for similar DNS requests unrelated to the offense, click **Clear Filter** for the **Offense is Local DNS Scanner** filter.



No results were returned.


- 9. What results are returned? Why?
- 10. To view events from the last 24 hours, in the **View** list, select **Last 24 Hours**.



No results were returned.

QRadar SIEM shows events of the low-level category DNS Protocol Anomaly that do not originate from the IP address 10.152.247.69, which is the source IP address of the offense triggered by DNS scanning.

11. Review the suspicious DNS requests from other sources.




Exercise 2 Saving search criteria and search results

To save the search criteria and search results for future reference, perform the following steps:

- 1. Save the current search criteria.
 - a. On the toolbar, click Save Criteria.


The Save Criteria window opens.




b. Configure the Save Criteria window as shown in the following table:

Field / Option	Setting	
Search Name	Dept - DNS Protocol Anomaly without 10.152.247.69	
Assign Search to Group(s)	CheckPoint	
Timespan options	Recent Last 24 Hours	
Include in my Quick Searches	Enable	
Set as Default	Disable	
Share with Everyone	Disable	

c. Verify that the Save Criteria settings look like the ones in the graphic.




- d. Click OK.
- 2. Save the current search results.
 - a. On the toolbar, click Save Results.




The Save Search Result window opens.

b. In the name field, type DNS Protocol Anomaly without 10.152.247.69.




- c. Click OK.
- 3. Revisit or delete your saved search results.
 - a. On the List of Events page's toolbar, click Search > Manage Search Results.



The Search Results Management page opens.

b. Select your search results and click **Delete**.



c. Close the Search Results Management page.

Exercise 3 Investigating event details

The details of an event, particularly its payload, can provide further insights. To investigate the details of an event, perform the following steps:

- 1. Find and run your saved search.
 - a. In the QRadar SIEM console, double-click the **Log Activity** tab.
 - b. On the Log Activity tab toolbar, click Quick Searches.
 - c. Select Dept DNS Protocol Anomaly without 10.152.247.69 Last 24 Hours.



Hint: If you do not see your saved search, double-click the **Log Activity** tab and click **Quick Searches** again.




d. In the search result, double-click an event.

The Event Details page opens in the Log Activity tab.

17

2. Verify with the firewall and DNS experts of your organization whether the log message that is displayed in the payload is a concern.



Note: Use Previous and Next on the Events Details toolbar to browse the events.

3. To return to the list of events, on the toolbar, click **Return to Event List**.

(This page intentionally left blank)



Investigating an offense that is triggered by flows exercises

Exercise 1 Investigating an offense that is triggered by flows

To investigate an offense that is triggered by flows, perform the following steps:

1. Generate network traffic. In the PuTTY command line, type the following command:

```
./startRdp.sh
```

- 2. In the QRadar SIEM console, click the **Network Activity** tab.
- 3. Observe the network events and verify that a network event triggers an offense.





Note: QRadar SIEM shows a red icon in the left-most column for network events that contribute to an offense.

4. To investigate the offense, click the red icon in the left-most column.




Note: There is a delay between the time the red icon is shown next to the network event and when the offense is created on the All Offenses page in the Offenses tab.



Note: Disable block pop-up windows in Firefox. On the Firefox toolbar, select **Tools > Options > Content > Disable block pop-up windows > OK**.

The Offense Summary page opens.



- 5. What is the name of the offense?
- 6. What is the offense type and offense source?
- 7. What is the destination IP?
- 8. How many events are associated with this offense?

How many flows are associated with this offense?

9. What rule contributed to this offense?



Hint: To determine which rule triggered the offense, click the **Display** list and select **Rules**.





Note: The *Policy Remote: Remote Desktop Access from the Internet* rule that triggered this offense is one of the default rules in the Enterprise tuning template. The rule evaluates Remote Desktop Access from external IP addresses to internally hosted Microsoft Windows servers.


10. To investigate the flows that contributed to the offense, click **Flows** on the Offense Summary page toolbar.



© Copyright IBM Corp. 2014 Student Exercises

21


The Flow List page opens.



- 11. Examine the flow associated with this offense. Double-click the network event listed. The Flow Details page opens.
- 12. Answer the following questions:
 - a. What is the flow direction?
 - b. What is the application name?
 - c. Based on your investigation, what behavior triggered this offense?
- 13. Tune the network event as a false positive.
 - a. On the Flow Details page's toolbar, click False Positive.



The False Positive page opens.



- b. Click Tune.
- c. Click Close.



Note: Tuning an event or flow as a false positive updates the **User-BB-FalsePositive: User Defined False Positives** building block.

- 14. Close the Flow Details page.
- 15. Close the offense.
 - a. On the **Offense** tab navigation menu, select **All Offenses**.
 - b. From the **Actions** list on the toolbar, select **Close**.
 - c. From the Reason for Closing list, select False-Positive, Tuned.
 - d. Click OK.

© Copyright IBM Corp. 2014 Student Exercises

23