

Deep Learning for Wine Quality Prediction: Neural Network Optimization and Performance Analysis

By Aaron Niecestro

Project Objective

What is Deep Learning?

- Deep Learning is a subset of machine learning that uses artificial neural networks with multiple hidden layers.
- These networks learn complex nonlinear relationships directly from data.
- Deep learning models automatically discover patterns and interactions that may be difficult to identify using traditional statistical approaches.

Goal

Develop and optimize neural network models capable of predicting wine quality from physicochemical measurements.

Objectives

- Establish a baseline neural network model.
- Evaluate the impact of feature scaling techniques.
- Compare activation functions.
- Compare neural network architectures.
- Optimize epochs, optimizers, and regularization methods.
- Identify the strongest overall model configuration.

Business Relevance

Understanding how wine chemistry influences quality can help support:

- Quality assessment
- Production consistency
- Process optimization
- Data-driven decision making

Why It Matters

Wine quality is influenced by complex interactions among acidity, alcohol, sulfur compounds, density, and other chemical properties.

Deep learning provides a powerful framework for learning these relationships and generating accurate quality predictions

Dataset Description

UCI Wine Quality Dataset

- Physicochemical measurements collected from Portuguese Vinho Verde wines.

Dataset Size

- 5,320 observations
- 11 chemistry features
- Quality scores from 3 to 9

Input Features

- Acidity measurements
- Sugar content
- Sulfur dioxide levels
- Density
- pH
- Alcohol concentration

Target Variable

- Wine Quality
- Predicted using neural networks

Interpretation

The dataset contains numerical chemistry measurements describing the physical and chemical composition of both red and white wines. These measurements serve as inputs to the neural network, while quality scores act as the prediction target.

Variable	Description	Was this Feature used for Modeling?
Fixed Acidity	Tartaric acid content	Yes
Volatile Acidity	Acetic acid concentration	Yes
Citric Acid	Citric acid level	Yes
Residual Sugar	Remaining sugar	Yes
Chlorides	Salt concentration	Yes
Free Sulfur Dioxide	SO_2 level	Yes
Total Sulfur Dioxide	Total SO_2	Yes
Density	Wine density	Yes
pH	Acidity measure	Yes
Sulphates	Sulfate concentration	Yes
Alcohol	Alcohol percentage	Yes
Quality	Wine quality score	Used for interpretation and evaluation
Type	Red or White	Used for interpretation and evaluation

Brief View of Wine Data

Variable	Mean	Range
Fixed Acidity (g/dm^3)	7.22	3.8-15.9
Volatile Acidity (g/dm^3)	0.34	0.08-1.58
Residual Sugar (g/dm^3)	5.05	0.6-65.8
Total Sulfur Dioxide (mg/dm^3)	114.11	6-440
Density (g/cm^3)	0.9945	0.987-1.039
pH	3.22	2.72-4.01
Alcohol (% Vol.)	10.55	8.0-14.9

Metric	Value
Observations	5,320
Features	11 Chemistry Variables
Wine Types	Red & White
Quality Range	3-9
Avg Alcohol	10.55%
Avg Residual Sugar	5.05 g/dm^3
Avg pH	3.22
Avg Total Sulfur Dioxide	114.11 mg/dm^3
Metric	Value

Wine Quality Distribution by Wine Type

Key Findings


- Alcohol exhibited the strongest positive relationship with wine quality.
- Volatile acidity showed a negative relationship with quality.
- Several chemistry variables demonstrated meaningful correlations with the target variable.
- Most wines were assigned quality scores between 5 and 6.


Interpretation

The observed relationships indicate that wine chemistry contains predictive information that can be leveraged by deep learning models.

Takeaway

Meaningful relationships exist between chemistry measurements and wine quality, supporting the use of neural networks for predictive modeling.





Data Preparation & Analysis Approach

Data Preparation

- Combined red and white wine datasets
- Removed duplicate observations
- Selected physicochemical predictors
- Defined wine quality as the target variable

Modeling Workflow

- Train/Test Split (80/20)
- Feature Scaling Analysis
- Activation Function Analysis
- Architecture Comparison
- Epoch Optimization
- Optimizer Benchmarking
- Regularization Analysis
- Final Model Selection

Why This Matters

- Neural networks are highly sensitive to feature scaling and architecture design.
- A structured optimization workflow helps identify the most effective model configuration.

Neural Networks Explained

What Is a Neural Network?

- A machine learning model inspired by biological neurons.
- Learns relationships between input features and target outcomes.
- Uses hidden layers to capture nonlinear patterns.

Why Use Deep Learning?

- Captures complex feature interactions.
- Learns nonlinear relationships.
- Adapts well to regression problems.

Evaluation Metrics

- MAE (Mean Absolute Error)
- RMSE (Root Mean Squared Error)
- Adjusted R^2
- Learning Curves
  - Training Loss
  - Validation Loss

Key Question

- Which neural network configuration produces the strongest wine quality predictions?

Learning Curve Comparison

Objective

- Evaluate how different activation functions influence neural network convergence, training stability, and generalization.

Why Analyze Learning Curves?

- Assess convergence speed
- Assess training stability
- Detect underfitting
- Detect overfitting
- Compare optimization behavior

Why It Matters

- Final metrics show model accuracy, but learning curves reveal how efficiently and reliably the model reaches that performance.

Baseline Neural Network Model

Baseline Architecture	Purpose	Evaluation	Graphs
• Input Layer (11 Features) • Hidden Layer: 16 Neurons • ReLU Activation • Adam Optimizer • Output Layer (Wine Quality)	• Establish an initial performance benchmark. • Measure improvements from later optimization steps.	• MAE • RMSE • Adjusted R^2 • Training Time	✅ Neural Network Architecture Diagram ✅ Training Loss Curve

Initial Model Performance

Key Findings

- The baseline model successfully learned relationships between wine chemistry and quality.
- Predictive accuracy remained moderate.
- Additional optimization was expected to improve performance.
- Results established a benchmark for future comparisons.

Interpretation

- While the baseline neural network demonstrated predictive capability, there was substantial opportunity for improvement through feature scaling, activation-function selection, architecture optimization, and training strategy refinement.

Metric	Baseline Model
MAE	0.5660
RMSE	0.7365
Adjusted R^2	0.2924
Training Time	(your value)

Feature Scaling Comparison

Objective	No Scaling	StandardScaler	MinMaxScaler	Why Compare?
Determine how feature scaling influences neural network performance, convergence behavior, and predictive accuracy.	• Uses raw feature values. • Preserves original measurement units. • Serves as the baseline preprocessing approach.	• Centers data around a mean of zero. • Scales features using standard deviation. • Commonly used with neural networks.	• Scales all features into the range of 0 to 1. • Preserves relative relationships between observations. • Frequently used when features have very different ranges.	Neural networks use gradient-based optimization. Large differences in feature magnitudes can negatively affect learning efficiency, convergence speed, and overall model performance.

Feature Scaling Comparison Plots

Interpretation and finding

Learning Cruve Graph

- Small workflow diagram showing:
  - Raw Features
  - No Scaling
  - StandardScaler
  - MinMaxScaler

Feature Scaling Comparison Plots

Findings

- StandardScaler achieved the lowest RMSE and strongest Adjusted R^2.
- MinMaxScaler improved performance relative to unscaled data.
- No Scaling consistently produced the weakest results.
- Proper scaling improved optimization efficiency and predictive accuracy.

Interpretation

The results demonstrate that preprocessing plays a significant role in neural network performance. StandardScaler produced more stable feature distributions which improved convergence and model effectiveness.

Graphs

✅ RMSE Comparison
✅ MAE Comparison
✅ Adjusted R^2 Comparison
✅ Performance Summary Table

Feature Scaling Conclusion

Conclusion

- StandardScaler was selected for all subsequent analyses and became the foundation for the optimized deep learning pipeline.

Key Insights

- Scaling was one of the largest contributors to performance improvement.
- Standardization improved both accuracy and model stability.
- Neural networks benefited from features having consistent magnitudes.

Takeaway

Feature engineering and preprocessing decisions can influence performance as much as architectural decisions.

Activation Functions

What Is an Activation Function?

Activation functions introduce nonlinearity into neural networks, allowing them to learn complex relationships between inputs and outputs.

ReLU

- Fast computation
- Strong gradient propagation
- Most common deep learning activation

Sigmoid

- Produces outputs between 0 and 1
- Historically important in neural networks
- Can suffer from vanishing gradients

Tanh

- Produces outputs between -1 and 1
- Stronger gradients than Sigmoid
- Often provides smoother learning dynamics

Why Are They Important?

Without activation functions, neural networks would behave like simple linear models and lose much of their predictive power.

Activation Function Comparison

Objective	Why Compare?	Evaluation Metrics	Key Question
Determine which activation function provides the strongest predictive performance and training behavior.	Activation functions influence: • Convergence speed • Stability • Predictive accuracy • Generalization performance	• MAE • RMSE • Adjusted R^2 • Learning Curves • Training Loss • Validation Loss	Which activation function is most effective for wine quality prediction?

Activation Function Results

Findings

ReLU

- Fastest convergence.
- Strong overall performance.
- Efficient optimization.

Sigmoid

- Slower convergence.
- Produced the strongest overall predictive performance in later analyses.
- Demonstrated consistent learning behavior.

Tanh

- Balanced convergence and stability.
- Competitive performance but did not outperform the best configuration.

Interpretation

Although ReLU converged more rapidly, Sigmoid ultimately produced the strongest predictive metrics when combined with the optimized architecture and preprocessing workflow.

Conclusion

Activation-function selection significantly influenced neural network behavior and predictive performance. Sigmoid was retained for subsequent optimization analyses because it produced the strongest overall results. (Adjust if your final metrics say otherwise.)

This should be one of the strongest interpretation slides.

Graphs

✅ Activation Comparison Bar Charts

✅ Combined Results Table

Architecture Comparison

Objective	Why Compare Architectures?	Key Question	Graph
• Evaluate how network depth and complexity influence predictive performance.	• The number of hidden layers and neurons determines a model's capacity to learn complex relationships.	• How much network complexity is necessary to accurately model wine quality?	• ✅ Neural network diagrams for Models A-D. • This will look much more professional than text alone.

Architectures Evaluated

Evaluation Goal

Identify the architecture that achieves the strongest balance between:

- Accuracy
- Generalization
- Training efficiency
- Model complexity

Model A: 16

Model B: 32 → 16

Model C: 64 → 32 → 16

Model D: 128 → 64 → 32 → 16

Why These Architectures?

The architectures were intentionally designed with increasing complexity to evaluate whether additional layers and neurons improve predictive performance.

Architecture Comparison Results

Findings

(Use actual values)

For example:

- Model C achieved the strongest overall predictive performance.
- Increasing complexity beyond Model C provided little benefit.
- Model D produced longer training times with minimal improvement.
- Shallow architectures underperformed deeper configurations.

Interpretation

The results suggest that increasing network depth improves predictive capability up to a point, after which additional complexity generates diminishing returns.

Conclusion

Model C (64 → 32 → 16) provided the strongest balance between predictive performance, model complexity, and computational efficiency.

Graphs

✅ RMSE Comparison

✅ MAE Comparison

✅ Adjusted R^2 Comparison

✅ Architecture Results Table

Epoch Optimization

Objective

Determine the optimal number of training epochs that maximizes predictive performance while maintaining strong model generalization.

What Is an Epoch?

One complete pass through the entire training dataset.

During each epoch, the neural network updates its weights to minimize prediction error.

Too few epochs may lead to underfitting.

Too many epochs may increase the risk of overfitting.

Epochs Evaluated

25

50

75

100

125

150

175

200

Why Compare?

Training duration directly influences:

Model accuracy

Convergence behavior

Generalization performance

Computational cost

Key Question

What number of epochs provides the strongest balance between predictive accuracy and training efficiency?

Epoch Study Results

Findings

- Performance improved steadily between 25 and 125 epochs.
- The strongest predictive performance occurred at 125 epochs.
- Additional training beyond 125 epochs failed to improve accuracy.
- Validation loss began increasing after 125 epochs, suggesting diminishing returns.
- Longer training times produced minimal practical benefit.

Interpretation

- Training for additional epochs initially allowed the model to learn increasingly complex relationships within the wine chemistry data. However, after 125 epochs, performance gains plateaued and validation behavior suggested that additional learning no longer improved generalization.

Conclusion

- 125 epochs provided the strongest balance between predictive performance, computational efficiency, and model generalization.

Optimizer Benchmarking

Objective

- Determine which optimization algorithm produces the strongest predictive performance while holding all other components constant.

SGD (Stochastic Gradient Descent)

- Traditional optimization method
- Simpler update mechanism
- Often requires additional tuning

RMSProp

- Adaptive learning-rate optimizer
- Designed for faster convergence
- Well-suited for neural networks

Adam

- Combines momentum and adaptive learning rates
- Widely used deep-learning optimizer
- Strong baseline performer

Why Optimizers Matter

- Optimizers control how neural network weights are updated during training.
- The choice of optimizer directly affects:
  - Convergence speed
  - Stability
  - Computational efficiency
  - Final model accuracy

Optimizer Benchmarking Results

Findings

- RMSProp achieved the lowest RMSE and highest Adjusted R^2.
- Adam delivered highly competitive performance but did not surpass RMSProp.
- SGD substantially underperformed the adaptive optimizers.
- Adaptive optimization methods proved more effective for this regression task.

Interpretation

Optimizer selection had a meaningful effect on predictive performance. Adaptive methods consistently learned more efficiently than traditional gradient descent and achieved stronger final prediction accuracy.

Conclusion

RMSProp produced the strongest overall predictive performance and was selected for subsequent analyses.

Graphs

✅ RMSE Comparison

✅ MAE Comparison

✅ Adjusted R^2 Comparison

✅ Optimizer Results Table

Regularization and Generalization

Objective	Baseline	L1 Regularization	L2 Regularization	Dropout	Early Stopping	Why Regularization Matters
Evaluate the impact of regularization techniques on predictive accuracy, model robustness, and generalization performance.	No regularization	Penalizes absolute weight values Encourages sparse models	Penalizes large weights Helps prevent excessive model complexity	Randomly disables neurons during training Forces the network to learn more robust representations	Terminates training when validation performance stops improving	Neural networks may memorize training data instead of learning general patterns. Regularization helps: Reduce overfitting Improve generalization Increase model robustness Stabilize training

Regularization and Generalization Results

Findings

- The baseline model achieved the strongest overall predictive performance.
- Early Stopping produced highly competitive results while maintaining strong generalization.
- Dropout provided moderate regularization benefits but did not improve predictive accuracy.
- L2 regularization reduced predictive performance relative to the baseline model.
- L1 regularization substantially degraded predictive performance.

Interpretation

- The optimized neural network already generalized effectively and showed minimal evidence of overfitting. Consequently, additional regularization introduced unnecessary constraints that reduced predictive capability.

Winner

- **Baseline (No Regularization)**

Conclusion

- Additional regularization provided little benefit because the optimized neural network already generalized effectively. The baseline model achieved the lowest RMSE and highest Adjusted R^2 and was retained as the final configuration.

Final Model Selection

Objective

Identify the strongest-performing neural network configuration discovered throughout the optimization process.

Why Was This Model Selected?

- Best overall predictive performance.
- Highest Adjusted R^2.
- Lowest RMSE among tested configurations.
- Strong convergence behavior.
- Stable generalization performance.
- Fully reproducible experimental workflow.

Conclusion

The final model combines the strongest-performing choices from every optimization stage. Together, these components produced the best balance of predictive accuracy, training stability, reproducibility, and model generalization.

Final Model Visual

Visual

Instead of only text, create a workflow graphic:

Wine Data

↓

StandardScaler

↓

64 → 32 → 16 Network

↓

Sigmoid

↓

RMSProp

↓

125 Epochs

↓

Final Model

Final Model Results

Final Performance Evaluation

The optimized neural network demonstrated substantial improvements over the baseline configuration and successfully captured relationships between wine chemistry measurements and wine quality scores.

The final model achieved the strongest predictive performance observed throughout the study while maintaining excellent generalization behavior.

Performance metrics indicate that the model can explain a meaningful portion of variance in wine quality while maintaining relatively low prediction error.

Key Findings

- Optimization improved prediction accuracy substantially.
- The final architecture consistently outperformed the baseline model.
- RMSProp and Sigmoid contributed significant performance gains.
- The model generalized effectively without requiring additional regularization.

Metric	Final Model
MAE	0.5383
RMSE	0.6933
Adjusted R^2	0.3731
Optimizer	RMSProp
Activation	Sigmoid
Architecture	64 → 32 → 16
Epochs	125

Performance Improvement

Findings

- MAE decreased by 4.89%, indicating more accurate predictions on average. RMSE decreased by 5.87%, demonstrating improved predictive precision. Adjusted R^2 increased by 27.60%, representing the largest gain achieved during optimization. Every optimization stage contributed to measurable performance improvements

Interpretation

Performance gains were achieved through a systematic optimization process that evaluated preprocessing methods, activation functions, architectures, training duration, optimization algorithms, and regularization techniques. The cumulative effect of these design decisions led to a significantly stronger neural network than the original baseline model.

Conclusion

The optimization workflow successfully transformed a moderately performing baseline neural network into a substantially stronger predictive model. The final configuration reduced prediction error while increasing explanatory power, demonstrating the value of systematic neural network optimization.

Metric	Baseline MLP	Final Model	Improvement
MAE	0.5660	0.5383	4.89%
RMSE	0.7365	0.6933	5.87%
Adjusted R^2	0.2924	0.3731	27.60%

Dataset Limitations

Dataset Feature Limitations

The Wine Quality dataset contains only physicochemical measurements and excludes several real-world factors that may influence wine quality, including:

- Grape variety
- Region of origin
- Production methods
- Storage conditions
- Climate and harvest conditions
- Expert tasting notes

Quality Score Limitations

- Wine quality scores are based on human sensory evaluations.
- Subjective scoring introduces variability between evaluators.
- Similar wines may receive different ratings.
- Some factors affecting quality may not be captured by chemical measurements alone.

Class Distribution Limitations

- Most wines received quality scores between 5 and 6.
- Very high-quality and very low-quality wines are underrepresented.
- Imbalanced target distributions can make prediction more challenging.

Key Takeaway

Although the dataset provides valuable chemistry information, it does not fully capture all factors that influence wine quality. Additional variables could improve predictive performance and model interpretability.

Method Limitations

Architecture Search Limitations

- Only four neural network architectures were evaluated.
- Additional architectures may achieve better performance.
- Wider or deeper networks were not tested.

Hyperparameter Limitations

- Hyperparameter optimization was limited.
- Learning rate tuning was not extensively explored.
- Batch size optimization was not investigated.

Model Complexity

- Neural networks often function as "black-box" models.
- Feature contributions are less interpretable than traditional statistical models.
- The model explains prediction outcomes but not necessarily causal relationships.

Generalization Considerations

- Results are specific to the Wine Quality dataset.
- Performance may differ when applied to other wine datasets or real-world production environments.

Key Limitation

No combination of experiments can guarantee identification of the globally optimal neural network configuration. The project identifies the strongest configuration among the evaluated alternatives.

Key Takeaway

While optimization substantially improved predictive performance, additional experimentation may uncover further improvements and provide deeper insight into model behavior.

Next Steps

Hyperparameter Optimization

Explore:

- Learning rates
- Batch sizes
- Weight initialization strategies
- Additional training schedules

Architecture Exploration

Evaluate:

- Deeper neural networks
- Wider hidden layers
- Residual architectures
- Modern neural network designs

Advanced Regularization

Investigate:

- Improved dropout strategies
- Batch Normalization
- Learning-rate scheduling
- Weight decay optimization

Explainable AI

Incorporate:

- SHAP values
- Feature importance analysis
- Model explainability techniques

Ensemble Approaches

Combine:

- Multiple neural networks
- Traditional machine learning methods
- Ensemble prediction systems

Long-Term Goal

Develop a robust and highly accurate wine quality prediction framework that combines deep learning optimization, explainable AI, and advanced model selection techniques.

Project Conclusion

Project Objective Achieved

This project successfully developed and optimized deep learning models for predicting wine quality using physicochemical measurements from the UCI Wine Quality dataset.

Feature Scaling Matters

- StandardScaler significantly improved neural network performance.
- Proper preprocessing enhanced stability and convergence.

Activation Functions Matter

- Different activation functions produced measurable differences in learning behavior and predictive accuracy.
- Sigmoid delivered the strongest overall results within the optimized workflow.

Architecture Design Matters

- Increasing model complexity improved performance up to a point.
- The 64 → 32 → 16 architecture achieved the strongest overall results.

Training Configuration Matters

- 125 epochs provided the best balance between accuracy and generalization.
- RMSProp emerged as the strongest optimizer.

Regularization Was Not Required

- The optimized baseline model generalized effectively without additional regularization.
- Extra regularization methods reduced predictive performance in this project.

Final Recommended Model

StandardScaler → 64 → 32 → 16 Architecture → Sigmoid → RMSProp → 125 Epochs → Baseline (No Regularization)

Final Takeaway

The project demonstrates that systematic optimization of preprocessing, architecture design, activation functions, training strategies, and optimization algorithms can substantially improve neural network performance. Through a structured experimental workflow, the baseline model was transformed into a significantly stronger predictive solution capable of providing reliable wine quality predictions.