

Slide Deck: Lecture 3 - Layered Monolith Implementation (CRUD)

1. Title Slide: From Design to Code

- **Title:** Software Architecture: Lecture 3
 - **Subtitle:** Layered Monolith Implementation (CRUD)
 - **Focus:** Translating the Logical View (Layer 2) into runnable Python code for **ShopSphere**.
-

2. Recap: The Layered Contract

- **Lecture 2 Goal:** We designed the **Layered Monolith** for the Product Catalog.
 - **The Flow:** **Controller** \rightarrow **Service** \rightarrow **Repository**.
 - **The Rule:** Each layer **must only import and call** the layer immediately below it.
 - **Goal Today:** Implement this structure using **Python and Flask** and the **CRUD** (Create, Read, Update, Delete) operations.
-

3. Knowledge Base: Separating Code by Concern

- **Concept:** In a Monolith, we use **directory structure** and **Python packages** to physically enforce the logical layer separation.
 - **Why?** It ensures developers don't accidentally violate the dependency rule (e.g., calling the Repository directly from the Controller).
 - **Project Structure:** We'll create three distinct folders to host our components.
-

4. Activity 1: Project Setup and Dependencies

- **Goal:** Create the physical directories and install the framework.
- **Installation Steps:**
 1. `mkdir shopsphere_monolith`
 2. `cd shopsphere_monolith`
 3. `python -m venv venv`
 4. `source venv/bin/activate`

5. pip install Flask

- **Directory Structure:**
 - shopsphere_monolith/
 - |— app.py (Main Entry Point)
 - |— presentation/ (Controllers)
 - |— business_logic/ (Services & Models)
 - |— persistence/ (Repositories)
-

5. Knowledge Base: The Product Model

- **Concept:** The **Model** (e.g., a Product class) is the core data structure passed *between* the layers. It lives in the Business Logic layer because it represents the domain concept.
 - **Implementation:** We define a simple class with attributes and a helper method for JSON serialization.
-

6. Code Step 1: Defining the Model

- **File:** business_logic/models.py

Python

```
class Product:
```

```
    def __init__(self, id, name, price, stock):
```

```
        self.id = id
```

```
        self.name = name
```

```
        self.price = price
```

```
        self.stock = stock
```

```
    def to_dict(self):
```

```
        # Used by the Presentation layer for JSON response
```

```
return {  
    "id": self.id,  
    "name": self.name,  
    "price": self.price,  
    "stock": self.stock  
}
```

7. Knowledge Base: The Persistence Layer (Repository)

- **Role:** To isolate the application from the underlying data storage mechanism.
 - **Data Store:** For simplicity, we use a Python **in-memory dictionary** (`product_db`) instead of a full database. The Repository hides this detail.
 - **Core Function:** Implement the low-level **CRUD** methods (`create`, `find_by_id`, `update`, `delete`).
-

8. Code Step 2: Implementing the Repository

- **File:** `persistence/product_repository.py`

Python

```
from business_logic.models import Product
```

```
# Simulates the Data Layer (Database)
```

```
product_db = {}
```

```
next_id = 1
```

```
class ProductRepository:
```

```
    def find_all(self):
```

```
        return list(product_db.values())
```

```

def create(self, name, price, stock):

    global next_id

    product_id = next_id

    new_product = Product(product_id, name, price, stock)

    product_db[product_id] = new_product

    next_id += 1

    return new_product


def find_by_id(self, product_id):

    return product_db.get(product_id)

```

9. Knowledge Base: The Business Logic Layer (Service)

- **Role:** Contains the "**Why**" of the application—the business rules.
 - **Constraint: MUST** import and use the ProductRepository.
 - **Value-Add:** Before calling the Repository, the Service should perform validation or logic (e.g., checking for valid inputs, calculating taxes, etc.).
-

10. Code Step 3: Implementing the Service

- **File:** `business_logic/product_service.py`

Python

ONLY imports from the persistence layer (Layer N-1)

from persistence.product_repository import ProductRepository

class ProductService:

```

def __init__(self):

    self.repo = ProductRepository()

```

```

def create_product(self, name, price, stock):

    # Business Rule 1: Price must be positive

    if price <= 0:

        raise ValueError("Product price must be greater than zero.")

    # Business Rule 2: Stock must be non-negative

    if stock < 0:

        stock = 0

    # Strict Downward Call

    return self.repo.create(name, price, stock)


def get_all_products(self):

    return self.repo.find_all()

```

11. Knowledge Base: The Presentation Layer (Controller)

- **Role:** The application's interface to the outside world (HTTP requests).
 - **Constraint: MUST** import and use the ProductService. **MUST NOT** import ProductRepository.
 - **Tasks:** Parse request data, call the Service, format the HTTP response (JSON), and handle HTTP status codes (400, 200, 201, 404).
-

12. Code Step 4: The Main Controller (app.py)

- **File:** app.py

Python

```
from flask import Flask, request, jsonify
```

```
# ONLY imports from the business_logic layer (Layer N-1)
```

```
from business_logic.product_service import ProductService
```

```
app = Flask(__name__)
```

```
product_service = ProductService() # Instantiate the service
```

```
@app.route('/api/products', methods=['POST'])
```

```
def add_product_api():
```

```
    data = request.json
```

```
    try:
```

```
        # 1. Call the Service Layer
```

```
        new_product = product_service.create_product(
```

```
            data.get('name'), data.get('price'), data.get('stock')
```

```
        )
```

```
        # 2. Format Response
```

```
        return jsonify(new_product.to_dict()), 201
```

```
    except ValueError as e:
```

```
        # Handle business logic exceptions
```

```
        return jsonify({"error": str(e)}), 400
```

```
# Add main execution block...
```

13. Activity 2: Proof of Concept - Dependency Enforcement

- **Goal:** Visually confirm the strict rule is enforced by the code's imports.
- **Demonstration:**
 - Look inside `product_service.py`: It imports `product_repository.py`. (Correct: Layer 2 \rightarrow Layer 3)

- Look inside app.py: It imports product_service.py. (Correct: Layer 1 \rightarrow Layer 2)
 - **Crucial Check:** If a developer tries to add from persistence.product_repository import * to app.py, it breaks the architecture and leads to coupling!
-

14. Code Step 5: The Read Endpoint (R in CRUD)

- **File: app.py (Add to existing routes)**

Python

```
@app.route('/api/products', methods=['GET'])  
  
def get_products_api():  
  
    # Call the Service, which calls the Repository  
    products = product_service.get_all_products()  
  
    # Format Response  
  
    return jsonify([p.to_dict() for p in products]), 200
```

15. Activity 3: Practical Implementation Steps

- **Goal:** Run the application and test the implemented C and R operations.
 - **Action Steps:**
 1. Complete all code files as outlined.
 2. Run the application: python app.py
 3. Verify the server is running on http://127.0.0.1:5000.
-

16. Verification (Hands-On): Testing the Flow

- **Tool:** Use Postman or cURL.
- **Test 1: Create Success (C):**
 - **Method:** POST
 - **URL:** http://127.0.0.1:5000/api/products

- **Body:** {"name": "Laptop X1", "price": 1000.00, "stock": 5}
 - **Expected:** HTTP 201 Created.
 - **Test 2: Create Failure (Business Rule):**
 - **Method:** POST
 - **URL:** http://127.0.0.1:5000/api/products
 - **Body:** {"name": "Freebie", "price": -5.00, "stock": 10}
 - **Expected:** HTTP 400 Bad Request (Handled by the Service Layer).
-

17. Verification (Cont.): Testing the Read Operation (R)

- **Test 3: Read All (R):**
 - **Method:** GET
 - **URL:** http://127.0.0.1:5000/api/products
 - **Expected:** HTTP 200 OK with a JSON array containing "Laptop X1".
-

18. Architectural Review: Monolith Pros and Cons

- **Pro:** We achieved fast setup and clear **Separation of Concerns (SoC)**. If we switch from in-memory data to MySQL, only the **Persistence Layer** changes.
 - **Con: Scaling:** If we need 10x capacity for the product list, we must deploy 10 copies of the **entire** system (including the User Admin module). This validates the need to move away from this pattern later.
-

19. Summary of Deliverables for Submission

- **Document 1:** Screenshot of the final project directory structure.
- **Document 2:** Code snippet of the create_product method in the **Service Layer** showing the business rule (price validation).
- **Document 3:** Output logs/screenshots showing the successful **POST (201)** request and the failed **POST (400)** request due to the enforced business rule.

20. Q&A and Next Steps

- **Questions?** (Review error handling flow from Service to Controller).
- **Pre-work:** Research **Microservice Decomposition**—how to identify boundaries based on business functions.
- **Next Lecture: Lecture 4: Microservices Decomposition & Context.** We break the Monolith into independent services, driven by the Scalability ASR.