Precision Control of an Autonomous Surface Vessel

Alejandro Alonso García, Anders Egelund Kjeldal, Himal Kooverjee,
Niels Skov Vestergaard, Noelia Villarmarzo Arruñada

Agenda

- **Introduction**
  - **Use Case**
- **System Description**
- **Model**
  - **Reference Frames**
  - **Model Equations**
  - **Model Verification**
- Control Approach
- Sensor Fusion
- Inner Controller
- Outer Controller
- Results
- Conclusion

Introduction

- What is an Autonomous Surface Vessel (ASV)
- Bathymetric Measurements
- Control of an ASV

Introduction
Use Case



- Used by Port of Aalborg
- Problem: No recent knowledge of depths of the port
- Solution: Automate smaller unmanned vessel

A: It shall be possible to select the area in which the bathymetric measurements are to be performed.

B: The ASV shall be able to plan a route, such that the entire survey area is mapped.

C: The ASV shall be able to follow the planned route.

D: The controller shall be robust to external disturbances.

E: The THU shall not exceed 30 cm with a 95% confidence interval.

F: The ASV shall record and store data locally for extraction at the end of the survey.

G: It shall be possible to give the ASV a command to stop and steer it back to land.

System Description





System Description
RTK GPS



Model
Reference Frames





$$
\begin{aligned}
m\ddot{x}_{\mathrm{b}} &= F_1 + F_2 - d_{\dot{x}_{\mathrm{b}}}\dot{x}_{\mathrm{b}} + F_{x_{\mathrm{b}}} \\
m\ddot{y}_{\mathrm{b}} &= -d_{\dot{y}_{\mathrm{b}}}\dot{y}_{\mathrm{b}} + F_{y_{\mathrm{b}}} \\
m\ddot{z}_{\mathrm{b}} &= -d_{\dot{z}_{\mathrm{b}}}\dot{z}_{\mathrm{b}} + F_{z_{\mathrm{b}}} \\
I_{\mathrm{x}}\ddot{\phi} &= -d_{\dot{\phi}}\dot{\phi} + T_{\phi} \\
I_{\mathrm{y}}\ddot{\theta} &= -d_{\dot{\theta}}\dot{\theta} + T_{\theta} \\
I_{\mathrm{z}}\ddot{\psi} &= F_1 l_1 - F_2 l_2 - d_{\dot{\psi}}\dot{\psi}
\end{aligned}
$$

Model
Model Verification





Agenda

- Introduction
- System Description
- Model
- **Control Approach**
- **Sensor Fusion**
  - **Attitude Kalman Filter**
  - **Position Kalman Filter**
- Inner Controller
- Outer Controller
- Results
- Conclusion

Control Approach



$$\hat{\mathbf{x}}_{\mathrm{att}}(k+1) = \mathbf{A}_{\mathrm{att}}\hat{\mathbf{x}}_{\mathrm{att}}(k) + \mathbf{B}_{\mathrm{att}}\mathbf{u}(k) + \mathbf{w}_{\mathrm{att}}(k)$$
$$\mathbf{y}_{\mathrm{att}}(k) = \mathbf{C}_{\mathrm{att}}\hat{\mathbf{x}}_{\mathrm{att}}(k) + \mathbf{v}_{\mathrm{att}}(k)$$

$$\mathbf{Q}_{\mathrm{att}} = diag\left(\sigma^2_{\phi}, \sigma^2_{\theta}, \sigma^2_{\psi}, \sigma^2_{\dot{\phi}}, \sigma^2_{\dot{\theta}}, \sigma^2_{\dot{\psi}}, \sigma^2_{\ddot{\phi}}, \sigma^2_{\ddot{\theta}}, \sigma^2_{\ddot{\psi}}\right)$$
$$\mathbf{R}_{\mathrm{att}} = diag\left(\sigma^2_{\phi,\mathrm{acc}}, \sigma^2_{\theta,\mathrm{acc}}, \sigma^2_{\psi,\mathrm{mag}}, \sigma^2_{\dot{\phi},\mathrm{gyro}}, \sigma^2_{\dot{\theta},\mathrm{gyro}}, \sigma^2_{\dot{\psi},\mathrm{gyro}}\right)$$

$$\hat{\mathbf{x}}_{\mathrm{att}} = \begin{bmatrix}\phi & \theta & \psi & \dot{\phi} & \dot{\theta} & \dot{\psi} & \ddot{\phi} & \ddot{\theta} & \ddot{\psi}\end{bmatrix}^{\mathrm{T}}$$

$$\mathbf{y}_{\mathrm{att}} = \begin{bmatrix}\phi_{\mathrm{acc}} & \theta_{\mathrm{acc}} & \psi_{\mathrm{mag}} & \dot{\phi}_{\mathrm{gyro}} & \dot{\theta}_{\mathrm{gyro}} & \dot{\psi}_{\mathrm{gyro}}\end{bmatrix}^{\mathrm{T}}$$

$$\mathbf{u} = \begin{bmatrix}F_1 & F_2\end{bmatrix}^{\mathrm{T}}$$

$$
\mathbf{A}_{\mathrm{att}} = \begin{bmatrix}
1 & 0 & 0 & T_\mathrm{s} & 0 & 0 & 0 & 0 & 0 \\
0 & 1 & 0 & 0 & T_\mathrm{s} & 0 & 0 & 0 & 0 \\
0 & 0 & 1 & 0 & 0 & T_\mathrm{s} & 0 & 0 & 0 \\
0 & 0 & 0 & 1 & 0 & 0 & T_\mathrm{s} & 0 & 0 \\
0 & 0 & 0 & 0 & 1 & 0 & 0 & T_\mathrm{s} & 0 \\
0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & T_\mathrm{s} \\
0 & 0 & 0 & -\frac{d_\phi}{I_\mathrm{x}} & 0 & 0 & -T_\mathrm{s}\frac{d_\phi}{I_\mathrm{x}} & 0 & 0 \\
0 & 0 & 0 & 0 & -\frac{d_\theta}{I_\mathrm{y}} & 0 & 0 & -T_\mathrm{s}\frac{d_\theta}{I_\mathrm{y}} & 0 \\
0 & 0 & 0 & 0 & 0 & -\frac{d_\psi}{I_\mathrm{z}} & 0 & 0 & -T_\mathrm{s}\frac{d_\psi}{I_\mathrm{z}}
\end{bmatrix}
$$

$$
\mathbf{B} = \begin{bmatrix}
0 & 0 \\
0 & 0 \\
0 & 0 \\
0 & 0 \\
0 & 0
\end{bmatrix}
\qquad
\mathbf{C} = \begin{bmatrix}
1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0
\end{bmatrix}
$$

$$\hat{\mathbf{x}}_{\mathrm{att}}(k+1|k) = \mathbf{A}_{\mathrm{att}}\hat{\mathbf{x}}_{\mathrm{att}}(k|k) + \mathbf{B}_{\mathrm{att}}\mathbf{u}(k)$$
$$\mathbf{P}_{\mathrm{att}}(k+1|k) = \mathbf{A}_{\mathrm{att}}\mathbf{P}_{\mathrm{att}}(k|k)\mathbf{A}_{\mathrm{att}}^{\mathrm{T}} + \mathbf{Q}_{\mathrm{att}}$$

$$\hat{\mathbf{x}}_{\mathrm{att}}(k+1|k+1) = \hat{\mathbf{x}}_{\mathrm{att}}(k+1|k) + \mathbf{K}(k+1)\left[\mathbf{y}_{\mathrm{att}}(k+1) - \mathbf{C}_{\mathrm{att}}\hat{\mathbf{x}}_{\mathrm{att}}(k+1|k)\right.$$
$$\mathbf{P}_{\mathrm{att}}(k+1|k+1) = \left[\mathbf{I} - \mathbf{K}(k+1)\mathbf{C}_{\mathrm{att}}^{\mathrm{T}}\right]\mathbf{P}_{\mathrm{att}}(k+1|k)$$

Sensor Fusion

Attitude Kalman Filter



$$\hat{\mathbf{x}}_{\mathrm{pos}}(k+1) = \mathbf{A}_{\mathrm{pos}}(k)\mathbf{x}_{\mathrm{pos}}(k) + \mathbf{B}_{\mathrm{pos}}\mathbf{u}(k) + \mathbf{w}_{\mathrm{pos}}(k)$$

$$\mathbf{y}_{\mathrm{pos}}(k) = \mathbf{C}_{\mathrm{pos}}\hat{\mathbf{x}}_{\mathrm{pos}}(k) + \mathbf{v}_{\mathrm{pos}}(k)$$

$$\mathbf{Q}_{\mathrm{pos}} = \mathrm{diag}\left(\sigma^2_{\mathrm{x_n}}, \sigma^2_{\mathrm{y_n}}, \sigma^2_{\dot{\mathrm{x}}_{\mathrm{b}}}, \sigma^2_{\dot{\mathrm{y}}_{\mathrm{b}}}, \sigma^2_{\ddot{\mathrm{x}}_{\mathrm{b}}}, \sigma^2_{\ddot{\mathrm{y}}_{\mathrm{b}}}\right)$$

$$\mathbf{R}_{\mathrm{pos}} = \mathrm{diag}\left(\sigma^2_{x_{\mathrm{n,GPS}}}, \sigma^2_{y_{\mathrm{n,GPS}}}, \sigma^2_{\ddot{x}_{\mathrm{b}},\mathrm{acc}}, \sigma^2_{\ddot{y}_{\mathrm{b}},\mathrm{acc}}\right)$$

$$\hat{\mathbf{x}}_{\mathrm{pos}} = \begin{bmatrix} x_{\mathrm{n}} & y_{\mathrm{n}} & \dot{x}_{\mathrm{b}} & \dot{y}_{\mathrm{b}} & \ddot{x}_{\mathrm{b}} & \ddot{y}_{\mathrm{b}} \end{bmatrix}^{\mathrm{T}}$$

$$\mathbf{y}_{\mathrm{pos}} = \begin{bmatrix} x_{\mathrm{n,GPS}} & y_{\mathrm{n,GPS}} & \ddot{x}_{\mathrm{b,acc}} & \ddot{y}_{\mathrm{b,acc}} \end{bmatrix}^{\mathrm{T}}$$

$$\mathbf{u} = \begin{bmatrix} F_1 & F_2 \end{bmatrix}^{\mathrm{T}}$$

$$\mathbf{A}_{\mathrm{pos}}(\phi(k),\theta(k),\psi(k)) = \begin{bmatrix} 1 & 0 & T_{\mathrm{s}}\ \mathbf{R}_{\mathrm{b}}^{\mathrm{n}}(1,1) & T_{\mathrm{s}}\ \mathbf{R}_{\mathrm{b}}^{\mathrm{n}}(1,2) & 0 & 0 \\ 0 & 1 & T_{\mathrm{s}}\ \mathbf{R}_{\mathrm{b}}^{\mathrm{n}}(2,1) & T_{\mathrm{s}}\ \mathbf{R}_{\mathrm{b}}^{\mathrm{n}}(2,2) & 0 & 0 \\ 0 & 0 & 1 & 0 & T_{\mathrm{s}} & 0 \\ 0 & 0 & 0 & 1 & 0 & T_{\mathrm{s}} \\ 0 & 0 & -\frac{d_{\mathrm{x}}}{m} & 0 & -T_{\mathrm{s}}\frac{d_{\mathrm{x}}}{m} & 0 \\ 0 & 0 & 0 & -\frac{d_{\mathrm{y}}}{m} & 0 & -T_{\mathrm{s}}\frac{d_{\mathrm{y}}}{m} \end{bmatrix}$$

Sensor Fusion

Position Kalman Filter





Agenda

Inner Controller



Inner Controller



- Linear Quadratic Regulator
- Robust Controller



$$
\begin{aligned}
\dot{\mathbf{x}}_\infty(t) &= \mathbf{A}_1\mathbf{x}_\infty(t) + \mathbf{B}_1\mathbf{w}(t) + \mathbf{B}_2\mathbf{u}(t)\\
\mathbf{z}(t) &= \mathbf{C}_1\mathbf{x}_\infty(t) + \mathbf{D}_{11}\mathbf{w}(t) + \mathbf{D}_{12}\mathbf{u}(t)\\
\mathbf{y}_\infty(t) &= \mathbf{C}_2\mathbf{x}_\infty(t) + \mathbf{D}_{21}\mathbf{w}(t) + \mathbf{D}_{22}\mathbf{u}(t)
\end{aligned}
$$

Agenda

Inner Controller
Linear Quadratic Controller Design

Inner Controller
Comparison of the Controllers

Agenda

Outer Controller



w_{beam}
d_{wps}
R_{turn}

Outer Controller
Path Following Algorithm



Outer Controller
Path Following Algorithm



$$\chi = \arctan\left(\frac{y_{\mathrm{LOS}} - y_{\mathrm{n}}}{x_{\mathrm{LOS}} - x_{\mathrm{n}}}\right)$$

Outer Controller

Path Following Algorithm



$$\chi = \text{arctan}\left(\frac{y_{\mathrm{LOS}} - y_{\mathrm{n}}}{x_{\mathrm{LOS}} - x_{\mathrm{n}}}\right)$$

$$\beta = \text{arctan}\left(\frac{\dot{y}_{\mathrm{b}}}{\dot{x}_{\mathrm{b}}}\right)$$



$$\chi = \arctan\left(\frac{y_{\mathrm{LOS}} - y_{\mathrm{n}}}{x_{\mathrm{LOS}} - x_{\mathrm{n}}}\right)$$

$$\beta = \arctan\left(\frac{\dot{y}_{\mathrm{b}}}{\dot{x}_{\mathrm{b}}}\right)$$

$$\psi_{\mathrm{ref}} = \chi - \beta$$

Outer Controller
Path Following Algorithm



Outer Controller

Path Following Algorithm





- LQR as inner controller





- Robust controller as inner controller





Results

Implementation Results

- RTK GPS test



Results

Implementation Results

- Inner controller test



Conclusion

- The estimator has been tuned and tested through simulation to check its performance.
- The outer controller performance when using both inner controllers has also been analyzed though simulations that include disturbances, noise and varying parameters.
- The simulated results have not been fully replicated in the real vessel, they show a promising behavior of the control system.

Precision Control of an Autonomous Surface Vessel

AALBORG UNIVERSITY
DENMARK