TLE / ICT 9

First Quarter

Lesson 3

HTML Links

There are two valid types of links in HTML, depending on the page your web browser is trying to access: External and Internal.

External link – a link to a file or to a webpage that does not belong to the webpage's own site.

Internal link – a link to a file or a webpage within the webpage's own site, or to any part of the webpage itself.

HTML Links

In addition, a dead link to a webpage or file does not exist. Clicking on this kind of link results in a webpage that displays such messages as “Error: File not found” or “The page could not be displayed”.

Only one tag, the anchor tag, is used to describe links.

Using Gifs as Links

Graphics or images can be used to take you to Another page in your website or to another website.

Syntax: *<a href="https://address of page">*
<img src="https://address of graphic.gif"></a>

image.txt

File Edit View

```
<!DOCTYPE html>
<html>
<head><title>Image</title></head>
<body background="wands.jpg">
<h1 align="center">Harry Potter</h1>
<p align="center">Watch the movies and enjoy the wizarding world!!</p><br>

<ul><font size="3"><b>Harry Potter Series</b><br><br>
<li><a href="https://www.imdb.com/title/tt0241527/" target="blank"><img src="pic.jpg" width="70" height="70"></a></li><br>
<li><a href="https://www.imdb.com/title/tt0295297/" target="blank"><img src="pic2.jpg" width="70" height="70"></a></li><br>
<li><a href="https://www.imdb.com/title/tt0304141/" target="blank"><img src="pic3.jpg" width="70" height="70"></a></li><br>
<li><a href="https://www.imdb.com/title/tt0330373/" target="blank"><img src="pic4.jpg" width="70" height="70"></a></li><br>
<li><a href="https://www.imdb.com/title/tt0373889/" target="blank"><img src="pic5.jpg" width="70" height="70"></a></li><br>
<li><a href="https://www.imdb.com/title/tt0417741/" target="blank"><img src="pic6.jpg" width="70" height="70"></a></li><br>
<li><a href="https://www.imdb.com/title/tt0926084/" target="blank"><img src="pic7.jpg" width="70" height="70"></a></li>
</ul>
</body>
</html>
```

Image
File C:/Users/username/Desktop/Grade%209%20files/codes/Lesson%203/image.html

Harry Potter

Watch the movies and enjoy the wizarding world!!

Harry Potter Series

-
-
-
-
-
-
-

Activate Windows

Using Graphics as Links

Graphics or images can be used to take you to Another page in your website or to another website.

Syntax: *<a href="https://address of page">*
<img src="https://address of graphic.gif"></a>

image2.txt

File Edit View

```
<!DOCTYPE html>
<html>
<head><title>Gifs</title></head>
<body background="pokemon.gif">
<h1 align="center">Pokemons</h1>
<p align="center">Gotta Catch Them All!!</p><br>

<ul><font size="3"><b>This is an example of animated images used as links</b><br><br>
<li><a href="https://bulbapedia.bulbagarden.net/wiki/Charizard_(Pok%C3%A9mon)" target="blank"><img src="charizard.gif"
width="70" height="70"></a></li><br>
<li><a href="https://bulbapedia.bulbagarden.net/wiki/Bulbasaur_(Pok%C3%A9mon)" target="blank"><img src="bulbasaur.gif"
width="70" height="70"></a></li><br>
<li><a href="https://bulbapedia.bulbagarden.net/wiki/Squirtle_(Pok%C3%A9mon)" target="blank"><img src="squirtle.gif"
width="70" height="70"></a></li><br>
<li><a href="https://bulbapedia.bulbagarden.net/wiki/Jigglypuff_(Pok%C3%A9mon)" target="blank"><img src="jiglly.gif"
width="70" height="70"></a></li><br>
</ul>
</body>
</html>">
```

HTML 5 INPUT TYPES and FORMS

HTML 5 features input controls and validation that are enhanced than the previous versions. The tag <input> is used to declare an input control. The matrix on the next slide shows only HTML input control that are supported by either of these browsers.

FORMS

- Form allows you to gather feedback from your readers or visitors and work on the data to provide better service.
- The areas in the form are called fields, text fields or text boxes.
- Forms also contains command buttons such as Send or Reset button.
- Standard controls such as check buttons or radio buttons and list boxes can be seen.

FORMS

Forms present a variety of means for users to key in information:

- Textboxes
- Password boxes
- Radio buttons
- Check boxes
- Dropdown menus
- Text areas
- Submit buttons
- Reset or Clear buttons

FORMS

- A form has two attributes: the **action** and the **method**
- **Action attribute** – responsible for indicating where the information will be passed whether it is to another Web page or to a script.
- **Method attribute** – responsible for indicating the way for sending the information.
- **Get** method of sending information appends the data into the URL.

- The **get** method is just basically for retrieving data whereas the **post** method may update or store data.

Attributes for <form></form>

1. action – indicates where the information will be submitted

   Syntax: <form action="process.html"> </form

   Values: filename (path could be included), URL

Attributes for <form></form>

2. method – indicates the method of submitting the information

Syntax: <form action="process.html" method="post"></form

Values: post, get

Creating a Form

The container tag <form></form> is used to create a form.

Note

A form contains input elements like text fields, check boxes, radio buttons, submit buttons and others. A form also contains select lists, text area and others.

form.txt

File Edit View

```
<!DOCTYPE html>
<html>
<head><title>Forms</title></head>
<body>
<h1 align="center">An example of a simple form</h1>
<form action="sample_keygen.asp" method="get">
Username: <input type="text" name="user_name"><br>
Encryption: <keygen name="encryption"><br>
<input type="submit">
</form>
</body></html>
```

Forms

File C:/Users/username/Desktop/Grade%209%20files/codes/Lesson%203/form.html

An example of a simple form

Username:

Encryption:

Submit

Form Elements

Form elements are responsible for functionality of the web pages.

Tag	Description
<datalist> </datalist>	Declares a list of pre-defined options for input controls.
<keygen>	Identifies a key-pair generator field (for forms)
<output> </output>	Generates the result of a calculation.

Data List Element

The data list element identifies a list of pre-defined choices for an input. It is used to offer an auto complete feature on input elements. Web surfers will notice a drop-down list of pre-defined selection as they input data. Tags <input> and <datalist> are used.

form2.txt

File Edit View

```
<!DOCTYPE html>
<html>
<head><title>Forms</title></head>
<body>
<h1 align="center">Data List Element</h1>
Choose your preferred flavor: <form action="ice_cream.asp" method="get">
<input list="flavors" name="flavors">
<datalist id="flavors"
<option value="Double Dutch">
<option value="Chocolate Mint">
<option value="Banana Split">
<option value="Peaches and Mangoes">
<option value="Butter Scotch">
</datalist>
<input type="submit">
</form>
</body>
</html>
```

Activate Windows
Go to Settings to a

Keygen Element

The keygen element ***<keygen>*** declares a key-pair generator field in a form. It was developed for the purpose of security through validation of users. Upon form submission, two keys are produced, a *private* and a *public*. The private key is locally saved while the public key is transmitted to the server. The public key could be used to generate a client certificate to authenticate the user in the future.

keygen.txt

File Edit View

```
<!DOCTYPE html>
<html>
<head><title>Forms</title></head>
<body>
<h1 align="center">Keygen</h1>
<form action="sample_keygen.asp" method="get">
Username: <input type="text" name="user_name"><br>
Encryption: <keygen name="encryption"><br>
<input type="submit">
</form>
</body>
</html>
```



Output Element

The output element, represented by the tag ***<output>***, specifies the result of a calculation such as computations performed in a script.

output.txt

File Edit View

```
<!DOCTYPE html>
<html>
<head><title>Forms</title></head>
<body>
<form
onininput="totalpoints.value=parseInt(technical.value)+parseInt(artistry.value)">
0 <input type="range" name="technical" value=6 min=0 max=6>6+
<input type="number" name="artistry" value=4 min=0 max=4>=
<output name="totalpoints" for="technical+artistry"></output>
</form>
</body>
</html>
```