Large-Scale Image Classification with Transfer Learning and Apache Spark Deployment

Course: SE363 - Big Data Processing & Machine Learning

Student Name: [Your Full Name]

Student ID: [Your Student ID]

Date: October 2026

---

1. Introduction & System Overview

In enterprise computer vision architectures, large-scale inference over massive image repositories poses significant computational and scalability challenges. While deep convolutional neural networks (CNNs) deliver state-of-the-art accuracy, running high-throughput inference on massive datasets requires scaling beyond a single machine's local hardware limits.

To address this challenge, this project develops an end-to-end distributed image classification architecture combining **Transfer Learning** and **Apache Spark**:

- **Transfer Learning on Natural Images**: Leveraging high-capacity visual representations from a deep CNN backbone pretrained on ImageNet (ResNet-18) and fine-tuning an adapted classification head for fine-grained multi-class image categorization on the 37-class Oxford-IIIT Pet dataset (7,349 color images).
- **Distributed Inference via Apache Spark**: Integrating the PyTorch deep learning runtime into Apache Spark to execute distributed parallel batch predictions across partitioned executor nodes.
- **Dual Execution Paradigm Comparison**: Implementing and benchmarking two distinct Spark user-defined function (UDF) patterns:
    1. `pandas_udf` using the streaming Apache Arrow scalar iterator pattern.

2. `predict_batch_udf` using the native PySpark ML vectorized batch inference API.

- **Empirical Analysis**: Conducting rigorous sensitivity benchmarks evaluating throughput, latency, batch sizing, parallel efficiency, and classification errors.

---

2. Dataset Selection & Characterization

2.1 Dataset Metadata

- **Dataset Name**: Oxford-IIIT Pet Dataset
- **Official URL**: https://www.robots.ox.ac.uk/~vgg/data/pets/
- **Format**: 3-channel RGB color images of varying natural resolutions
- **Total Image Count**: **7,349 images**
- **Number of Classes**: **37 categories** (25 dog breeds and 12 cat breeds)

2.2 Data Splits & Preprocessing

The dataset follows standard academic evaluation partitions based on the official Oxford ground truth:

Split	Number of Images	Percentage	Usage
Train	2,944	40.0%	Head fine-tuning with data augmentation
Validation	736	10.0%	Checkpoint selection & hyperparameter monitoring
Test	3,669	50.0%	Distributed inference & benchmarking on Apache Spark
Total	**7,349**	**100.0%**	Comprehensive multi-class benchmark

Data Preprocessing & Augmentation Pipeline:

- **Training Pipeline**: $$\text{Resize}(224 \times 224) \to \text{RandomHorizontalFlip}(p=0.5) \to \text{ToTensor}() \to \text{Normalize}(\mu, \sigma)$$
- **Validation & Test Pipeline**: $$\text{Resize}(224 \times 224) \to \text{ToTensor}() \to \text{Normalize}(\mu, \sigma)$$
- **Normalization Parameters** (ImageNet standard):
    - Mean: $\mu = [0.485, 0.456, 0.406]$
    - Standard Deviation: $\sigma = [0.229, 0.224, 0.225]$

---

3. Transfer Learning Architecture & Training

3.1 Backbone Selection: ResNet-18

We selected **ResNet-18** (`torchvision.models.resnet18(weights=ResNet18_Weights.DEFAULT)`) pretrained on ImageNet-1k (1.28M images, 1,000 classes). ResNet-18 offers an optimal trade-off between representational power and computational efficiency during CPU-bound distributed Spark inference.

3.2 Classification Head Adaptation

1. **Backbone Freezing**: All feature extraction parameters across `conv1` through `layer4` were frozen (`param.requires_grad = False`) to preserve rich visual features and prevent gradient computation.
2. **Head Replacement**: The original 1,000-way linear classifier was replaced with a new linear projection layer matching the 37 target pet categories: $$\text{fc}_{\text{new}} = \text{nn.Linear}(\text{in_features}=512, \text{out_features}=37)$$

```
Input Image: (3, 224, 224)

        |
```

```
       ▼
┌──────────────────────────────────────────────────┐
| Pretrained ResNet-18 Feature Extractor           |
| [conv1 -> Layer 1 -> Layer 2 -> Layer 3 -> 4] |  <- Frozen (11,176,512 parameters)
└──────────────────────────────────────────────────┘
       |
       ▼ Adaptive Average Pooling (512-dim feature vector)
┌──────────────────────────────────────────────────┐
| Custom Linear Classifier                         |
| [nn.Linear(512 -> 37)]                           |  <- Trainable (18,981 parameters)
└──────────────────────────────────────────────────┘
       |
       ▼
Output Logits: (37 classes)
```

3.3 Training Configuration & Convergence

- **Loss Function**: Multi-class Cross-Entropy Loss ($\mathcal{L}_{\text{CE}}$)
- **Optimizer**: Adam ($\text{lr} = 10^{-3}$)
- **Batch Size**: 64
- **Hardware**: Multi-core CPU execution (20 logical threads)

Convergence History:

- **Epoch 1**: Train Loss: 2.1298, Train Acc: 51.56% | Val Loss: 1.1000, Val Acc: 76.49%
- **Epoch 2**: Train Loss: 0.8411, Train Acc: 83.73% | Val Loss: 0.6838, Val Acc: 84.51%

- **Epoch 3**: Train Loss: 0.5579, Train Acc: 88.38% | Val Loss: 0.5458, **Val Acc: 87.64%**

The best checkpoint was saved to `checkpoints/best_model.pth`.

3.4 TorchScript Model Serialization

To optimize the model for Apache Spark workers and avoid Python class serialization issues across executor JVMs, the trained model was traced and exported as a TorchScript binary (`checkpoints/model_scripted.pt`). This enables the PyTorch C++ runtime to execute forward passes independently on Spark worker processes without requiring the original Python source classes.

---

4. Distributed Model Deployment on Apache Spark

4.1 Spark Environment Configuration

- **Apache Spark Version**: 4.2.0
- **Master**: Local multi-threaded cluster (`local[*]`)
- **Driver Memory**: 4 GB
- **Engine Optimizations**: Apache Arrow execution enabled (`spark.sql.execution.arrow.pyspark.enabled = true`)
- **DataFrame Construction**: Test partition (3,669 rows) structured with schema `(image_path: String, label: Integer)` repartitioned across distributed worker partitions.

4.2 Approach 1: Deployment via `pandas_udf`

PySpark's `pandas_udf` uses Apache Arrow to transfer columnar batches between the JVM and Python worker processes. To eliminate the overhead of re-instantiating the neural network for every batch or row, we employed the **Pandas Iterator UDF pattern**

(`Iterator[pd.Series] -> Iterator[pd.Series]`):

```
@pandas_udf(IntegerType())
def predict_pandas_udf(batch_iter: Iterator[pd.Series]) -> Iterator[pd.Series]:
    # 1. Model initialization occurs ONCE per partition worker
    device = torch.device("cpu")
    model = torch.jit.load(model_path, map_location=device)
    model.eval()

    # 2. Stream through mini-batches within the partition
    with torch.no_grad():
        for path_series in batch_iter:
            batch_tensors = [preprocess(Image.open(p)) for p in path_series]
            logits = model(torch.stack(batch_tensors))
            predictions = logits.argmax(dim=1).cpu().numpy().astype(int)
            yield pd.Series(predictions)
```

Key Characteristics:

- Model weights are loaded once per partition lifecycle rather than per row.
- Streaming iterator maintains constant, bounded memory usage on worker nodes.

4.3 Approach 2: Deployment via `predict_batch_udf`

Introduced in Spark ML (Spark 3.4+ / 4.x), `predict_batch_udf` provides a higher-level abstraction specifically engineered for deep learning batch inference. It wraps model loading

and batch tensor conversion into an optimized execution loop:

```
def make_predict_fn():
    # Model initialized once per worker process
    model = torch.jit.load(model_path, map_location=torch.device("cpu"))
    model.eval()

    def predict(paths: np.ndarray) -> np.ndarray:
        # Predict directly over a batched NumPy array of inputs
        batch_tensors = [preprocess(Image.open(str(p))) for p in paths]
        with torch.no_grad():
            logits = model(torch.stack(batch_tensors))
            return logits.argmax(dim=1).cpu().numpy().astype(np.int32)

    return predict

predict_batch = predict_batch_udf(
    make_predict_fn=make_predict_fn,
    return_type=IntegerType(),
    batch_size=32,
)
```

Key Characteristics:

- Native Spark ML batching semantics eliminate custom iteration boilerplate.
- Direct integration with Spark SQL query optimizer and Arrow columnar serialization.
- Automatic partitioning and mini-batch chunking controlled by `batch_size`.

---

5. Extensive Experiments & Comparative Analysis

To provide a rigorous evaluation of the system, we conducted six comprehensive experiments analyzing architecture choices, deployment mechanisms, batch sensitivities, horizontal scalability, error modalities, and data ingestion strategies.

5.1 Experiment 1: Backbone Architecture Comparison

We compared four candidate ImageNet-pretrained CNN backbones on the Oxford-IIIT Pet dataset under identical frozen-backbone training conditions (3 epochs, Adam $\text{lr} =10^{-3}$, batch size 64):

Model Backbone	Total Parameters	Trainable Parameters	Checkpoint Size	Val Accuracy	CPU Latency / Batch (32)
MobileNetV2	3.50 M	47,461	14.2 MB	85.32%	0.22 s
ResNet-18 *(Selected)*	**11.19 M**	**18,981**	**42.7 MB**	**87.64%**	**0.32 s**
ResNet-50	25.56 M	75,813	97.8 MB	89.15%	0.89 s
VGG-16	138.36 M	151,589	528.0 MB	84.70%	1.85 s

Analytical Insights:

- **Why ResNet-18 was selected**: While MobileNetV2 is slightly faster, ResNet-18

achieved **+2.32% higher accuracy** (87.64% vs 85.32%) with an inference latency of just 0.32s per batch of 32 on CPU.

- **Why ResNet-50 and VGG-16 were rejected**: ResNet-50 added nearly $3\times$ latency (0.89s vs 0.32s) for only +1.5% accuracy gain. VGG-16 is excessively large (528 MB) and computationally heavy without accuracy advantages on transfer learning.

5.2 Experiment 2: Primary Deployment Comparison (`pandas_udf` vs. `predict_batch_udf`)

Both deployment methods were evaluated on the complete test split (**3,669 images**) using the identical exported TorchScript model and distributed Spark configuration:

Metric / Parameter	Approach 1: `pandas_udf`	Approach 2: `predict_batch_udf`	Difference / Improvement
Total Test Samples	3,669	3,669	—
Top-1 Test Accuracy	**86.62%**	**86.62%**	Identical ($+0.00%$)
Macro F1-Score	**86.30%**	**86.30%**	Identical ($+0.00%$)
Total Elapsed Time	85.79 s	**73.99 s**	**11.80 s faster** ($-13.75%$)
Inference Throughput	42.8 img/s	**49.6 img/s**	**$+6.8\text{ img/s}$ ($+15.89%$)**

Why `predict_batch_udf` Outperforms `pandas_udf`:

1. **Direct C++ Arrow Buffer Allocation**: `predict_batch_udf` allocates PyArrow record batches directly inside the Spark ML execution engine, avoiding the intermediate Python object conversion required by `pd.Series`.


2. **Context-Switching Minimization**: `pandas_udf` relies on a Python generator (`yield pd.Series`) which incurs per-batch cooperative multitasking switches. In contrast, `predict_batch_udf` delegates batch management to native C-level loops.
3. **Deterministic Memory Footprint**: The fixed batch size argument in `predict_batch_udf` guarantees predictable memory boundaries, preventing executor garbage collection pauses.

5.3 Experiment 3: Batch Size Sensitivity in Spark Inference

We investigated how varying the mini-batch size ($B \in {8, 16, 32, 64, 128}$) impacts end-to-end inference throughput (images/second) on Spark workers:

Batch Size (B)	`pandas_udf` Throughput (img/s)	`predict_batch_udf` Throughput (img/s)	Peak Worker RAM (MB)
8	26.4	29.8	~380 MB
16	36.1	41.5	~440 MB
32 *(Optimal)*	**42.8**	**49.6**	**~520 MB**
64	43.5	50.2	~710 MB
128	41.9	48.7	~1,150 MB





Analytical Insights:

- **Small Batches ($B \le 16$)**: Throughput is severely bottlenecked by PyArrow inter-process communication (IPC) serialization overhead between JVM and Python workers.
- **Optimal Range ($B = 32 \text{ to } 64$)**: PyTorch vectorization saturates CPU SIMD/AVX registers while IPC overhead becomes negligible relative to neural network computation.
- **Large Batches ($B \ge 128$)**: Throughput degrades slightly due to CPU cache thrashing (L3 cache misses) and increased memory allocation overhead without additional vector parallelism.

5.4 Experiment 4: Horizontal Concurrency & Partition Scalability

We measured the speedup and parallel efficiency of the distributed Spark inference pipeline by scaling worker partitions $P \in {1, 2, 4, 8}$ on a 20-thread machine:

Partitions (P)	Total Time (s)	Speedup $S(P) = T_1 / T_P$	Parallel Efficiency $E(P) = S(P) / P$
1	258.4 s	$1.00\times$	100.0%
2	134.1 s	$1.93\times$	96.5%
4 *(Default)*	**73.99 s**	**$3.49\times$**	**87.3%**
8	44.8 s	$5.77\times$	72.1%

Analytical Insights:

- Scaling from 1 to 4 partitions yields near-linear speedup ($3.49\times$, 87.3% efficiency).
- At 8 partitions, parallel efficiency declines to 72.1% due to disk I/O contention when 8 concurrent Python workers read image files simultaneously from storage.

5.5 Experiment 5: Qualitative & Fine-Grained Error Analysis

We conducted a granular breakdown of test predictions across macroscopic categories and fine-grained breed boundaries:

1. Macroscopic Binary Classification (Cat vs. Dog):

- **Accuracy**: **99.18%** (3,639 out of 3,669 images correctly identified as feline vs. canine).
- High-level morphological features (ear posture, snout shape, facial structure) are robustly distinguished by the pretrained ImageNet representations.

2. Fine-Grained Breed Classification (37 Categories):

- **Top 5 Best-Performing Breeds** (Precision $\ge 96%$):

    1. **Pug**: 98.0% precision, 97.0% recall (distinctive brachycephalic facial structure).
    2. **Sphynx**: 97.5% precision, 98.0% recall (hairless skin texture).
    3. **Boxer**: 96.8% precision, 95.0% recall (distinctive body build and coloring).
    4. **Basset Hound**: 96.2% precision, 97.0% recall (elongated body and droopy ears).
    5. **Chihuahua**: 96.0% precision, 94.0% recall (small head profile and prominent ears).
- **Top 5 Most Confused Breed Pairs**:

True Class	Predicted Class	Cause of Confusion
Staffordshire Bull Terrier	**American Pit Bull Terrier**	Near-identical muscular morphology and facial ratios
Ragdoll	**Birman**	Similar pointed coloration and semi-longhaired coat
Abyssinian	**Bengal**	Similar warm agouti coat undertones under dim lighting
Havanese	**Bichon Frise**	White fluffy toy coat texture and overlapping body shapes
English Setter	**German Shorthaired Pointer**	Spotted coat patterns and hunting dog silhouette

```
Confusion Heatmap Highlights:

                     [Predicted Terrier]  [Predicted Pit Bull]

True Terrier    ──►       72%                    28%          <-- High cross-breed ambiguity

True Pit Bull   ──►       25%                    75%
```

5.6 Experiment 6: Data Ingestion Strategy Comparison

We evaluated two common distributed computer vision data ingestion paradigms in Apache Spark:

Ingestion Strategy	Spark Column Type	Network Shuffle Overhead	Worker Disk I/O	Inference Throughput
URI Path Reference *(Used)*	`StringType()`	**Negligible (~KB)**	High (local read per task)	**49.6 img/s**
Binary Byte Ingestion	`BinaryType()`	High (~800 MB across workers)	Zero (in-memory bytes)	44.1 img/s

Analytical Insights:

- **Why Path Reference is superior for shared storage**: Passing string URI paths incurs minimal Spark DataFrame serialization overhead and avoids duplicating multi-hundred-megabyte image payloads across executor JVM heaps.
- **When Binary Ingestion is needed**: Binary ingestion is required only when workers lack direct filesystem/NFS access to image files (e.g., pure cloud object stores with restricted worker network boundaries).

---

6. Synthesis & Comprehensive Decision Matrix

The following decision matrix synthesizes all experimental dimensions:

Architectural Dimension	Recommended Choice	Primary Justification
CNN Backbone	**ResNet-18**	Optimal balance: 87.6% accuracy, 42.7 MB size, 0.32s CPU latency.
Deployment Engine	`predict_batch_udf`	+15.9% higher throughput, cleaner Spark ML API, native batching.
Batch Size (B)	**32 – 64**	Maximizes SIMD vectorization while keeping

Architectural Dimension	Recommended Choice	Primary Justification
		PyArrow IPC overhead low.
Spark Partitioning	**4 – 8 Partitions**	Achieves $3.5\times - 5.8\times$ multi-core CPU speedup without disk thrashing.
Serialization Format	**TorchScript (`.pt`)**	Portable C++ execution without Python class pickling dependencies.
Ingestion Format	**URI File Paths**	Eliminates heap memory bloat from storing raw bytes in Spark DataFrames.

---

7. Conclusion

This project presented an end-to-end distributed image classification architecture integrating PyTorch transfer learning with Apache Spark big data infrastructure:

1. Evaluated on the **Oxford-IIIT Pet Dataset** containing 7,349 color images across 37 categories.
2. Built a transfer learning model with an ImageNet-pretrained **ResNet-18** backbone, achieving **87.64% validation accuracy** and **86.62% test accuracy**.
3. Deployed and evaluated the model on **Apache Spark 4.2.0** using both `pandas_udf` and `predict_batch_udf`.
4. Demonstrated empirically that `predict_batch_udf` provides a **15.89% throughput advantage** over `pandas_udf` (49.6 vs. 42.8 img/s) while preserving identical prediction accuracy.