

PROGRAM

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/wait.h>
#include <sys/types.h>

int main() {
    pid_t cpid;

    if (fork() == 0) {
        // Child Process
        printf("Child Process starts. PID = %d\n", getpid());
        sleep(2); // Simulate doing some work
        printf("Child Process finishing.\n");
        exit(0);
    }
    else {
        // Parent Process
        printf("Parent Process starts. PID = %d\n", getpid());

        // Wait for the child to finish
        cpid = wait(NULL);

        printf("Parent resumed. Finished Child PID = %d\n", cpid);
    }

    printf("Parent Terminated.\n");
    return 0;
}
```

OUTPUT

```
blackie@blackie-pc:~/GEC_PKD_IT/S4/OS_LAB/EXPERIMENT_1$ gcc 1.3.c
blackie@blackie-pc:~/GEC_PKD_IT/S4/OS_LAB/EXPERIMENT_1$ ./a.out
Parent Process starts. PID = 22580
Child Process starts. PID = 22581
Child Process finishing.
Parent resumed. Finished Child PID = 22581
Parent Terminated.
blackie@blackie-pc:~/GEC_PKD_IT/S4/OS_LAB/EXPERIMENT_1$
```