

## **PROGRAM**

```
#include <stdio.h>
#include <stdlib.h>
#include <math.h>

int main() {
    int n, head, total_seek = 0;

    printf("Enter initial head position: ");
    scanf("%d", &head);
    if (head < 0) { printf("Invalid Input\n"); exit(0); }

    printf("Enter number of requests: ");
    scanf("%d", &n);

    int request[n];
    printf("Enter the requests: ");
    for (int i = 0; i < n; i++) {
        scanf("%d", &request[i]);
        if (request[i] < 0) { printf("Invalid Input\n"); exit(0); }
    }

    for (int i = 0; i < n; i++) {
        total_seek += abs(head - request[i]);
        head = request[i]; // New head position
    }

    printf("Total Seek Operations (FCFS) = %d\n", total_seek);
    return 0;
}
```

## **OUTPUT**

```
blackie@blackie-pc:~/GEC_PKD_IT/S4/OS_LAB/EXPERIMENT_10$ gcc fcfs.c
blackie@blackie-pc:~/GEC_PKD_IT/S4/OS_LAB/EXPERIMENT_10$ ./a.out
Enter initial head position: 53
Enter number of requests: 8
Enter the requests: 98
183
41
122
14
124
65
67
Total Seek Operations (FCFS) = 632
```