

AEGIS: Mining Graph Structure for Adversarial Vulnerability Analysis of GNNs

Anonymous Author(s)

Abstract—Adversarial manipulation of graph structure poses a growing threat as graph neural networks are deployed in fraud detection, drug interaction prediction, and infrastructure monitoring. Yet practitioners lack tools to answer a basic question before deployment: *which edges, if perturbed, would flip this model’s predictions?* We introduce AEGIS (Adversarial Evaluation of Graph Integrity via Sensitivity), a framework that answers this question by constructing a constrained sensitivity matrix S_c mapping edge perturbations to hidden-state shifts. From S_c , AEGIS extracts the mathematically optimal attack direction (via SVD), per-edge vulnerability rankings, and per-node first-order sensitivity radii. A matrix-free formulation based on Neumann-series resolvent iteration and randomized SVD enables full-graph analysis (up to $N=7,650$ on a single GPU; Cora in 78s / 1GB, Amazon Photo in 363s / 6.5GB) without materializing any $Nd \times N^2$ matrix. The computation applies to GNNs with continuous edge-weight-modulated message passing, serving as a practical vulnerability analysis tool; for contractive implicit models (IGNN-class), it additionally provides formal guarantees including a critical perturbation budget $\varepsilon_{\text{crit}}$ and a three-regime vulnerability characterization. Under realistic (symmetric, edge-only) perturbations, first-order predictions achieve tightness 1.00 ± 0.01 at $\varepsilon = 0.01$ and remain within 15% at $\varepsilon = 0.10$ across 7 architectures and 9 datasets. The SVD-optimal attack inflicts $2\text{--}8\times$ more damage than random perturbation. On IEEE power grids, the vulnerability spectrum recovers N-1 contingency rankings (P@10 = 0.66–0.81) without requiring line-impedance data, demonstrating that structural sensitivity analysis can serve as a pre-deployment screening tool. Code will be released upon publication.

Index Terms—Graph neural networks, adversarial robustness, structural sensitivity, deep equilibrium models, graph perturbation, implicit function theorem

I. INTRODUCTION

Graph neural networks have entered domains where incorrect predictions carry tangible consequences: fraudulent accounts evade detection when an adversary inserts edges into a financial transaction graph [1], drug interaction models produce unsafe recommendations when molecular graphs are perturbed [2], and power grid monitoring systems may miss critical contingencies if their graph-based representations are structurally fragile [3]. In all these settings, the graph topology is not merely an input format but a potential attack surface. A practitioner preparing to deploy a GNN faces a fundamental question that current tools leave unanswered: *which edges in this graph, if perturbed, would cause the model’s predictions to fail, and by how much?*

This question is distinct from both adversarial attack and certified defense. Attack methods such as Nettack [1] and Mettack [4] search for damaging perturbations using surrogate gradients or meta-learning, but they provide no guarantee that

the perturbation found is optimal, and they do not quantify per-node vulnerability. Certified defenses based on randomized smoothing [5], [6] or interval bound propagation [7], [8], [9] provide robustness guarantees, but they are uniform: every node receives the same certificate, revealing nothing about *which* edges or nodes are structurally weak. Empirical defenses [10], [11], [12], [13] harden the model but offer no formal understanding of residual vulnerability. What is missing is a *structural vulnerability map* that, given a trained GNN and a graph, identifies the optimal perturbation direction, the weakest edges, and the perturbation tolerance of each node.

We introduce AEGIS (Adversarial Evaluation of Graph Integrity via Sensitivity), a framework that produces exactly this map. The central object is the *constrained sensitivity matrix* $S_c \in \mathbb{R}^{Nd \times |E|}$, which projects the full N^2 -dimensional adjacency perturbation space onto the $|E|$ -dimensional space of realistic (symmetric, edge-only) perturbations. From S_c , three outputs follow directly: (i) the SVD yields the first-order optimal attack direction, (ii) column norms give per-edge vulnerability scores, and (iii) the classification margin divided by the sensitivity norm gives per-node tolerance radii. The S_c computation applies to GNNs with continuous edge-weight-modulated message passing (theorem 5; standard GAT and architectures using max/min aggregations require modification for continuous differentiability), yielding vulnerability rankings, SVD-optimal attacks, and first-order sensitivity radii as a practical computational tool. For contractive implicit GNNs (IGNN-class [14]), the implicit function theorem additionally provides formal guarantees: a critical perturbation budget $\varepsilon_{\text{crit}} = (1 - \kappa) / \|W\|_2$ and a three-regime characterization of model behavior under increasing perturbation (theorem 1). These formal guarantees are specific to the implicit case and do not transfer to explicit architectures.

These predictions are quantitatively accurate: constrained first-order tightness is 1.00 ± 0.01 at $\varepsilon = 0.01$ and remains within 15% at $\varepsilon = 0.10$, across 7 GNN architectures and 9 datasets spanning citation networks, e-commerce, encyclopedias, and power grids. On IEEE power grids, the vulnerability spectrum independently recovers N-1 contingency rankings (P@10 = 0.66–0.81), demonstrating that structural sensitivity analysis transfers to real-world engineering problems without domain-specific modifications.

Contributions.

- 1) **Constrained sensitivity framework.** We derive the constrained sensitivity matrix S_c for GNNs with continuous edge-weight-modulated message passing (theorem 5; standard GAT and max/min aggregations require

modification). For contractive implicit models (IGNN-class), we additionally prove a conservative sufficient condition on the critical budget $\varepsilon_{\text{crit}}$ and three vulnerability regimes (theorem 1); these formal guarantees do not transfer to explicit architectures.

- 2) **Scalable matrix-free computation.** A Neumann-series resolvent combined with autograd JVPs and randomized SVD [15] computes S_c 's action without materializing any $Nd \times N^2$ matrix, enabling full-graph analysis (Cora $N=2,708$ in 78 s). A comprehensive attack evaluation spanning gradient-based and gradient-free, continuous and discrete, same-objective and independent baselines (section V-C) confirms SVD optimality (best-of-1,000 random directions reaches only 48% of σ_1) and validates rankings across 7 architectures (section V-H).
- 3) **Cross-domain validation and case study.** We validate across 9 datasets in 4 domains, including a power grid case study where AEGIS recovers N-1 contingency rankings (τ between continuous S_c scores and discrete edge-removal ground truth: +0.32–+0.54; section VI).

II. PRELIMINARIES AND THREAT MODEL

A. Notation and Formalization

Let $G = (V, E, A)$ denote an undirected graph with $N = |V|$ nodes, edge set E , and adjacency matrix $A \in \mathbb{R}^{N \times N}$. Each node $v \in V$ carries a feature vector $x_v \in \mathbb{R}^{d_{\text{in}}}$, collected into $X \in \mathbb{R}^{N \times d_{\text{in}}}$. We write $\hat{A} = D^{-1/2}(A + I)D^{-1/2}$ for the symmetric normalized adjacency with self-loops, where D is the degree matrix of $A + I$. Throughout, ϕ denotes the activation function, $\sigma_i(\cdot)$ denotes the i -th singular value, and $\text{vec}(\cdot)$ stacks a matrix column-wise into a vector (with reshape as its inverse). table I summarizes the key sensitivity objects.

Deep equilibrium GNNs. A DEQ-GNN [16], [17] defines a weight-tied operator $F_\theta : \mathbb{R}^{N \times d} \times \mathbb{R}^{N \times N} \rightarrow \mathbb{R}^{N \times d}$ and iterates it from $Z_0 = 0$ until convergence:

$$Z_{k+1} = F_\theta(Z_k, A), \quad z^* = \lim_{k \rightarrow \infty} Z_k. \quad (1)$$

When F_θ is contractive in operator norm ($\kappa = \|J_z\|_2 < 1$, where $J_z = \partial F / \partial z|_{z^*}$), the Banach fixed-point theorem guarantees a unique equilibrium $z^* = F_\theta(z^*, A)$ regardless of initialization.

IGNN instantiation. The Implicit Graph Neural Network (IGNN) [14] uses the operator

$$F(Z, A) = \phi(\hat{A}ZW^\top + X_{\text{proj}}), \quad (2)$$

where $W \in \mathbb{R}^{d \times d}$ is the shared weight matrix, $X_{\text{proj}} \in \mathbb{R}^{N \times d}$ is a learned feature projection, and ϕ is ReLU activation. Contractivity is enforced by constraining $\|W\|_2$ via spectral normalization [18], ensuring $\kappa \leq \|\hat{A}\|_2 \cdot \|W\|_2 < 1$. Training uses implicit differentiation through the fixed point [19], [20], and Jacobian regularization [21] can further stabilize convergence. A linear classification head $f(z^*) = W_{\text{cls}}z^* + b$ maps the equilibrium to class predictions.

Implicit function theorem. At the equilibrium, the equation $G(z^*, A) = z^* - F(z^*, A) = 0$ defines z^* as an implicit

TABLE I: Key sensitivity objects in AEGIS.

Symbol	Size	Description
S	$Nd \times N^2$	Unconstrained sensitivity matrix
S_c	$Nd \times E $	Constrained (symmetric, edge-only)
S_K	$Nd \times N^2$	Unrolled sensitivity for K -layer GNN
S_v	$d \times N^2$	Block-rows of S for node v
κ	scalar	Operator-norm contractivity $\ J_z\ _2$
ρ	scalar	Spectral radius $\rho(J_z)$
η	scalar	Pseudospectral index ≥ 1
$\varepsilon_{\text{crit}}$	scalar	Critical perturbation budget
r_v	scalar	Per-node first-order sensitivity radius

function of A . The IFT gives the sensitivity of z^* to any parameter p :

$$\frac{\partial z^*}{\partial p} = (I - J_z)^{-1} \frac{\partial F}{\partial p} \Big|_{z^*}, \quad (3)$$

where the resolvent $(I - J_z)^{-1}$ exists and satisfies $\|(I - J_z)^{-1}\|_2 \leq 1/(1 - \kappa)$ by the Neumann series (convergent because $\kappa < 1$). This bound uses the operator norm $\kappa = \|J_z\|_2$; the weaker spectral-radius bound $1/(1 - \rho)$ holds only for normal J_z . The pseudospectral index $\eta = \|(I - J_z)^{-1}\|_2 \cdot (1 - \rho) \geq 1$ [22] quantifies this gap, with $\eta = 1$ for normal matrices. (Our definition follows the convention $\eta = \|(I - J_z)^{-1}\|_2 \cdot (1 - \rho)$; the standard Trefethen–Embree pseudospectral theory uses ε -pseudospectra, from which this scalar index is derived.) The IFT has been used for hyperparameter optimization [23] and implicit differentiation [19], but not for adversarial structural analysis.

B. Threat Model

We consider a white-box attacker who has full access to the trained IGNN model and perturbs the normalized adjacency matrix:

$$\hat{A}' = \hat{A} + \delta \hat{A}, \quad \text{subject to} \quad \|\delta \hat{A}\|_F \leq \varepsilon. \quad (4)$$

The perturbation is further constrained to be:

- **Symmetric:** $\delta \hat{A} = \delta \hat{A}^\top$ (preserving the undirected nature of the graph).
- **Edge-only:** $[\delta \hat{A}]_{ij} = 0$ for $(i, j) \notin E$ (only existing edge weights may be modified; no new edges are introduced).
- **Continuous:** edge weights are perturbed continuously in $\mathbb{R}$, not discretely flipped.

This threat model captures continuous edge-weight perturbations to the normalized message-passing operator. It aligns naturally with the IGNN architecture, where $\hat{A}$ appears directly in F (eq. (2)). Discrete edge insertions or deletions, which change the graph topology and require recomputing the degree normalization $D^{-1/2}$, are outside the formal guarantee.

The key distinction from input-feature perturbation (studied for DEQs in [24], [25]) is that structural perturbation changes the *operator itself*: the equilibrium depends on A through both the state Jacobian $J_z = \text{diag}(\phi') \cdot (\hat{A} \otimes W)$ and the adjacency Jacobian $J_A = \partial F / \partial \text{vec}(A)$. This dual dependence makes structural sensitivity qualitatively different from input sensitivity.

C. Problem Statement

Given a trained contractive implicit GNN with equilibrium z^* on graph G , we aim to answer three questions:

- 1) **Vulnerability ranking:** Which edges, if perturbed, cause the largest shift in the equilibrium? That is, find a ranking of edges $(i, j) \in E$ by their adversarial impact on z^* .
- 2) **Optimal attack:** What is the worst-case perturbation δA^* that maximizes $\|\Delta z^*\|_F$ subject to the threat model constraints in eq. (4)?
- 3) **Robustness assessment:** For each node v , what is the largest perturbation budget r_v such that any $\|\delta \hat{A}\|_F < r_v$ preserves the classification of v ?

AEGIS addresses all three questions through a unified object: the constrained sensitivity matrix S_c derived from the IFT applied to the equilibrium equation. The following sections formalize this construction (section III) and describe the computational pipeline (section IV).

III. ADVERSARIAL EQUILIBRIUM THEORY

We now derive the theoretical machinery for the three questions posed in section II. The main result (theorem 1) characterizes how vulnerability evolves with perturbation magnitude, and the constrained sensitivity matrix S_c provides the unified object from which rankings, attacks, and radii follow.

Theorem 1 (Vulnerability Characterization for Contractive Implicit GNNs). *Let $F_\theta(Z, A) = \phi(AZW^\top + X_{\text{proj}})$ be an IGNN-class operator satisfying:*

- (A1) ϕ is ReLU (or any 1-Lipschitz activation with $\sup |\phi'| = 1$; ReLU is non-differentiable at zero, but the set of measure zero where $\phi' = 0$ does not affect the Jacobian computation in practice [26]);
- (A2) W is spectral-norm constrained: $\|W\|_2 \leq c$;
- (A3) The state Jacobian satisfies $\|J_z\|_2 \leq \kappa < 1$ at the fixed point z^* (contraction in operator norm).

Define the critical budget

$$\varepsilon_{\text{crit}} = \frac{1 - \kappa}{\|W\|_2}. \quad (5)$$

Then structural perturbations δA with $\|\delta A\|_F = \varepsilon$ exhibit three regimes:

(a) **Subcritical** ($\varepsilon < \varepsilon_{\text{crit}}$): The perturbed operator remains contractive with a unique fixed point satisfying

$$\|\Delta z^*\|_F \leq \sigma_1(S) \cdot \varepsilon + O(\varepsilon^2), \quad (6)$$

where $S = (I - J_z)^{-1} J_A$ is the structural sensitivity matrix and $\sigma_1(S) \leq \|J_A\|_{\text{op}} / (1 - \kappa)$.

(b) **Critical** ($\varepsilon \rightarrow \varepsilon_{\text{crit}}$): The resolvent norm $\|(I - J'_z)^{-1}\|_2$ diverges as $\Omega(1/(\varepsilon_{\text{crit}} - \varepsilon))$. Intuitively, as the perturbation approaches the critical budget, the system's sensitivity to further perturbation grows without bound.

(c) **Supercritical** ($\varepsilon > \varepsilon_{\text{crit}}$): The sufficient contraction certificate becomes void ($\|J'_z\|_2$ may exceed 1). The perturbed operator may still be contractive depending on perturbation

direction, but the Banach fixed-point theorem no longer guarantees uniqueness, and the first-order guarantees from part (a) cease to apply.

The intuition behind this three-regime picture is physical: a contractive system has a restoring force that pulls trajectories toward the equilibrium. Small perturbations shift the equilibrium smoothly (subcritical). As the perturbation approaches $\varepsilon_{\text{crit}}$, the restoring force weakens until the system becomes critically sensitive. Beyond $\varepsilon_{\text{crit}}$, the restoring force may vanish entirely, and the equilibrium can bifurcate or disappear.

Proof. Part (a). The Jacobian of F with respect to $\text{vec}(Z)$ takes the form $J_z = \text{diag}(\phi') \cdot (\hat{A} \otimes W)$ (column-major vectorization throughout), where $\phi' \in \{0, 1\}^{Nd}$ for ReLU (A1). The operator norm satisfies $\kappa = \|J_z\|_2 \leq \|\hat{A}\|_2 \cdot \|W\|_2 \cdot \sup |\phi'| = \|\hat{A}\|_2 \cdot \|W\|_2$. Applying the IFT to $G(z, A) = z - F(z, A) = 0$ at (z^*, A) :

$$\Delta z^* = (I - J_z)^{-1} J_A \cdot \text{vec}(\delta A) + O(\|\delta A\|^2). \quad (7)$$

Taking operator norms and using the Neumann series bound $\|(I - J_z)^{-1}\|_2 \leq 1/(1 - \kappa)$ (convergent because $\kappa < 1$) yields (6).

For contractivity preservation: the perturbed Jacobian satisfies $\|J'_z\|_2 \leq (\|A\|_2 + \|\delta A\|_F) \cdot \|W\|_2$ (using $\|\cdot\|_2 \leq \|\cdot\|_F$ for the perturbation). The condition $\varepsilon < (1 - \kappa)/\|W\|_2$ ensures $\|J'_z\|_2 < 1$. Note that $\varepsilon_{\text{crit}}$ is a Frobenius-norm sufficient condition: perturbation budgets are measured in $\|\cdot\|_F$, while κ is the operator norm $\|J_z\|_2$. The Frobenius norm exceeds the operator norm for rank- > 1 perturbations, so $\varepsilon_{\text{crit}}$ may be conservative by a factor up to $\sqrt{\text{rank}(\delta A)}$; the constrained projection S_c mitigates this by restricting to realistic perturbation directions.

Part (b). As $\varepsilon \rightarrow \varepsilon_{\text{crit}}$, we have $\|J'_z\|_2 \rightarrow 1$, so $\|(I - J'_z)^{-1}\|_2 \geq 1/(1 - \|J'_z\|_2) \rightarrow \infty$. Unlike the spectral-radius bound $1/(1 - \rho)$, which requires normality, the operator-norm bound holds for all J_z with $\kappa < 1$. In our experiments, the pseudospectral index η ranges from 1.02 to 1.28 (section V-F), confirming mild non-normality.

Part (c). When $\|J'_z\|_2 \geq 1$, the contraction mapping condition fails. The Banach theorem no longer guarantees existence or uniqueness; the iteration may converge to a different equilibrium, oscillate, or diverge. $\square$

Remark (conservativeness). The critical budget $\varepsilon_{\text{crit}}$ is a sufficient, not necessary, condition for contractivity preservation. The perturbed system may remain contractive beyond $\varepsilon_{\text{crit}}$ if the perturbation is aligned with low-sensitivity directions. The unconstrained bound uses worst-case $\|\cdot\|_F$ relaxation; for a rank- r constrained perturbation, $\|\delta A\|_F \leq \sqrt{r} \cdot \|\delta A\|_2$, so $\varepsilon_{\text{crit}}$ is conservative by a factor up to $\sqrt{|E|} \approx 7\text{--}14\times$ on our 50-node subgraphs. Under constrained perturbations, the first-order prediction achieves tightness ≈ 1.00 (section V-A). We use $\kappa = \|J_z\|_2$ rather than the spectral radius $\rho(J_z)$ because the Neumann series requires operator-norm contractivity [27]; for normal J_z the two coincide, while

for non-normal J_z the κ -based bound is more conservative but requires no normality assumption.

Proposition 2 (Optimal First-Order Structural Attack). *The perturbation δA^* maximizing $\|\Delta z^*\|$ to first order subject to $\|\delta A\|_F \leq \varepsilon$ is $\delta A^* = \varepsilon \cdot \text{reshape}(v_1, N \times N)$, where v_1 is the leading right singular vector of S . The maximum first-order shift is $\varepsilon \cdot \sigma_1(S)$.*

This result follows directly from the variational characterization of the largest singular value: the SVD of S identifies the perturbation direction that amplifies the equilibrium shift most efficiently.

Constrained sensitivity. Under the threat model of section II (symmetric, edge-only, $\|\delta \hat{A}\|_F \leq \varepsilon$), we construct the *constrained sensitivity matrix* $S_c \in \mathbb{R}^{Nd \times |E|}$ with column

$$[S_c]_{:,k} = S_{:,iN+j} + S_{:,jN+i} \quad (8)$$

for each edge $(i, j) \in E$. This reduces the perturbation space from N^2 dimensions to $|E|$ dimensions and enforces symmetry by construction. The constrained-optimal attack uses $\sigma_1(S_c)$, achieving tightness ≈ 1.00 empirically (section V-A). The construction of S_c is the central technical contribution of this work: it transforms unconstrained sensitivity analysis into a tight, practical tool for realistic graph perturbations.

Proposition 3 (Per-Node First-Order Sensitivity Radius). *Assume a linear classification head $f(z) = Wz + b$ (as in standard IGNN). For node v with margin $m_v = f_{y_v}(z_v^*) - \max_{c \neq y_v} f_c(z_v^*) > 0$, the first-order sensitivity radius is*

$$r_v = \frac{m_v}{\|W_{y_v} - W_{c^*}\|_2 \cdot \|S_v\|_2}, \quad (9)$$

where S_v denotes the block-rows of S corresponding to node v , W_{y_v} and W_{c^*} are the classification weight vectors for the predicted class y_v and runner-up class c^* , respectively. Any perturbation with $\|\delta \hat{A}\|_F < r_v$ preserves the classification of node v to first order. Under the constrained threat model (section II), a tighter radius $r_v^{(c)} = m_v / (\|W_{y_v} - W_{c^*}\|_2 \cdot \|S_{c,v}\|_2)$ holds, where $S_{c,v}$ denotes the block-rows of S_c for node v ; since $\|S_{c,v}\|_2 \leq \|S_v\|_2$, we have $r_v^{(c)} \geq r_v$. Our experiments report the conservative unconstrained r_v .

The radius r_v has an intuitive interpretation: it is the classification margin m_v (how confident the model is) divided by the product of two amplification factors. The term $\|W_{y_v} - W_{c^*}\|_2$ measures how sensitive the decision boundary is to hidden-state changes, while $\|S_v\|_2$ measures how sensitive node v 's equilibrium position is to structural perturbation. Nodes with large margins and low sensitivity receive large radii; boundary nodes in structurally sensitive positions receive small ones.

Proof sketch. By Theorem 1(a), $\Delta z_v^* \approx S_v \cdot \text{vec}(\delta A)$, so $|\Delta f_{y_v}| \leq \|\partial f / \partial z_v^*\| \cdot \|S_v\| \cdot \|\delta A\|_F$. Misclassification requires $|\Delta f_{y_v}| \geq m_v$; inverting gives r_v . Note S_v already contains the $(I - J_z)^{-1}$ factor.

Certificate semantics. These radii are *deterministic-local* guarantees: they hold with certainty but are first-order approximations, locally tight for small ε but increasingly conservative

as perturbation magnitude grows. This is fundamentally different from *probabilistic-global* certificates such as randomized smoothing [5], which hold with probability $1 - \alpha$ but are valid for all perturbation magnitudes up to the certified radius. The two approaches are complementary: smoothing provides uniform probabilistic coverage (every node gets the same certificate); AEGIS provides structurally differentiated sensitivity measures that identify *which* nodes and edges are most vulnerable. We present the comparison as complementary rather than competitive in section V-B. Empirically, the first-order radii hold: 0% breach rate at $\varepsilon = 0.01$ and $< 1\%$ at $\varepsilon = 0.10$ (section V-C).

A. Continuous-to-Discrete Transfer

The vulnerability scores $v_k = \|[S_c]_{:,k}\|_2$ measure sensitivity to *continuous* edge-weight perturbations, while practical adversarial threats involve *discrete* edge removal (setting $\hat{A}_{ij} = 0$). The following result bridges this gap by showing that discrete damage is a scaled version of continuous vulnerability, with a remainder bounded by contractivity.

Proposition 4 (Continuous-to-Discrete Ranking Transfer). *Under (A1)–(A3), let $w_k = [\hat{A}]_{ij}$ denote the normalized weight of edge $k = (i, j) \in E$, $v_k = \|[S_c]_{:,k}\|_2$ the continuous vulnerability score, and $d_k = \|z^*(A) - z^*(A \setminus k)\|_2$ the discrete damage from full removal of edge k . Assume all single-edge removals are subcritical: $\sqrt{2} \max_k w_k < \varepsilon_{\text{crit}}$.*

(a) First-order bridge. *The discrete damage satisfies*

$$d_k = w_k \cdot v_k + R_k, \quad |R_k| \leq \frac{L_J}{2(1 - \kappa)^2} \cdot w_k^2, \quad (10)$$

where L_J is the Lipschitz constant of the state Jacobian J_z with respect to $\text{vec}(A)$.

(b) Ranking preservation. *For two edges k_1, k_2 with $v_{k_1} > v_{k_2}$ and $w_{k_1} \geq w_{k_2}$, we have $d_{k_1} > d_{k_2}$ whenever*

$$w_{k_1} < \frac{v_{k_1} - v_{k_2}}{L_J / (1 - \kappa)^2}. \quad (11)$$

Under uniform weights ($w_k = w$ for all k), $v_{k_1} > v_{k_2}$ implies $d_{k_1} > d_{k_2}$ whenever $w < \min_{k_1 \neq k_2} (v_{k_1} - v_{k_2}) \cdot (1 - \kappa)^2 / L_J$.

Proof. Part (a). Removing edge $k = (i, j)$ corresponds to the perturbation $\delta \hat{A}$ with $[\delta \hat{A}]_{ij} = [\delta \hat{A}]_{ji} = -w_k$ and zero elsewhere. By the S_c construction, the first-order equilibrium shift is $\Delta z^* \approx S_c \cdot (-w_k \cdot e_k) = -w_k \cdot [S_c]_{:,k}$, so $\|\Delta z^*\| \approx w_k \cdot v_k$.

For the remainder, define $g(t) = z^*(A + t \cdot \delta \hat{A}_k)$. By the IFT, g is differentiable with $g'(0) = S \cdot \text{vec}(\delta \hat{A}_k)$. By Taylor's theorem, $g(1) - g(0) = g'(0) + \frac{1}{2} g''(\xi)$ for some $\xi \in [0, 1]$. The second derivative $g''(t)$ involves the derivative of $(I - J_z(t))^{-1} J_A(t)$ with respect to t , which by the resolvent identity contributes a factor $\|(I - J_z)^{-1}\|_2^2 \leq 1/(1 - \kappa)^2$ times the rate of change of J_z with respect to A , bounded by $L_J \cdot \|\delta \hat{A}_k\|_F^2 = 2L_J w_k^2$. Combining gives $|R_k| = \|g(1) - g(0) - g'(0)\| \leq L_J w_k^2 / (2(1 - \kappa)^2)$.

Part (b). From part (a), $d_{k_1} - d_{k_2} \geq w_{k_1} v_{k_1} - w_{k_2} v_{k_2} - C(w_{k_1}^2 + w_{k_2}^2)$ where $C = L_J / (2(1 - \kappa)^2)$. Since $v_{k_1} > v_{k_2}$

and $w_{k_1} \geq w_{k_2}$, the first term is positive. The condition (11) ensures the first-order gap exceeds the second-order remainder. $\square$

Remark (ReLU non-differentiability). The remainder bound in part (a) requires Lipschitz continuity of J_z with respect to $\text{vec}(A)$ via the constant L_J . For ReLU activation, J_z is piecewise constant (the activation pattern $\phi' \in \{0, 1\}^{Nd}$ is locally fixed), so $L_J = 0$ within each linear region and the bound holds trivially. Across activation-pattern boundaries, J_z jumps discontinuously; however, the set of perturbation paths that cross a boundary has Lebesgue measure zero in $\mathbb{R}^{|E|}$ [26]. For generic perturbation directions (including the S_c -optimal direction, which is determined by the current activation pattern), the Taylor remainder in (10) holds with L_J interpreted as the piecewise-constant bound within the active linear region. Empirically, the ranking transfer $\tau > 0$ across 29 of 33 architecture–dataset combinations (table X) confirms that the piecewise-linear structure does not degrade the first-order bridge.

Interpretation. Part (a) shows that discrete damage is the edge weight w_k times the continuous vulnerability v_k , plus a remainder quadratic in the weight. On graphs with approximately uniform normalized weights (a property of regular-ish graphs after $D^{-1/2}AD^{-1/2}$ normalization), the factor w_k is nearly constant and the vulnerability ranking v_k directly predicts the discrete damage ranking. Part (b) quantifies when ranking transfer holds: the gap between vulnerability scores must exceed $C \cdot w^2/w = C \cdot w$, which is small when edge weights are small (sparse normalized adjacency). This explains our empirical observations (section V-H): models with near-uniform vulnerability scores (GCN-2, whose shallow depth limits sensitivity differentiation) fail the ranking condition, while models with larger gaps (GCN-4, GAT, APPNP) satisfy it. The constant L_J can be estimated as $\|W\|_2^2$ for IGNN-class operators (section V-F).

Relationship to existing sensitivity analysis. The individual mathematical ingredients of AEGIS are classical: the IFT resolvent $(I - J_z)^{-1}$ and its Neumann-series expansion are standard in matrix perturbation theory [27], the SVD characterization of optimal linear perturbation follows from the variational characterization of singular values, and the contraction-mapping threshold is the Banach fixed-point theorem. The contribution of AEGIS is not these individual tools but rather (i) the *constrained projection* S_c that reduces the N^2 -dimensional perturbation space to the $|E|$ -dimensional space of realistic graph perturbations, transforming vacuous unconstrained bounds into tight predictions; (ii) the three-output design (attacks, rankings, radii) from a single S_c computation; and (iii) the cross-architecture pipeline that applies this analysis to both implicit and explicit GNNs. The S_c construction is what makes first-order analysis practical under realistic constraints, and it has no precedent in the GNN robustness literature.

B. Generalization to Explicit GNNs

The sensitivity framework above is derived for implicit GNNs, which enjoy the strongest theoretical guarantees (critical budget, convergence regimes). The S_c construction itself, however, generalizes to any K -layer GNN whose message passing is differentiable with respect to edge weights, serving as a computational tool for vulnerability analysis.

Observation 5 (Structural Sensitivity for K -Layer GNNs). *Let $Z_K = g_K \circ \dots \circ g_1(X, A)$ be a K -layer GNN where each layer g_l is differentiable with respect to both its input and A . Define the unrolled sensitivity matrix*

$$S_K = \frac{\partial \text{vec}(Z_K)}{\partial \text{vec}(A)} = \sum_{l=1}^K \left(\prod_{k=l+1}^K J_z^{(k)} \right) J_A^{(l)}, \quad (12)$$

where $J_z^{(k)} = \partial g_k / \partial Z_{k-1}$ and $J_A^{(l)} = \partial g_l / \partial \text{vec}(A)$. Then:

(a) *The first-order shift bound $\|\Delta Z_K\|_F \leq \sigma_1(S_K) \cdot \|\delta A\|_F + O(\|\delta A\|^2)$ holds, with*

$$\sigma_1(S_K) \leq \sum_{l=1}^K \left(\prod_{k=l+1}^K \|J_z^{(k)}\|_2 \right) \|J_A^{(l)}\|_2. \quad (13)$$

(b) *The constrained construction S_c and per-node radius r_v (theorem 3) apply identically with S_K in place of S .*

For weight-tied models ($J_z^{(k)} = J_z$, $J_A^{(l)} = J_A$ for all k, l), the bound simplifies to $\sigma_1(S_K) \leq \|J_A\|_2 \cdot (1 - \kappa^K)/(1 - \kappa)$, which converges to the IGNN bound $\|J_A\|_2/(1 - \kappa)$ as $K \rightarrow \infty$.

What explicit GNNs gain and lack. From theorem 5, any GNN with edge-weight-differentiable message passing inherits the practical analysis tools: (i) the S_c construction, (ii) SVD-optimal attacks, (iii) per-edge vulnerability rankings, and (iv) per-node first-order sensitivity radii. The mathematical content of this observation is a direct application of the multivariate chain rule; the contribution is empirical, validating that the resulting rankings transfer to discrete edge removal across six architectures (section V-H). What explicit models *lack* is the critical budget $\varepsilon_{\text{crit}}$ and the three-regime convergence characterization of theorem 1, which require the contraction assumption (A3).

IV. AEGIS CONSTRUCTION

Translating the results of section III into a practical tool requires overcoming two computational barriers: the full sensitivity matrix $S \in \mathbb{R}^{Nd \times N^2}$ is too large to materialize, and the resolvent $(I - J_z)^{-1}$ is too expensive to form directly. The AEGIS pipeline addresses both through matrix-free computation.

A. Architecture Overview

AEGIS takes as input a trained GNN (any architecture whose message passing is differentiable with respect to edge weights) together with a target graph and produces three outputs: (i) a per-edge vulnerability spectrum ranking edges by adversarial impact, (ii) SVD-optimal attack perturbations,




Fig. 1: The AEGIS pipeline. The matrix-free formulation (Stages 2–4) operates via JVP/VJP queries without materializing S or S_c , enabling full-graph analysis (tested up to $N=7,650$).

and (iii) per-node first-order sensitivity radii. For contractive implicit GNNs (IGNN-class satisfying A1–A3), the pipeline additionally computes the critical budget $\varepsilon_{\text{crit}}$ and convergence diagnostics; these theoretical guarantees are specific to the implicit case. The pipeline consists of four stages executed sequentially, as illustrated in fig. 1.

B. Stage 1: Subgraph Extraction and Forward Pass

For subgraph-level analysis, AEGIS extracts a local BFS ego-subgraph centered on the target node and runs the model to convergence (implicit GNNs) or forward pass (explicit). Localization is justified empirically (section V-E). The matrix-free pipeline also supports full-graph analysis without subgraph extraction (section V-D).

C. Stage 2: Matrix-Free Sensitivity Computation

AEGIS requires the action of the constrained sensitivity operator S_c on vectors, without materializing the full matrix $S \in \mathbb{R}^{Nd \times N^2}$. For an edge perturbation vector $v \in \mathbb{R}^{|E|}$, the operator computes $S_c v = (I - J_z)^{-1} J_A P_c v$, where P_c maps edge weights to symmetric adjacency perturbations, J_A is the structural Jacobian, and $J_z = \partial F / \partial Z$ is the state Jacobian. Two ingredients make this matrix-free:

Neumann-series resolvent. The resolvent $(I - J_z)^{-1} b$ is evaluated via the truncated Neumann series $\sum_{k=0}^K J_z^k b$, which converges geometrically when $\kappa < 1$ (Assumption A3). Each term requires a single Jacobian-vector product (JVP) $J_z \cdot v$, computed via forward-mode automatic differentiation in $O(Nd)$ time. The depth K is set adaptively from a power-iteration estimate of κ , with early stopping when $\|J_z^k b\| < 10^{-6} \|b\|$.

Autograd structural JVPs. The adjacency Jacobian $J_A \cdot \text{vec}(\delta A)$ is computed as a single forward-mode JVP of F with respect to A in direction δA , avoiding the $O(N^2)$ finite-difference columns required by the dense path.

The adjoint operator $S_c^\top u$ is computed analogously using vector-Jacobian products (VJPs) and the adjoint Neumann series $(I - J_z^\top)^{-1}$.

For small subgraphs ($N \leq 200$), the dense path (forming J_z, J_A explicitly and solving via `torch.linalg.solve`) remains available and gives exact results.

D. Stage 3: Constrained Projection

The constraint projection P_c (section III) maps edge vectors to symmetric adjacency perturbations ($\delta A_{ij} = \delta A_{ji} = v_k$). In the matrix-free formulation, P_c is applied implicitly within the $S_c v$ operator, so S_c is never formed. This $N^2 \rightarrow |E|$ reduction is what enables tight first-order predictions (sections V-A and V-H).

E. Stage 4: Vulnerability Analysis

From S_c , AEGIS extracts three complementary outputs:

Optimal attack direction. A randomized SVD [15] of the S_c operator (using only matrix-vector products) yields the leading singular triplet (u_1, σ_1, v_1) . The first-order optimal perturbation is $\delta A^* = \varepsilon \cdot v_1$, achieving a shift of $\varepsilon \cdot \sigma_1(S_c)$. For small subgraphs where S_c is materialized, the standard deterministic SVD is used instead.

Per-edge vulnerability spectrum. For each edge $(i, j) \in E$, the vulnerability score $v_{ij} = \|[S_c]_{:,k}\|_2$ measures how much a unit perturbation of that edge shifts the equilibrium. Sorting edges by v_{ij} produces a vulnerability ranking that identifies structurally critical connections without running any attack.

Per-node first-order sensitivity radii. For node v with classification margin m_v (gap between the predicted and runner-up class logits), the sensitivity radius from theorem 3 is

$$r_v = \frac{m_v}{\|W_{y_v} - W_{c^*}\|_2 \cdot \|S_v\|_2}, \quad (14)$$

where S_v denotes the block-rows of S corresponding to node v , and W_{y_v}, W_{c^*} are the classification head weights for the predicted and runner-up classes. Any perturbation with $\|\delta \hat{A}\|_F < r_v$ preserves the classification of node v to first order (this is a local sensitivity guarantee, not a global certificate).

F. Computational Cost

Matrix-free pipeline. Each $S_c v$ or $S_c^\top u$ evaluation costs $O(K \cdot Nd)$, where K is the Neumann depth (set adaptively from κ ; typically $K = 20$ – 50 for $\kappa < 0.8$, up to ~ 340 for $\kappa \approx 0.96$). The randomized SVD performs $O((k+p) \cdot n_{\text{iter}})$ such evaluations, where k is the number of requested singular values, p the oversampling, and n_{iter} the power iterations. Per-edge vulnerability requires $|E|$ column evaluations, each at $O(K \cdot Nd)$. Memory is $O(Nd)$ per operation; no large matrix is stored.

Scalability. On a single NVIDIA RTX 4090 (24 GB), the matrix-free pipeline completes in 1.1s for $N=50$, 4.5s for $N=200$, 24s for $N=1,000$, and 78s for full Cora ($N=2,708$, $Nd=173,312$) using 1 GB GPU memory (section V-D). The dense path runs faster for $N \leq 100$ (0.7s at $N=50$) but exceeds 24 GB at $N=500$.

The matrix-free formulation removes the $O((Nd)^3)$ linear-solve bottleneck and the $O(N^3d)$ storage requirement that previously limited analysis to $N \approx 300$, enabling full-graph vulnerability analysis on graphs with thousands of nodes (validated up to $N=7,650$; section V-D).

V. EXPERIMENTS

We evaluate AEGIS on 9 datasets across 4 domains with 10 random seeds each (seeds: 42, 137, 271, 314, 1729, 2718, 3141, 5772, 6561, 9999). All experiments use PyTorch [28].

Implementation. IGNN [14]: input projection $U \in \mathbb{R}^{d_{in} \times 64}$, spectral-normalized $W \in \mathbb{R}^{64 \times 64}$ [18], readout head $\mathbb{R}^{64 \times C}$; operator $F(Z) = \text{ReLU}(\hat{A}ZW^\top + U(X))$; fixed-point iteration (max 50 steps, tolerance 10^{-5}); Adam optimizer (lr 0.01, weight decay 5×10^{-4}), early stopping on validation accuracy over 200 epochs. ContractiveGCN-PF: same architecture with 5 bus features and 2-head readout ($\Delta|V|$, $\Delta\theta$). Subgraph extraction: BFS from highest-degree node, capped at 50 nodes to guarantee connectivity. Randomized smoothing baseline: Gaussian $\sigma = 0.01$, 200 MC samples, Clopper-Pearson $\alpha = 0.001$. Mettack baseline: Meta-Self GCN surrogate on IGNN pseudo-labels, sign-corrected gradient for edge scoring.

Datasets. We use five graph benchmarks: Cora (2,708 nodes), Citeseer (3,327), and Pubmed (19,717) from the Planetoid collection [29]; Amazon Photo (7,650) from the Amazon co-purchase graphs [30]; and WikiCS (11,701) from Wikipedia-based benchmarks [31]. For power flow, we use four IEEE standard test cases [32]: case14 (14 buses), case30 (30), case57 (57), and case118 (118), with training data generated via PandaPower [33].

Notation. All formal bounds (theorem 1) and tables use the operator-norm contraction constant $\kappa = \|J_z\|_2$, estimated via power iteration. Since non-normality is mild across our datasets ($\eta = 1.02$ – 1.28 , section V-F), the κ -based bounds are at most 28% more conservative than spectral-radius bounds; we report κ as the primary quantity because the formal guarantees (theorem 1) require operator-norm contractivity. The κ -based $\varepsilon_{\text{crit}}$ is therefore a conservative but formally justified safety quantity; ρ -based estimates would be up to 28% less conservative but lack theoretical backing without normality. Since η is near unity across all datasets, the practical difference is moderate. The matrix-free pipeline (section IV) sets the Neumann-series depth adaptively from κ .

A. Cross-Domain Adversarial Analysis

We begin by validating that the constrained first-order prediction is accurate across domains. table II reports the tightness ratio (actual equilibrium shift divided by predicted shift at $\varepsilon = 0.01$), the attack advantage of AEGIS over random

TABLE II: Cross-domain adversarial analysis (IGNN, 10 seeds). κ : operator-norm contraction constant $\|J_z\|_2$. Tight.: actual/predicted shift ratio. AtkAdv: AEGIS damage / random damage. $\varepsilon_{\text{crit}}$: critical perturbation budget (theorem 1). Test Acc: full-graph accuracy (%). Cov%: fraction of nodes in the 50-node BFS subgraph with positive first-order radius $r_v > 0$ (i.e., correctly classified nodes in the subgraph).

Dataset	Test Acc	κ	Tight.	AtkAdv	$\varepsilon_{\text{crit}}$	Cov%
Cora	77.5 $\pm$ 1.7	.33 $\pm$.14	1.01 $\pm$.01	3.6 $\pm$.6	.66 $\pm$.15	81 $\pm$ 9
Citeseer	66.0 $\pm$ 0.7	.59 $\pm$.02	1.01 $\pm$.01	4.1 $\pm$.5	.41 $\pm$.02	83 $\pm$ 4
Pubmed	78.9 $\pm$ 0.7	.41 $\pm$.11	1.01 $\pm$.01	3.2 $\pm$.4	.59 $\pm$.11	74 $\pm$ 23
Amazon	94.8 $\pm$ 0.3	.14 $\pm$.02	1.00 $\pm$.00	3.8 $\pm$.2	.86 $\pm$.02	92 $\pm$ 4
WikiCS	77.9 $\pm$ 0.4	.34 $\pm$.04	1.00 $\pm$.01	3.8 $\pm$.4	.66 $\pm$.04	70 $\pm$ 3

TABLE III: Tightness degradation with increasing ε (10 seeds, S_c -optimal constrained perturbation). Flip%: fraction of nodes whose prediction changes.

Dataset	$\varepsilon=.01$	$\varepsilon=.05$	$\varepsilon=.10$	$\varepsilon=.20$
<i>Tightness (actual/predicted shift)</i>				
Cora	1.01 $\pm$.00	1.07 $\pm$.01	1.15 $\pm$.03	1.36 $\pm$.08
Citeseer	1.01 $\pm$.00	1.07 $\pm$.01	1.16 $\pm$.03	1.39 $\pm$.07
Pubmed	1.01 $\pm$.00	1.07 $\pm$.01	1.15 $\pm$.02	1.38 $\pm$.06
WikiCS	1.00 $\pm$.01	1.01 $\pm$.01	1.02 $\pm$.01	1.05 $\pm$.01
Amazon	1.00 $\pm$.00	1.01 $\pm$.00	1.03 $\pm$.01	1.07 $\pm$.01
<i>Prediction flip rate (%)</i>				
Cora	0.4 $\pm$ 0.8	0.6 $\pm$ 0.9	1.8 $\pm$ 2.4	5.8 $\pm$ 5.0
Citeseer	0.0 $\pm$ 0.0	0.6 $\pm$ 1.3	2.0 $\pm$ 2.4	3.0 $\pm$ 2.6
WikiCS	0.2 $\pm$ 0.6	0.4 $\pm$ 0.8	0.6 $\pm$ 0.9	1.2 $\pm$ 1.0

perturbation, and the coverage (fraction of nodes with positive first-order radius) across 50-node BFS ego-subgraphs.

Tightness is 1.00 ± 0.01 across all datasets at $\varepsilon = 0.01$. Tightness values ≥ 1 are expected: the first-order prediction underestimates the actual shift because the true response includes convex higher-order terms. First-order accuracy at small ε is mathematically expected; the contribution is that S_c makes this tractable under *constrained* perturbations ($N^2 \rightarrow |E|$ projection). table III shows how tightness degrades at larger budgets: the first-order prediction remains within 7% at $\varepsilon = 0.05$ and within 15% at $\varepsilon = 0.10$ on Cora/Citeseer, and within 7% at $\varepsilon = 0.20$ on Amazon Photo and WikiCS. Prediction flip rate stays below 2% at $\varepsilon \leq 0.10$ and below 6% at $\varepsilon = 0.20$. The attack advantage (3.2 – $4.1\times$ over random in table II) confirms that S_c identifies the most vulnerable perturbation directions. Coverage (Cov%) ranges from 70% to 92%, representing clean subgraph accuracy; only correctly classified nodes have positive margin.

Surrogate baseline. As a sanity check, we also compared against Mettack [4] (GCN [34] surrogate): AEGIS inflicts 3–10 $\times$ more damage at every budget (149/150 wins across $k = 1, \dots, 5$ edge removals, 3 datasets, 10 seeds; the single loss occurs at $k=1$ on WikiCS seed 5772, where Mettack’s surrogate gradient happens to select a higher-impact edge).

TABLE IV: Structured attack baselines (IGNN, 50-node subgraph, 10 seeds). AtkAdv: method damage / random damage at $\varepsilon = 0.01$.

Dataset	AEGIS	Degree	Spectral	Between.
Cora	3.50 ± 0.20	3.30 ± 0.20	2.37 ± 0.20	3.29 ± 0.19
Citeseer	4.23 ± 0.21	3.91 ± 0.17	2.72 ± 0.35	3.89 ± 0.16
WikiCS	4.02 ± 0.78	3.93 ± 0.76	1.62 ± 0.27	3.93 ± 0.76

However, this gap largely reflects surrogate-to-IGNN architectural mismatch rather than AEGIS’s analytical superiority alone: Mettack optimizes against a GCN surrogate, not the target IGNN. The more meaningful comparison is the adaptive attacker below, which accesses the same IFT gradients as AEGIS.

Structured baselines. To contextualize the attack advantage beyond random perturbation, we compare AEGIS against three structured baselines: degree-proportional (perturbation weight $\propto \max(d_i, d_j)$), spectral (top eigenvector of A restricted to existing edges), and edge-betweenness centrality. table IV reports the attack advantage (damage / random damage) at $\varepsilon = 0.01$.

AEGIS consistently achieves the highest attack advantage, outperforming degree-proportional by 6–8% and spectral by 48–148% (Wilcoxon signed-rank: AEGIS > degree in 10/10 seeds on all three datasets, $p < 0.001$). Degree and betweenness centrality are competitive for continuous perturbation, but under discrete edge removal (table VI), AEGIS is 2–4 $\times$ better and degree-ranked removal is worse than random on Cora. AEGIS captures model-specific sensitivity beyond graph topology: the SVD direction optimizes the equilibrium shift, while degree-based heuristics rely solely on structural position.

B. Radius Comparison: AEGIS vs. Smoothing

We compare AEGIS sensitivity radii against randomized smoothing [5] ($\sigma \in \{0.01, 0.05, 0.10, 0.15\}$, 1000 MC samples, 10 seeds). The two methods provide fundamentally different certificate types (see section III): smoothing gives probabilistic-global guarantees valid at any perturbation magnitude, while AEGIS gives deterministic-local sensitivity measures that are first-order tight but degrade with increasing ε . At $\sigma \leq 0.10$, smoothing radii are *constant* across all nodes ($r = \sigma \cdot \Phi^{-1}(p_{\text{lower}})$), yielding larger absolute values (0.123 vs. AEGIS’s 0.046 at $\sigma = 0.05$) but zero per-node differentiation. AEGIS radii are structurally informative: dense-region nodes get $r_v \approx 0.09$, boundary nodes $r_v \approx 0.01$. The two are complementary: practitioners should use smoothing for worst-case certification and AEGIS for vulnerability ranking and defense prioritization.

C. Comprehensive Attack Evaluation

We evaluate AEGIS against baselines spanning four quadrants: gradient-based vs. gradient-free, and same-objective (equilibrium shift) vs. different-objective (classification loss or discrete removal). This taxonomy ensures no comparison

TABLE V: Full attack comparison (IGNN, 50-node subgraph, 10 seeds). SVD: AEGIS optimal. Cls-PGD: classification-loss PGD (autograd, cross-entropy). Shift-PGD: equilibrium-shift PGD (IFT gradients, same objective as SVD—a solver validation, not an independent baseline). Flip%: prediction flip rate.

Dataset	ε	Equil. damage (ℓ_2)				Flip%	
		SVD	Cls	Shift	Rand	SVD	Cls
Cora	.01	.33 $\pm$.07	.28 $\pm$.06	.27 $\pm$.06	.10 $\pm$.02	0.4	0.0
Cora	.10	3.70 $\pm$.79	2.51 $\pm$.48	3.05 $\pm$.70	.97 $\pm$.25	1.8	1.2
Cite	.01	.40 $\pm$.06	.33 $\pm$.05	.34 $\pm$.05	.10 $\pm$.02	0.0	0.0
Cite	.10	4.63 $\pm$.71	2.97 $\pm$.42	3.35 $\pm$.57	1.01 $\pm$.15	0.2	1.4
Wiki	.01	.21 $\pm$.02	.06 $\pm$.01	.19 $\pm$.02	.05 $\pm$.01	0.2	0.2
Wiki	.10	2.10 $\pm$.22	.67 $\pm$.11	1.93 $\pm$.20	.53 $\pm$.09	0.6	0.4

shares both the optimization pathway and the objective with AEGIS.

SVD optimality. We first verify that the SVD direction is genuinely special, not an artifact of a flat sensitivity landscape. Sampling 1,000 random unit directions in $\mathbb{R}^{|E|}$ and evaluating $\|S_c d\|$ for each (10 seeds): the best random direction achieves only 0.45–0.49 $\times$ of $\sigma_1(S_c)$ across all datasets, and *zero* of 30 runs reach 90% of the SVD damage. The singular value gap $(\sigma_1 - \sigma_2)/\sigma_1 = 0.39$ –0.50 confirms v_1 occupies a narrow, well-separated cone. Additionally, an equilibrium-shift PGD attacker [35] using the same IFT gradients as AEGIS (50 steps, step size $\varepsilon/10$) achieves 72–92% of SVD damage (table V), confirming that PGD as an iterative solver cannot match the closed-form SVD solution.

Independent adaptive baseline. To avoid circularity, we implement a classification-loss PGD attacker that optimizes cross-entropy via standard autograd through the unrolled fixed-point iteration—a fundamentally different gradient signal (backpropagation through unrolled iterations, not the IFT resolvent) and a different objective (prediction flipping, not equilibrium shift). table V reports both equilibrium damage and prediction flip rate for all methods. AEGIS inflicts 15–70% more equilibrium damage than classification-loss PGD across all settings, while achieving comparable flip rates (0–1.8%). The SVD direction is effective for flipping predictions even though it optimizes a different objective.

Classification-gradient edge ranking. To test whether a classification-targeted attacker identifies the same vulnerable edges, we compute per-edge gradients $|\partial \mathcal{L}_{\text{CE}} / \partial A_{ij}|$ via autograd and compare the resulting ranking against the brute-force discrete ground truth (single-edge removal). The classification-gradient ranking is anti-correlated with discrete vulnerability on Cora ($\tau = -0.20$, vs. AEGIS’s +0.32) and near-zero elsewhere (Citeseer: -0.03 vs. +0.32; WikiCS: +0.05 vs. +0.14). P@10 for AEGIS is 2–6 $\times$ higher. The two methods identify genuinely different edges: cross-correlation τ is only +0.19 (Cora) to -0.06 (WikiCS), confirming that equilibrium sensitivity and classification sensitivity are distinct vulnerability surfaces.

Discrete edge removal. The strongest gradient-free test: we

TABLE VI: Cumulative damage from sequential discrete edge removal (IGNN, 50-node subgraph, 10 seeds). Greedy: brute-force optimal. Degree: by $\max(d_i, d_j)$.

Dataset	k	Greedy	AEGIS	Degree	Random
Cora	5	$3.36 \pm .68$	$1.80 \pm .44$	$0.90 \pm .19$	$1.27 \pm .25$
Cora	10	$4.08 \pm .82$	$2.75 \pm .66$	$1.48 \pm .28$	$2.02 \pm .36$
Citeseer	5	$5.27 \pm .87$	5.12 ± 1.2	$1.34 \pm .18$	$1.61 \pm .49$
Citeseer	10	$6.01 \pm .94$	$6.01 \pm .94$	$1.93 \pm .26$	$2.46 \pm .56$
WikiCS	5	$.14 \pm .01$	$.14 \pm .02$	$.09 \pm .01$	$.07 \pm .01$
WikiCS	10	$.23 \pm .02$	$.21 \pm .03$	$.12 \pm .01$	$.12 \pm .01$

TABLE VII: Breach rate (%) at increasing ε (IGNN, 50-node subgraph, 10 seeds). All observed breaches respect the first-order radii: every breached node has $\varepsilon > r_v$.

Dataset	$\varepsilon=.01$	$\varepsilon=.05$	$\varepsilon=.10$	$\varepsilon=.20$
Cora	0.6 ± 1.2	0.8 ± 1.3	2.4 ± 3.7	7.6 ± 7.5
Citeseer	0.0 ± 0.0	0.0 ± 0.0	0.2 ± 0.8	1.5 ± 2.4
Pubmed	0.0 ± 0.0	7.0 ± 8.3	10.3 ± 11.0	27.4 ± 21.1
WikiCS	0.3 ± 0.9	0.6 ± 1.3	0.9 ± 1.4	1.8 ± 1.5

remove edges sequentially and compare cumulative damage under four orderings—brute-force greedy-optimal (remove the most-damaging remaining edge at each step), AEGIS-ranked, degree-ranked, and random (table VI). On Citeseer/WikiCS, AEGIS matches or exceeds greedy-optimal (95–101% at $k=5$). On Cora, AEGIS reaches 54% of greedy, reflecting the cascade effects that static rankings cannot capture. Crucially, degree-ranked removal is *worse than random* on Cora at every k : removing high-degree edges first is the least disruptive strategy because hub nodes have redundant connections. This contrasts with table IV, where degree-proportional *continuous* perturbation is within 6–8% of AEGIS; for discrete removal, AEGIS is 2–4 $\times$ better.

Numerical validation. Per-edge finite-difference sensitivity ($\delta = 0.001$, $|E|$ forward passes) reproduces the S_c column-norm ranking exactly ($\tau = 0.999$ across all datasets), confirming numerical correctness of the IFT computation. The resolvent $(I - J_z)^{-1}$ amplifies all edges uniformly and thus does not change the per-edge ranking; S_c ’s unique value is the global SVD structure (optimal attack direction, unreachable by random search) and the matrix-free scalability that avoids $|E|$ forward passes at large N .

Breach rates. table VII reports the fraction of nodes whose prediction changes under the S_c -optimal attack at increasing ε .

Breach rates are below 1% at $\varepsilon = 0.01$ across all datasets. At $\varepsilon = 0.20$, rates range from 1.5% (Citeseer) to 27.4% (Pubmed), reflecting expected first-order degradation. The Pubmed distribution is right-skewed (median 7.8%, IQR [0.6%, 16.7%] at $\varepsilon = 0.10$; 3 of 10 seeds show 0% breach), so the mean overstates typical behavior. All breaches respect the first-order radii: every breached node has $\varepsilon > r_v$.

TABLE VIII: Scalability: dense vs. matrix-free pipeline (RTX 4090, 24 GB). OOM = out of memory. Mem = peak GPU memory.

N	Dense (s)	MatFree (s)	Mem-Dense	Mem-MF
50	0.7	1.1	343 MB	92 MB
200	5.4	4.5	8.9 GB	129 MB
500	OOM	11	>24 GB	207 MB
1,000	OOM	24	>24 GB	373 MB
2,708	OOM	78	>24 GB	1.1 GB
7,650	OOM	363	>24 GB	6.5 GB
19,717	OOM	OOM	>24 GB	>24 GB

D. Phase Transition and Scalability

Phase transition. To empirically validate theorem 1, we train IGNN on Cora with the spectral normalization ceiling varying from $\kappa_{\max} = 0.30$ to 0.99 (10 seeds each). The theoretical critical budget $\varepsilon_{\text{crit}} = (1 - \kappa) / \|W\|_2$ drops 230 $\times$ from 2.33 to 0.01, confirming the predicted sensitivity explosion. However, the actual spectral radius $\rho(J_z)$ saturates at ≈ 0.42 even at $\kappa_{\max} = 0.99$: the ReLU activation pattern prevents the Jacobian from reaching its theoretical maximum. The resolvent norm $\|(I - J_z)^{-1}\|_2$ increases from 1.17 to 1.80 (1.5 $\times$), not the $\sim 70\times$ that $1/(1 - 0.99)$ would predict, because the *actual* κ remains well below the ceiling. This finding is practically important: it means IGNN’s empirical vulnerability grows modestly with relaxed spectral constraints, even as the theoretical worst case diverges. The phase transition is thus a *theoretical safety boundary* rather than an empirically observable discontinuity, analogous to how worst-case complexity bounds rarely match typical-case behavior.

Scalability. The matrix-free pipeline removes the $O((Nd)^3)$ bottleneck. On a single NVIDIA RTX 4090 (24 GB), the dense path handles $N \leq 200$ (5.4s, 8.9 GB) but exceeds 24 GB at $N=500$. The matrix-free path scales to full Cora ($N=2,708$) in 78 s / 1 GB and to Amazon Photo ($N=7,650$) in 363 s / 6.5 GB, with σ_1 accuracy within 0.03% of the dense reference at $N=200$. Pubmed ($N=19,717$) exceeds 24 GB, establishing the current scalability boundary at $N \approx 7,650$ on a single GPU. table VIII compares both paths.

E. Subgraph Size Ablation

Varying $N \in \{30, 50, 100, 200\}$ on Cora (10 seeds): tightness is stable at 1.01–1.02 for $N \leq 100$ and degrades to 1.031 at $N = 200$ (higher κ). Coverage is 82–89% across all sizes. We use $N = 50$ (tightness 1.013 ± 0.003 , 1.3s) as the default for subgraph-level experiments: 66 $\times$ faster than $N = 200$ with negligible quality loss. For full-graph analysis, the matrix-free pipeline (table VIII) enables vulnerability assessment of the entire graph without subgraph extraction. To validate that subgraph extraction preserves vulnerability rankings, we compare per-edge S_c rankings from BFS subgraphs against full-graph rankings on IEEE case14 and case30 (10 seeds). On case14, Kendall τ between subgraph and full-graph rankings is 0.80 ± 0.14 at $N_{\text{sub}}=8$ (57% of nodes) and 0.86 ± 0.06 at $N_{\text{sub}}=12$ (86%); $P@5 \geq 0.90$ at all sizes. On case30,

$\tau = 0.78 \pm 0.07$ at $N_{\text{sub}}=10$ (33% of nodes) with $P@5 = 0.96 \pm 0.08$, remaining stable through $N_{\text{sub}}=25$. The locality assumption underlying subgraph extraction thus holds well for power grids (small, dense graphs where a 50-node BFS covers 33–86% of nodes), but weakens substantially on larger citation networks. On Cora ($N=2,708$), comparing 50-node BFS subgraph rankings against full-graph matrix-free rankings (10 seeds) yields Kendall $\tau = 0.16 \pm 0.13$ with $P@10 = 0.17 \pm 0.10$. The low correlation reflects that a 50-node subgraph covers only $\sim 1.8\%$ of Cora’s edges, so the subgraph’s local view misses graph-wide vulnerability patterns. For citation-scale graphs, practitioners should prefer the matrix-free full-graph pipeline (table VIII) over subgraph extraction; the subgraph approach remains appropriate for dense graphs where coverage is high (power grids, molecular graphs) or when full-graph analysis exceeds available memory.

F. Sensitivity and Convergence

Hyperparameters. Tightness is stable across $d \in \{16, 32, 64, 128\}$ (1.012–1.013). Varying $c \in \{0.5, 0.7, 0.9, 0.95\}$ reveals the predicted accuracy-robustness tradeoff: $c = 0.5$ gives $r_v = 0.090$ (72.1% acc); $c = 0.9$ gives $r_v = 0.051$ (80.6% acc).

Convergence. 100% convergence across all 9 datasets and 10 seeds. Pseudospectral index $\eta = 1.02$ –1.28, confirming mild non-normality and validating the κ -based bounds.

G. Defense-Informed Edge Protection

We evaluate vulnerability-aware protection: mask the top- k edges by v_{ij} from the perturbation space, then re-run the SVD attack on the reduced S_c . On Cora (IGNN, $N = 50$, 10 seeds): masking the top-5 edges reduces SVD attack damage by $42 \pm 8\%$ vs. $11 \pm 6\%$ for random 5-edge masking. At top-10: $61 \pm 7\%$ vs. $18 \pm 9\%$. AEGIS identifies edges whose removal disproportionately reduces vulnerability.

H. Extension to Explicit GNNs

A key question is whether the S_c framework extends beyond implicit models. For a K -layer explicit GNN, there is no equilibrium, but the hidden representation Z_K is still a differentiable function of A . We define the *unrolled sensitivity matrix* $S_K = \partial \text{vec}(Z_K) / \partial \text{vec}(A)$ (computed via finite differences on the forward pass), construct S_c from S_K identically to the IGNN case, and apply the same SVD attack and vulnerability ranking.

table IX applies the S_c framework to six explicit GNN architectures on Cora. All six achieve near-perfect first-order tightness (0.99–1.02), confirming that constrained sensitivity analysis generalizes beyond implicit models. Attack advantage ranges from $2.0\times$ (SAGE) to $7.6\times$ (IGNN), showing that S_c identifies the most vulnerable perturbation directions across all architectures. Test accuracy ranges from 76.6% (GIN) to 82.2% (APPNP). $\text{GAT}^\dagger$ and GCN-4 produce the strongest vulnerability rankings ($\tau = +0.54$ and $+0.49$). APPNP achieves the best accuracy-vulnerability balance ($\tau = +0.35$, 82.2% accuracy).

TABLE IX: S_c framework applied to 7 GNN architectures (Cora, 10 seeds). Tight.: actual/predicted shift ratio. AtkAdv: AEGIS/random damage. τ : Kendall rank correlation of continuous S_c vulnerability scores vs. discrete single-edge-removal ground truth (brute-force). Test Acc: full-graph accuracy. $\text{GAT}^\dagger$: edge-weighted variant for continuous differentiability (see text).

Model	Tight.	AtkAdv	τ	Test Acc
IGNN (equil.)	1.01 $\pm$.00	7.6 $\pm$ 0.5X	+0.32 $\pm$.04	77.5 $\pm$ 1.7%
GCN-2	1.00 $\pm$.00	3.6 $\pm$ 0.6X	−0.04 $\pm$.03	78.9 $\pm$ 0.9%
GCN-4	1.02 $\pm$.00	3.4 $\pm$ 0.4X	+0.49 $\pm$.02	78.3 $\pm$ 1.8%
GIN-2	1.01 $\pm$.00	2.6 $\pm$ 0.1X	+0.33 $\pm$.03	76.6 $\pm$ 1.9%
$\text{GAT}^\dagger$	1.01 $\pm$.01	2.1 $\pm$ 0.1X	+0.54 $\pm$.06	77.8 $\pm$ 1.2%
SAGE-2	1.00 $\pm$.00	1.9 $\pm$ 0.2X	+0.22 $\pm$.10	77.5 $\pm$ 1.5%
APPNP	1.02 $\pm$.00	3.4 $\pm$ 0.3X	+0.35 $\pm$.01	82.2 $\pm$ 0.6%

Accuracy-vs-guarantee frontier. The results reveal a trade-off: IGNN (77.5% accuracy) provides the full theoretical apparatus (theorem 1: $\varepsilon_{\text{crit}}$, three regimes, convergence guarantees), while higher-accuracy models like APPNP (82.2%) receive only the computational tool (S_c rankings, SVD attacks, first-order radii) without formal regime characterization. Practitioners may choose IGNN when formal guarantees are required (e.g., safety-critical applications where $\varepsilon_{\text{crit}}$ serves as a deployment criterion) or higher-accuracy explicit models when the practical vulnerability ranking suffices. This trade-off is inherent to contractive architectures: spectral normalization constrains model capacity to ensure well-posedness, and higher κ values (approaching 1) yield better accuracy but weaker formal guarantees. The S_c framework itself is architecture-independent; theorem 1 provides *qualitative* insight about vulnerability phase transitions that informs analysis of all architectures, even though the *quantitative* bounds apply only to implicit models.

GAT requires an edge-weighted formulation for continuous differentiability. Standard GAT computes attention $\alpha_{ij} = \text{softmax}_j(\text{LeakyReLU}(a^\top [Wh_i \| Wh_j]))$ and aggregates as $h'_i = \sum_{j \in \mathcal{N}(i)} \alpha_{ij} Wh_j$, using A as a binary mask that zeros non-edges, so $\partial Z / \partial A_{ij} = 0$ for all existing edges. Our edge-weighted variant, $\text{GAT}^\dagger$, modulates attention by the edge weight:

$$h'_i = \sum_{j \in \mathcal{N}(i)} \hat{A}_{ij} \cdot \alpha_{ij} \cdot Wh_j, \quad (15)$$

restoring continuous differentiability with respect to $\hat{A}_{ij}$. GATv2 [36] partially addresses this via dynamic attention but still applies a binary mask at the neighborhood level. With the $\text{GAT}^\dagger$ modification, GAT achieves tightness 0.99, attack advantage $4.4\times$, and $\tau = +0.36$.

Cross-dataset continuous-to-discrete transfer. To validate that continuous-to-discrete transfer is not Cora-specific, we evaluate τ across all 5 datasets and 7 architectures (330 runs total, 10 seeds each; table X). Positive τ is observed in 29 of 33 dataset-architecture combinations. Transfer is strongest on Pubmed (IGNN: $+0.82$, GCN-4: $+0.89$, APPNP: $+0.83$, all with $P@10 = 1.0$), moderate on Citeseer ($\text{GAT}^\dagger$:

TABLE X: Continuous-to-discrete transfer τ across 5 datasets and 7 architectures (10 seeds each, 330 runs total). Bold: best per dataset. —: GPU OOM (GAT attention on $N > 10,000$).

Model	Cora		Citeseer		Pubmed		WikiCS	
	τ	P@10	τ	P@10	τ	P@10	τ	P@10
IGNN	+0.32 $\pm$.04	.19	+0.31 $\pm$.04	.93	+0.82 $\pm$.02	1.0	+0.14 $\pm$.04	.50
GCN-2	−0.03 $\pm$.03	.09	−0.28 $\pm$.07	.06	+0.21 $\pm$.01	.26	+0.05 $\pm$.03	.33
GCN-4	+0.49 $\pm$.02	.32	+0.64 $\pm$.02	.87	+0.89 $\pm$.01	1.0	+0.45 $\pm$.10	.56
GIN-2	+0.33 $\pm$.04	.26	+0.57 $\pm$.03	.81	+0.54 $\pm$.33	.60	+0.63 $\pm$.08	.70
GAT [†]	+0.54 $\pm$.06	.54	+0.66 $\pm$.03	.63	—	—	—	—
SAGE-2	+0.22 $\pm$.11	.15	+0.38 $\pm$.18	.45	+0.36 $\pm$.10	.58	+0.22 $\pm$.04	.55
APPNP	+0.35 $\pm$.02	.36	+0.36 $\pm$.06	.96	+0.83 $\pm$.01	1.0	+0.22 $\pm$.03	.56

+0.66, GCN-4: +0.64), and weaker on WikiCS and Amazon Photo. On Amazon Photo, IGNN shows negative τ (−0.15) on 50-node subgraphs. We investigate three contributing factors. (i) *Subgraph artifact*: the 50-node BFS subgraph has $\|\hat{A}_{\text{sub}}\|_2 = 0.20$, capping $\kappa_{\text{sub}} \leq 0.20$ regardless of $\|W\|_2$; a κ -sweep from 0.5 to 0.99 confirms τ remains negative on the subgraph (all 20 runs, mean $\tau = -0.12$). Full-graph matrix-free analysis ($N=7,650$, $\rho = 0.73$, resolvent amplification $3.9\times$) partially recovers: column-based τ shifts from −0.14 (subgraph) to +0.03 (full graph), with one of three seeds reaching $\tau = +0.24$. (ii) *Weak signal*: Amazon Photo’s high average degree (~ 31) makes single-edge removal damage near-uniform, reducing the signal-to-noise ratio for any ranking method. (iii) *Architecture-specific*: explicit GNNs without the contraction constraint achieve strong transfer on the same dataset (SAGE-2: $\tau = +0.60$, APPNP: +0.43), confirming that the S_c framework itself is not the bottleneck. For dense graphs where IGNN’s subgraph κ is low, practitioners should prefer explicit-GNN alternatives or full-graph matrix-free analysis. GCN-2 shows weak or negative τ on 3 of 5 datasets (−0.03 Cora, −0.28 Citeseer), confirming the shallow-depth hypothesis: models with larger receptive fields consistently produce better transfer. The best architecture varies by dataset (GAT[†] on Cora/Citeseer, GCN-4/APPNP on Pubmed, GIN-2 on WikiCS, SAGE-2 on Amazon Photo), suggesting that the relationship between continuous sensitivity and discrete impact depends on how well the model’s aggregation pattern captures local connectivity structure.

The τ column in table IX directly measures whether continuous S_c vulnerability scores predict discrete edge-removal impact. theorem 4 provides the formal justification: discrete damage $d_k = w_k \cdot v_k + O(w_k^2)$, so the continuous ranking v_k predicts the discrete ranking when the first-order gap between edges exceeds the second-order remainder. Positive τ across 6 of 7 architectures (+0.22 to +0.54) validates this first-order bridge empirically. The one exception is GCN-2 ($\tau = -0.04$). We attribute this to the interaction between shallow depth and the continuous-discrete gap: a 2-layer GCN aggregates only 2-hop neighborhoods, so continuous edge-weight changes produce nearly uniform first-order shifts across edges with similar endpoint degrees, yielding poor rank discrimination.

Under discrete removal (a non-infinitesimal perturbation), the impact depends on higher-order network effects (path redundancy, component connectivity) that the 2-layer model cannot capture in its first-order sensitivity. Deeper models (GCN-4: $\tau = +0.49$) and models with global receptive fields (APPNP: $\tau = +0.35$) show substantially better transfer, suggesting that continuous-to-discrete transfer improves with model depth and receptive field size.

Comparison with gradient attribution. Against the same brute-force discrete ground truth, gradient-based edge attribution [67], [38] produces consistently negative τ (−0.07, −0.17, −0.23 for IGNN, GCN-2, GIN-2 respectively). Gradient methods optimize for prediction fidelity rather than adversarial vulnerability.

Proposition 5 bound tightness. The ratio (Prop. 4 bound)/ $\sigma_1(S_K)$ ranges from $1.4\times$ (SAGE-2) to $5.9\times$ (APPNP), with 2-layer models achieving tighter ratios (GCN-2: $1.8\times$, GIN-2: $2.1\times$) than deeper ones (GCN-4: $4.2\times$, GAT-2: $3.7\times$). The looseness in deeper models reflects direction-dependent cancellations that the norm product overestimates.

Degree-vulnerability correlation. To assess whether S_c merely recapitulates graph topology, we compute the Kendall τ between per-edge vulnerability v_{ij} and endpoint degree $\max(d_i, d_j)$ across all datasets and architectures. The correlation varies substantially: strong on Citeseer (IGNN: $\tau = +0.63$), moderate on Cora (+0.43) and Pubmed (+0.38), and weak on WikiCS (IGNN: +0.27, GCN-2: −0.10). This variation confirms that S_c captures model-specific sensitivity beyond degree centrality: on WikiCS (a large, heterogeneous graph), degree is a poor predictor of vulnerability. Weighting S_c columns by endpoint degree does not improve ranking: uniform $\tau = +0.042$, degree-weighted +0.037, inverse-degree −0.008 (GCN-2, 10 seeds).

The S_c framework thus generalizes to GNNs with continuous edge-weight-modulated message passing. The theoretical guarantees (theorem 1: critical budget, convergence) remain specific to contractive implicit GNNs, but the practical vulnerability analysis (SVD attacks, rankings, first-order sensitivity radii) transfers broadly.

VI. CASE STUDY: POWER FLOW CONTINGENCY

The experiments above validate AEGIS on classification benchmarks. We now test whether the vulnerability spectrum captures domain-specific structure by applying it to AC power flow, where the spectrum recovers a classical engineering problem: N-1 contingency analysis. Recent work has applied GNNs to power flow computation [39], [40] and contingency screening [3]; AEGIS approaches the same problem from the vulnerability-analysis perspective.

A. Background: N-1 Contingency

Power grid operators must ensure that no single transmission line failure causes system instability. The standard N-1 contingency assessment removes each line in turn, re-solves the power flow equations, and ranks lines by the severity of the resulting voltage and flow deviations [41]. This brute-force

TABLE XI: AEGIS on IEEE power flow benchmarks (10 seeds). Model quality (per-unit RMSE): $|V|$ = voltage magnitude, θ = angle. τ : Kendall rank correlation vs. brute-force N-1 contingency. P@10: top-10 precision.

Case	N	$ E $	Model (p.u.)		AEGIS	
			$ V $	θ	τ	P@10
case14	14	20	.007	.020	$+.42_{\pm.19}$	$.74_{\pm.12}$
case30	30	41	.014	.024	$+.37_{\pm.17}$	$.68_{\pm.06}$
case57	57	78	.033	.059	$+.67_{\pm.09}$	$.66_{\pm.13}$
case118	118	179	.014	.076	$+.62_{\pm.11}$	$.81_{\pm.10}$
case300 [‡]	300	411	.031	.394	$+.72_{\pm.03}$	$.87_{\pm.06}$

[‡]200-node BFS subgraph; 1,000 training samples (dense analysis OOMs at $N > 200$).

procedure scales as $O(|E|)$ full power flow solves, which is expensive for large grids and infeasible for real-time operation.

We observe that AEGIS’s per-edge vulnerability $v_{ij} = \|[S_c]_{:,k}\|_2$ computes an analogous quantity via a single IFT analysis: edge perturbation maps to line trips, the vulnerability spectrum maps to contingency severity, and critical budget $\varepsilon_{\text{crit}}$ maps to a model sensitivity threshold (a mathematical property of the IGNN model, distinct from physical voltage or transient stability margins). The correspondence is approximate (continuous first-order vs. discrete removal), analogous to how PTDF/LODF [41] linearize the effect of line trips.

B. Experimental Setup

We train ContractiveGCN-PF, an IGNN variant for AC power flow, on five IEEE test cases [32] including a 300-bus system to address scalability concerns. Training data is generated via PandaPower’s [33] full AC Newton-Raphson solver (2,000 load samples per case, uniformly sampled at 70–130% of nominal load). The model takes binary adjacency from the admittance matrix and 5 bus features: bus type indicators (slack, PV), active and reactive power injections (P, Q), and voltage magnitude $|V|$. For case14–118 (14–118 buses), full-graph dense analysis is used. For case300 (300 buses), a 200-node BFS subgraph is extracted because the dense S_c computation exceeds GPU memory at $N > 200$.

Limitation. Training data covers uniform load scaling (2,000 samples) but not seasonal or generator-outage variation.

C. Results

table XI reports constrained tightness and N-1 ranking correlation (Kendall τ between AEGIS vulnerability spectrum and brute-force contingency ranking) across 10 seeds.

Key observations. First, tightness transfers to the power flow domain (≈ 1.00), confirming that the first-order prediction is not domain-specific. Second, ranking correlation ($\tau = 0.37$ – 0.72) is moderate to strong and the operationally relevant P@10 is 0.66–0.87, identifying 7–9 of the top 10 critical lines. Notably, case300 achieves $\tau = +0.72$ and P@10 = 0.87 using a 200-node subgraph, demonstrating that AEGIS scales to grids beyond the 118-bus systems used in prior work.

Baseline comparison and timing. LODF (industry-standard DC screening [41]) achieves $\tau = 0.44$ – 0.58 ; AEGIS

outperforms on larger grids ($\tau = 0.62$ – 0.67 on case57/118) by capturing nonlinear AC effects. LODF computes in < 0.13 s (analytic formula from line reactances); AEGIS requires training (2–10 s) plus S_c computation (0.2–13 s), totaling 2–23 s per case (case300: 23 s with 200-node subgraph). Brute-force N-1 takes 0.1–2 s. AEGIS is thus slower than LODF but provides richer output (vulnerability spectrum, SVD attacks, sensitivity radii) without requiring line-impedance data.

N-2 contingency connection. The leading singular vector v_1 of S_c naturally identifies multi-edge vulnerabilities. Extracting the top-5 edges from $|v_1|$ and checking their pairwise impact against brute-force N-2 ground truth: edge-level overlap is 40–64% (edges from the SVD direction appear in the ground-truth critical N-2 pairs), with stronger overlap on larger grids (case118: 64%). Pair-level overlap is lower (7–18%) because the SVD direction captures the *most damaging direction* rather than specific pairs, but the constituent edges are individually critical.

Rank stability. Pairwise Kendall τ of AEGIS vulnerability rankings across 10 seeds: $+0.40 \pm 0.29$ (case14), $+0.34 \pm 0.24$ (case30), $+0.78 \pm 0.07$ (case57), $+0.67 \pm 0.12$ (case118). Rankings are more stable on larger grids where the topology is richer. On case118, 60% of the top-10 edges appear in every seed’s top-10, and 90% appear in $\geq 80\%$ of seeds.

Binary vs. admittance-weighted adjacency. Binary adjacency outperforms admittance-weighted (P@10 = 0.81 vs. 0.27 on case118). Spearman correlation between admittance magnitude and N-1 severity is near zero across all cases (-0.01 to $+0.15$), confirming that high-admittance lines are not preferentially critical. This reflects the discrete nature of N-1: a line trip fully removes the line regardless of its impedance, so binary sensitivity (uniform per edge) correctly models the all-or-nothing character. Effective-resistance on the binary graph shows moderate correlation with severity ($\tau = +0.49$ on case14/30), consistent with graph-theoretic contingency screening.

Operational caveat. AEGIS is a screening layer, not a standalone contingency tool ($\tau = 0.37$ – 0.67 is insufficient for direct operational use).

VII. RELATED WORK

We position AEGIS against four research threads.

Adversarial attacks on graph structure. Nettack [1] and Mettack [4] demonstrated structural vulnerability via targeted and global poisoning using GCN [34] surrogates. Subsequent work explored RL-based [2], spectral [42], and bilevel [43] formulations; Wu et al. [44] survey the landscape. Gosch et al. [45] identify pitfalls in adversarial training for GNNs. These methods use surrogate gradients or heuristic search. AEGIS instead computes the closed-form optimal attack direction via SVD of S_c .

Certified robustness and defense. Convex relaxations [8], [7], randomized smoothing [5], [6], and deterministic certificates [46], [47] provide robustness guarantees but do not identify *which* edges are vulnerable. Schuchardt et al. [48] extend smoothing to localized per-node certificates. Empirical

defenses [10], [12], [11] harden models without formal vulnerability maps. AEGIS complements both by providing per-edge rankings and per-node radii that reveal the attack surface geometry (section V-B).

Implicit networks and equilibrium analysis. The DEQ framework [16] introduced fixed-point models; IGNN [14] enforces unique equilibria via spectral normalization [18]; EIGNN [49] improves efficiency. For robustness, monotone operator networks [50] provide built-in Lipschitz bounds, and El Ghaoui et al. [24] analyze well-posedness. All address input sensitivity $\|\partial z^*/\partial x\|$, not structural sensitivity $\|\partial Z/\partial A\|$. AEGIS addresses structural sensitivity via the resolvent $(I - J_z)^{-1}J_A$ for implicit models (theorem 1) and the unrolled Jacobian S_K for explicit ones (theorem 5).

Sensitivity analysis and explainability. Stability of graph neural networks under perturbation has been studied from a signal-processing perspective [51]. AEGIS draws on matrix perturbation theory [27], [22]. GNN explanation methods (GNNExplainer [38], PGExplainer [52], gradient-based [37]) optimize for *prediction fidelity*, not adversarial vulnerability: they identify edges important for a correct prediction, while AEGIS identifies edges whose perturbation maximally damages predictions. AEGIS’s S_c is perturbation-space optimal by construction (SVD) and provides quantitative sensitivity radii. Our case study (section VI) connects to GNN-based power flow [39], [40], [53] and contingency screening [3].

Over-smoothing and depth. Deep GNNs suffer from over-smoothing [54], which GRAND/GRAND++ [55], [56] address via continuous-depth diffusion. Entezari et al. [57] and Mujkanovic et al. [58] show that many adversarial attacks fail against simple defenses or are artifacts of evaluation. AEGIS sidesteps this debate by analyzing the model’s own sensitivity surface rather than searching for attacks via surrogates.

VIII. CONCLUSION

AEGIS provides a principled pre-deployment diagnostic for GNNs on safety-critical graphs: from a single S_c computation, practitioners obtain the optimal attack direction, per-edge vulnerability rankings, and per-node tolerance budgets. Predictions are tight across 7 architectures and 9 datasets (tightness 1.00 ± 0.01 at $\varepsilon = 0.01$), and the vulnerability spectrum transfers to power grid contingency analysis ($P@10 = 0.66\text{--}0.81$). The per-edge ranking directly informs defense design (section V-G).

Limitations. (1) First-order sensitivity radii are locally tight but not global certificates without second-order bounds. (2) Continuous edge-weight perturbations; discrete insertions/deletions are outside the formal guarantee, though continuous S_c rankings transfer well to discrete removal ($\tau = +0.22\text{--}+0.54$; table IX). (2b) On dense graphs (e.g., Amazon Photo, avg. degree ~ 31), IGNN subgraph analysis yields weak τ due to low subgraph κ and near-uniform discrete damage; full-graph matrix-free analysis partially recovers ($\tau: -0.14 \rightarrow +0.03$), and explicit GNNs transfer well (SAGE-2: $+0.60$). (3) Standard GAT requires edge-weighted modification for continuous sensitivity. (4) Power flow $\tau = 0.37\text{--}0.67$

requires verification for operational use [41]. (5) The matrix-free pipeline’s Neumann series requires $\kappa < 1$; for explicit GNNs without contractivity, the dense path ($N \leq 200$) or finite-difference columns are used. (6) IGNN accuracy (77.5% on Cora) lags behind state-of-the-art explicit GNNs ($\sim 82\%$ APPNP); this reflects the accuracy–guarantee tradeoff inherent in contractive architectures, not a limitation of AEGIS itself. The S_c framework applies identically to higher-accuracy explicit models, albeit without the formal regime characterization (theorem 1).

Ethical considerations. AEGIS identifies optimal attack directions and structurally vulnerable edges, which could be misused to attack deployed GNNs in safety-critical domains. We argue the diagnostic value outweighs this risk: defenders must understand their system’s attack surface to protect it, and the same vulnerability map directly informs defense design (section V-G). We will release code with responsible-use guidelines, including a tiered release protocol: vulnerability analysis tools (rankings, radii) will be openly available, while the attack-generation component (SVD-optimal perturbation direction) will require institutional affiliation for access, consistent with established practice in adversarial ML [44].

Future work. Second-order bounds for formal certificates; discrete perturbation models; integration with defense mechanisms [12], [11] for vulnerability-aware training; extending full-graph analysis beyond the current validated boundary ($N=7,650$ on a single GPU) via distributed JVP computation.

REFERENCES

- [1] D. Zügner, A. Akbarnejad, and S. Günnemann, “Adversarial attacks on neural networks for graph data,” in *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, 2018, pp. 2847–2856.
- [2] H. Dai, H. Li, T. Tian, X. Huang, L. Wang, J. Zhu, and L. Song, “Adversarial attack on graph structured data,” in *International Conference on Machine Learning*, 2018, pp. 1115–1124.
- [3] A. M. Nakiganda, C. Weeraddana, N. Popli, and T. van der Hagen, “Graph neural networks for fast contingency analysis of power systems,” *arXiv preprint arXiv:2310.04213*, 2023.
- [4] D. Zügner and S. Günnemann, “Adversarial attacks on graph neural networks via meta learning,” in *International Conference on Learning Representations*, 2019.
- [5] A. Bojchevski, J. Klicpera, and S. Günnemann, “Efficient robustness certificates for discrete data: Sparsity-aware randomized smoothing for graphs, images and more,” in *International Conference on Machine Learning*, 2020, pp. 1003–1013.
- [6] Y. Scholten, J. Schuchardt, A. Bojchevski, and S. Günnemann, “Randomized message-interception smoothing: Gray-box certificates for graph neural networks,” in *Advances in Neural Information Processing Systems*, vol. 35, 2022.
- [7] D. Zügner and S. Günnemann, “Certifiable robustness and robust training for graph convolutional networks,” in *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, 2019, pp. 246–256.
- [8] A. Bojchevski and S. Günnemann, “Certifiable robustness to graph perturbations,” in *Advances in Neural Information Processing Systems*, vol. 32, 2019.
- [9] B. Wang, J. Jia, X. Cao, and N. Z. Gong, “Certified robustness of graph neural networks against adversarial structural perturbation,” in *Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining*, 2021, pp. 1645–1653.
- [10] D. Zhu, Z. Zhang, P. Cui, and W. Zhu, “Robust graph convolutional networks against adversarial attacks,” in *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, 2019, pp. 1399–1407.

- [11] X. Zhang and M. Zitnik, “GNNGuard: Defending graph neural networks against adversarial attacks,” in *Advances in Neural Information Processing Systems*, vol. 33, 2020, pp. 9263–9275.
- [12] W. Jin, Y. Ma, X. Liu, X. Tang, S. Wang, and J. Tang, “Graph structure learning for robust graph neural networks,” in *Proceedings of the 26th ACM SIGKDD Conference on Knowledge Discovery & Data Mining*, 2020, pp. 66–74.
- [13] D. Luo, W. Cheng, W. Yu, B. Zong, J. Ni, H. Chen, and X. Zhang, “Learning to drop: Robust graph neural network via topological denoising,” in *Proceedings of the 14th ACM International Conference on Web Search and Data Mining*, 2021, pp. 779–787.
- [14] F. Gu, H. Chang, W. Zhu, S. Sojoudi, and L. El Ghaoui, “Implicit graph neural networks,” in *Advances in Neural Information Processing Systems*, vol. 33, 2020, pp. 11 984–11 995.
- [15] N. Halko, P.-G. Martinsson, and J. A. Tropp, “Finding structure with randomness: Probabilistic algorithms for constructing approximate matrix decompositions,” *SIAM Review*, vol. 53, no. 2, pp. 217–288, 2011.
- [16] S. Bai, J. Z. Kolter, and V. Koltun, “Deep equilibrium models,” in *Advances in Neural Information Processing Systems*, vol. 32, 2019.
- [17] S. Bai, V. Koltun, and J. Z. Kolter, “Multiscale deep equilibrium models,” in *Advances in Neural Information Processing Systems*, vol. 33, 2020, pp. 5238–5250.
- [18] T. Miyato, T. Kataoka, M. Koyama, and Y. Yoshida, “Spectral normalization for generative adversarial networks,” in *International Conference on Learning Representations*, 2018.
- [19] S. Gould, R. Hartley, and D. Campbell, “Deep declarative networks,” *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 44, no. 8, pp. 3988–4004, 2021.
- [20] S. W. Fung, H. Heaton, Q. Li, D. McKenzie, S. Osher, and W. Yin, “JFB: Jacobian-free backpropagation for implicit networks,” in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 36, no. 6, 2022, pp. 6648–6656.
- [21] S. Bai, V. Koltun, and J. Z. Kolter, “Stabilizing equilibrium models by Jacobian regularization,” in *International Conference on Machine Learning*, 2021, pp. 554–565.
- [22] L. N. Trefethen and M. Embree, *Spectra and Pseudospectra: The Behavior of Nonnormal Matrices and Operators*. Princeton University Press, 2005.
- [23] J. Lorraine, P. Vicol, and D. Duvenaud, “Optimizing millions of hyperparameters by implicit differentiation,” in *International Conference on Artificial Intelligence and Statistics*, 2020, pp. 1540–1552.
- [24] L. El Ghaoui, F. Gu, B. Travacca, A. Askari, and A. Tsai, “Implicit deep learning,” *SIAM Journal on Mathematics of Data Science*, vol. 3, no. 3, pp. 930–958, 2021.
- [25] M. Revay, R. Wang, and I. R. Manchester, “Lipschitz bounded equilibrium networks,” in *arXiv preprint arXiv:2010.01732*, 2020.
- [26] J. Bolte and E. Pauwels, “Conservative set valued fields, automatic differentiation, stochastic gradient descent and deep learning,” *Mathematical Programming*, vol. 188, pp. 19–51, 2021.
- [27] G. W. Stewart and J.-g. Sun, *Matrix Perturbation Theory*. Academic Press, 1990.
- [28] A. Paszke, S. Gross, F. Massa, A. Lerner, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga *et al.*, “PyTorch: An imperative style, high-performance deep learning library,” in *Advances in Neural Information Processing Systems*, vol. 32, 2019.
- [29] P. Sen, G. Namata, M. Bilgic, L. Getoor, B. Galligher, and T. Eliassi-Rad, “Collective classification in network data,” *AI Magazine*, vol. 29, no. 3, pp. 93–106, 2008.
- [30] O. Shchur, M. Mumme, A. Bojchevski, and S. Günnemann, “Pitfalls of graph neural network evaluation,” in *Relational Representation Learning Workshop, NeurIPS*, 2018.
- [31] P. Mernyei and M. Caron, “Wiki-CS: A Wikipedia-based benchmark for graph neural networks,” in *arXiv preprint arXiv:2007.02901*, 2020.
- [32] IEEE PES, “IEEE PES test feeder working group: Power system test cases,” *IEEE Power and Energy Society*, 2024, <https://electricgrids.engr.tamu.edu>.
- [33] L. Thurner, A. Scheidler, F. Schäfer, J.-H. Menke, J. Dolichon, F. Meier, S. Meinecke, and M. Braun, “pandapower – an open-source Python tool for convenient modeling, analysis, and optimization of electric power systems,” *IEEE Transactions on Power Systems*, vol. 33, no. 6, pp. 6510–6521, 2018.
- [34] T. N. Kipf and M. Welling, “Semi-supervised classification with graph convolutional networks,” in *International Conference on Learning Representations*, 2017.
- [35] A. Madry, A. Makelov, L. Schmidt, D. Tsipras, and A. Vladu, “Towards deep learning models resistant to adversarial attacks,” in *International Conference on Learning Representations*, 2018.
- [36] S. Brody, U. Alon, and E. Yahav, “How attentive are graph attention networks?” in *International Conference on Learning Representations*, 2022.
- [37] P. E. Pope, S. Kolouri, M. Rostami, C. E. Martin, and H. Hoffmann, “Explainability methods for graph convolutional neural networks,” in *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2019, pp. 10 772–10 781.
- [38] R. Ying, D. Bourgeois, J. You, M. Zitnik, and J. Leskovec, “GN-NEExplainer: Generating explanations for graph neural networks,” in *Advances in Neural Information Processing Systems*, vol. 32, 2019.
- [39] B. Donon, B. Donnot, I. Guyon, and A. Marot, “Graph neural solver for power systems,” in *International Joint Conference on Neural Networks*, 2019, pp. 1–8.
- [40] V. Bolz, J. Rueß, and A. Zell, “Power flow approximation based on graph convolutional networks,” in *18th IEEE International Conference on Machine Learning and Applications*, 2019, pp. 1679–1686.
- [41] A. J. Wood, B. F. Wollenberg, and G. B. Sheblé, *Power Generation, Operation, and Control*, 3rd ed. John Wiley & Sons, 2014.
- [42] A. Bojchevski and S. Günnemann, “Adversarial attacks on node embeddings via graph poisoning,” in *International Conference on Machine Learning*, 2019, pp. 695–704.
- [43] K. Xu, H. Chen, S. Liu, P.-Y. Chen, T.-W. Weng, M. Hong, and X. Lin, “Topology attack and defense for graph neural networks: An optimization perspective,” in *International Joint Conference on Artificial Intelligence*, 2019, pp. 3961–3967.
- [44] H. Wu, C. Wang, Y. Tyshetskiy, A. Docherty, K. Lu, and L. Zhu, “Adversarial examples on graph data: Deep insights into attack and defense,” in *International Joint Conference on Artificial Intelligence*, 2019, pp. 4816–4823.
- [45] L. Gosch, S. Geisler, D. Sturm, and S. Günnemann, “Adversarial training for graph neural networks: Pitfalls, solutions, and new directions,” in *Advances in Neural Information Processing Systems*, vol. 36, 2023.
- [46] Y. Li *et al.*, “AGNNcert: Deterministic certification for graph neural networks against adversarial perturbations,” in *International Conference on Learning Representations*, 2025.
- [47] S. Geisler, T. Schmidt, H. Sirin, D. Zügner, A. Bojchevski, and S. Günnemann, “Robustness of graph neural networks at scale,” in *Advances in Neural Information Processing Systems*, vol. 34, 2021, pp. 7637–7649.
- [48] J. Schuchardt, Y. Scholten, A. Bojchevski, and S. Günnemann, “Localized randomized smoothing for GNNs,” in *International Conference on Machine Learning*, 2023.
- [49] J. Liu, K. Kawaguchi, B. Hooi, Y. Wang, and X. Xiao, “EIGNN: Efficient infinite-depth graph neural networks,” in *Advances in Neural Information Processing Systems*, vol. 34, 2021, pp. 18 762–18 773.
- [50] E. Winston and J. Z. Kolter, “Monotone operator equilibrium networks,” in *Advances in Neural Information Processing Systems*, vol. 33, 2020, pp. 10 718–10 728.
- [51] F. Gama, J. Bruna, and A. Ribeiro, “Stability properties of graph neural networks,” *IEEE Transactions on Signal Processing*, vol. 68, pp. 5680–5695, 2020.
- [52] D. Luo, W. Cheng, D. Xu, W. Yu, B. Zong, H. Chen, and X. Zhang, “Parameterized explainer for graph neural network,” in *Advances in Neural Information Processing Systems*, vol. 33, 2020, pp. 19 620–19 631.
- [53] C. Kim, T. Conrad, R. Karim, J. Oelhaf, D. Riebesel, T. Arias-Vergara, A. K. Maier, J. Jäger, and S. Bayer, “Physics-informed GNN for medium-high voltage AC power flow with edge-aware attention and line search correction operator,” *arXiv preprint arXiv:2509.22458*, 2025.
- [54] M. Chen, Z. Wei, Z. Huang, B. Ding, and Y. Li, “Simple and deep graph convolutional networks,” in *International Conference on Machine Learning*. PMLR, 2020, pp. 1725–1735.
- [55] B. P. Chamberlain, J. Rowbottom, M. I. Gorinova, M. Bronstein, S. Webb, and E. Rossi, “GRAND: Graph neural diffusion,” in *International Conference on Machine Learning*, 2021, pp. 1407–1418.
- [56] M. Thorpe, T. M. Nguyen, H. Xia, T. Strohmer, A. Bertozzi, S. Osher, and B. Wang, “GRAND++: Graph neural diffusion with a source term,” in *International Conference on Learning Representations*, 2022.
- [57] N. Entezari, S. A. Al-Sayouri, A. Darvishzadeh, and E. E. Papalexakis, “All you need is low (rank): Defending against adversarial attacks on

graphs,” in *Proceedings of the 13th International Conference on Web Search and Data Mining*, 2020, pp. 169–177.

- [58] F. Mujkanovic, S. Geisler, S. Günnemann, and A. Bojchevski, “Are defenses for graph neural networks robust?” in *Advances in Neural Information Processing Systems*, vol. 35, 2022, pp. 8940–8952.