

# AEGIS: Mining Graph Structure for Adversarial Vulnerability Analysis of GNNs

Anonymous Author(s)

**Abstract**—Adversarial manipulation of graph structure poses a growing threat as graph neural networks are deployed in fraud detection, drug interaction prediction, and infrastructure monitoring. Yet practitioners lack tools to answer a basic question before deployment: *which edges, if perturbed, would flip this model’s predictions?* We introduce AEGIS (Adversarial Evaluation of Graph Integrity via Sensitivity), a framework that answers this question by constructing a constrained sensitivity matrix  $S_c$  mapping edge perturbations to hidden-state shifts. From  $S_c$ , AEGIS extracts the mathematically optimal attack direction (via SVD), per-edge vulnerability rankings, and per-node first-order sensitivity radii. A matrix-free formulation based on Neumann-series resolvent iteration and randomized SVD enables full-graph analysis (up to  $N=7,650$  on a single GPU; Cora in 78s / 1GB, Amazon Photo in 363s / 6.5GB) without materializing any  $Nd \times N^2$  matrix. The computation applies to any GNN whose message passing is differentiable with respect to continuous edge weights, serving as a practical vulnerability analysis tool; for contractive implicit models (IGNN-class), it additionally provides formal guarantees including a critical perturbation budget  $\varepsilon_{\text{crit}}$  and a three-regime vulnerability characterization. Under realistic (symmetric, edge-only) perturbations, first-order predictions achieve tightness  $1.00 \pm 0.01$  at  $\varepsilon = 0.01$  and remain within 15% at  $\varepsilon = 0.10$  across 7 architectures and 9 datasets. The SVD-optimal attack inflicts  $2\text{--}8\times$  more damage than random perturbation. On IEEE power grids, the vulnerability spectrum recovers N-1 contingency rankings ( $P@10 = 0.66\text{--}0.81$ ) without requiring line-impedance data, demonstrating that structural sensitivity analysis can serve as a pre-deployment screening tool. Code will be released upon publication.

**Index Terms**—Graph neural networks, adversarial robustness, structural sensitivity, deep equilibrium models, graph perturbation, implicit function theorem

## I. INTRODUCTION

Graph neural networks have entered domains where incorrect predictions carry tangible consequences: fraudulent accounts evade detection when an adversary inserts edges into a financial transaction graph [1], drug interaction models produce unsafe recommendations when molecular graphs are perturbed [2], and power grid monitoring systems may miss critical contingencies if their graph-based representations are structurally fragile [3]. In all these settings, the graph topology is not merely an input format but a potential attack surface. A practitioner preparing to deploy a GNN faces a fundamental question that current tools leave unanswered: *which edges in this graph, if perturbed, would cause the model’s predictions to fail, and by how much?*

This question is distinct from both adversarial attack and certified defense. Attack methods such as Nettack [1] and Mettack [4] search for damaging perturbations using surrogate gradients or meta-learning, but they provide no guarantee that

the perturbation found is optimal, and they do not quantify per-node vulnerability. Certified defenses based on randomized smoothing [5], [6] or interval bound propagation [7], [8], [9] provide robustness guarantees, but they are uniform: every node receives the same certificate, revealing nothing about *which* edges or nodes are structurally weak. Empirical defenses [10], [11], [12], [13] harden the model but offer no formal understanding of residual vulnerability. What is missing is a *structural vulnerability map* that, given a trained GNN and a graph, identifies the optimal perturbation direction, the weakest edges, and the perturbation tolerance of each node.

We introduce AEGIS (Adversarial Evaluation of Graph Integrity via Sensitivity), a framework that produces exactly this map. The central object is the *constrained sensitivity matrix*  $S_c \in \mathbb{R}^{Nd \times |E|}$ , which projects the full  $N^2$ -dimensional adjacency perturbation space onto the  $|E|$ -dimensional space of realistic (symmetric, edge-only) perturbations. From  $S_c$ , three outputs follow directly: (i) the SVD yields the first-order optimal attack direction, (ii) column norms give per-edge vulnerability scores, and (iii) the classification margin divided by the sensitivity norm gives per-node tolerance radii. The  $S_c$  computation applies to any GNN whose message passing is differentiable with respect to continuous edge weights (theorem 4), yielding vulnerability rankings, SVD-optimal attacks, and first-order sensitivity radii as a practical computational tool. For contractive implicit GNNs (IGNN-class [14]), the implicit function theorem additionally provides formal guarantees: a critical perturbation budget  $\varepsilon_{\text{crit}} = (1 - \kappa) / \|W\|_2$  and a three-regime characterization of model behavior under increasing perturbation (theorem 1). These formal guarantees are specific to the implicit case and do not transfer to explicit architectures.

These predictions are quantitatively accurate: constrained first-order tightness is  $1.00 \pm 0.01$  at  $\varepsilon = 0.01$  and remains within 15% at  $\varepsilon = 0.10$ , across 7 GNN architectures and 9 datasets spanning citation networks, e-commerce, encyclopedias, and power grids. On IEEE power grids, the vulnerability spectrum independently recovers N-1 contingency rankings ( $P@10 = 0.66\text{--}0.81$ ), demonstrating that structural sensitivity analysis transfers to real-world engineering problems without domain-specific modifications.

### Contributions.

- 1) **Constrained sensitivity framework.** We derive the constrained sensitivity matrix  $S_c$  for any GNN whose message passing is differentiable with respect to edge weights (theorem 4). For contractive implicit models (IGNN-class), we additionally prove a critical budget

























- [33] L. Thurner, A. Scheidler, F. Schäfer, J.-H. Menke, J. Dollichon, F. Meier, S. Meinecke, and M. Braun, “pandapower – an open-source Python tool for convenient modeling, analysis, and optimization of electric power systems,” *IEEE Transactions on Power Systems*, vol. 33, no. 6, pp. 6510–6521, 2018.
- [34] T. N. Kipf and M. Welling, “Semi-supervised classification with graph convolutional networks,” in *International Conference on Learning Representations*, 2017.
- [35] A. Madry, A. Makelov, L. Schmidt, D. Tsipras, and A. Vladu, “Towards deep learning models resistant to adversarial attacks,” in *International Conference on Learning Representations*, 2018.
- [36] S. Brody, U. Alon, and E. Yahav, “How attentive are graph attention networks?” in *International Conference on Learning Representations*, 2022.
- [37] P. E. Pope, S. Kolouri, M. Rostami, C. E. Martin, and H. Hoffmann, “Explainability methods for graph convolutional neural networks,” in *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2019, pp. 10 772–10 781.
- [38] R. Ying, D. Bourgeois, J. You, M. Zitnik, and J. Leskovec, “GN-NEExplainer: Generating explanations for graph neural networks,” in *Advances in Neural Information Processing Systems*, vol. 32, 2019.
- [39] B. Donon, B. Donnot, I. Guyon, and A. Marot, “Graph neural solver for power systems,” in *International Joint Conference on Neural Networks*, 2019, pp. 1–8.
- [40] V. Bolz, J. Rueß, and A. Zell, “Power flow approximation based on graph convolutional networks,” in *18th IEEE International Conference on Machine Learning and Applications*, 2019, pp. 1679–1686.
- [41] A. J. Wood, B. F. Wollenberg, and G. B. Sheblé, *Power Generation, Operation, and Control*, 3rd ed. John Wiley & Sons, 2014.
- [42] C. Kim, T. Conrad, R. Karim, J. Oelhaf, D. Riebesel, T. Arias-Vergara, A. K. Maier, J. Jäger, and S. Bayer, “Physics-informed GNN for medium-high voltage AC power flow with edge-aware attention and line search correction operator,” *arXiv preprint arXiv:2509.22458*, 2025.
- [43] A. Bojchevski and S. Günnemann, “Adversarial attacks on node embeddings via graph poisoning,” in *International Conference on Machine Learning*, 2019, pp. 695–704.
- [44] K. Xu, H. Chen, S. Liu, P.-Y. Chen, T.-W. Weng, M. Hong, and X. Lin, “Topology attack and defense for graph neural networks: An optimization perspective,” in *International Joint Conference on Artificial Intelligence*, 2019, pp. 3961–3967.
- [45] H. Wu, C. Wang, Y. Tyshetskiy, A. Docherty, K. Lu, and L. Zhu, “Adversarial examples on graph data: Deep insights into attack and defense,” in *International Joint Conference on Artificial Intelligence*, 2019, pp. 4816–4823.
- [46] Y. Li *et al.*, “AGNNcert: Deterministic certification for graph neural networks against adversarial perturbations,” in *International Conference on Learning Representations*, 2025.
- [47] S. Geisler, T. Schmidt, H. Sirin, D. Zügner, A. Bojchevski, and S. Günnemann, “Robustness of graph neural networks at scale,” in *Advances in Neural Information Processing Systems*, vol. 34, 2021, pp. 7637–7649.
- [48] J. Liu, K. Kawaguchi, B. Hooi, Y. Wang, and X. Xiao, “EIGNN: Efficient infinite-depth graph neural networks,” in *Advances in Neural Information Processing Systems*, vol. 34, 2021, pp. 18 762–18 773.
- [49] E. Winston and J. Z. Kolter, “Monotone operator equilibrium networks,” in *Advances in Neural Information Processing Systems*, vol. 33, 2020, pp. 10 718–10 728.
- [50] D. Luo, W. Cheng, D. Xu, W. Yu, B. Zong, H. Chen, and X. Zhang, “Parameterized explainer for graph neural network,” in *Advances in Neural Information Processing Systems*, vol. 33, 2020, pp. 19 620–19 631.
- [51] M. Chen, Z. Wei, Z. Huang, B. Ding, and Y. Li, “Simple and deep graph convolutional networks,” in *International Conference on Machine Learning*. PMLR, 2020, pp. 1725–1735.
- [52] B. P. Chamberlain, J. Rowbottom, M. I. Gorinova, M. Bronstein, S. Webb, and E. Rossi, “GRAND: Graph neural diffusion,” in *International Conference on Machine Learning*, 2021, pp. 1407–1418.
- [53] M. Thorpe, T. M. Nguyen, H. Xia, T. Strohmer, A. Bertozzi, S. Osher, and B. Wang, “GRAND++: Graph neural diffusion with a source term,” in *International Conference on Learning Representations*, 2022.
- [54] N. Entezari, S. A. Al-Sayouri, A. Darvishzadeh, and E. E. Papalexakis, “All you need is low (rank): Defending against adversarial attacks on graphs,” in *Proceedings of the 13th International Conference on Web Search and Data Mining*, 2020, pp. 169–177.
- [55] F. Mujkanovic, S. Geisler, S. Günnemann, and A. Bojchevski, “Are defenses for graph neural networks robust?” in *Advances in Neural Information Processing Systems*, vol. 35, 2022, pp. 8940–8952.