



RFIC Technology Corporation
www.rfintc.com

AP1110

2.4~2.5 GHz Power Amplifier

2008. 08. 29 Update

DESCRIPTION


AP1110 is a linear, low current power amplifier in ISM band utilizing InGaP /GaAs HBT process. The AP1110 is well suitable to be used for portable, low current 2.4GHz WLAN applications as well as for BT (Bluetooth) Class1 applications.

AP1110 is packaged in **2x2** compact profile. For WLAN application, it features low current of **85mA** at linear power of **18.5dBm**, gain of 26dB under 3.3V. For Bluetooth applications, it features of gain at 26 dB; typical power of **23dBm** and PAE of **40%** under 3.3V. AP1110 is also suitable for the new BT 2.0 (EDR) standard.

Major Applications

- Bluetooth Class 1 including V1.1,1.2 & (2.0)EDR standard
- IEEE 802.11b/g WLAN system
- WLAN Portable Devices
- WLAN USB Devices
- Other 2.4 GHz ISM Band

Functional Block Diagram



DFN - 8 pin, 2 x 2 (mm)

KEY FEATURES

Ultra Small Profile: 2x2(mm), DFN-8pin

WLAN Applications:

(Under Vc=3.3V, Vref=2.8V)

- **LOW Current:** 85mA at 18.5dBm
- **High efficiency:** PAE: 25% at 18dBm
- **Gain:** 26 dB

BT Applications:

(BT V.1.1&1.2, Under Vc=3.3V, Vref=2.85V)

- **LOW Current:** 85mA at 18dBm
60mA at 16dBm
50mA at 14dBm
- **High efficiency:** PAE: 40% at 23dBm
- **Gain:** 26 dB
- **Harmonic:** -33dBc at 23dBm

(BT EDR version, under Vc&Vref=3.3V)

- **LOW Current:** 110mA at 18dBm
95mA at 16dBm
75mA at 14dBm
- **Gain:** 23dB

Note: The different applications are based on different outside circuit, please refer to the Application Note for more details.

Pin Details

Pin Number	Name	Description
1	Vcc	Supply voltage.
2	RF IN	RF input.
3	Vcc_Bias	Supply voltage for bias circuit.
4	NC	No connection.
5	V _{REF1}	PA 1 st stage bias control voltage.
6	V _{REF2}	PA 2 nd stage bias control voltage.
7	RF OUT	RF output. Require external matching.
8	RF OUT	
Package Base	Center Metal	The package ground provides circuit ground as well as heat dissipation path for the power amplifier.

AP1110

For more information, please contact us at:

Sales Dept.

Tel: +886-2-2698-1022

e-mail: sales@rfintc.com

© 2006 RFIC Technology Corporation All rights reserved.

RFIC Technology Corp. reserved the right to make any changes to the specifications without notice.

1 of 10



RFIC Technology Corporation
www.rfintc.com

AP1110

2.4~2.5 GHz Power Amplifier

2008. 08. 29 Update

Electrical Characteristics: WLAN Applications

Under $V_c=3.3V$, $V_{ref}=2.8V$, $T_a=25^{\circ}C$

PARAMETERS	CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
Freq.		f	2.4		2.5	GHz
Total current	$P_{out}=18.5dBm$	I_{cc}		85		mA
Basic control reference current	$I_{cq}=21mA$	I_{ref}		0.5		mA
Power Gain	$P_{out}=18dBm$	G_p		26.5		dB
Quiescent current		I_{cq}		21		mA
Input VSWR				1.5		
Output VSWR				2		
Output power	EVM 3%	P_{out}		18.5		dBm
PAE		PAE		25		%

Note: For high power application, $V_{cc} = V_{bias} = 4.5 V$ is what we recommend and please make an advance contact with RFIC.

Absolute Maximum Ratings

Parameter	Rating	Unit
DC Power Supply For Collector	+5	V
DC Supply Current For Collector	280	mA
RF Input Power	+5	dBm
Operating Ambient Temperature	-40 to +85	$^{\circ}C$
Storage Temperature	-40 to +125	$^{\circ}C$

Important Note:

The information provided in this datasheet is deemed to be accurate and reliable only at present time. RFIC Technology Corp. reserves the right to make any changes to the specifications in this datasheet without prior notice.



Caution: ESD Sensitive
Appropriate precaution in handling, packaging
And testing devices must be observed.

AP1110

For more information, please contact us at:

Sales Dept.

Tel: +886-2-2698-1022

e-mail: sales@rfintc.com

© 2006 RFIC Technology Corporation All rights reserved.

RFIC Technology Corp. reserved the right to make any changes to the specifications without notice.

2 of 10



RFIC Technology Corporation
www.rfintc.com

AP1110

2.4~2.5 GHz Power Amplifier

2008. 08. 29 Update

Electrical Characteristics: BT Applications

BT V.1.0-1.2, under $V_c=3.3V$, $V_{ref}=2.85V$, $T_a=25^\circ C$

PARAMETERS	CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
Freq.		f	2.4		2.5	GHz
Total current	Pout=23dBm Pout=20dBm Pout=14dBm	Icc		140 95 50		mA
Basic control reference current	Icq=18mA	Iref		0.5		mA
Power Gain	Pout=20dBm	Gp		26		dB
Quiescent current		Icq		18		mA
Harmonic	Pout=23dBm	2f		-33		dBc
Input VSWR				2		
Output VSWR				2.5		
PAE	Pout=23dBm	PAE		40		%
Power		P1dB		23		dBm

BT v.2.0 (EDR), under $V_c \& V_{ref}=3.3V$, $T_a=25^\circ C$

PARAMETERS	CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
Freq.		f	2.4		2.5	GHz
Total current	Pout=18dBm Pout=16dBm Pout=14dBm	Icc		110 95 75		mA
Power Gain	Pout=18dBm	Gp		23		dB
Harmonic	Pout=18dBm	2f		-20		dBc
PAE	Pout=18dBm	PAE		18		%

For more information, please contact us at:

Sales Dept.

Tel: +886-2-2698-1022

e-mail: sales@rfintc.com

© 2006 RFIC Technology Corporation All rights reserved.

RFIC Technology Corp. reserved the right to make any changes to the specifications without notice.

3 of 10



RFIC Technology Corporation
www.rfintc.com

AP1110

2.4~2.5 GHz Power Amplifier

2008. 08. 29 Update

Data Charts: WLAN Applications

Fig.1 – Pin, PAE and Icc vs. Pout





Fig.2 - Power Gain and EVM vs. Pout



AP1110

For more information, please contact us at:

Sales Dept.


Tel: +886-2-2698-1022

e-mail: sales@rfintc.com

© 2006 RFIC Technology Corporation All rights reserved.

RFIC Technology Corp. reserved the right to make any changes to the specifications without notice.

4 of 10

RFIC**RFIC Technology Corporation**
www.rfintc.com**AP1110****2.4~2.5 GHz Power Amplifier****2008. 08. 29 Update****Data Charts: WLAN Applications****Fig.3 – S Parameters**

AP1110

For more information, please contact us at:

Sales Dept.

Tel: +886-2-2698-1022

e-mail: sales@rfintc.com

© 2006 RFIC Technology Corporation All rights reserved.

RFIC Technology Corp. reserved the right to make any changes to the specifications without notice.

5 of 10



RFIC Technology Corporation
www.rfintc.com

AP1110

2.4~2.5 GHz Power Amplifier

2008. 08. 29 Update

Data Charts: BT V1.1-1.2 Applications

Fig.4

Pin & Icc vs. Pout





Fig.5

Power Gain vs. Pin



AP1110

For more information, please contact us at:

Sales Dept.

Tel: +886-2-2698-1022

e-mail: sales@rfintc.com

© 2006 RFIC Technology Corporation All rights reserved.

RFIC Technology Corp. reserved the right to make any changes to the specifications without notice.

6 of 10



RFIC Technology Corporation
www.rfintc.com

AP1110

2.4~2.5 GHz Power Amplifier

2008. 08. 29 Update

Data Charts: BT V2.0(EDR) Applications

Fig.6

Pin, PAE & Icc vs. Pout





Fig.7

Power Gain vs. Pin



AP1110

For more information, please contact us at:

Sales Dept.

Tel: +886-2-2698-1022

e-mail: sales@rfintc.com

© 2006 RFIC Technology Corporation All rights reserved.

RFIC Technology Corp. reserved the right to make any changes to the specifications without notice.

7 of 10



RFIC Technology Corporation
www.rfintc.com

AP1110

2.4~2.5 GHz Power Amplifier

2008. 08. 29 Update

Data Charts: BT v.1.1-1.2 Applications




Fig.8

AP1110

For more information, please contact us at:

Sales Dept.

Tel: +886-2-2698-1022

e-mail: sales@rfintc.com

© 2006 RFIC Technology Corporation All rights reserved.

RFIC Technology Corp. reserved the right to make any changes to the specifications without notice.

8 of 10



RFIC Technology Corporation
www.rfintc.com

AP1110

2.4~2.5 GHz Power Amplifier

2008. 08. 29 Update

Data Charts: BT v.2.0(EDR) Applications




Fig.9

AP1110

For more information, please contact us at:

Sales Dept.

Tel: +886-2-2698-1022

e-mail: sales@rfintc.com

© 2006 RFIC Technology Corporation All rights reserved.

RFIC Technology Corp. reserved the right to make any changes to the specifications without notice.

9 of 10



RFIC Technology Corporation
www.rfintc.com


AP1110

2.4~2.5 GHz Power Amplifier


2008. 08. 29 Update

Package Outline

Top View




Bottom View



Unit: mm

Side View



Note :

1. Dimension and tolerance conform to ASME Y14.5M-1994.
2. Refer to JEDEC STD. MO-220 WEED-2 ISSUE B

For more information, please contact us at:

Sales Dept.

Tel: +886-2-2698-1022

e-mail: sales@rfintc.com

© 2006 RFIC Technology Corporation All rights reserved.

RFIC Technology Corp. reserved the right to make any changes to the specifications without notice.

10 of 10

AP1110