



TrioDocs

Version: 0.4.0

Date: August 31, 2026

Download the latest version on:
<https://triodocs.org>

Customizations

Customize with Browser Build

Change the Branch for a Submodule

If you ever want to use a different `branch` or `commit` for a submodule than the one provided by your current Trio workspace, this is how to do it.

1. Go to the repository of interest - it does not need to be in the same repository that Trio uses
 - If you provide the full SHA, GitHub can find that specific code version while running the `build_trio.yml` action
2. Identify the exact `commit` you want to use and record the full SHA
3. Go into the `.github/workflows/build_trio.yml` file and edit it at or around line 217 (in the Customize Trio section)
4. Add 3 lines to bring in the desired `commit`
 - First line is a comment explaining what you are doing
 - Second line defines the submodule `commit` you want to use
 - Third line updates that submodule as you just specified

An example is shown below. While this particular example is for an older submodule which is no longer part of Trio, you can still use it as a prototype for changing the SHA for any submodule as desired.

Copy and Paste to Customize - Edit SHA and Submodule Name for your situation

```
# Point to the most recent SHA for OmniBLE branch pod-keep-alive
git update-index --cacheinfo 160000 dade6ed309eb72232a187d88179a367e34f800d9 "OmniBLE"
git submodule update
```