



TrioDocs

Version: 0.4.0

Date: August 13, 2026

Download the latest version on:
<https://triodocs.org>

Secrets Introduction

Introduction to Secrets

In order to build using the Browser Build method, you will need to collect and save six secrets from your free [GitHub](#) account and your paid Apple Developer account.

Save Your Information

Everyone needs to read this section!

You need to keep a digital copy of your 6 `Secrets` .

- You need to copy and paste those `Secrets` to build the app with a browser
- Make sure your editor does not change any characters in your `Secrets` ; use a text-only editor like NotePad (PC) or TextEdit (Mac)
- Many people add other information to the `Secrets` file for easy reference

A Note about Capitalization and Spaces

In places, you use a name like " `FastLane API Key` " or " `FastLane Access Token` ". Please copy from the docs to use those exact names.

The `Secrets` that you add use names that are capitalized and use underscore `_` instead of spaces or hyphens. Be precise and careful.

Use a Text-Only Editor

Be sure to use a Text-Only editor like NotePad (PC) or TextEdit (Mac) to archive your information.

If you use a "smart" editor, it may change small letters to capital letters at the beginning of a line when you paste items into your archive file.

If even one character is capitalized when it should not be, you will get errors.

Make a `Secrets` Reference File

Please save yourself a lot of agony. Make a `Secrets` Reference folder and then create a `Secrets` Reference file in it.

You don't need to know anything about the `Secrets` to do this. Come up with your own names, but make sure you know where you put this file.

1. Decide where you want your `Secrets` saved and create a special folder
2. Open a text-only editor (do not use a Smart Editor, those might change capitalization or formatting and ruin your `Secrets`)
 - Create a blank `Secrets` Reference file using the text-only editor
 - Tap on the copy icon below to copy the template and paste it into your blank file

- Save the file
3. As you move through the steps of collecting the six secrets, fill in the file
 - The `##` characters are used to indicate sections or title (text only file)
 - There is a reference pattern for each SECRET: replace that with your SECRET or you can add your secret below the pattern to give yourself confidence you got the correct item
 4. In addition to the `Secrets`, this template has places for other pieces of information you may find handy to save in the same file
 5. At the very beginning is a place to indicate the last day you updated the file

Template to use for Secrets

MySecretsReferenceFile.txt

This file updated on: DD MMM YYYY

Information needed to use Browser Build.
The same secrets are used **for** every app you build.

First some handy username and password information:

Apple ID username for your Developer account is the associated email:
<your information here>
suggest you use your desired password tool to save the password **for** this account

GitHub personal account username
<your information here>
suggest you use your desired password tool to save the password **for** this account

GitHub organization name
<your GitHub organization name>
Using an organization is optional.
But if you **do** use one, add the name here **for** reference.
You always log **in** using your GitHub personal account to access your organization.

There are Six Secrets and One Variable:
- the list below shows the expected format of each.
You can replace each prototype with your secret as you gather them,
- or put your secret below a prototype.
The letter A indicates an alphanumeric character;
- some may be small letter, some capital letters and some numerals.
The FASTLANE_KEY may have additional characters included.
Be sure to copy the entire key including
-----BEGIN PRIVATE KEY-----
through
-----END PRIVATE KEY-----

SECRETS BELOW:

TEAMID
<looks like this>
AAAAAAAAAA

FASTLANE_ISSUER_ID
<looks like this>
AAAAA-AAAA-AAAA-AAAA-AAAAAAAAA

FASTLANE_KEY_ID
<looks like this>
AAAAAAAAAA

FASTLANE_KEY
<looks like this>
-----BEGIN PRIVATE KEY-----
AA
AA
AA
AAAAA
-----END PRIVATE KEY-----

GH_PAT
<looks like this>
ghp_AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

MATCH_PASSWORD
<looks like this>

```
AnythingYouWant-sameForEveryRepository
```

This Variable (not a secret) is required for the annual certificate renewal:

```
ENABLE_NUKE_CERTS = true
```

```
## Repository Names for my Fork:
```

If you use an organization (recommended)

```
https://github.com/my-name-org/Trio
```

or (if you don't use an organization):

```
https://github.com/my-name/Trio
```

Add additional apps here if you decide to build any

New Terms with `GitHub` Browser Build

The `GitHub` Browser Build may use new and unfamiliar **terms**.

These instructions can be used without knowing what any of these terms mean. But if you are curious:

Some of these **terms** have ToolTips, so hover your mouse over those - or review them in the [Glossary ↗](#).

- Some terms in the Glossary are not in alphabetical order to improve logical grouping. All the individual `Secrets` are listed after `Secrets` in the Glossary.
- `Actions`: available in your `GitHub` repositories to build your app
 - You must be logged in to `GitHub` to run the actions manually
 - The build action is automatically run for you once your repository is configured
- `Fork`: you make a copy of the code needed to build an app and store it in your `GitHub` account (using a free `GitHub` organization is recommended for storing your forks)
- `Secrets`: are required to enable `GitHub` to build an app from a repository using `GitHub` Actions
 - Six `Secrets` must be entered to enable your app (or apps) to build
 - These `Secrets` work for any branch in your fork (`main` or `dev`, for example) and if you use the recommended free `GitHub` organization to build, they work for any app you fork to your organization
 - If you build more than one app, they use the same `Secrets` and the use of a `GitHub` organization is even more strongly recommended
- `Certificates`: These are required to enable `GitHub` to build an app from a repository using `GitHub` Actions
 - They are manually created with the Create Certificates action
 - They expire at the end of one year
 - Certificates are automatically renewed as long as you [add the required Variable ↗](#)
- `API Key`: Application Programming Interface Key
 - You create an API key from the *Apple Developer* website
 - Doing this provides 3 of your `Secrets`
 - These secrets enable your `GitHub` account to interface with *Apple* to create your app

- `Identifiers` : are required to build the *Trio* app with `Github Browser Build` (these are automatically generated for you) when you run `Add Identifiers`
 - `App Store Connect` : a website available for *Apple Developers* to review apps build with your *Apple Developer* account
 - Once you purchase an *Apple Developer* annual account, you are an *Apple Developer* and have access to this site
 - Most users will not have an App until using the `Github Browser Build`
 - The instructions walk you through creating and naming your app: [Create Trio App in App Store Connect ↗](#)
-

Next Step

Ready to begin? Proceed to:

→ [Create Github Account](#)

Navigation: [← Back to Overview](#) | Next: [Create Github Account](#) →