



Router0

Physical

Config

CLI

Attributes

GLOBAL

Settings

Algorithm Settings

ROUTING

Static

RIP

SWITCHING

VLAN Database

INTERFACE

GigabitEthernet0/0

GigabitEthernet0/1

GigabitEthernet0/2

GigabitEthernet0/1

Port Status

On

Bandwidth

1000 Mbps

100 Mbps

10 Mbps

Auto

Duplex

Half Duplex

Full Duplex

Auto

MAC Address

00D0.FF7D.5102

IP Configuration

IPv4 Address

101.168.10.1

Subnet Mask

255.0.0.0

Tx Ring Limit

10

Equivalent IOS Commands

Link 0 changed: Interface GigabitEthernet0/2, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface GigabitEthernet0/2, changed state to up

ip address 102.168.10.1 255.0.0.0

Router(config-if)#ip address 102.168.10.1 255.0.0.0

Router(config-if)#

Router(config-if)#

Router(config-if)#

Router(config-if)#exit

Router(config)#interface GigabitEthernet0/0

Router(config-if)#

Router(config-if)#exit

Router(config)#interface GigabitEthernet0/1

Router(config-if)#

Top

Router0

Physical

Config

CLI

Attributes

GLOBAL

Settings

Algorithm Settings

ROUTING

Static

RIP

SWITCHING

VLAN Database

INTERFACE

GigabitEthernet0/0

GigabitEthernet0/1

GigabitEthernet0/2

GigabitEthernet0/0

Port Status

☒ On

Bandwidth

☒ 1000 Mbps ☐ 100 Mbps ☐ 10 Mbps 

☒ Auto

Duplex

☐ Half Duplex ☒ Full Duplex 

☒ Auto

MAC Address00D0.FF7D.5101

IP Configuration

IPv4 Address100.168.10.1

Subnet Mask255.0.0.0

Tx Ring Limit10

Equivalent IOS Commands

```
Router(config)#interface GigabitEthernet0/2
Router(config-if)#no shutdown
Router(config-if)#
%LINK-5-CHANGED: Interface GigabitEthernet0/2, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface GigabitEthernet0/2, changed state to up
ip address 102.168.10.1 255.0.0.0
Router(config-if)#ip address 102.168.10.1 255.0.0.0
Router(config-if)#
Router(config-if)#
Router(config-if)#
Router(config-if)#exit
Router(config)#interface GigabitEthernet0/0
Router(config-if)#
```

☐ Top

