

2025-2026 | Neurorobotics

Lab06 | ERD/ERS on logarithmic band power

1. Logarithmic band power

Import and concatenate all the offline GDF files and compute the band power. With respect to the previous exercise, apply a laplacian spatial filter to the data. Here a reminder about the steps to be implemented:

a. Apply a laplacian filters by exploiting the mask provided in the moodle:

```
>> load('laplacian16.mat');  
>> s_lap = s*lap;
```

where *s* is the data matrix [sample x channels]

where *lap* is the laplacian mask [channels x channels]

b. Filter the signal in the μ and β bands

- Use a Butterworth filter (choose the order and cutoff frequencies).
- Apply zero-phase filtering with MATLAB's `filtfilt` function.
- To verify the stability of the filter, you may use the `fvtool()` function.

c. Rectify the signal (square it).

d. Apply a moving average using a 1-second window.

e. ~~Apply a logarithmic transform to the result.~~

we do not apply the log, since the data will be normalized with the ERD/ERS

f. Extracting trials for the two MI tasks

2. Event related desynchronization and synchronization (ERD/ERS)

Compute the ERD/ERS of the data by considering the fixation period as reference period and the continuous feedback as activity period.

```
>> Reference = repmat(mean(FixData), [size(TrialData, 1) 1 1]);  
>> ERD = 100 * (TrialData - Reference) ./ Reference
```

where *FixData* refers to the fixation period [samples x channels x trials];

where *TrialData* is refers to the whole trial period [samples x channels x trials]

3. Temporal visualization

a. Select a meaningful channel

b. Average the ERD/ERS across trials for the two classes

c. Plot the average and the standard error of the ERD/ERS over time for the two classes

4. Spatial visualization

- Visualize the topographic maps of the average ERD/ERS during the Reference Period and the Activity period

```
>> load('chanlocs16.mat');  
>> ERD_Ref_771 = mean(mean(ERD(FixPeriod(1):FixPeriod(2), :, Ck == 771, 3), 1);  
>> ERD_Act_771 = mean(mean(ERD(CFPeriod(1):CFPeriod(2), :, Ck == 771, 3), 1);  
>> topoplot(squeeze(ERD_Ref_771), chanlocs16);  
>> topoplot(squeeze(ERD_Act_771), chanlocs16);
```

Expected results

