

Lab05 | Spatial filters on logarithmic band power

1. EEG Data

Import all the offline **GDF files** provided in the previous assignment. Write a MATLAB script that performs the following steps:

1. **Load** the offline GDF files.
2. **Concatenate** the GDF files.
3. **Extract and concatenate** the corresponding event information.

2. Data Processing

At this point, you should have a single matrix of size **[samples × channels]** containing all the data from the different GDF files. You should also have an **EVENT** structure with all the events (**TYP**, **POS**, **DUR**) correctly concatenated.

Write a MATLAB script to process the data and compute the **logarithmic band power**. In particular, implement the following steps:

- a. **Filter** the signal in the μ and β bands
 - o Use a Butterworth filter (choose the order and cutoff frequencies).
 - o Apply zero-phase filtering with MATLAB's `filtfilt` function.
 - o To verify the stability of the filter, you may use the `fvttool()` function.
- b. **Rectify** the signal (square it).
- c. Apply a **moving average** using a 1-second window.
- d. Apply a **logarithmic transform** to the result.

3. Trial Extraction

Extract trials corresponding to the **two motor imagery (MI) tasks**.

- a. Use the event types (**EVENT.TYP**) to identify which tasks correspond to which class.
- b. You may assume that a trial lasts from the **fixation cross** to the **end of the continuous feedback** period.

4. Visualization

- a. Select **three meaningful EEG channels**.
- b. Plot the **raw** and **filtered** signals for a given trial and for the selected channels
- c. Plot the power of the three channels after **averaging across all trials** for each class.

5. Spatial Filtering

Redo the entire process by applying two different **spatial filters** to the raw data:

- a. **Common Average Reference (CAR) filter**
 - o Apply the CAR filter to the raw data.
 - o Repeat steps 2 to 4 (Data Processing → Visualization).
 - o Compare the results with the unfiltered data.


b. Laplacian filter

- Apply the Laplacian filter to the raw data (the Laplacian mask is available on Moodle).
- Repeat steps 2 to 4.
- Compare the results with both the unfiltered and CAR-filtered data.


Expected Results

You should obtain and analyze the **averaged logarithmic band power** in the μ and β frequency bands for the two MI classes.

No spatial filters



Car Filter



Laplacian Filter

