

ORM / ODM CRUD Methods Comparison

Mongoose • Prisma • GORM — syntax with required parameters

Operation	Mongoose (Node / MongoDB)	Prisma (Node / SQL)	GORM (Go / SQL)
Create One	<code>create({...})</code>	<code>create({ data:{...} })</code>	<code>db.Create(&obj)</code>
Create Many	<code>insertMany([{...}])</code>	<code>createMany({ data:[{...}] })</code>	<code>db.Create(&[]obj)</code>
Find All	<code>find({})</code>	<code>findMany()</code>	<code>db.Find(&[]obj)</code>
Find One	<code>findOne({ key:val })</code>	<code>findFirst({ where:{...} })</code>	<code>db.First(&obj)</code>
Find By ID	<code>findById(id)</code>	<code>findUnique({ where:{id} })</code>	<code>db.First(&obj, id)</code>
Update One	<code>updateOne({ _id:id }, { \$set:{...} })</code>	<code>update({ where:{id}, data:{...} })</code>	<code>db.Model(&Model{}).Where("id=?", id).Updates(&obj)</code>
Update Many	<code>updateMany({ key:val }, { \$set:{...} })</code>	<code>updateMany({ where:{...}, data:{...} })</code>	<code>db.Model(&obj).Updates({...})</code>
Delete One	<code>deleteOne({ _id:id })</code>	<code>delete({ where:{id} })</code>	<code>db.Delete(&obj, id)</code>
Delete Many	<code>deleteMany({ key:val })</code>	<code>deleteMany({ where:{...} })</code>	<code>db.Where("key=?", val).Delete(&obj)</code>
Count	<code>countDocuments({})</code>	<code>count({ where:{...} })</code>	<code>db.Model(&obj).Count(&n)</code>
Sort	<code>find().sort({ key:1 })</code>	<code>findMany({ orderBy:{ key:'asc' } })</code>	<code>db.Order("key asc").Find(&[]obj)</code>
Limit	<code>find().limit(n)</code>	<code>findMany({ take:n })</code>	<code>db.Limit(n).Find(&[]obj)</code>
Skip	<code>find().skip(n)</code>	<code>findMany({ skip:n })</code>	<code>db.Offset(n).Find(&[]obj)</code>
Pagination	<code>find().skip(n).limit(n)</code>	<code>findMany({ skip:n, take:n })</code>	<code>db.Offset(n).Limit(n).Find(&[]obj)</code>
Filter	<code>find({ key:val })</code>	<code>findMany({ where:{ key:val } })</code>	<code>db.Where("key=?", val).Find(&[]obj)</code>
Select Fields	<code>find().select('f1 f2')</code>	<code>findMany({ select:{ f1:true } })</code>	<code>db.Select("f1, f2").Find(&[]obj)</code>
Populate / Include	<code>find().populate('ref')</code>	<code>findMany({ include:{ model:true } })</code>	<code>db.Preload("Model").Find(&[]obj)</code>
Transactions	<code>session.withTransaction(fn)</code>	<code>\$transaction([...])</code>	<code>db.Transaction(func(tx *gorm.DB))</code>
Raw Query	<code>collection.aggregate([...])</code>	<code>\$queryRaw`SQL`</code>	<code>db.Raw("SQL").Scan(&obj)</code>
Auto Timestamps	<code>timestamps: true</code>	<code>@default(now()) / @updatedAt</code>	<code>gorm.Model embed</code>

Note: {...} = object/struct fields | [...] = array | n = number | val = value | obj = model instance | &obj; = pointer to struct (Go)