print

In [2]:
```
a=20
b=40
a
b
```

Out[2]: 40

In [3]:
```
a=20
b=40
print(a)
print(b)
```

```
20
40
```

In [6]:
```
print(15)
print(15,75)
print('aadhya sree')
print(10,20,'avyukth')
```

```
15
15 75
aadhya sree
10 20 avyukth
```

In [4]:
```
print(10)
print(10,20)
print('python')
print(10,20,'python')
```

```
10
10 20
python
10 20 python
```

In [5]:
```
num1=30
num2=50
add=num1+num2
print(add)
```

```
80
```

In [7]:
```
chocolate= 15
biscuit = 35
lunch = chocolate + biscuit
print(lunch)
```

```
50
```

print result with string

In [39]:
```
num1=20
num2=30
add=num1+num2
print('The addition of',num1,'and',num2,'is',add)
```

```
The addition of 20 and 30 is 50
```

In [40]:
```
toy=100
gift=150
party=toy+gift
print('The addition of',toy, 'and' ,gift, 'is', party)
```

```
The addition of 100 and 150 is 250
```

In [41]:
```
name='Alexa'
age=50
city='hyd'
#hellow my name is python and i am 50 year old from hydrabad
```

In [15]:
```
print('my name is', name, 'and I am', age, 'years old from', city)
```

```
my name is Alexa and I am 50 years old from hyd
```

print Format method

In [42]:
```
num1=20
num2=30
add=num1+num2
print('The addition of {} and {} is {}'.format(num1,num2,add))
```

```
The addition of 20 and 30 is 50
```

In [43]:
```
bottle=100
box= 200
total=bottle + box
print('the total of {} and {} is {}'.format(bottle,box,total))
```

```
the total of 100 and 200 is 300
```

first deside how the print statement should be

like:- The addition of 20 and 30 is = 50

then replace the variable position with curly brtacesm { }

then appply .format(val1,val2,....val-n methodm

In [25]:
```
name='Python'
age=20
city='hyd'
#hellow my name is python and i am 10 year old from hydrabad
```

In [26]:
```
print('hello my name is {}, and i am {} years old from {} '.format(name,age,city))
```

```
hello my name is Python, and i am 20 years old from hyd
```

In [37]:
```
num1=100
num2=25
num3=333
avg=(num1+num2+num3)/3 # or we can use avg=round(num1+num2+num3)/3,2)
avg1=round((num1+num2+num3)/3,2)
# The avrage of num1,num2,num3 is = avg
print('The avrage of {}, {}, and {} is {} or {}'.format(num1,num2,num3, avg,avg1))
# here we can use round(avg,2) also
```

```
The avrage of 100, 25, and 333 is 152.66666666666666 or 152.67
```

In [38]:
```
english=97
science=91
maths=99
average=(english+science+maths)/3
average1=round((english+science+maths)/3,2)
print('the average of {},{},and {} is {} or {}'.format(english, science,maths, aver
```

```
the average of 97,91,and 99 is 95.66666666666667 or 95.67
```

round(avg,2) # round of till 2 digite after decimal

More short format meythod(f string method)

.variable should be in curly braces

and write everything inside quots ' '

at starting simpaly add f

In [32]:
```
num1=20
num2=30
```

In [44]:
```
add=num1+num2
print(f'The addition of {num1} and {num2} is {add}')
```

```
The addition of 20 and 30 is 50
```

In [36]:
```
pen=59
pencil= 25
box = pen + pencil
print(f'the combination of {pen} and {pencil} is {box}')
```

```
the combination of 59 and 25 is 84
```

In [34]:
```
name='Python'
age=20
city='hyd'
#hellow my name is python and i am 10 year old from hydrabad
```

In [45]:
```
name='Python'
age=20
city='hyd'
#hellow my name is python and i am 10 year old from hydrabad
```

In [46]:
```
print(f'hello my name is {name}, and i am {age} year old, from {city}.')
```

```
hello my name is Python, and i am 20 year old, from hyd.
```

In [47]:
```
num1=100
num2=25
num3=333
avg=round((num1+num2+num3)/3,2)
# or we can use avg=round(num1+num2+num3)/3,2) # The avrage of num1,num2,num3 is =
```

In [48]:
```
english=97
science=91
maths=99
average=(english+science+maths)/3
average1=round((english+science+maths)/3,2)
```

In [50]:
```
print(f'the average of {english},{science},and {maths} is {average} ')
```

```
the average of 97,91,and 99 is 95.66666666666667
```

In [51]:
```
# lete combine all
num1=10
num2=20
add = num1+ num2
print('The addition of',num1,'and',num2,'is=',add)
print('The addition of {} and {} is= {}'.format(num1,num2,add))
print(f'The addition of {num1} and {num2} is= {add}')
```

```
The addition of 10 and 20 is= 30
The addition of 10 and 20 is= 30
The addition of 10 and 20 is= 30
```

In [52]:
```
table=1500
chair=500
dining=table + chair
print('The addition of',table,'and',chair,'is=',dining)
print('The addition of {} and {} is= {}'.format(table,chair, dining))
print(f'The addition of {table} and {chair} is= {dining}')
```

```
The addition of 1500 and 500 is= 2000
The addition of 1500 and 500 is= 2000
The addition of 1500 and 500 is= 2000
```

End statement

In [53]:
```
print('hello') # 1st statement
print('good moorning') # 2nd statement)
# i want print like:- hellow good morning
```

```
hello
good moorning
```

Here we will use end statement that joint line from end of one string to starting of other string

In [54]:
```
print('hello', end=' ') # 1st statement
print('world good day') # 2nd statement
```

```
hello world good day
```

In [55]:
```
print('my name is', end=' ')
print('niharika')
```

```
my name is niharika
```

seperator

here one print statement only we use

insisde one print statement we have multipal values

we want to seperate these multiple values with anything

In [57]:
```
print('hello','hai','how are you',sep='--->')
```

```
hello--->hai--->how are you
```

In [58]:
```
print('hello','hai','how are you',sep='&')
```

```
hello&hai&how are you
```

In [59]:
```
print('hello','hai','how are you',sep='@')
```

```
hello@hai@how are you
```

In [60]:
```
print('hello','hai','how are you',sep=' ')
```

```
hello hai how are you
```

In [61]:
```
print(3,'.') # . is far from 3 so here we will use sep method
```

```
3 .
```

In [62]:
```
print(3,'.',sep='') # see now space setteld(also use to remove space B/W words)
```

```
3.
```

In [64]:
```
print(1,2,end=' ')
print(3,'.',sep='') # will print 1 2 3.
```

```
1 2 3.
```

In [ ]: