

```
#include <stdio.h>
```

```
int main() {
```

```
    char operator;
```

```
    double num1, num2, result;
```

```
    // Ask the user for the operator
```

```
    printf("Enter an operator (+, -, *, /): ");
```

```
    scanf(" %c", &operator);
```

```
    // Ask the user for two operands
```

```
    printf("Enter two numbers: ");
```

```
    scanf("%lf %lf", &num1, &num2);
```

```
    // Perform the operation based on the operator selected
```

```
    switch (operator) {
```

```
        case '+':
```

```
            result = num1 + num2;
```

```
            printf("%.2lf + %.2lf = %.2lf\n", num1, num2, result);
```

```
            break;
```

```
        case '-':
```

```
            result = num1 - num2;
```

```
            printf("%.2lf - %.2lf = %.2lf\n", num1, num2, result);
```

```
            break;
```

```

case '*':
    result = num1 * num2;
    printf("%.2lf * %.2lf = %.2lf\n", num1, num2, result);
    break;

case '/':
    // Check for division by zero
    if (num2 == 0) {
        printf("Error! Division by zero is not allowed.\n");
    } else {
        result = num1 / num2;
        printf("%.2lf / %.2lf = %.2lf\n", num1, num2, result);
    }
    break;

// If the operator doesn't match any of the cases
default:
    printf("Error! Invalid operator.\n");
}

return 0;
}

```