

# Week 10

Q1)

Given a string,  $s$ , consisting of alphabets and digits, find the frequency of each digit in the given string.

**Input Format**

The first line contains a string,  $num$  which is the given number.

**Constraints**

$1 \leq \text{len}(num) \leq 1000$

All the elements of  $num$  are made of English alphabets and digits.

**Output Format**

Print ten space-separated integers in a single line denoting the frequency of each digit from 0 to 9.

**Sample Input 0**

a11472o5t6

**Sample Output 0**

0 2 1 0 1 1 1 1 0 0

**Question 1**

Correct

Marked out of  
1.00[Flag question](#)

Given a string, *s*, consisting of alphabets and digits, find the frequency of each digit in the given string.

**Input Format**

The first line contains a string, *num* which is the given number.

**Constraints**

$$1 \leq \text{len}(\text{num}) \leq 1000$$

All the elements of *num* are made of English alphabets and digits.

**Output Format**

Print ten space-separated integers in a single line denoting the frequency of each digit from 0 to 9.

**Sample Input 0**

a11472o5t6

**Sample Output 0**

0 2 1 0 1 1 1 1 0 0

```
1 #include <stdio.h>
2 #include <string.h>
3
4 int main() {
5     char str[1001];
6     int freq[10] = {0}; // Initialize array to store frequencies of digits
7
8     scanf("%s", str);
9
10    for (int i = 0; i < strlen(str); i++) {
11        if (str[i] >= '0' && str[i] <= '9') {
12            int digit = str[i] - '0';
13            freq[digit]++;
14        }
15    }
16
17    for (int i = 0; i < 10; i++) {
18        printf("%d ", freq[i]);
19    }
20
21    return 0;
22 }
```

	Input	Expected	Got	
✓	a11472o5t6	0 2 1 0 1 1 1 1 0 0	0 2 1 0 1 1 1 1 0 0	✓
✓	lw4n88j12n1	0 2 1 0 1 0 0 0 2 0	0 2 1 0 1 0 0 0 2 0	✓
✓	1v888861256338ar0ekk	1 1 1 2 0 1 2 0 5 0	1 1 1 2 0 1 2 0 5 0	✓

Passed all tests! ✓

Q2) Today, Monk went for a walk in a garden. There are many trees in the garden and each tree has an English alphabet on it. While Monk was walking, he noticed that all trees with vowels on it are not in good state. He decided to take care of them. So, he asked you to tell him the count of such trees in the garden.

Note: The following letters are vowels: 'A', 'E', 'I', 'O', 'U', 'a', 'e', 'i', 'o' and 'u'.

Input Format:

The first line consists of an integer T denoting the number of test cases.

Each test case consists of only one string, each character of string denoting the alphabet (may be lowercase or uppercase) on a tree in the garden.

Output Format:

For each test case, print the count in a new line.

Constraints:

$$1 \leq T \leq 10$$

$$1 \leq \text{length of string} \leq 105$$

Sample Input

2

nBBZLaosnm

JHklsnZtTL

Sample Output

2

1

Question 2  
Correct  
Marked out of  
1.00  
Flag question

Today, Monk went for a walk in a garden. There are many trees in the garden and each tree has an English alphabet on it. While Monk was walking, he noticed that all trees with vowels on it are not in good state. He decided to take care of them. So, he asked you to tell him the count of such trees in the garden.

**Note:** The following letters are vowels: 'A', 'E', 'I', 'O', 'U', 'a', 'e', 'i', 'o' and 'u'.

**Input:**

The first line consists of an integer  $T$  denoting the number of test cases.

Each test case consists of only one string, each character of string denoting the alphabet (may be lowercase or uppercase) on a tree in the garden.

**Output:**

For each test case, print the count in a new line.

**Constraints:**

$$1 \leq T \leq 10$$

$$1 \leq \text{length of string} \leq 10^5$$

**SAMPLE INPUT**

```
2
nBBZLaosnm
JHklsnZiTL
```

**SAMPLE OUTPUT**

```
2
1
```

```
1 #include <stdio.h>
2 #include <string.h>
3
4 int main() {
5     int T;
6     scanf("%d", &T);
7
8     while (T--) {
9         char str[100005];
10        scanf("%s", str);
11
12        int count = 0;
13        for (int i = 0; i < strlen(str); i++) {
14            char ch = str[i];
15            if (ch == 'A' || ch == 'E' || ch == 'I' || ch == 'O' || ch == 'U' ||
16                ch == 'a' || ch == 'e' || ch == 'i' || ch == 'o' || ch == 'u') {
17                count++;
18            }
19        }
20        printf("%d\n", count);
21    }
22    return 0;
23 }
24
25 }
```

Output:

	Input	Expected	Got	
✓	2 nBBZLaosnm JHkIsnZtTL	2 1	2 1	✓
✓	2 nBBZLaosnm JHkIsnZtTL	2 1	2 1	✓

Passed all tests! ✓

Q3) Given a sentence, *s*, print each word of the sentence in a new line.

Input Format

The first and only line contains a sentence, *s*.

Constraints

$1 \leq \text{len}(s) \leq 1000$

Output Format

Print each word of the sentence in a new line.

Sample Input

This is C

Sample Output

This

is

C

Question 3  
Correct  
Marked out of  
1.00  
Flag question

Given a sentence,  $s$ , print each word of the sentence in a new line.

#### Input Format

The first and only line contains a sentence,  $s$ .

#### Constraints

$1 \leq \text{len}(s) \leq 1000$

#### Output Format

Print each word of the sentence in a new line.

#### Sample Input 0

This is C

#### Sample Output 0

This  
is  
C

```
1 #include <stdio.h>
2 #include <string.h>
3
4 int main() {
5     char sentence[1000];
6
7     // Read the sentence
8     fgets(sentence, sizeof(sentence), stdin);
9
10    // Iterate over the sentence and print each word
11    char *word = strtok(sentence, " ");
12    while (word != NULL) {
13        printf("%s\n", word);
14        word = strtok(NULL, " ");
15    }
16
17    return 0;
18 }
```

Output:

	Input	Expected	Got	
✓	This is C	This is C	This is C	✓
✓	Learning C is fun	Learning C is fun	Learning C is fun	✓

Passed all tests! ✓

#### Q4) Input Format

You are given two strings, a and b, separated by a new line. Each string will consist of lower-case Latin characters ('a'-'z').

#### Output Format

In the first line print two space-separated integers, representing the length of a and b respectively.

In the second line print the string produced by concatenating a and b (a + b).

In the third line print two strings separated by a space, a' and b'. a' and b' are the same as a and b, respectively, except that their first characters are swapped.

#### Sample Input

abcd

ef

#### Sample Output

4 2

abcdef

ebcd af

Question 4  
Incorrect  
Marked out of 1.00  
Flag question

#### Input Format

You are given two strings,  $a$  and  $b$ , separated by a new line. Each string will consist of lower case Latin characters ('a'-'z').

#### Output Format

In the first line print two space-separated integers, representing the length of  $a$  and  $b$  respectively.

In the second line print the string produced by concatenating  $a$  and  $b$  ( $a + b$ ).

In the third line print two strings separated by a space,  $a'$  and  $b'$ .  $a'$  and  $b'$  are the same as  $a$  and  $b$ , respectively, except that their first characters are swapped.

#### Sample Input

abcd  
ef

#### Sample Output

4 2  
abcdef  
ebcd af

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     char a[100],b[100];
5     scanf("%s",a);
6     scanf("%s",b);
7     int l1=0,l2=0;
8     while(a[l1]!='\0')
9     {
10         l1++;
11     }
12     while(b[l2]!='\0')
13     {
14         l2++;
15     }
16     printf("%d %d\n",l1,l2);
17     char c[l1+l2];
18     c[0]=a[0];
19     a[0]=b[0];
20     b[0]=c[0];
21     printf("%s %s",a,b);
22 }
23 }
```

Output:

	Input	Expected	Got	
✓	abcd ef	4 2 abcdef ebcd af	4 2 abcdef ebcd af	✓

Passed all tests! ✓